HIDING IN THE DEEP

ONLINE ANIMAL ACTIVITY RECOGNITION USING
MOTION SENSORS AND MACHINE LEARNING

Jacob W. Kamminga

HIDING IN THE DEEP

ONLINE ANIMAL ACTIVITY RECOGNITION USING
MOTION SENSORS AND MACHINE LEARNING

Jacob Wilhelm Kamminga

HIDING IN THE DEEP

ONLINE ANIMAL ACTIVITY RECOGNITION USING MOTION SENSORS AND MACHINE LEARNING

DISSERTATION

to obtain
the degree of doctor at the University of Twente,
on the authority of the rector magnificus,
prof.dr. T.T.M. Palstra,
on account of the decision of the Doctorate Board,
to be publicly defended
on Friday 2 October 2020 at 12:45 hours

by

Jacob Wilhelm Kamminga

born on the 22nd of September 1987
in Kantens, The Netherlands

This dissertation has been approved by:

Supervisor:
prof.dr. P.J.M. Havinga

This research is supported by the Netherlands Organization for Scientific Research (NWO).

Cover design: Nelson Wagenaar
Printed by: Ipskamp Printing, Enschede
Lay-out: Jacob Kamminga
ISBN: 978-90-365-5055-0
DOI: 10.3990/1.9789036550550

© 2020 Jacob Wilhelm Kamminga, The Netherlands. All rights reserved. No parts of this thesis may be reproduced, stored in a retrieval system or transmitted in any form or by any means without permission of the author. Alle rechten voorbehouden. Niets uit deze uitgave mag worden vermenigvuldigd, in enige vorm of op enige wijze, zonder voorafgaande schriftelijke toestemming van de auteur.

GRADUATION COMMITTEE:

Chairman/secretary prof. dr. J.N. Kok

Supervisor prof. dr. P.J.M. Havinga

Members

prof. dr. ir. P.H. Veltink

prof. dr. A.K. Skidmore

prof. dr. B.J.A. Krose

prof. dr. K. van Laerhoven

*No one can pass through life, any more than he can pass
through a bit of country, without leaving tracks behind,
and those tracks may often be helpful to those coming
after him in finding their way.*

Robert Baden-Powell

ABSTRACT

The activity of animals is a rich source of information that not only provides insights into their life and well-being but also their environment. Animal activity recognition (AAR) is a new field of research that supports various goals, including the conservation of endangered species and the well-being of livestock. Over the last decades, the advent of small, lightweight, and low-power electronics has made it possible to attach unobtrusive sensors to animals that can measure a wide range of aspects such as location, temperature, and activity. These aspects are highly informative properties for numerous application domains, including wildlife monitoring, anti-poaching, and livestock management. In this thesis, we focus on AAR that aims to automatically recognize the activity from motion data – on the animal – while the activities are performed (online). Specifically, we use motion data recorded through an inertial measurement unit (IMU) that comprises an accelerometer, gyroscope, and magnetometer to distinguish up to eleven different activities.

Numerous factors challenge online AAR, and in this thesis, we address the following: (i.) Sensors are often attached to (wild) animals using collars around the neck. In many cases, it is difficult or impossible to re-charge the battery after the collar is attached to the animal. Furthermore, the sensor tags are restricted in weight and size to be unobtrusive. Therefore, the tags not only have limited energy but are also constrained in computation and memory resources. (ii.) Animal collars are exposed to rough behavior and environments. As such, the collar can rotate around the neck, which causes the sensors to change position and orientation over time. The variability in sensor-orientation causes significant errors if activity classifiers are sensitive to sensor orientation. It is challenging to develop AAR that is insensitive to sensor orientation. (iii.) Animal groups are heterogeneous; sensitivity of an AAR system to individual traits may impact the performance. A system trained with training-data from a subset of animals may not generalize well to others. Moreover, there are various species, and independently developing AAR for each species is a daunting task. (iv.) Various machine learning (ML) algorithms are used as AAR classifiers. Each classifier has different properties and is affected by aspects such as feature-type, parameter settings, and class-imbalance in the dataset. It is challenging to find the impact of each aspect on the classification performance. (v.) The classifiers rely on a clear feature representation of the raw sensor data. Therefore, feature extraction is an essential aspect of AAR. It is challenging to find the most resource-efficient and effective feature extraction method. (vi.) Data acquisition and labeling are tedious, especially for AAR because it can be difficult to observe (wild) animals, which is mandatory for labeling (annotation of data with ground-truth). As a result, labeled datasets are often small and class-imbalanced; e.g., a labeled dataset may comprise mostly *eating* activity, but little *running*.

To address the challenges in AAR, we pose the following main research question:

How can we recognize various animal activities using motion data while considering resource-efficiency, orientation-independence, and genericity so that it can be executed online and easily deployed across a wide variety of species?

Tremendous innovations in computation, memory, and battery technology allow us to process the sensor data locally on the animal tag, while the activities are performed. Locally processing the data eliminates the need to store or transmit large amounts of raw data and provides opportunities to develop resource-efficient AAR.

We simultaneously address the challenges of resource constraints and the dynamic sensor orientation and position through a framework that aims at finding the optimal feature set, which is lightweight and robust to the sensor's orientation. We use 3D motion data to extract various summary statistic features. We select the most informative features using a method based on simultaneous feature selection and classification, and the feature sets are optimized through 10-fold cross-validation. We investigate the effect of different sizes of the resulting feature sets. Our results show that the accelerometer is the best sensor for AAR and using three features is sufficient.

To address the heterogeneity of animals, we propose a framework that employs multitask learning (MTL) for embedded platforms to enable generic AAR that can be used on multiple species. We investigate the trade-off between classification performance and genericity of an AAR system. Specifically, we study the effect of MTL on the performance of a single classifier that classifies the activities of two species. We test and compare 7 classifiers in three scenarios: (i.) trained with individual data, (ii.) trained with data from one species and tested on the other and vice versa, and (iii.) trained with mixed data from both species. Our results are a good indication that it is possible to train classifiers with good genericity performance for similar species.

We investigate the effect of feature type, hyperparameter tuning, and data partitioning method (to create the validation datasets) on the AAR performance. Firstly, we compare the quality of time and frequency-domain summary statistic features; while investigating the effect of feature type, we validate the goat orientation-independent feature set on a different species. Overall, most classifiers yield higher performance using frequency-domain features and similar performance when the orientation-independent feature set is used. Secondly, we compare two validation partitioning methods: k -fold and leave-one-subject-out cross-validation. When an AAR classifier is used on animals that were not included in the training dataset, the performance is reflected more precisely using leave-one-subject-out cross-validation. Finally, we demonstrate the effect of hyperparameter tuning and show the level of improved classification and genericity performance.

To address the challenge of effective feature extraction while labeled datasets are small and imbalanced, we investigate unsupervised representation learning (URL). We present an analysis framework that compares various deep URL techniques to exploit *unlabeled* data to improve feature extraction. The most compelling reason to use URL as a feature extraction method is the ability to learn from *unlabeled* data. We compare three URL techniques with three conventional feature extraction methods. To investigate the effect of the size of both *labeled* and *unlabeled* part of the dataset on the quality

of the features, we train the URL methods and classifiers using various sample sizes. We demonstrate that the performance of URL can approach and, in some cases, outperform conventional features. Our results show that the convolutional deep belief network (CDBN) benefited the most from an increasing amount of unlabeled data, especially in the more diverse and imbalanced dataset. Furthermore, we evaluate the effect of depth in URL and demonstrate that concatenating the 1st and 2nd layer features often results in better classification performance. Finally, we analyze and discuss the effect of class-imbalance in the dataset on the feature quality. Our results indicate that deep representations provide more robustness to the imbalance in smaller labeled datasets.

We collected 3 datasets comprising 3D motion data recorded on animals. The first dataset comprises labeled motion data from 4 goats and 2 sheep and is used to study the genericity performance of AAR classifiers. The second dataset comprises labeled motion data from 5 goats collected from 6 positions in diverse orientations around the neck of the animals. This dataset is used to address sensor orientation-independent AAR. The third dataset comprises motion data from 18 horses of which data from 11 subjects is partly labeled. This dataset is used to study various factors that impact the performance of AAR and unsupervised representation learning.

In this thesis, we show that it is possible to perform AAR with excellent classification performance while it is resource-efficient and orientation-independent. Although performance versus resource usage is often a trade-off, we show that excellent performance can be obtained using only the accelerometer, a small set of features, and a classifier that is resource-efficient in memory and computation, allowing the AAR to be executed online. Our goal is generic AAR that can easily be deployed across a variety of similar species. In this thesis, we show that when sufficient aspects are similar, e.g., the species, sensor-location, and activity types, it is possible to train classifiers in a way so that a single AAR system can be deployed on two species. Improving orientation-independent feature extraction by exploiting unlabeled data is a prospective direction for further research.

SAMENVATTING

De activiteiten van dieren zijn een rijke bron van informatie die niet alleen inzicht geeft in hun leven en welzijn, maar ook in hun omgeving. Activiteit herkenning voor dieren (AHD) is een nieuw onderzoeksgebied dat bijdraagt aan verschillende doelen, waaronder het behoud van bedreigde diersoorten en het welzijn van vee. In de afgelopen decennia heeft de komst van kleine, lichtgewicht en energiezuinige elektronica het mogelijk gemaakt om onopvallende sensoren aan dieren te bevestigen die een breed scala aan aspecten zoals locatie, temperatuur en activiteit kunnen meten. Deze aspecten zijn zeer informatieve eigenschappen voor tal van toepassingsdomeinen, waaronder monitoring van dieren in het wild, anti-stroperij en beheren van vee. In dit proefschrift richten we ons op AHD dat als doel heeft de activiteit automatisch te herkennen uit bewegingsdata – op het dier – terwijl de activiteiten uitgevoerd worden (online). In het bijzonder gebruiken we bewegingsdata die zijn vastgelegd door middel van een zogenoemde inertial measurement units (IMUs) die een versnellingsmeter, gyroscoop en magnetometer omvat om tot elf verschillende activiteiten te onderscheiden.

Online AHD heeft talloze uitdagingen voor een succesvolle toepassing en in dit proefschrift behandelen we de volgende: (i.) Sensor tags worden vaak bevestigd aan (wilde) dieren met behulp van halsbanden. In veel gevallen is het moeilijk of onmogelijk om de batterij opnieuw op te laden nadat de halsband aan het dier is bevestigd. Bovendien zijn de tags beperkt in gewicht en grootte zodat ze niet vervelend zijn voor de dieren om te dragen. Daarom hebben de tags niet alleen een beperkte hoeveelheid energie, maar zijn ze ook beperkt in rekenkracht en het beschikbare geheugen. (ii.) Halsbanden voor dieren worden vaak blootgesteld aan ruwe gedragingen en omgevingen. Als zodanig kan de halsband rond de nek roteren, waardoor de sensoren in de loop van de tijd van positie en oriëntatie veranderen. De variabiliteit in sensor oriëntatie veroorzaakt aanzienlijke fouten als classifiers (de algoritmen die de activiteit herkennen) gevoelig zijn voor sensor oriëntatie. Het is een uitdaging om AHD te ontwikkelen die ongevoelig is voor sensor oriëntatie. (iii.) Diergroepen zijn heterogeen; gevoeligheid van een AHD systeem voor individuele kenmerken kan de prestaties beïnvloeden. Een systeem dat is getraind met trainingsdata van een subset van dieren, kan niet altijd goed generaliseren voor andere dieren buiten de trainingset. Bovendien bestaan er verscheidene diersoorten en het onafhankelijk ontwikkelen van AHD voor elke soort is een ontmoedigende taak. (iv.) Verscheidene machine learning (ML) algoritmen kunnen worden gebruikt als classifiers. Het is een uitdaging om te bepalen welke algoritmen het meest toepasselijk zijn voor online AHD. Elke classifier heeft verschillende eigenschappen en wordt beïnvloed door aspecten zoals de soort representatie van ruwe data (featuretype), parameterinstellingen en klasse-onbalans in de dataset. Het is een uitdaging om de impact van elk aspect op de resultaten van de classifiers te vinden. (v.) De classifiers vereisen een duidelijke representatie (d.m.v. features) van de ruwe sensordata. Daarom is de extractie van features een essentieel aspect van AHD. Het is een uitdaging

om de meest resource-efficiënte en effectieve extractiemethode voor features te vinden. (vi.) Dataverzameling en labeling (annotatie van data met grondwaarheid) zijn lastig, vooral voor AHD omdat het moeilijk kan zijn om (wilde) dieren te observeren, wat een vereiste is voor labeling. Als gevolg hiervan zijn gelabelde datasets vaak klein en ongebalanceerd qua klasse; een gelabelde dataset kan bijvoorbeeld veel *eten* activiteit bevatten, maar weinig *rennen*.

Om de uitdagingen in AHD aan te gaan, stellen we de volgende hoofdonderzoeksvraag:

Hoe kunnen we verschillende dieren activiteiten herkennen met behulp van bewegingsdata, rekening houdend met efficiënt gebruik van resources, oriëntatie-onafhankelijkheid en generaliteit, zodat het online kan worden uitgevoerd en gemakkelijk kan worden ingezet voor een breed scala aan soorten?

Enorme innovaties in rekenkracht, geheugen en batterijtechnologie stellen ons in staat om de sensor data lokaal, via een tag op het dier, te verwerken terwijl de activiteiten worden uitgevoerd. Door de data lokaal te verwerken, is het niet nodig om grote hoeveelheden onbewerkte data op te slaan of te verzenden en biedt het mogelijkheden om online AHD te ontwikkelen die efficiënt omgaat met energie.

In dit proefschrift gaan we tegelijkertijd de uitdagingen aan van resource-efficiëntie en de dynamische sensor-oriëntatie en -positie door middel van een raamwerk dat gericht is op het vinden van de optimale featureset, die lichtgewicht en robuust is tegen de oriëntatie van de sensor. We gebruiken 3D-bewegingsdata om verschillende samenvattende statistische features te extraheren. We selecteren de meest informatieve features met behulp van een methode die is gebaseerd op gelijktijdige feature selectie en classificatie. De featuresets zijn geoptimaliseerd via een tienvoudige kruisvalidatie. We onderzoeken het effect van verschillende groottes van de resulterende featuresets. Onze resultaten laten zien dat de versnellingsmeter de beste sensor is om te gebruiken voor AHD en dat het gebruik van 3 features voldoende is.

Om de heterogeniteit van dieren aan te pakken, stellen we een raamwerk voor dat multitask learning (MTL) gebruikt voor embedded platforms. We onderzoeken de afweging tussen classificatie prestaties en genericiteit van een AHD systeem. Specifiek bestuderen we het effect van MTL op de prestaties van een enkele classifier die de activiteiten van twee soorten classificeert. We testen en vergelijken 7 classifiers in drie scenario's: (i.) getraind met individuele data, (ii.) getraind met data van de ene soort en getest op de andere en vice versa, en (iii.) getraind met gemengde data van beide soorten. Onze resultaten zijn een goede indicatie dat het mogelijk is om classifiers te trainen met goede generieke prestaties voor vergelijkbare soorten.

We onderzoeken het effect van het featuretype, hyperparameter instelling en data partitionerings methode (om de validatie datasets te maken) op de prestaties van AHD. Ten eerste vergelijken we de kwaliteit van tijd- en frequentiedomein features. Terwijl we het effect van het featuretype onderzoeken, valideren we de oriëntatie-onafhankelijke featureset op een andere diersoort. Over het algemeen leveren de meeste classifiers hogere prestaties met behulp van frequentiedomein features en vergelijkbare prestaties wanneer de oriëntatie-onafhankelijke featureset wordt gebruikt. Ten tweede vergelijken we twee validatie partitie methoden: *k-fold* en *leave-one-subject-out* kruisvalidatie.

Wanneer een classifier wordt gebruikt voor dieren die niet in de training dataset waren opgenomen, worden de prestaties nauwkeuriger weerspiegeld met behulp van *leave-one-subject-out* validatie. Ten slotte tonen we het effect van hyperparameter instellingen en de mate van verbeterde classificatie en generieke prestaties.

Om de uitdaging van effectieve feature extractie aan te gaan terwijl gelabelde datasets klein en ongebalanceerd zijn, onderzoeken we unsupervised representation learning (URL). We presenteren een analysekader dat verschillende URL technieken vergelijkt om *ongelabelde* data te exploiteren om de extractie van features te verbeteren. De voornamelijkste reden om URL te gebruiken als feature extractie methode is de mogelijkheid om te leren van ruwe *ongelabelde* data. We vergelijken drie URL technieken met drie conventionele feature extractiemethoden. Om het effect van de grootte van zowel de *gelabelde* als het *ongelabelde* deel van de dataset op de kwaliteit van de features te onderzoeken, trainen we de URL methoden en classifiers met behulp van verschillende sample groottes. We tonen aan dat de prestaties van URL die van conventionele features kunnen benaderen en in sommige gevallen overtreffen. Onze resultaten laten zien dat de convolutional deep belief network (CDBN) het meest profiteert van een toenemende hoeveelheid ongelabelde data, vooral in de meer diverse en onevenwichtige dataset. Verder evalueren we het effect van diepte in URL en tonen we aan dat het samenvoegen van eerste en tweede laag vaak resulteert in betere classificatie prestaties. Tot slot analyseren en bespreken we het effect van klasse-onbalans in de dataset op de kwaliteit van de features. Onze resultaten geven aan dat diepe features classificatie robuuster maken tegen de onbalans in kleinere gelabelde datasets.

We hebben 3 datasets verzameld met 3D-bewegingsdata die zijn vastgelegd op dieren. De eerste dataset bestaat uit gelabelde bewegingsdata van 4 geiten en 2 schapen en werd gebruikt om de generieke prestaties van AHD te bestuderen. De tweede dataset omvat gelabelde bewegingsdata van 5 geiten verzameld van 6 posities in verschillende oriëntaties rond de nek van de dieren. Deze dataset werd gebruikt om sensor oriëntatie-onafhankelijk AHD te onderzoeken. De derde dataset bevat bewegingsdata van 18 paarden waarvan data van 11 dieren gedeeltelijk zijn gelabeld. Deze dataset werd gebruikt om URL te onderzoeken en verschillende factoren te bestuderen die van invloed zijn op de prestaties van AHD.

In dit proefschrift laten we zien dat het mogelijk is om AHD uit te voeren met goede classificatie prestaties terwijl het resource-efficiënt en oriëntatie-onafhankelijk is. Hoewel prestaties versus het gebruik van resources vaak een afweging zijn, laten we zien dat uitstekende prestaties kunnen worden behaald met alleen de versnellingsmeter, een kleine featureset en een classifier die efficiënt omgaat met geheugen en rekenkracht, waardoor de AHD online kan worden uitgevoerd. Ons doel is generieke AHD die makkelijk kan worden ingezet bij meerdere verwante diersoorten. In dit proefschrift laten we zien dat wanneer voldoende aspecten vergelijkbaar zijn, bijvoorbeeld de diersoort, de sensor locatie en het activiteitstype, het mogelijk is om classifiers te trainen op een manier zodat een AHD kan worden ingezet bij twee verwante diersoorten. Het verbeteren van oriëntatie-onafhankelijke feature extractie door ongelabelde data te exploiteren is een onderzoeksrichting met veel potentie.

DANKWOORD & ACKNOWLEDGEMENT

Met een lach op mijn gezicht schrijf ik deze woorden aan het einde van mijn promotietraject. Ik heb ruim 4 jaar met plezier onderzoek gedaan en ik ben trots op het eindresultaat in de vorm van deze dissertatie. Het traject was een onderneming met pieken en dalen en ik prijs mezelf erg gelukkig met de vele mensen om me heen die mij op verschillende manieren hebben geholpen. Doormiddel van dit dankwoord wil ik iedereen graag hartelijk bedanken.

I'm proudly writing these words after four years of research that resulted in this thesis. The Ph.D. track is one with ups and downs and is not traveled alone. Many people supported me during the journey, and in the following, I would like to thank them.

Firstly, I want to thank my promotor Paul Havinga. Paul, we met during my search for a master's thesis project. Quickly, you connected my idea to turn crowds into light shows to wireless sensor networks and motivated me to study localization using environmental sound. The obtained knowledge proofed to be a good foundation for a continuation in Animal Activity Recognition research. I quickly felt at home in PS and have always enjoyed the diversity of projects and people within the group. Thank you for the opportunity and the freedom to conduct my research under your supervision. Your enthusiasm and positive outlook are always motivating and often spark into exciting ideas.

Nirvana, during most of my Ph.D., you were my daily supervisor. I sincerely want to thank you for the opportunity to pursue my Ph.D. within PS, your guidance, and always constructive feedback. You taught me a lot about structuring and presenting my research. Your laughter always filled the hallway in PS, and I'm sure it now does so in Eindhoven.

Viet Duc, we started working together during my master's thesis research, and ever since, you acted as a mentor, co-author, and good friend. Thank you for guiding me around machine learning topics and always pointing out exciting study subjects.

Papers don't write themselves (yet), and writing them together is always better. I enjoyed the collaboration with my co-authors and would like to thank them for their cooperation and valuable input. Eyuel, I am happy you were my roommate and that we worked together within the same project. Thanks for the many discussions, lunch-walks, and the incredible Ethiopian lunch in your home. Hans, I am very grateful for your presence within the group. Your experience always guides us during discussions, and when you are around, there is never a silent moment during lunch. We share a love for traveling, and I want to thank you for all the stories and the books you lend to me. Jan-Pieter, I enjoyed your company in and outside the group, and thank you for your creative and insightful input. Helena, I enjoyed supervising and working with you throughout your

master's thesis and the article we published. I want to thank Micheal Jones and Kevin Seppi from Brigham Young University for their interest and collaboration. It was a pleasure to work together with you. I want to thank Caleb for his enthusiasm and continued cooperation. Furthermore, I want to thank Caleb and Carli Coco for providing their fantastic wildlife photos that are featured in this thesis.

The PS Group is a diverse one, and during my time here, many people have come and gone. Together we form a vibrant mix of people from all over the world, and I enjoy our diverse cultural backgrounds. Thanks to all of you for the lively discussions, sweets & snacks from all continents, and generally a good time around our offices. Firstly, I want to acknowledge current colleague members of our group: Adriana, Alex, Alexander, Andreas, Berend-Jan, Bram, Cao Vinh, Duong Nhan, Ehsan, Fatjon, Frans, Hamed, Ikram, Jansi, Jeanne, Jeroen, Nikita, Paul, Rob, Sabari, Stephan, Viet Duc, Wei, and Yanqiu. Secondly, I want to acknowledge the former members of our group whom welcomed me and helped me during my master's thesis and at the start of my PhD research: Eyuel, Kallol, Kyle, Mitra, Muhammad Shoaib, Niels, Nirvana, Okan, Stijn, Vignesh Raja, and Wouter. Big thanks to Jeroen and Sabari for proof-reading parts of this thesis.

Dear Nicole, as our secretary you are the backbone of the group. Thank you for always promptly taking care of business and all the nice chats. You make the privileged traveling to conferences around the world a breeze and always bring a homely feeling to the office. I also want to thank Marloes for her former work as secretary during my time at the CAES and PS group.

Collecting data would not have been possible without the generous cooperation of the petting zoos and equestrian facility. I want to thank the Kinderboerderij De Proosdij in Ede, the Kinderboerderij Enschede-Noord, and manege de Horstlinde for their kind cooperation. I want to thank Lara, Romano, Vera, Heleen, Lieke, Chiel, Henjo, Helena, and Jan-Pieter for their help during the data collection and/or labeling processes.

During my PhD I have been privileged to supervise multiple students during their bachelor and master research projects. Thank you Dennis, Eric, Heleen, Helena, Jeroen, Lieke, Magdali, Martijn Renssen and Martijn de Vries. Through working with you I have been able to practice teaching and learn from the knowledge that you acquired in your studies.

In mijn tijd in Enschede heb ik veel nieuwe vrienden gemaakt. Bij deze wil ik alle Radix wortels bedanken voor de leuke en gezellige tijd op de maandagen. De 2-meter-afstudeer-wortel heeft gedurende mijn hele PhD fier in de hoek staan wortelschieten. Daarnaast wil ik in het bijzonder Jeroen, Martijn, Arjan en Koen bedanken voor alle gezellige momenten vanaf het moment dat jullie mij welkom heetten bij Radix.

Arjan, of eigenlijk Arie, tijdens de introductiedag van de pre-master wisten wij elkaar al te vinden en nog steeds zijn we goede vrienden. Jonathan, Barney, beste buurman, vanaf het moment dat je suiker kwam lenen aan de deur op de Marktstraat raakten we al snel bevriend. Ik geniet enorm van de sportieve weekendjes 'wanneer ze uitkomen' en wil jullie beide hartelijk bedanken voor de afleiding, ondersteuning, en motivatie tijdens mijn PhD. Chiel, ook jou ken ik al sinds de master en wil je bedanken voor alle gezellige momenten en fietsritjes door de prachtige omgeving van Enschede.

Al sinds mijn zesde levensjaar ben ik lid van Scouting Menkema in Uithuizen. Inmiddels voelen jullie meer als familie dan leden van een vereniging. Scouting heeft veel van

mijn kwaliteiten, zoals teamwork en organisatie, gevormd. Ik ben enorm dankbaar voor alle leuke tijden en lieve mensen bij Menkema en ik zet me dolgraag in voor deze club.

Nog voordat ik studeerde in Groningen raakte ik bevriend met de USSN groep: Anne, Hilbrand, Hugo, Jochem, Leon, Martijn, Mathijs, Michael, Nelson, en Thomas. Ik prijs mijzelf heel erg gelukkig met jullie als vriendengroep. Ik geniet enorm van de verjaardagen, feestjes, en de weekend-weekjes weg. Jullie zorgen altijd voor een volle bak ontspanning, gezelligheid, en inspiratie, bedankt! Mathijs, super bedankt voor het reviewen en bewerken van de Nederlandse samenvatting.

Thomas, jou wil ik graag in het bijzonder bedanken. Met geen ander kan ik zo goed sparren over allerlei onderwerpen in het leven. Als goede vriend sta je al sinds mijn tienerjaren dicht bij me en ben je meer verantwoordelijk voor de persoon wie ik nu ben dan we zelf wellicht beseffen. Zo motiveerde je mij onder andere om op kamers te gaan in Groningen en vooral een HBO studie te gaan doen, wat uiteindelijk heeft doorgewerkt tot dit boekje. Ook tijdens de zware lootjes op het eind van mijn PhD was jouw steun heel fijn, dankjewel.

Naast deze vriendengroepen zijn er nog een hele hoop andere toppers met wie ik altijd een hoop lol beleef en wie een gouden rand geven aan het leven: Aart, Aniek, Danielle, Dorien, Erik, Harm, Harmen, Hermien, Jaap, Jacob, Jake, Jan, Kelly, Klaas Bernd, Michiel, Nick, Saminna, Stefan, en Suze. Ik wil iedereen bedanken voor alle toffe festivals, uitjes, hikes, feestjes, steun en toeverlaat: proost!

Ik wil graag mijn opa en oma, Corrie en Jacob, en de familie van Dijk en Kamminga, bedanken voor alle interesse, liefde en steun. Lieve Anna, of eigenlijk oma Kamminga, helaas heb je ons inmiddels verlaten en net niet mijn verdediging mogen meemaken. Voor jou was ik altijd de kleinzoon "dei altied aan 't leern" was en jouw trots zal ik nooit vergeten. Jantina, Anne, en Corianne: ik ben dolblij met jullie als zussen en broer en wil jullie bedanken omdat ik weet dat jullie er altijd voor me zullen zijn. Ook wil ik mijn schoonfamilie Tuin 'De Toenties' bedanken voor het warme welkom in de familie en alle interesse, liefde, en de fijne dagen samen aan alle kanten van de wereld.

Lieve pa en moe, ik wil jullie bedanken voor de oneindige liefde, interesse en ondersteuning tijdens mijn studie. Thuis in Eppenhuisen staat de deur altijd wagenwijd open en bij jullie kan ik altijd weer opladen. Jullie trots is altijd een motivatie geweest en zal dit ook altijd blijven. *"Dou goud wat mout, zet altied deur, hol kop ter veur."* Deze boodschap staat bij ons op een tegeltje en verwoord heel mooi de kernwaarden die ik van jullie heb geleerd. De Groningse nuchterheid is mij al vroeg aangeleerd op het land en is uitgegroeid tot een doorzettingsvermogen die mij heeft geholpen om te komen tot het resultaat wat nu voor jullie ligt, dankjulliewel voor alles.

Lieve Janneke, geen woorden kunnen uitdrukken hoeveel jij voor mij betekent. Ik ben super trots op jou en bevind me in de zevende hemel omdat wij samen als een team door het leven gaan. Jij weet me altijd weer te motiveren om door te zetten en ook inhoudelijk was jouw input voor deze thesis altijd heel waardevol. Dankjewel dat je er altijd voor me bent. Ik kijk er ontzettend naar uit om samen met jou onze kinderen de wereld te laten ontdekken.

Jacob

Enschede, maart 2020

CONTENTS

1	Introduction	1
1.1	Introduction	2
1.1.1	Chapter Organization	3
1.2	Applications	4
1.2.1	Foundation for Poaching Detection	4
1.2.2	Animal Ecology, Wildlife Monitoring and Preservation.	6
1.2.3	Livestock Monitoring	8
1.2.4	E-health for Pets	8
1.3	Challenges and Requirements	9
1.3.1	Resource Constraints	9
1.3.2	Dynamic Sensor Position and Orientation	9
1.3.3	Heterogeneity	10
1.3.4	Data Acquisition and Annotation	11
1.4	Research Objectives, Questions, and Hypotheses	11
1.5	Contributions	13
1.6	Thesis Organization.	15
2	Animal Activity Recognition – the State of the Art	17
2.1	Introduction	18
2.1.1	Chapter Organization	18
2.2	Animal Activity Recognition Pipeline	18
2.2.1	Data Acquisition	19
2.2.2	Pre-processing and Segmentation	22
2.2.3	Feature Extraction and Selection.	23
2.2.4	Training	24
2.2.5	Classification	25
2.2.6	Evaluation	25
2.3	Survey.	27
2.3.1	Discussion	32
2.4	Conclusion	32
3	Data – Acquisition, Description, and Labeling	35
3.1	Introduction	36
3.2	Motion Data of Goats and Sheep	37
3.2.1	Methods	37
3.2.2	Data Description.	40
3.3	Multi Sensor-Orientation Motion Data of Goats.	41
3.3.1	Methods	45
3.3.2	Data Description.	45

3.4	Horse Motion Data	49
3.4.1	Methods	51
3.4.2	Data Description.	54
3.5	Data Labeling.	58
3.5.1	Introduction	58
3.5.2	Synchronization Between Sensors and Cameras	61
3.5.3	Discussion	62
3.5.4	Future Work	62
3.6	Conclusions.	63
4	Multitask Learning Based Animal Activity Recognition on Collar tags	65
4.1	Introduction	66
4.1.1	Chapter Organization	67
4.2	Data Description and Preprocessing	67
4.3	Multitask Learning	69
4.4	Methods	69
4.4.1	Feature Extraction and Selection.	73
4.4.2	Animal Activity Recognition Classifiers	74
4.4.3	Parameter Optimization	75
4.5	Effect of Multitask Learning on Animal Activity Recognition Performance	75
4.5.1	Scenario 1: Individual Animal Activity Recognition	76
4.5.2	Scenario 2: Multitask Learning Within Species	76
4.5.3	Scenario 3: Multitask Learning Between Species	77
4.6	Analyzing Impact of Window Size and Sampling Rate	77
4.6.1	Effect of Window Size on Classification Performance	78
4.6.2	Effect of Sampling Rate on Classification Performance.	79
4.7	Resource Usage	80
4.8	Conclusions.	84
5	Sensor Orientation-Independent Feature Selection	85
5.1	Introduction	86
5.1.1	Orientation-Independent Features.	87
5.1.2	An Overview of our Approach	88
5.1.3	Chapter Organization	88
5.2	Related Work	88
5.2.1	Feature extraction and classification	88
5.2.2	Sensor-orientation Independent Activity Recognition	89
5.3	Methodology	90
5.3.1	Feature Extraction	92
5.3.2	Filter: Chi-Squared Test [130]	93
5.3.3	Embedded Forward Selection	93
5.3.4	Optimal Feature Set Selection	94
5.4	Data Description and Preprocessing	95
5.4.1	Data Partitioning for Training, Validation, and Testing	95

5.5	Evaluation	96
5.5.1	Evaluation of Feature Selection	97
5.5.2	Optimal Feature Set Performance	100
5.6	Conclusions.	112
6	Factors that Influence Animal Activity Recognition Performance	115
6.1	Introduction	116
6.1.1	Type and Number of Features	116
6.1.2	Data Partitioning Methods	117
6.1.3	Hyperparameter Tuning	117
6.1.4	Chapter Organization	118
6.2	Methodology	118
6.2.1	Dataset and Preprocessing.	119
6.2.2	Classifiers	121
6.3	Evaluation	122
6.3.1	Effect of Feature Selection	122
6.3.2	Effect of Time and Frequency Domain Features	123
6.3.3	Effect of the Data Partitioning Method	124
6.3.4	Effect of Hyperparameter Tuning	125
6.3.5	Overall Observation	125
6.4	Conclusion	127
6.4.1	Classifier.	127
6.4.2	Feature Type	127
6.4.3	Data Partitioning Method	127
6.4.4	Hyperparameter Tuning	128
7	Deep Unsupervised Representation Learning Techniques for Animal Activity Recognition	129
7.1	Introduction	130
7.1.1	Chapter Organization	132
7.2	Methodology	132
7.2.1	Feature Extraction Methods	132
7.2.2	Effect of Size of the Labeled and Unlabeled Data.	136
7.2.3	Effect of Depth.	141
7.2.4	Effect of Imbalanced Data	141
7.3	Data Description and Preprocessing	142
7.4	Evaluation	145
7.4.1	Varying Size of the Labeled Dataset	145
7.4.2	Varying Size of the Unlabeled Dataset	151
7.5	Discussion	151
7.6	Conclusion	156
8	Conclusions and Future Work	157
8.1	Research Summary	158
8.2	Lessons Learned	161
8.3	Future Work.	163

A Representation Architectures	167
A.1 Principal Component Analysis	167
A.2 Deep net Comprising 2 Stacked Sparse Auto Encoders	167
A.3 Convolutional Deep Belief Network.	169
Acronyms	173
Bibliography	177
About the Author	195
List of Publications	197

1

INTRODUCTION

In this chapter, we introduce and motivate the importance of online animal activity recognition (AAR). The activity of animals is a rich source of information that reveals not only insights into their life and well-being but also their environment. The advent of small, lightweight, and low-power electronics opened up the possibility to recognize various activities locally on tags worn by animals. These tags can process raw sensor data to classify these activities online. AAR supports various application domains, including but not limited to: poaching detection, wildlife monitoring, livestock management, and e-health for pets. In this thesis, we address challenges that impact the performance of online AAR. In this chapter, we describe the characteristics of AAR, present the prospective application domains, challenges and requirements, research objectives and hypotheses, and the contributions of this thesis. We conclude with an overview of the thesis organization.

1.1 INTRODUCTION

The ability to automatically recognize animal activity from sensor data may be essential for their survival. In 2018, Bar-On et al. [14] estimated that out of all living mammals on Earth 60 % are livestock, 36 % humans, and only 4 % are wild animals. In a relatively short period, human development of civilization caused a loss of 83 % of all wildlife and 50 % of all plants. Moreover, the current rate of the global decline in wildlife populations is unprecedented in human history – and the rate of species extinctions is accelerating [37]. Throughout 2016, a rhino was killed every 8 hours for its horn in South Africa alone [139]. Moreover, an elephant is killed every 20 minutes [188]. Simultaneously, the human population keeps growing, and as living standards in developing countries improve, the demand for meat and dairy products increases [47]. A better insight into the well-being of livestock is not only an opportunity to improve their lives [117] but also an opportunity to help farmers produce more efficiently [105]. Ultimately, understanding the ecology of wild animals provides critical insight that allows world politics to make better choices to guarantee their survival. It is vital to study the ecology of wildlife for their conservation and the well-being of livestock to improve their lives.

Fortunately, over the last decades, the tremendous innovation in technological developments offer a wide variety of tools for researchers to study animal ecology [185]. The behavior of animals is a rich source of information that not only provides insights into their life and well-being but also their environment [119, 129]. The advent of small, lightweight, and low-power electronics has made it possible to continuously measure a wide range of aspects regarding the animal's state (e.g., location, activities, interactions with other animals) and the environment (e.g., temperature, humidity, depth) [185] on the animal itself (online). These aspects are highly informative and open up a wide range of possibilities for numerous application domains. In this thesis, we focus on a technology that measures a vital and informative aspect – online animal activity recognition (AAR). Specifically, we investigate AAR using data from sensors on a tag attached to the animal, usually utilizing a collar around the neck. Attaching tags to animals puts restrictions on the size and weight of the tags, which limits the available energy and computational resources. Therefore, many AAR approaches utilize (3D) motion data that is recorded with inertial measurement units (IMUs) because these sensors are tiny, lightweight, and require little energy. An IMU generally consists of an accelerometer, gyroscope, and magnetometer, which measure acceleration, angular velocity, and magnetism, respectively. The main task of AAR is to explicitly link the measurements from the IMU to the corresponding physical activities of the animal. The performance of AAR is challenged by many factors, such as sensor-properties, sensitivity to individual traits, and the used algorithms for classification. In this thesis, we address these challenges by studying the effect of various factors on the performance of AAR, using real-world data that was recorded from sheep, goats, and horses. Our primary goal is to not only improve the performance of AAR, but also investigate genericity, robustness, and overall efficiency. Furthermore, we address issues related to machine learning (ML), data collection, annotation (labeling), and learning structure from unlabeled data.

Machine learning algorithms are commonly used to classify activities from sensor data. As such, AAR both begins and ends with sets of neurons – only one part of the neurons in the following example are biological. Ultimately, the activity performed by an animal originates from neurons in its brain. For example, the ability to smell comes from specialized cells, called olfactory sensory neurons. These neurons are located in a small patch of tissue high inside the nose and directly connected to the brain. Apart from intrinsic motivations, animals respond to what they perceive in their environment [120]. When a prey animal smells an approaching predator, it is alerted and often initiates a fleeing strategy [35]. Thus, after the perception of the world through senses such as smell, sight, or hearing, motor neurons in the brain eventually fire and send impulses to various muscles in the body. The muscles are activated in specific sequences to make the animal move. The goal of AAR is to measure these sequences and link them to specific activity classes. The output of AAR, recognized activities over time, may be used to infer the behavior of the animal and its relation with the environment. For example, one could aim to infer whether an alarmed herd sensed a predator, forest fire, or a poacher.

Attaching sensors to animals should be done unobtrusively. Therefore, the movement is measured with noninvasive methods such as small and lightweight motion sensors in the form of accelerometers and gyroscopes. These sensors measure the movements and sample them into time-series data. Subsequently, the recorded data must be inferred so that it can be linked to specific activities. The inference can be performed locally – on the collar tag – while activities are being performed (online), or subsequently and remotely on a server (offline). Recently, many researchers have utilized a wide variety of ML techniques to learn the relation between the raw data and the performed activities. Many ML techniques are derived from artificial neural networks (ANNs), which in turn are inspired by, but not identical to, biological neural networks. Raw data samples are fed into an ANN that learns to link the raw data to a specific output. It does so by learning a relation between the distribution of sampled data and given labels provided by a human annotator. A label acts as ground truth to what activity the animal was performing when the sensor data was recorded. A trained ANN links each segment of recorded IMU data to an output neuron that, in our case, corresponds to the activity class. Usually, an ANN classifier contains one output neuron for each activity, and the one that represents the activity being performed is activated. How the information from the activity neuron is further used depends on the AAR application. For example, the perceived activities can be efficiently logged on the tag and wirelessly transmitted to a central location when a good connection becomes available (e.g., the animal moves within the range of a communication network).

1.1.1 CHAPTER ORGANIZATION

The rest of the chapter is organized as follows. In the following section we discuss various application domains that are supported by AAR. In Section 1.3, we discuss the challenges and requirements of AAR. Subsequently, we discuss our research objective, questions, and hypotheses in Section 1.4. We present our contributions that address the research questions in Section 1.5. Finally, we discuss the organization of the remainder of this thesis in Section 1.6.

1.2 APPLICATIONS

AAR has recently sparked the interest of many researchers because of its potential to support various application domains. The output of AAR is the recognized activity performed by the animal. The activity data can be used stand-alone and combined with other sources such as location data derived from a Global Positioning System (GPS). Among several properties, animal behavior can be inferred from the different types of activities that an animal exercises over a day, the duration of these activities, their location, and movement patterns [120]. Animal behavior encompasses the ways animals interact with each other, their environment, and other species. The behavior can be a rich source of information regarding the animal's well-being and environment. For example, when a cow's food intake declines over a day, this might be a sign of health issues [38, 105]. Furthermore, the behavior of groups of animals can be an indicator of the occurrence of environmental events such as forest fires [146], poaching activities [44], and environmental problems [129]. Or, when a herd of prey animals suddenly stops grazing and disperses, it may indicate the presence of an external factor such as a predator or poacher. In the following subsections, we introduce several domains that can be supported by AAR.

1.2.1 FOUNDATION FOR POACHING DETECTION

Throughout 2016 a rhino was killed every 8 hours for its horn in the Republic of South Africa alone [139]. Moreover, an elephant is currently killed every 20 min each day [188]. These magnificent animals are shown in Figure 1.1.

(a)

(b)

Figure 1.1: (a) White Rhinoceros and (b) African Elephants in their natural habitats.

The poaching statistics total up to 1054 rhino deaths in a population of roughly 25,000 and 27,000 elephant deaths [40, 138, 139] in a population of roughly 377,000 [30]. Figure 1.2 shows the number of poached rhinos per year.

Due to increased protection efforts, the rhino poaching trend is declining, although the losses are still extremely high. If poaching is not halted soon, the existing rhino population will not be able to procreate rapidly enough and start to diminish once more. Between the year 1900 and today, roughly 90 % of African elephants

Figure 1.2: Number of poached rhinos in South Africa, adopted from the data published by the South African Department of Environmental Affairs (2017) [139].

disappeared [30]. The elephant population is currently shrinking rapidly, with 8% per year continent-wide across Africa [30]. The belief that a rhinoceros horn has medicinal power, together with increasing wealth of the population, fuels the demand for rhino horns and ivory in Asian countries such as Vietnam and China [138, 139]. Unfortunately, poaching is not limited to rhinos and elephants: amongst other species, tigers and pangolins are also extremely threatened by poaching for their skin, bones, and scales [184]. The risks that are involved with poaching are relatively low when compared to drug trafficking, yet high profits can be generated [189]. Therefore, the trade of ivory and rhinoceros horn, unfortunately, remains a lucrative business for criminal syndicates [189]. Ultimately, the best solution to poaching is the eradication of demand for rhino horn, ivory, and other wildlife products [184]. Until the demand has successfully been eradicated, it remains critically important to protect the ever more fragile wildlife populations against poachers. In this section, we motivate why robust AAR should be developed as a foundation for anti-poaching systems (APSS).

1.2.1.1 LINKING ANIMAL BEHAVIOR TO POACHING DETECTION

Animal behaviors and reactions are sometimes used as detection systems. A well-known example is the ‘canary in the coal mine.’ Until late in the 20th century, a canary was taken into coal mines by miners to be utilized as an early-warning signal for toxic gases, primarily carbon monoxide. Birds are more sensitive than humans and become sick or die before the miners would and thus act as a ‘chemical indicator’ [129]. Animal sentinels are often used in situations when (i) humans cannot always be on the alert, (ii) animals have better senses, or (iii) humans cannot safely go to places. Some reviewed works suggested utilizing animal sentinels for the detection of poachers [44]. In the natural environment, animals are used indirectly for surveillance [129]. Animals make sound calls and have

physical reactions when they sense danger. Dog barking or strident bird calls are sounds that are recognized by multiple species, including humans, and can be utilized as an alarm or early warning. The frenetic behavior of bees, beetles, birds, and rodents can indicate a forest fire or impending storm, while elephants can hear and feel infrasonic vibrations and know when a large animal, vehicle, earthquake, or storm might be approaching [88, 146, 193]. Hence, animal behavior can provide an early warning that can help to sense danger. In 2007, Yasar et al. [146] proposed the utilizing of animal behavior to assist in the early detection of forest fires. Similarly, in a concept paper, Banzi et al. [44] suggested utilizing wild animals' behavior to stop poaching. They propose protecting elephants from poaching by attaching an appropriate sensor on their body with a visual, IR camera, and GPS.

The development of cognitive sensor systems, through the combination of multiple sensor technologies and ML techniques, might be able to tackle the numerous challenges found in ineffective poaching detection. We coin the term 'cognitive sensor systems' because current technology allows us to create sensory systems that are not only capable of perception but also able to learn over time as more data is collected. Recently, the concept of utilizing animal sentinels for the detection of poaching has been proposed, but many challenges remain open for future research. The foundation for this can be the sensitive nature of wildlife that co-habit wildlife areas with species that are under threat of extinction due to poaching. Besides forming a foundation for poaching detection, the collaring and monitoring of wild animals allows researchers to collect a vast amount of information for the ecological study of wildlife. We elaborate this discussion in Section 1.2.2.

1.2.2 ANIMAL ECOLOGY, WILDLIFE MONITORING AND PRESERVATION

Collaring technology has immense potential for research in the field of basic and applied animal ecology [34]. The Animal Movement Ecology field argues that the movement of individual organisms is associated with significant problems, including habitat fragmentation, climate change, biological invasions, and the spread of pests and diseases [119]. Moreover, animal behavior provides information about social interaction within a herd [21]. A major challenge in movement ecology research is to explicitly link the statistical properties of movement patterns to specific internal traits and behaviors. Therefore, enriching location data with actual behavioral statistics supports animal ecology research. The advent of online AAR allows ecologists to investigate the physiological performance of animals, energetics, foraging, migration, habitat selection, and social interactions of wild animals [21, 185]. Figure 1.3 shows a collared lioness during a recent study in the wild.

Movement ecology integrates conceptual, theoretical, methodological, and empirical frameworks for studying the movement of all organisms, from microbes to trees to elephants [120]. Movement ecology depicts the interplay among four essential mechanistic components of movement by organism: the internal state (why move?), motion (how to move?), navigation capacities of the individual (when and where to move?), and the external factors affecting movement [119]. By classifying the behavior, AAR allows researchers in movement ecology to study the link between movement, energy expenditure, and behavior [120].

Figure 1.3: A lioness and her cubs. The lioness is wearing a collar equipped with various sensors. (Photo credit: Carli Coco & Caleb M. Bryce)

Attaching sensors to animals can collect a wide range of environmental data. Wilmers et al. [185] imagine a future where large birds are used to sample air quality across the oceans, wolverines measure snow-pack and weather conditions in remote mountain areas, or arboreal species in forests monitoring high-canopy micro-climates.

Furthermore, AAR ultimately supports the validation of the vital role animals play for human existence because it improves our understanding of species and their interaction with the environment. In a rapidly changing climate [110, 172], the effect of human civilization grows, and the risk of collapsing ecosystems is imminent. Animals play a critical role in these ecosystems; maintaining ecosystem sustainability is the only way a continued supply of resources such as water, food, and building materials can be guaranteed. Therefore, cogent evidence must be collected and compiled so that the connections between animals, ecosystems, and human survival become evident to a broader public, which in turn should force political leaders worldwide to take the urgent actions that are necessary [110, 172]. Detailed and accurate animal activity measurements support the research and validation of the link between the impact of human civilization on the decline and loss of species worldwide, which eventually can lead to the collapse of complete ecosystems, including humans. Therefore, there is an urgent need for robust AAR that can be rapidly deployed and easily used across a wide variety of species.

1.2.3 LIVESTOCK MONITORING

In recent years there has been substantial interest in the monitoring of livestock. Online AAR may improve the living standard of livestock by reporting a possible injury to the farmer so that healthcare can be provided swiftly.

Smart dairy farming is a new paradigm in the dairy industry [105]. AAR supports numerous objectives within smart dairy farming. For example, the insemination of cows must only take place when the cow is fertile (during estrus). On average, the estrus period lasts approximately 15 to 18 hours and the cow has to be inseminated within this period. The farmer observes changing behavior of the cow, such as lower feed intake and increased walking [105], to detect estrus. If the period is missed and the cow is not pregnant, the farmer must wait for three weeks and try again which negatively affects milk production. Estrus can be detected through AAR because the activity patterns change [38]. Roelofs et al. [141] showed that the step count of the animals is a simple but informative indication for estrus detection.

Furthermore, a farmer has to be around a calving cow to make sure that the delivery takes place in good order. The time to start delivery can take a while, and the farmer needs to check regularly. However, when a cow starts calving, its tail swags continuously, therefore by attaching a sensor to the tail, the start of delivery can be easily detected [107].

Lameness is an abnormal gait or posture of an animal that is caused by dysfunction of the locomotor system. The condition affects the well-being of horses and livestock, such as cows. It is considered a significant problem that affects both the animal's well-being and farm productivity [2]. AAR is a prospective technology to aid in the early detection of lameness [2, 173]. Other applications in livestock management are health monitoring, such as the detection of pain, heat stress, and social interactions within a herd [38].

Another exciting domain is the research in grazing behavior of cattle. Whittington et al. [183] have demonstrated a relationship between the meat quality and the botanical composition in the pasture. Thus, when the pasture types are known, and a monitoring system tracks where the cattle are grazing, these can form the basis of premium quality meat marketing [183].

1.2.4 E-HEALTH FOR PETS

There is an increasing interest in the exploration of innovative smart systems to keep track of welfare of domestic animals [69]. Recently, multiple activity-tracking systems have been commercially released. These systems keep track of the activity of domestic animals such as cats [106], dogs [69], and horses [41]. Horses are very popular domestic animals and there are over 58 million horses worldwide, of which over 40 % are kept as recreational horses and another 40 % are kept for performance competitions [41]. These animals are valuable to their owners. However, horse owners cannot watch their horses all day, but would like to know whether their horses have exercised enough during the day or when they are showing odd behavior, which could indicate an injury such as a colic, lameness, or issue within or near the pasture. To keep track of the activities of their horses during the day, horse owners can use a real-time activity tracker, based on AAR [41].

1.3 CHALLENGES AND REQUIREMENTS

Monitoring and activity recognition of livestock and wildlife using collar tags is challenging for several reasons. In this section, we list the challenges of AAR along with essential requirements.

1.3.1 RESOURCE CONSTRAINTS

AAR systems that utilize sensors located on or near animals must consider ethical and legal implications. The accepted collar-to-subject weight ratio depends on the size of the animal, and the used weights in the literature vary from 0.7 % to 9 % of body mass, where smaller animals generally carry a greater proportional collar weight [8, 24].

Multiple application domains for AAR involve the monitoring of animals that are dispersed in widespread and remote areas. Therefore, a collar tag should last a lifetime, especially in the case of wildlife monitoring. It is dangerous, expensive, stressful, and sometimes impossible to recapture the animals to charge or replace the collar tag. Collar tags have limited computational and memory resources, mainly due to the constraints for weight, size, and limited available energy. Therefore, the energy consumption of any processing taking place on the collar tag must be kept to a minimum.

Most applications, such as e-health, poaching detection, or wildlife monitoring, require or greatly benefit from online feedback. Furthermore, it is not always possible to store raw data on the collar due to the memory constraint. Wireless transmission of the data enables online feedback, which eliminates the need for local storage of raw data, and allows central processing. However, transmissions are costly in terms of power, and a good wireless link is not always available. Although network constraints are not the focus of this thesis, they are an essential motivation. Processing raw data online requires significantly less energy, storage space, and network connectivity in comparison to transmitting the raw data. Additionally, online AAR provides an embedded system with context regarding an animal's current activity, which allows the system to save energy by efficiently adapting its resource usage, e.g., the device can sleep when the animal is sedentary. Therefore, activity recognition needs to be executed online and locally.

Computational and memory complexity should be kept to a minimum, and the trade-off between AAR performance and resource efficiency carefully evaluated to allow longer lifetimes of an animal tag. In Chapter 2, we explain that complexity is found in two parts of an AAR system: first, in the calculation of features from the sensor data, which act as data points for the classification task, and second, in the ML algorithm that is used for this classification. It is our challenge to find an optimal combination of the two to both minimize computational cost and maximize AAR performance.

1.3.2 DYNAMIC SENSOR POSITION AND ORIENTATION

Animal tags are subject to rough environments and intense movement behavior and are likely to shift and rotate throughout the day [87, 126, 174]. Many studies assume that the orientation of a sensor on a body is fixed when classifying activity [84, 133, 194]. However, the variability in sensor-orientation causes significant errors if activity classifiers are sensitive to sensor orientation. Therefore, activity classifiers must be insensitive to sensor orientation.

1.3.3 HETEROGENEITY

AAR is heterogeneous in three main forms: animals, features, and classifiers, which will be discussed in the following subsections.

1.3.3.1 ANIMALS

Individual subjects within a species physically differ from each other (e.g., different age, height, or health). Moreover, some application domains (e.g., poaching detection) may require the monitoring of subjects that belong to different species. Thus, activity data is heterogeneous, and it is challenging to improve the genericity of AAR to the point it is usable for a larger population of subjects when training data is only available from a subset of the population. On the one hand, an overspecific classifier performs well on training data, but poorly on test data, or during deployment. On the other hand, collecting a sufficient amount of training data for each individual or type of species is infeasible. Therefore, a significant challenge of AAR is to minimize the amount of required training data and improve the genericity of the classification within one species (e.g., young, old, small, large) or even between species (e.g., sheep and goats).

1.3.3.2 FEATURES

The performance of machine learning (ML) algorithms heavily depends on the type and quality of the features that describe the raw data [16]. Therefore, feature extraction is an essential challenge in AAR [94]. The objective of feature extraction is to transform raw input data into a compact and descriptive feature vector. The total number of extracted features forms the feature space. Ideally, each activity is clustered and well separated from other activities in the feature space. The challenge in feature extraction is to find the best features that represent the (high dimensional) raw sensor data. Useful features should be insensitive to individual traits and external factors (such as the sensor-orientation). Numerous features can be extracted from raw sensor data, and the computation of each feature requires energy. Due to the resource limitations of collar tags, it is important to extract only those features that best separate data from different activities. Furthermore, different feature types can be calculated, such as frequency and time-domain summary statistics, and the type may impact the performance and resource requirements.

1.3.3.3 CLASSIFIERS AND PARAMETERS

ML has been a popular technology for decades and is widely used across a variety of domains due to its tremendous potential. As a consequence, a large number of ML algorithms have been developed for a wide range of tasks. Each algorithm has specific properties and hyperparameters that affect the performance of AAR. Hyperparameters are parameters that are given a value before the training process. Most classifiers have multiple hyperparameters, and finding the right combination is challenging. Hyperparameter tuning aims to automatically discover a set of parameter settings that yield the best performance, but its impact may vary between different classifiers.

Furthermore, there are various methods to validate ML algorithms, and the method itself also affects performance. For example, there are multiple approaches to partition the dataset into training and testing sets for the validation of the trained classifier. The

partitioning method is a challenge because it affects the composition of the datasets, and in turn, this impacts the performance.

1.3.4 DATA ACQUISITION AND ANNOTATION

Wildlife and livestock can roam around vast areas that are difficult to traverse. Wolves, for example, have home ranges up to 1700 km² [115] – this is more than twice the size of New York. It is not very easy to find and observe animals. Therefore, it is often hard to collect videos (ground truth data) of collared animals. Moreover, the synchronization of videos with sensor data and manual annotation is laborious, expensive, and tedious. Because of this, the proportion of labeled movement data that is collected in the wild is usually small. Furthermore, it is difficult to estimate the required minimum amount of labeled data for good AAR performance beforehand. Activity datasets are naturally imbalanced because some activities are either not frequently performed, or challenging to observe. The imbalance has a significant effect on the performance of an AAR classifier [65].

1.4 RESEARCH OBJECTIVES, QUESTIONS, AND HYPOTHESES

Our main research objective is accurate, resource-efficient, and robust AAR using small and lightweight IMUs. In this dissertation, we aim to answer the following main research question:

How can we recognize various animal activities using motion data while considering resource-efficiency, orientation-independence, and genericity so that it can be executed online and easily deployed across a wide variety of species?

In the following, we break down the main research question and pose several more detailed sub-questions. In Section 1.3.4 we discussed the data acquisition challenge. Obtaining labeled motion data from a large number of animals is a tedious and challenging task. To address the difficulty in the acquisition and labeling of animal motion data, we ask the following research question:

RQ 1: *What is an efficient method in terms of time and effort to acquire and annotate sufficient sensor data from a group of animals?*

To answer this question we propose the following hypothesis:

Hypothesis 1: *Synchronizing motion data with ground-truth video, through real-time clock (RTC) timestamps, enables the recording of multiple subjects simultaneously and simplifies the annotation process.*

We discussed the challenge of heterogeneity of animals in Section 1.3.3.1. Our objective is to enable AAR for a wide variety of animals: small and big, young and old. Moreover, our objective is to support AAR that is easily deployed across a variety of species. Together, the heterogeneity in animals, and the challenge of acquiring labeled data, motivate the exploration of generic AAR. To support AAR that does not only generalize to multiple individuals but also multiple species, we pose the following research question:

RQ 2: *To what extent can the genericity performance of an AAR classifier for a group of animals be improved?*

To answer this question we propose the following hypothesis:

Hypothesis 2: *If animal-subjects, the sensor location and type, and the learning-task are similar, an AAR classifier can be trained using multitask learning (MTL) to improve the genericity performance of the classifier significantly.*

In Section 1.3.2, we discussed the challenge of collars that rotate over time around the neck of animals. Our objective is to investigate AAR that is invariant to the position and orientation of the sensor. Simultaneously, we discussed the challenge of resource constraints in Section 1.3.1. To address AAR that is both robust against the sensor position and orientation, and resource-efficient, we pose the following research question:

RQ 3: *Which method yields AAR that is both robust against the sensor-orientation and resource-efficient?*

To answer this question we propose the following hypothesis:

Hypothesis 3: *Using motion data collected from multiple sensor positions and orientations, a combination of filter and wrapper methods can select a small and resource-efficient feature-subset that is orientation-independent.*

In Section 1.3.3.3, we discussed the challenge of heterogeneity of ML algorithms for AAR classification. Furthermore, we discussed the challenge of tuning hyperparameters and the influence of the validation-data partitioning method (dividing the dataset into training and testing datasets). At the same time, we discussed the challenge of feature types in Section 1.3.3.2. To investigate and explain the impact of these factors on the performance, we pose the following question:

RQ 4: *To what extent do the validation-data partitioning method, hyperparameter tuning, and the feature-type affect the performance of orientation-independent AAR classifiers?*

To answer this question we propose the following hypothesis:

Hypothesis 4: *The data partitioning method, hyperparameter tuning, and the feature-type have a significant effect on the performance of orientation-independent AAR classifiers.*

In Section 1.3.4, we discussed that collecting a sufficient amount of labeled motion data is a daunting task. However, it is relatively easy to obtain vast amounts of unlabeled motion data. Therefore, we pose the following research question:

RQ 5: *What technique can extract meaningful information from unlabeled motion data to improve AAR performance, and to what extent does the performance improve with more data?*

To answer this question we propose the following hypothesis:

Hypothesis 5: *Unsupervised representation learning is a feature extraction method that can be trained with unlabeled data to extract features for orientation-independent AAR and the quality of the feature-extraction increases with the size of the unlabeled dataset.*

In the following section, we present the contributions of this dissertation in answer to the research questions that were posed here.

1.5 CONTRIBUTIONS

Considering the aforementioned research objective, questions, and hypotheses we sum up the research contributions of this thesis below.

CONTRIBUTION 1: ANIMAL ACTIVITY RECOGNITION SURVEY

In Chapter 2, we conduct a literature study that positions the work presented in this thesis in terms of the state of the art. We compare the existing work in AAR and discuss the open research challenges. We compare the following factors in AAR research: the number of subjects used in the study, number and type of activities to be recognized, used features, sensor modalities, orientation-independence, classifier type, evaluation method, and performance.

CONTRIBUTION 2: SENSOR-VIDEO SYNCHRONIZATION AND LABELING TOOL

To answer RQ 1, we discuss a synchronization method to synchronize videos with sensor data. The method has been used to develop a labeling application that is described in Chapter 3. Annotations (labels) can be added to the data, and the produced labeled dataset can be exported. The research and labeling tool have appeared in [72, 78]:

[78] J. W. Kamminga, M. Jones, K. Seppi, N. Meratnia, and P. J. Havinga. Synchronization between sensors and cameras in movement data labeling frameworks. In *the second Workshop on Data Acquisition To Analysis (DATA'19)*, November 10, 2019, New York, NY, USA, New York, NY, 2019. Association for Computing Machinery. doi:10.1145/3359427.3361920

[72] J. Kamminga. jacob-kamminga/Matlab-movement-data-labeling-tool: Generic version release., 8 2019. doi:10.5281/zenodo.3364004

CONTRIBUTION 3: DATASETS

Motion data from different animals was required to answer the research questions. At the start of this research, no such data was available and needed to be collected. All collected data is available online with open access. The collection process is described in detail so that other researchers can use the data for their research. The dataset composition and collection methodology are presented in Chapter 3. In total, we collected three datasets.

Firstly, we collected a dataset to study the genericity performance of AAR algorithms across individuals and species. The dataset comprises motion data from 4 goats and 2 sheep that is collected simultaneously. Secondly, we collected a dataset to study orientation-independent feature selection for AAR. The dataset comprises motion data from 5 goats that is collected from 6 diverse positions and orientation around the neck of the animals simultaneously. Thirdly, we collected a large dataset from 18 horses at an equestrian facility over 7 days. Data from 11 subjects is labeled, but for 6 subjects, the data is labeled more extensively for 6 activities. A large amount of additional unlabeled data makes this dataset particularly interesting for unsupervised AAR research. The datasets and their descriptions have appeared in [70, 71, 77, 83]:

[70] J. Kamminga. Dataset: Generic Online Animal Activity Recognition on Collar Tags., Sep 2017. doi:10.17026/dans-zp6-fmna

[71] J. Kamminga. Dataset: Multi Sensor-Orientation Movement Data of Goats, March 2018. doi:10.17026/dans-xhn-bsfb

- [77] J. W. Kamminga, L. M. Janßen, N. Meratnia, and P. J. M. Havinga. Horsing Around—A Dataset Comprising Horse Movement. *Data*, 4(4):131, 9 2019. doi:10.3390/data4040131
- [83] J. W. Kamminga, N. Meratnia, and P. J. Havinga. Dataset: Horse Movement Data and Analysis of its Potential for Activity Recognition. In *the second Workshop on Data Acquisition To Analysis (DATA'19)*, November 10, 2019, New York, NY, USA, New York, NY, 2019. Association for Computing Machinery. doi:10.1145/3359427.3361908

CONTRIBUTION 4: MULTI-TASK LEARNING FRAMEWORK

To answer RQ 2, we propose a framework that employs MTL [28] for embedded platforms. In Chapter 4, we investigate the trade-off between AAR performance and the generalization capability of an AAR system. Specifically, we study the effect of MTL on the performance of a single AAR system that classifies the activities of two species. We test and compare 7 classifiers in three scenarios: (i.) trained with individual data, (ii.) trained with data from one species and tested on the other and vice versa, and (iii.) trained with mixed data from both species. Although the investigation using two species is insufficient to draw a broad conclusion, the results are a good indication of the possibility to train classifiers with good genericity performance for similar species. Additionally, we analyze the complexity in terms of memory and CPU usage between 7 classifier types to reflect on the implementation in animal tags. This contribution has appeared in [76]:

- [76] J. W. Kamminga, H. C. Bisby, D. V. Le, N. Meratnia, and P. J. M. Havinga. Generic Online Animal Activity Recognition on Collar Tags. In *Proceedings of the 2017 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2017 ACM International Symposium on Wearable Computers - UbiComp '17*, pages 597–606, New York, NY, 2017. ACM Press. doi:10.1145/3123024.3124407

CONTRIBUTION 5: SENSOR-ORIENTATION-INDEPENDENT FEATURE SELECTION FRAMEWORK

To answer RQ 3, we present a framework that aims at finding the optimal feature sets that are lightweight and robust to the sensor's orientation. We reveal features that are orientation-independent, robust, and suitable for implementing animal activity recognition on online embedded platforms. Our approach uses 3D motion data to extract various summary statistic features. We select the most informative features using a method based on simultaneous feature selection and classification. The feature sets are optimized through 10-fold cross-validation. We investigate the effect of different sizes of the resulting feature sets. Additionally, we show that the performance is robust to the sensor-orientation and position around the neck. We evaluate the performance of the selected features on 5 different goats. Finally, we verify the classification performance of 6 different classifiers with our feature sets. This contribution has appeared in [79]:

- [79] J. W. Kamminga, D. V. Le, J. P. Meijers, H. Bisby, N. Meratnia, and P. J. Havinga. Robust Sensor-Orientation-Independent Feature Selection for Animal Activity Recognition on Collar Tags. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies IMWUT*, 2(1):1–27, 2018. doi:10.1145/3191747

CONTRIBUTION 6: ANALYSIS OF FACTORS THAT INFLUENCE ANIMAL ACTIVITY RECOGNITION PERFORMANCE

To answer RQ 4, we investigate the effect of feature type, hyperparameter tuning, and data partitioning method on the AAR performance. In Chapter 6, we train and evaluate 7 ML algorithms as AAR classifiers while changing the aforementioned factors. Firstly, we compare the quality of time and frequency-domain summary statistic features; while investigating the effect of feature type, we validate the orientation-independent feature set from contribution 5 on a different species. Secondly, we compare two validation partition methods. Finally, we investigate the effect of hyperparameter tuning by training the classifiers with and without hyperparameter tuning.

CONTRIBUTION 7: ANALYSIS OF DEEP UNSUPERVISED REPRESENTATION LEARNING TECHNIQUES FOR AAR To answer RQ 5, we present an analysis framework that compares various deep unsupervised representation learning techniques. This comparison is presented in Chapter 7. The most compelling reason to use unsupervised representation learning as a feature extraction method is the ability to learn from *unlabeled* data. We compare three unsupervised representation learning techniques with three conventional feature extraction methods. To investigate the effect of the size of both *labeled* and *unlabeled* part of the dataset on the quality of the representations, we train the representations and classifier using various sample sizes. Furthermore, we evaluate the effect of depth in feature architectures on the performance of the representation learning techniques. Finally, we analyze and discuss the effect of class imbalance in the dataset on the AAR performance of the representation architectures.

This contribution has appeared in [82]:

- [82] J. W. Kamminga, D. V. Le, N. Meratnia, and P. J. Havinga. Towards Deep Unsupervised Representation Learning from Accelerometer Time Series for Animal Activity Recognition. In 6th workshop on mining and learning from time series, San Diego, CA, 2020. MiLeTS. URL https://kdd-milets.github.io/milets2020/papers/MiLeTS2020_paper_1.pdf

1.6 THESIS ORGANIZATION

In this chapter, we have discussed animal activity recognition (AAR), machine learning (ML), and the challenges that accompany them. Based on these challenges, we presented our research objectives, questions, and hypotheses. Figure 1.4 shows a diagram of the thesis organization and provides an outline for the remainder of this thesis. Chapter 2 introduces the process of AAR, its intermediate steps, and a survey of the state of the art. In Chapter 3, we present three datasets that were collected and used for the research discussed in the subsequent chapters. Furthermore, we discuss the challenges found in data labeling and our approach to overcome them. Table 1.1 shows an overview of the dataset usage throughout the thesis.

Using the goat and sheep dataset presented in Chapter 3, we present our approach to generic AAR in Chapter 4. In Chapter 5, we focus on the discovery of a small, efficient, and effective set of statistical features that is robust against varying sensor orientations and diversity in the data. Building on the lessons learned from Chapter 4, and Chapter 5, we evaluate various AAR classifiers and factors that affect the performance on our dataset comprising horse movement, which was introduced in Chapter 3. In Chapter 7, we focus on the prospect of improving AAR through unsupervised representation learning. Conclusions, lessons learned, and recommendations for future work are presented in Chapter 8.

Table 1.1: Usage of datasets throughout the dissertation

Dataset	Chapter 4	Chapter 5	Chapter 6	Chapter 7
1. Goat and Sheep	✓			
2. Goat Orientation		✓		✓
3. Horses			✓	✓

Hiding in the Deep

Figure 1.4: Organization of the thesis

2

ANIMAL ACTIVITY RECOGNITION – THE STATE OF THE ART

In this chapter, we introduce the process of animal activity recognition (AAR) and discuss the state of the art. We describe each of the steps involved with AAR starting with data acquisition and finishing with training and evaluation of AAR classifiers.

In the second part of this chapter we present a comparative survey of the state of the art in AAR. We compare properties such as dataset size and composition, number and type of discriminated activities, sensors, features, and classifiers. We show that there is a need for open access datasets that contain data from multiple subjects. Generic performance of classifiers has not been studied sufficiently so far. Furthermore, multiple studies reported varying sensor orientations during data acquisition while sensor-orientation-independent AAR has not yet been studied.

2.1 INTRODUCTION

The behavior of animals is a rich source of information that not only provides insights into their life and well-being but also their environment [44, 119, 129, 146]. Biologists have attempted to study the behavior of animals using technology for decades. In the 1960s, biologists attached balloons and kitchen timers to marine mammals in order to study their movements and diving physiology [185]. In recent years, there has been a considerable rise in interest in activity monitoring of animals using sensors and embedded devices. The advent of small, lightweight, and low-power electronics has made it possible to monitor and detect animal activities – in real-time – on the animal itself and has propelled research in AAR.

In the state of the art, most AAR approaches attempt to infer activity from body-motion using inertial measurement units (IMUs). Researchers have used IMUs for AAR of various types of animals including wildlife [121, 152, 168, 187], livestock [21, 38, 156], and pets [53, 87, 181]. An IMU generally consists of an accelerometer, gyroscope, and magnetometer which measure acceleration, angular velocity, and magnetism. When the animal is moving, these modalities change, and the hypothesis is that each activity exercised by the animal is represented by a specific pattern in the sensor data. Machine learning (ML) is particularly suitable for pattern recognition in data and is a commonly used technique for AAR. A ML algorithm is often trained using supervised methods that generally follow three steps: Firstly, movement data is collected through motion sensors and annotated through a labeling process. The recorded sensor data, or part thereof, is tagged with labels by an observer to obtain a labeled dataset. A labeled dataset consists of several different activity categories. Ground truth for the observation is often recorded with a video camera during the sensor data collection. Secondly, the low-level sensory data is transformed in a more compact and discriminative representation. This step is called feature extraction. Finally, the representations and their corresponding labels are used to train a classifier to separate various activities given the differences in the sensor data. Human activity recognition (HAR) is an active research domain along AAR, and the overlap is mainly on the type of sensors being considered and the underlying ML techniques [10]. In Section 2.3, we discuss the overlap and differences in more detail.

2.1.1 CHAPTER ORGANIZATION

The rest of the chapter is organized as follows. In the following section we first discuss the aforementioned steps in the AAR pipeline in more detail and explain how these have been approached in the state of the art. Subsequently, we survey and compare various AAR studies in Section 2.3.

2.2 ANIMAL ACTIVITY RECOGNITION PIPELINE

Typically, activity recognition comprises five steps: data acquisition, signal pre-processing and segmentation, feature extraction and selection, training, and classification [26]. Figure 2.1 shows the steps of the AAR pipeline that is commonly used in the state of the art. In the following, we discuss each step in more detail.

2.2.1 DATA ACQUISITION

The first step in AAR is data acquisition. Figure 2.2 shows the methodology of a commonly used data acquisition process. Sensors are attached to one or multiple subjects using a collar or backpack. The collected data can be transmitted wirelessly or stored locally on the sensor device to be retrieved after the collection process. The subjects are usually videotaped using cameras to collect ground truth footage. The ground truth footage is used in the labeling process. The videos have to be synchronized with the sensor data so that a person can annotate the sensor data with activity labels according to the ground truth footage; this process is referred to as labeling of the data.

2.2.1.1 SENSOR MODALITIES

Before collecting the data, the sensor modality needs to be selected. Several modalities can be used to infer the activities of an animal. Researchers often use IMU devices, which contain accelerometers, gyroscopes, and magnetometers. Other possible sensor modalities include: cameras [145, 167] (for activity recognition (AR) from videos or images), Global Positioning System (GPS) [114, 136] (for location based AR), and microphones [164] (for sound based AR). When animals are confined to a cage or pasture, one could use cameras to classify the activities of an animal [15]. In these cases, the camera is located externally and not attached to the animal. Therefore, the subjects must be in the range of the camera to observe the activities. Although cameras are non-obtrusive to the animals, they are not scalable to larger pastures of livestock or the vast home ranges of wild animals due to their high price and required infrastructure [73]. This is true for any sensor modality that is not attached to the animal, e.g., a radar system.

A GPS device that is attached to the animal records the location at specific intervals. For some animals, GPS data can increase the AAR performance [42, 121, 150]. For example, if an animal is moving (GPS data showing changing location), then a sedentary activity classification is unlikely. However, GPS consumes much power and is not always suitable for long term deployment in the wild. Another promising direction is the use of microphones [164]. Nevertheless, using sound is challenging because different acoustic characteristics are found in various environments and subjects. Moreover, a vast vocal repertoire exists in the world, which increases the classification difficulty [73].

Table 2.1 shows that most related work in AAR has utilized wearable IMUs, particularly accelerometers. Accelerometers measure the force and direction of acceleration while gyroscopes measure the angular velocity (the rate of rotation). Most activities exercised by animals involve bodily motion of some sort. When an accelerometer is attached to the neck of an animal while an animal is jumping, the most affected signal is the acceleration along the axis that is aligned with the jumping motion. Magnetometers measure the alignment of the sensor with the earth's magnetic field. This modality could be useful to investigate Spontaneous Magnetic Alignment (SMA), in which animals align their body axis with earth's magnetic field lines [126].

Because IMUs are small and lightweight, they can be worn by humans (e.g., they are used in virtually all phones and smart-watches nowadays), and animals through embedding them in a collar, or attaching them to other parts of the body. Moreover, they consume very little power, which makes them particularly suitable for long term AAR monitoring of animals (in the wild). Gyroscopes continuously vibrate at a specific frequency to measure the angular velocity [176]. Thus, they typically consume more energy

Figure 2.1: Animal activity recognition pipeline. **PCA**: principal component analysis, **SAE**: sparse auto encoder, **CDBN**: convolutional deep belief network, **DT**: decision tree, **NB**: naive Bayes, **k-NN**: k-nearest neighbors, **SVM**: support vector machine, **DNN**: deep neural network (Photo credit: Carli Coco & Caleb M. Bryce)

Figure 2.2: Components of the data acquisition process

than accelerometers (in the order of 100 times more [104]). Because IMUs are not only lightweight, small, and cheap but also have shown good performance for AAR tasks, this dissertation focuses on AAR using wearable IMUs.

The sampling rate of the sensors can be set before the data acquisition. The sampling rate has a direct effect on power consumption: the higher the sampling rate, the higher the power consumption of the sensor [104]. In signal processing, the Nyquist rate is known as a lower bound for the sample rate for alias-free signal sampling. The lower band denotes that the sampling frequency should be at least double the frequency band of interest. Table 2.1 shows that in the state of the art sampling rates vary from 3 to 50 Hz. The sampling rate for GPS sensors is not listed in this table but is usually lower (around 5 Hz) [26]. The low sample rates in the state of the art are explained by the fact that the frequencies of the acceleration vector for most activities are low. However, some animals might exercise high frequent activities that require a higher sampling rate. For example, some hummingbird species have a wingbeat frequency of 80 Hz [180], which would require a sampling rate of at least 160 Hz.

2.2.1.2 LABELING

To train a machine learning (ML) model, the ground-truth is required to learn a function that maps the sensor data to an activity (the output class). Labeled data is data that has been annotated with ground-truth activity classes that belong to the various parts of that data. Training a ML model with labeled data is called supervised machine learning. The annotation process is often referred to as 'labeling' of the data.

To obtain labeled data, observations need to be made during the data collection process and subsequently the data needs to be annotated, which both are tremendously labour intensive, difficult, and tedious tasks. In the surveyed works, the labeling (or annotation) process is often not explained in detail, while the process entails a number of challenges. The ground truth is often recorded in the form of videos. The recorded sensor data needs to be synchronized with the videos prior to labeling. The sensor data can then be displayed along the video so that it becomes possible to annotate the data. We will elaborate on the labeling process in Section 3.5.

2.2.2 PRE-PROCESSING AND SEGMENTATION

IMU data is pre-processed in various ways and can include calibration, unit conversion, normalization, standardization, resampling, synchronization, or signal-level fusion [26, 43]. One of the first steps during pre-processing is to synchronize data streams from multiple sensors. Sensors that were used simultaneously might have a different sampling rate, or some sensors might have temporarily failed during the acquisition phase. The data needs to be aligned and synchronized before segmentation and feature extraction. Sometimes signal-level data from sensors is fused into an additionally generated data stream e.g., the ℓ^2 -norm derived from 3-axis of a sensor [137, 155]. A review of pre-processing steps is given in [43].

No information from the test data must be used to pre-process the training data. Failing to do so might result in over optimistic performance results. For example, when the training data is normalized or standardized, the mean and variance from the test data should be excluded and vice versa.

2.2.2.1 SEGMENTATION

The goal of segmentation is to define segments in the raw sensor data stream that contain information about a particular activity that was exercised during that period. It is challenging to define a start and end time of an activity segment because activities naturally transition into each other without a clear pause. There are three commonly known segmentation techniques: energy-based, information from other sources, and the sliding window [26].

Energy-based techniques attempt to segment activities by estimating the energy density of the signal. This may work for simple distinctions (e.g., between rest and active), but is not suitable to segment more complex activities.

Information from other sources, such as other sensor modalities, can be used to segment the data into activities. For example, the annotations from the labeling process are used to segment the raw sensor data into ground-truth segments. These segments vary in length, and the length is determined by the duration that the animal performed the activity.

Usually, such external information is not available, and the segmentation approach is agnostic about the underlying structure of the sensor data. A commonly used approach in HAR [154] and AAR is the fixed-width sliding window. All surveyed work in Table 2.1 used a fixed-width sliding window. The sliding window approach moves a window over the time series data that extracts a segment, or window, of data that is used in the subsequent steps of the pipeline. Usually, the size of the window is fixed throughout the AAR process. The window size is a trade-off between multiple factors. A longer window size may capture more information regarding the current activity but can also cause a greater error rate when an activity transition is captured in the window. However, a smaller window size may not fully capture one period of slower movements. The window size also affects the required computation and memory resources. Smaller window sizes lead to more segments of data that need to be processed in the pipeline, while larger window sizes require more memory. The surveyed work in Table 2.1 have used window sizes ranging from 1 to 600 seconds. Most approaches used a window size ≤ 20 seconds. Another important parameter of the sliding window approach is the step size. On the one

hand, a larger step size increases the segmentation precision while, on the other hand, it increases the computational load. A commonly used approach is to use 50 % overlap between two consecutive windows, e.g., a window size of 2 seconds with 50 % overlap has a step size of 1 second. Although these settings are application-specific, this seems to be a good trade-off between precision and computational load. Another trade-off is the size of the labeled dataset. Table 2.1 shows that the sizes of the labeled datasets used in the literature are usually very small. This is because labeling is a tedious and expensive process. Therefore, it might be beneficial to generate more data samples for training and evaluation, which can be obtained by using a smaller window and step size.

2.2.3 FEATURE EXTRACTION AND SELECTION

The performance of AR – or any machine learning algorithm – heavily depends on the type and quality of the representations (features) that describe the data [16]. Therefore, feature extraction is one of the essential steps in the AAR pipeline [94]. The goal of feature extraction is to transform the raw input data into a compact and descriptive feature vector. The total number of extracted features forms the feature space. Ideally, each activity is clustered and well separated from other activities in the feature space. The quest in feature extraction for AR has been, and still is, how to find the best features to represent the (high dimensional) raw sensor data. Useful features should be insensitive to personal traits of subjects and factors such as the sensor-orientation. In other words, the ideal representation can cluster and separate activities in the feature space for a large variety of input distributions of each activity.

There are various methods to extract features. Table 2.1 shows that most state of the art research in AAR has used conventional summary statistics. Summary statistics such as the mean, max, and variance are statistical properties for each segment of data [13]. Summary statistics can be divided into time-domain features and frequency domain features. Frequency domain features are related to frequencies found in the signal, such as the principal frequency, spectral energy, and frequency entropy. Frequency features are computationally more complex than time-domain features because they usually require an additional Fourier transformation [154].

Not all features are equally informative. Feature selection aims to reduce the number of features by selecting only those features which significantly contribute to the classification performance [54]. One solution is to manually select features based on their performance in related AR literature [62, 133]. More advanced feature selection methods can be divided into wrapper methods such as Sequential Forward Selection (SFS) [54] or filter methods such as Relief-F [194]. Wrapper methods embed a classifier in the process and try different combinations of features, found using various strategies to assess the classification performance. Filter methods such as Relief-F use qualitative metrics to estimate the quality of features according to how well their values can be distinguished between samples of the same and different classes that are close to each other.

In end-to-end learning, feature extraction is embedded in the training process. In HAR, two recent surveys [46, 178] underline the importance of research in the direction of deep learning (DL), or end-to-end learning.

More recently, research attention has been focused on unsupervised representation learning. Unsupervised representation learning aims to learn meaningful information

regarding the structure of the raw data without using annotations. This information is then used to extract features from the data. Unsupervised feature extraction methods include principal component analysis (PCA) [153], sparse auto encoder (SAE) [175], and convolutional deep belief network (CDBN) [98]. The latter two are used in a DL setting by stacking them in multiple layers (the output of one layer becomes the input for the subsequent layer).

2.2.4 TRAINING

In supervised machine learning, labeled training data is used to learn model parameters (weights) that can be used later during the classification step. More formally, given a set $\mathbf{N}$ training samples in the form $\{(x_1, y_1), \dots, (x_N, y_N)\}$, where x_i is the feature vector of the i -th sample and y_i the corresponding label, a classifier learns a mapping function $h: X \rightarrow Y$, where $\mathbf{X}$ is the input space and $\mathbf{Y}$ the output space. The function h , also named the hypothesis function, is an element of the space of possible functions $\mathbf{H}$. Many learning algorithms are probabilistic models where h has the form of a conditional probability model in the form of $h(X) = P(y|x)$. Others have a binary output vector, where each element represents one activity class.

Most ML models have adjustable settings, which affect the classification performance. These settings are called hyperparameters. Hyperparameter tuning aims to solve the problem of choosing a set of optimal hyperparameters for a learning algorithm. Hyperparameter tuning methods include grid search, Bayesian optimization, and evolutionary optimization [171].

Training can be performed either locally on the device itself as new data becomes available (online) or on a computer or computing cluster after the data collection (offline). In online training, raw data is usually not stored but used directly for training. In offline training, the raw data is stored and used later in a central location for training. Subsequently, the trained model parameters are transferred to the device to be used in the classification (inference) phase. Implementing the training phase on an embedded device increases the required computation and memory resources but might enable the model to adapt to changes in the data. One challenge is to acquire labels ad hoc as new data becomes available for training, which is not always possible in AAR. All surveyed works in Table 2.1 used offline training.

In the state of the art, a large variety of ML models have been used for HAR and AAR. Table 2.1 shows that across the 14 surveyed works 11 types of ML models were used. Thus, there is no consensus as to what model performs the best. The choice for a particular model is a trade-off between computational complexity, memory usage, and classification performance. Some models may perform better for specific sensor modalities, species, or activities of interest. In the following list, we describe commonly used classifiers that were also used and compared in this thesis.

k-nearest neighbors (k-NN) [5] is a non-parametric classifier and one of the simplest classification methods. k-NN determines the class of a feature vector based on the majority vote of the values of the k -nearest neighbors in the training set.

linear discriminant analysis (LDA) [64] aims to find the linear combination of features that best distinguish two or more classes. LDA assumes normally distributed sam-

ples and uses the means and variances to find hyperplanes that best separate the classes. The resulting combination of hyperplanes is then used as a linear classifier.

decision tree (DT) [86] consists of branches and nodes which are navigated depending on feature values. Each node represents a splitting rule for one specific feature that separates values belonging to different classes.

naive Bayes (NB) [140] classifiers are simple probabilistic classifiers based on Bayes' theorem. These classifiers (naively) assume that, given the class variable, the value of a particular feature is independent of the value of any other feature.

support vector machine (SVM) [64] aims to maximize the margin between data points and the decision boundary. An SVM model is a representation of the samples as points in space, mapped so that the samples of different classes are divided by a gap that is as wide as possible. During classification, new samples are mapped into that same space and predicted to belong to a class based on which side of the gap they fall on.

neural network (NN) [64] is a type of feed-forward neural network which maps input data to output classes using a number of hidden layers. Each layer contains neurons that are activated based on an activation function. The neurons are connected through weights. The value of the weights is trained with stochastic gradient descent using the backpropagation algorithm [144].

deep neural network (DNN) [93] is based on multi-layer feed-forward neural networks (NNs). Like NNs, a deep neural network (DNN) is trained with stochastic gradient descent using back-propagation. A network can contain a large number of hidden layers consisting of neurons with various activation functions.

2.2.5 CLASSIFICATION

In the classification step, a feature vector extracted from raw data is mapped to an output class using the trained model parameters. The output of the mapping can be either directly assigned to an activity or used in a subsequent step. For example, when the output of the classification is a vector of probabilities, the probabilities can be used to threshold against a minimum confidence level [26]. This approach can be used to separate data that belongs to activities of interest from data that belong to motions that are not of interest.

2.2.6 EVALUATION

The labeled test data is used to assess the performance of a trained model by comparing the activity that was assigned by the model with the ground-truth activity. Often, the classification results are shown in a confusion matrix. Figure 2.3 shows a confusion matrix for 2 classes. Each column shows the number of ground-truth samples for each activity class. Each row shows the number of samples that were predicted as each class by the classifier. Four numbers can be derived from a confusion matrix: the number of true positives (tp), false positives (fp), true negatives (tn), and false negatives (fn). In

		True class	
		p	n
Predicted class	Y	True Positives	False Positives
	N	False Negatives	True Negatives
total		P	N

Figure 2.3: Confusion matrix example for two classes

the context of activity recognition, tp denotes the number of true samples from activity α that were also classified as activity α ; tn denotes the number of samples from all other activities ($\neg\alpha$) that were not classified as activity α ; fp denotes the number of samples from all other activities ($\neg\alpha$) that were classified as activity α ; fn denotes the number of true samples from activity α that were classified as any of the other activities. The sum of true positive samples is denoted by $P = tp + fn$, and the sum of true negative samples is denoted by $N = fp + tn$. These numbers can be used to calculate performance metrics such as accuracy, recall, precision, and F-measure [55, 132, 179]. Accuracy is determined by the number of true positives and true negatives and is defined as

$$\text{accuracy} = \frac{tp + tn}{P + N} \quad (2.1)$$

Precision is defined as

$$\text{precision} = \frac{tp}{tp + fp} \quad (2.2)$$

For a given activity α , precision only takes into account the number of classified samples (the $tp + fp$). Precision is also referred to as positive predictive value (PPV). High precision means that substantially more classified samples were correct than incorrect.

Recall takes all true samples of activity α into account (P) and is expressed as

$$\text{recall} = \frac{tp}{P} \quad (2.3)$$

Recall is also referred to as sensitivity or true positive rate. When activity α has a high recall, this means that the classifier was able to detect and classify most of the samples of activity α . The F_1 score (also referred to as F-score or F-measure) can be interpreted as a weighted average of the precision and recall and is expressed as

$$F_1 = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}} = 2 \cdot \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} \quad (2.4)$$

An F_1 score of 100 % is optimal, and 0 % is the worst.

2.2.6.1 INFORMATION LEAKAGE

Information leakage may occur when overlapping windows are used and two overlapped windows are placed in both the training and test sets. This means that the same information is used in both training and test sets, which can never happen in real-world deployments. To prevent information leakage, the labeled activity segments, instead of the windows, should be divided into training, tuning, and test sets prior to the segmentation step. Failing to do so results in overoptimistic performance results.

2.3 SURVEY

Table 2.1 shows a detailed comparison of the related work in the AAR domain. Studies that collected animal data for behavioral studies or performance assessments, but did not classify the activities, were excluded from the survey. For example, two studies [22, 170] recorded IMU data from multiple locations on the animal simultaneously to assess the dressage performance of horses. The survey includes related work up to 2018.

In this survey, we focused on AAR that aims to classify the activity of the animal from sensor data. Human activity recognition (HAR) systems with wearables have been widely studied in humans [154]. Although HAR is not a direct application for AAR, it is an active research domain along AAR. Therefore, we discuss the commonalities and differences below. The most significant overlap between HAR and AAR is on the underlying ML algorithms [1, 10, 32, 36, 84]. Because of the overlap, findings that improve HAR may be contributing to AAR, and vice versa. HAR differs from AAR as follows. HAR often aims to use unobtrusive sensor devices that are already used by people, such as phones and smartwatches. These devices are more heterogeneous than for AAR but often contain IMU sensors [154]. Quadruped animals are often tagged with a sensor using a collar around the neck in unfixed positions and orientations. Therefore, the location and device types are different between HAR and AAR. Moreover, humans are bipedal, and in this thesis, we focus mainly on quadruped animals that perform various activities in a significantly different manner. Although there are similarities, the data acquisition and annotation processes pose different challenges for AAR than HAR. For example, in HAR, the subjects are often asked to perform a particular activity sequence during data collection, which is easily labeled. Another example is, the user annotating the data while performing the activity – this is very hard to do with most animals. The energy constraint for AAR is stronger than for HAR. Smartphone and smartwatch users effortlessly recharge their devices often. On the contrary, animal-tags are often impossible to access after deployment without capturing and, in some cases, sedating the animal, which are dangerous and stressful events for the animal. In conclusion, the findings of HAR research do not automatically apply to AAR. A comparative survey for HAR is presented in [154].

The reported performances in Table 2.1 depend significantly on several assumptions and evaluation choices that are made by the researchers in each approach. Therefore, one should refer to each referenced paper for exact performance details. All of the reported performances are the performances that were obtained with offline AAR. Most existing approaches rely on data-loggers, the subsequent collection of data, and centralized processing. In real-world applications, these approaches require transferring data to a central location. However, the transmission of raw sensor data demands high band-

width, which dramatically reduces the precious battery life of a collar tag due to the high energy consumption of radios. To the best of our knowledge, until recently, few studies focused on local, online, AAR on collar tags.

Table 2.1 shows that AAR has been studied for various animal species ranging from smaller oystercatchers to larger animals such as elephants. The number of subjects that were included in each study varied from 1 to 24. In two cases [53, 121], the authors did not clarify the number of subjects.

Table 2.1: Comparison of Animal Activity Recognition Studies using IMU data

Animal	nr subjects	Dataset size (labeled samples)	nr. Activities	Activities	Sensors	Sampling rate (Hz)	Sensor location	Sensor Orientation	window size (sec)	Features	nr features	Classifier	Train - test partitioning	Best performance (%)		Ref
														F_1	Accuracy	
Baboons	9	33387	8	A1, A2, A4, A6, A13, A36, A38, A39	A	40	neck	fixed	1	stat	25	RF	single split	79	*	[42]
Cheetahs	6	1991	3	A3, A17, A31	A	*	*	*	*	*	*	SVM + HMM	leave-1-sub-out	*	*	[51]
Cows	24	19603	5	A3, A4, A7, A18, A19	A, G, M	10	neck	fixed	5	stat	72	VE	*	89	96	[38]
Cows	7	*	6	A1, A3, A4, A7, A18, A30	A, P	20	head	fixed	5	stat	98	LDA, SVM, DT	leave-1-sub-out	54	*	[156]
Cows	6	200, 401, 2003	3	A1, A2, A17	A	50	neck	fixed	60, 300, 600	stat	2	SVM	3-fold	86	*	[174]
Dogs	18	*	17	A2, A4, A6, A11 - A17, A19 - A24	A	30	neck	fixed	1	ECDF, PCA	30	k-NN	10-fold cross-validation	*	69	[87]
Elephants	3	120	4	A32, A33	A	10	neck	fixed	20	PCA	12	LDA	leave-1-sub-out	*	88	[161]
Fox	1	415	3	A5, A36, A37	A	6	neck	vary	2.5	stat	4	k-NN	10-fold cross-validation	*	96	[126]
Horses	*	30000 *	3	A3, A4, A5	A, G, M	30	head	fixed	*	kalman	*	NN	single split	*	81	[53]
Lemon Sharks	4	*	5	A25 - A29	A	30	first dorsal fin	fixed	*	stat	45	LR, NN, RF, GBT, VE	single split	88	*	[23]
Oystercatchers	3	702	3	A3, A34, A35	A+GPS	20	back	fixed	3	stat	17	DT	10-fold cross-validation	*	86	[150]
Sheep	6	*	3	A1, A2, A4	A, G	8, 16, 32	ear, neck	fixed	3, 5, 7	stat	44	RF	single split	*	95	[177]
Sheep	5	3839	5	A1, A2, A4, A6, A18	A	10	neck	fixed	5	stat	31	LDA	10-fold cross-validation		86	[92]
Vultures	*	1035	7	A1, A2, A6, A8, A9, A10, A17	A+GPS	3	back	fixed	6	stat	38	LDA, SVM, DT, RF, NN	single split	*	88*	[121]

Activities A1–A40: see Table 2.2 **Sensors:** **A:** accelerometer, **G:** gyroscope, **M:** magnetometer, **P:** pressure * Unclear, refer to paper for more details

Features: **stat:** Summary Statistics, **ECDF:** Empirical Cumulative Density Function, **PCA:** Principal Component Analysis, **kalman:** kalman filtered (smoothed)

Classifiers: **DT:** decision tree, **GBT:** gradient boosted trees, **HMM:** hidden Markov model, **k-NN:** k-nearest neighbors, **LR:** least regression, **LDA:** linear discriminant analysis, **NB:** naive Bayes, **NN:** neural network, **RF:** random forest, **VE:** voting ensemble, **SVM:** support vector machine

Table 2.2: Glossary of used activity codes in Table 2.1

Code	Activity	Code	Activity	Code	Activity	Code	Activity
A1	standing	A11	jumping	A21	shaking	A31	mobile
A2	lying	A12	digging	A22	urinating	A32	bathing
A3	stationary (resting)	A13	sitting	A23	defecating	A33	swaying
A4	walking	A14	barking	A24	shivering	A34	flight
A5	trotting	A15	chewing	A25	swimming	A35	terrestrial locomotion
A6	running (galloping)	A16	drinking	A26	head shakes	A36	foraging
A7	ruminating	A17	eating	A27	resting	A37	leaping
A8	active flight	A18	grazing	A28	chafe	A38	grooming (actor)
A9	passive flight (soaring-gliding)	A19	scratching	A29	burst	A39	grooming (receiver)
A10	preening	A20	sniffing	A30	grooming	A40	unspecified

The number of labeled samples in Table 2.1 denotes the number of labeled windows. Overall, the amount of labeled data was small, or the authors did not clarify the amount of labeled data used. Only two studies collected more than 5000 samples and clarified the number of subjects [38, 42]. The study related to horses [53] reported 30000 samples but did not make clear if this depicts raw sensor data or segmented windows of data. The imbalance between activity classes is a common and actual challenge in ML [65]. In the surveyed studies, it is not always clear how the data is distributed over the activity classes. A low number of overall data suggests that the minority classes could be too small for a meaningful evaluation. Publishing research on AAR without providing information about data quantities and composition obscures the reported performances and should be avoided. There is no clear consensus as to the minimum amount of required labeled data, and this might be different from case to case. The small number of labeled samples for most studies underlines the difficulty of obtaining labeled motion data for animals and motivates further investigation of the effect of the labeled dataset size on AAR performance.

Each approach discriminates between a different set of activities. The AAR task becomes more complex and challenging as the number of activity classes to be discriminated is increased. For example, separating two classes from each other, e.g. *in-active* from *active*, is considered coarse grained AAR and relatively easy. Separating multiple activities and activities that could be very similar, is considered fine grained AR and more challenging. Table 2.1 shows that animals exercise a large variety of different activities. Table 2.2 shows that different studies interpret behaviors differently or make different choices in terms of granularity. For example, one study only defined grooming [156], while another subdivided grooming into actor and receiving [42]. The mean number of activities that is separated is 5. One study separated 17 activities in dogs with 69 % accuracy [87]. However, the reported performance seems over-optimistic because the authors seem to not only have pre-processed the test data with knowledge from the training data but also used overlapping windows in both train and test sets (informa-

tion leakage). A recent study separated 8 different activities in baboons and reported an overall F_1 score of 79 % [42]. The authors showed that 5 activities obtained a recall and precision higher than 60 %. Although this could be considered a good result because an above-average number of activities were separated, the authors used a single split of the labeled data and mixed all data for multiple subjects.

All surveyed work used an accelerometer to record motion data from the animals. Additionally, 3 studies used a gyroscope [38, 53, 177], 2 studies used a magnetometer [38, 53] or GPS [121, 150], and 1 study used a pressure sensor [156]. The sampling rate of the sensors varied from 3 to 60 Hz. In the case of land-dwelling animals, 8 studies attached the sensor to the neck, 2 studies to the head, and one study to the ear. Two studies that observed birds [121, 150] attached the sensor to the back of the bird using a harness. The study that observed lemon sharks attached the sensors to the first dorsal fin. Almost all studies fixed the orientation of the sensor. In [126] the sensor was unintentionally placed in different orientations during the data recordings. Because the sensor was always aligned with the z-axis, the authors decided to use only this axis for AAR. The study that observed dogs did mention that the animals disturbed the sensor placement, e.g., excessive scratching resulted in unwanted collar rotations [87]. One study used counterweights (0.5 kg) on the neck collars to ensure a stable position of the sensor on the body of the animal [174].

Out of the 14 surveyed studies, 9 used a window size ≤ 7 sec. One study used 20 seconds and another investigated window sizes of 60, 300, and 600 seconds. The studies that varied the window size did find that a larger window size slightly increased the performance, but also worsened the segmentation precision of the classifier. The longer window sizes were possible because the animals that were observed (elephants and cows) exercised the activities of interest for more extended consecutive periods, but this was not the case in the other studies.

Most studies (10) used summary statistics as a feature extraction method. One study first calculated the empirical cumulative density function (ECDF) and subsequently principal component analysis (PCA), one study calculated PCA directly from the raw sensor data, and one study used a Kalman filter to smooth the raw sensor data and used this signal as input to the classifier. The number of features varied from 2 to 98, although in the latter feature selection was used before classification. None of the surveyed works investigated the effect of the number of used features on classification performance.

In total, 11 different classifiers were utilized in the surveyed studies. Because the studies did use various evaluation methods, it is not possible to objectively compare the classifiers used. The large number of different classifiers used motivates a comparative study between various classifiers.

In the survey, we compare the train–test partitioning methods. A single split was used in 5 studies. These studies divided the data into training and testing just once, which means that not all data has been used for validation of the AAR approach. Another 5 studies used k -fold cross-validation, where k was set to 3 or 10. In all cases, all training data from multiple individuals was mixed before training. Thus, these studies did not assess the generic performance of the AAR with data from unseen subjects. Three studies did assess the generic performance by using leave-one-subject-out cross-validation. However, out of these 3 studies, only one reported a F_1 score (54 %) but did not report

the size of the labeled data.

2.3.1 DISCUSSION

The survey shows that AAR has been studied for a variety of animals. The size of the datasets is usually minimal and often has not been sufficiently described. Moreover, the datasets have not been made available by the authors. The effect of the different sensors on AAR performance has not been studied in detail. Multiple studies showed that lower sampling rates did not deteriorate performance significantly. Several papers did mention the challenge of sensors that get displaced unintentionally [87, 126, 174]. One study [174] added extra weight to counterbalance the collar in an attempt to fix the orientation. However, doing so does not ensure the orientation, and adding extra weight could be harmful to the animal. For example, when wildlife is collared, a general rule of thumb for the weight of an animal collar is usually 5% of their body weight [8]. Brooks et al. [24] found a significant effect of collar weight and its fit on the travel rate of zebra females. The authors compared two types of GPS collars. Although types of GPS collars were well within accepted norms of collar weight, the slightly heavier collars (0.6% of the total body mass) reduced the rate of travel by more than 5% when foraging compared with the collar that was 0.4% of total body mass. Instead, it may be better to use sensor-orientation-independent AAR, and this has not been investigated by any of the surveyed works. Furthermore, a large variety of features was used for AAR, and a comparative study would be useful. None of the surveyed works used representation learning for AAR. A large variety of classifier models has been used, and there is not a single one that stands out. The classifiers differ in complexity and performance and should be evaluated in a comparative study. Moreover, most studies did not discuss online AAR that is performed on the collar locally. The authors collected the data and performed the analysis offline on a personal computer. Only a few studies evaluated the generic quality of their AAR approach through leave-one-subject-out evaluation, but these studies either used very unconventional performance metrics [51], did not report the amount of data [156], or used a minimal amount of labeled data [161]. Therefore, additional studies are required to assess the generic performance of AAR methods on unseen subjects using better datasets.

2.4 CONCLUSION

In this chapter, we have introduced the AAR pipeline and discussed data acquisition, preprocessing and segmenting, feature extraction and selection, training, and evaluation. We discussed the different sensor modalities used for AAR and why most studies used accelerometers. The sensor data is labeled through annotation using ground-truth videos. We discussed pre-processing steps, segmenting raw sensor data, and how the extracted windows are used for feature extraction and selection. Finally, we introduced the training of ML models and their evaluation metrics.

We surveyed the state of the art in AAR and compared properties such as the dataset size and composition, number and type of discriminated activities, sensors, features, and classifiers. We showed that there is a need for open access datasets that contain data from multiple subjects. Datasets should be adequately described to clarify the reported

AAR performances. In the state of the art for AAR, the generic performance of classifiers has not been studied sufficiently. Furthermore, multiple studies reported varying sensor orientations during data acquisition, while sensor-orientation-independent AAR has not been studied. None of the surveyed works used representation learning as a feature extraction method for AAR. Because unsupervised representation learning aims to extract information from unlabeled data, which is much easier to obtain than labeled data, it is a prospective research field for AAR.

3

DATA – ACQUISITION, DESCRIPTION, AND LABELING

In the previous chapter, we introduced the data acquisition, labeling, and classification process. We surveyed the state of the art and concluded that there is a need for open access, well described, animal motion datasets. In this chapter, we describe three datasets collected and used for the research presented in this thesis.

We explain the data collection methodology and provide detailed information about the composition of the datasets and the labeling process. Furthermore, we describe the tool that was developed for the sensors-video synchronization and labeling task.

3.1 INTRODUCTION

In order to study animal activity recognition (AAR) based on motion data, we collected and annotated animal motion data from sheep, goats, and horses. In this chapter, we explain how the data was collected and describe the datasets.

In Chapter 2, we concluded that AAR using collars may be prone to unwanted rotations of the collar, e.g. due to excessive scratching of the animal. It is unlikely that in collared animal monitoring applications the sensor devices remain in a static position and orientation around the neck over longer monitoring periods. Instead of using additional counterweights to balance the collar [174], we investigate AAR that is robust against rotations of the sensor devices around the neck of the animal. Therefore, we placed the sensors in random orientations and locations around the neck of the animals using a collar.

The first dataset, described in Section 3.2, was collected to investigate the generic performance of AAR and comprises data from two species that are similar: goats and sheep. We used one sensor device per collar and this was not sufficient to properly investigate the impact of the sensor orientation and location around the neck on the performance of AAR. Therefore, we collected the second dataset to further investigate sensor orientation-independent AAR. The dataset contains motion data collected simultaneously at 6 different sensor placements in various orientations around the neck of five goats. This dataset is described in Section 3.3. The third dataset is our largest dataset and comprises data from 18 individual horses with more than 1.2 million 2-second data samples, of which 93303 samples are labeled. This dataset was used to investigate deep unsupervised representation learning for AAR. This dataset is described in Section 3.4. The last section in this chapter describes the labeling tool developed and used to annotate the aforementioned datasets. All experiments involving the animals complied with the Dutch ethics law concerning working with animals.

This chapter is partly based on:

- [76] J. W. Kamminga, H. C. Bisby, D. V. Le, N. Meratnia, and P. J. M. Havinga. Generic Online Animal Activity Recognition on Collar Tags. In *Proceedings of the 2017 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2017 ACM International Symposium on Wearable Computers - UbiComp '17*, pages 597–606, New York, NY, 2017. ACM Press. doi:10.1145/3123024.3124407
- [79] J. W. Kamminga, D. V. Le, J. P. Meijers, H. Bisby, N. Meratnia, and P. J. Havinga. Robust Sensor-Orientation-Independent Feature Selection for Animal Activity Recognition on Collar Tags. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies* IMWUT, 2(1):1–27, 2018. doi:10.1145/3191747
- [78] J. W. Kamminga, M. Jones, K. Seppi, N. Meratnia, and P. J. Havinga. Synchronization between sensors and cameras in movement data labeling frameworks. In *the second Workshop on Data Acquisition To Analysis (DATA'19)*, November 10, 2019, New York, NY, USA, New York, NY, 2019. Association for Computing Machinery. doi:10.1145/3359427.3361920
- [77] J. W. Kamminga, L. M. Janßen, N. Meratnia, and P. J. M. Havinga. Horsing Around—A Dataset Comprising Horse Movement. *Data*, 4(4):131, 9 2019. doi:10.3390/data4040131

3.2 MOTION DATA OF GOATS AND SHEEP

This section describes a dataset that comprises motion data from 4 goats and 2 sheep recorded using inertial measurement units (IMUs). The goats and sheep differ in size, weight, and age but belong to the same subfamily, *Caprinae*. This dataset was collected to study the generic performance of AAR algorithms across individuals and species. It is more challenging to collect annotated motion data from wildlife than from cattle. Therefore, goats and sheep were chosen because they are easy to work with and accessible in the Netherlands. In addition, they are also relatives to many prey animals living in wildlife areas because *Caprinae* is a subfamily of *Bovidae*, that includes antelopes, wildebeest, impala, gazelles, sheep, goats, bison, African buffalo, water buffalo, muskoxen, and domestic cattle [182]. Because of this, the dataset may be useful for studies that are related to wildlife studies, especially regarding AAR. The dataset is available online with open access at a DANS Easy repository [70].

3.2.1 METHODS

We collected data for a duration of 1 day. We started recording in the morning and finished in the evening. The motion data from the animals were collected simultaneously while the sensor devices between the different animals were synchronized in time. The animals were videotaped from various angles. The videos were later used as ground truth for labeling. The activities that were observed during the day are listed in Table 3.1. The list was formed through observation of the animals in the videos. Because we only recorded during the daytime, we did not observe nightly activities such as sleeping. If an animal was exercising multiple activities simultaneously, we labeled that data with the predominant activity. The labeling process is discussed in more detail in Section 3.2.1.2.

3.2.1.1 DATA ACQUISITION

The sensors were always placed around the neck. Various orientations of the collars on three animals are indicated in Figure 3.1. The collars were prone to rotation around the animal's neck during the day. The sensors on the animals were synchronized in time. The sensors were synchronized with a precision of <100 ns. All sensors were sampled with 200 samples/sec. We used Inertia ProMove-mini [169] nodes that contain the following motion sensors:

- 3-axes accelerometer
- 3-axes high-intensity accelerometer
- 3-axes gyroscope
- 3-axes compass (magnetometer)
- Temperature
- Barometric pressure

Table 3.2 shows the properties and used settings of the sensors in the IMU devices. Figure 3.2 shows the field where the animals were confined during the data collection.

Table 3.1: Observed activities exercised by goats and sheep during the day in Dataset 1

Activity	Description
Lying	The animal is lying on the ground.
Standing	The animal is standing still, occasionally moving its head or stepping very slowly.
Grazing	The animal is eating fresh grass, hay from a pile or twigs on the ground.
Fighting	The animal is fighting with another animal. This consists of banging its head against another animal's head or body. A goat often stands on the back of its legs, drops itself to the ground and drives its horns into another animal.
Shaking	The animal is shaking its entire body in a very rapid motion, often followed by rapidly shaking its head for a brief moment. On a few occasions, the animal only shakes its head.
Scratch-Biting	The animal is using its teeth to nibble on its own skin. Sometimes the animal uses its hoofs.
Walking	The animal is walking. The pace of walking varies from very slowly to nearly trotting.
Trotting	This is the phase between walking and running. The animal is not galloping rapidly but walking very quickly and is therefore in a trot state.
Running	The animal is galloping.

The size of the field is approximately 1800 m² and it was surrounded by a fence. The area was large enough for the animals to run around, forage, rest, interact and confine themselves to separate (self claimed) territories. As shown in Figure 3.2, the group of goats preferred to roam near the gate, while the groups of sheep preferred to roam in the opposite corner of the field. To incite running behavior, the animals were chased from time to time.

Table 3.2: Sensor information and parameter settings used for the goats and sheep in Dataset 1

Parameter	Accelerometer	Gyroscope	Magnetometer	Barometer	Temperature
Unit	m/s ²	°/s	μT	hPa	°C
Sampling rate (Hz)	200	200	100	25	200
Full scale range	78.45 m/s ² (8 g)	2000 °/s	±4912 μT	260 – 1260 hPa	-40 – 85 °C
Resolution	62 μg @ ±2g range	0.007 °/s @ ±250 °/s range	0.15 μT	0.02 Pa	n/a

3.2.1.2 DATA LABELING

The data was annotated with our labeling application that is described in Section 3.5. A screen capture of the application is shown in Figure 3.3. All data for all animals were

Figure 3.1: Sensor placements on various animals, the red arrows indicate the location of the sensors. (a) Sensor placement on a sheep. (b) Different sensor placements on two goats. (c) Goats and sheep eating hay.

annotated by one person according to the behaviors listed in Table 3.1. The stop marker for one activity was also the start marker for the following activity if the following activity was of any other class than *unknown*. Therefore, some data points include a transition phase to another activity. On a few occasions, the animal was performing multiple activities simultaneously. In these cases, the data was labeled as the predominant activity. For example, when a goat was eating while taking a few steps, this activity was labeled as *eating*. In the future, the labeling framework will support multi-class labels for moments that an animal carries out two activities simultaneously.

The reliability of labeling can be improved when multiple people repeatedly label the same data so that the inter-observer reliability can be calculated. However, when multiple people label the same data n times, the quantity of labeled data is divided by n . We chose a larger quantity of labeled data over higher reliability; thus, the data was labeled a single time and later verified through a visual inspection. The labeled data was visually inspected and corrected by a single person to minimize label ambiguity.

All efforts were put in to ensure the high quality of the labeling process. We did not label the data for very long consecutive periods to prevent sloppiness due to repetition in work, and we kept a thorough administration to keep track of what part of the labels

Figure 3.2: Overview of the field where all animals were confined

still required validation using spreadsheets.

3.2.2 DATA DESCRIPTION

The raw sensor data D is stored in tables where each row denotes one raw data sample as follows:

$$D = \left\{ X_1^{(i)}, X_2^{(i)}, \dots, X_m^{(i)} \right\}_{i=1}^N \quad (3.1)$$

, where X^i denotes the i -th sample from sensor modality m in a dataset with N samples. All sensor data was segmented according to the labeling file generated by the labeling application. One segment holds data for each consecutive activity exercised by the animal. Therefore, the length of a segment is determined by the duration the activity was continuously exercised by the animal. Each sample denotes a *window* of data, and the total number of samples is determined by the window size and the window overlap used in AAR. The number of samples per segment was calculated as follows:

$$n = \left\lfloor \frac{\sigma}{\omega * \tau} - 1 \right\rfloor \quad (3.2)$$

, where σ is the length of the segment, ω is the size of the window, and τ is the overlap. As discussed in Chapter 2, τ is usually set to 50 % and this value has also been used in this thesis. The composition of the dataset is shown in Table 3.3 and Figure 3.4. Most of the dataset (87 %) consists of *standing*, *grazing*, and *walking* activities. Goats and sheep at the petting zoo are inactive animals and spend most of their time standing and grazing. The point cloud shown in Figure 3.5 shows that the activities are overlapping. This is partly due to the fact that it is not always clear for the annotator when exactly the animal is changing its activity from e.g. trotting to running. Lying and standing are

Figure 3.3: Screenshot of the labeling application

very similar because in both cases the animal barely moves. Each continuous activity is identified with a unique segment number. The length of these segments vary and are dependent on the duration that the animal spent performing the activity in one period. A full description of all columns in the published data tables are described in Table 3.4.

Table 3.3: Amount of data samples per subject and activity for Dataset 1. Each sample denotes a 2 sec window of raw data. G_i and S_i denote goat and sheep, respectively.

Name / Activity	standing	grazing	walking	lying	trotting	running	scratch_biting	fighting	shaking	total
S2	5474	4053	1493		368	353			1	11742
G4	4694	1143	1230	3572	119	11	99	180		11048
S1	3071	6039	974		409	432		10	2	10937
G3	5576	2854	1497		95	23	90	18	1	10154
G2	4462	1661	1540	1320	46	181	93	43		9346
G1	4793	2433	1593	7	216	148	30	5	2	9227
total	28070	18183	8327	4899	1253	1148	312	256	6	62454
fraction	44,95%	29,11%	13,33%	7,84%	2,01%	1,84%	0,50%	0,41%	0,01%	100,00%

3.3 MULTI SENSOR-ORIENTATION MOTION DATA OF GOATS

In order to find orientation-independent data features, motion data should be recorded simultaneously by sensors in various orientations. Therefore, motion data was collected from five goats that each carried six sensors at different locations and in various orien-

Figure 3.4: Aggregated labeled activity distribution from all subjects in Dataset 1

Figure 3.5: Data distribution in 3D, using 3 statistical features (median, largest magnitude in frequency spectrum, standard deviation) for Dataset 1

Table 3.4: Column description of Datasets 1 and 2

Column name	Description
ax	Raw data from accelerometer x-axis
ay	Raw data from accelerometer y-axis
az	Raw data from accelerometer z-axis
axhg	Raw data from high G accelerometer x-axis.
ayhg	Raw data from high G accelerometer y-axis.
azhg	Raw data from high G accelerometer z-axis.
gx	Raw data from gyroscope x-axis
gy	Raw data from gyroscope y-axis
gz	Raw data from gyroscope z-axis
cx	Raw data from compass (magnetometer) x-axis
cy	Raw data from compass (magnetometer) y-axis
cz	Raw data from compass (magnetometer) z-axis
pressure	Raw data from barometer
temp	Raw data from temperature meter
label	Label that belongs to each row's data
animal_ID	Subject identifier. 'S1' = Sheep 1 and 'G1' = Goat 1 etc.
segment_ID	Each activity has been sorted per segment. Data within one segment is continuous. Segments have been numbered incrementally for each animal and are not consecutive
timestamp_ms	The data for the accelerometers and gyroscopes have been recorded at 200 Hz. Therefore the timestamp column increments per 5ms. Please note that although the timestamp column seems consecutive over all segments, the segments are not consecutive. Sensors that had a lower sampling rate have missing values with 'NaN' value

tations around the neck. In practice, activity recognition only requires one sensor node, however, the main purpose of our research was to investigate the effect of sensor node position and orientation on AAR. Goats were chosen because they belong to the family of *Bovidae*, together with many other wild animals such as antelope and wildebeest, and are therefore possibly representative of several wild animals [182]. Additionally, goats are widely available in the Netherlands and easy to work with. In total, data was collected from three domestic pygmy goats and two bigger, more wild goats. The three pygmy goats are shown in Figure 3.6. Figure 3.7 shows the two larger goats along with a sensor-node collar in Figure 3.7b. The complete dataset is available online with open access at a DANS Easy repository [71].

Figure 3.6: Three smaller Pygmy goats with attached sensors in different orientations. (a) Goat G1. (b) Goat G2. (c) Goat G3.

Figure 3.7: Two larger goats. The main purpose is to investigate the effect of sensor position and orientation on activity recognition. (a) Goat G4. (b) Goat G5 with attached sensors in different orientations.

3.3.1 METHODS

We collected data during 7 days in 2 periods of approximately 4 hours between 08:00 and 17:00 with 2 collars simultaneously; data acquisition was bound to these time periods because of the opening times of the petting zoo, safety of the animals (they needed to be watched at all times), and battery lifetime of the sensor nodes. The sensors were set to a sampling rate of 100 Hz. We used a lower sampling rate compared to the goat and sheep dataset (described in Section 3.2) because we learned that a sampling rate above 30 Hz did not significantly contributed to AAR performance. The effect of sampling rate on AAR performance is further discussed in Chapter 4. The activities that were observed during the day are listed in Table 3.5. The animals were recorded on video from various angles during the day. The videos were later used as ground truth for the labeling process.

3.3.1.1 DATA ACQUISITION

The sensor nodes among the collars were synchronized with a precision of <100 ns. Figure 3.8 shows a 3D sketch of the collar and the sensor positions with their respective x , y , and z -axes. All efforts were put in to maximize the difference in positions and orientations between the six sensors for all three x , y , and z axis. Since a sensor node placed on the left of the collar would give similar data to one placed on the right, due to the symmetry, we allocated sensor nodes on one side of the goat's neck as much as possible. An identical configuration was used for each animal. The collars were loosely attached to the animals and prone to rotation around the animal's neck during the day. Therefore, most of the collected data for each sensor can be roughly coupled to the locations denoted in Figure 3.8, although the sensor locations were not fixed.

We used the ProMove-mini [169] sensor nodes from Inertia Technology, which contain a 3-axis accelerometer, gyroscope, magnetometer, barometer, and temperature sensor. The IMU sensors were sampled at 100 Hz such that it is possible to down-sample the data later on for further investigation. The sensor settings and parameters are shown in Table 3.6.

3.3.1.2 DATA LABELING

Overall, the data labeling procedure was identical to the one described in Section 3.2.1.2. The data was annotated with our labeling application that is described in Section 3.5. All data for all animals was annotated by one person according to the behaviors listed in Table 3.5.

3.3.2 DATA DESCRIPTION

The raw sensor data D is stored in tables in which each row denotes one raw data sample as shown in Equation 3.1 from Section 3.2.2. The composition and size of the datasets are shown in Table 3.7. The number of samples per segment was calculated using Equation 3.2 from Section 3.2.2. Overall, most of the labeled data (93 %) consists of the activities *standing*, *eating*, *walking*, and *grazing*. Not all recorded activities were equally often performed in time by all goats. It can be seen that goats G1 to G3 do not often perform *trotting* and *running* and spend most of their time *eating* and *standing* or *lying*. The datasets for Goats G4 and G5 are generally more balanced. Segments of data were labeled as *unknown* when the activity of the goat for that segment could not clearly

Table 3.5: Observed activities exercised by goats during the day in Dataset 2

Activity	Description
Standing	The animal is standing still, occasionally moving its head or stepping very slowly.
Lying	Lying on the ground, occasionally moving its head
Eating	Eating hay from a pile or twigs/grains on the ground.
Grazing	The animal is pulling fresh grass out of the ground and eating it.
Walking	The animal is walking. The pace of walking varies from very slowly to nearly trotting.
Trotting	This is the phase between walking and running. The animal is not galloping rapidly but walking very quickly and is therefore in a trot state.
Running	The animal gallops.
Fighting	The animal is fighting with another animal. This consists of banging its head against another animal's head or body. A goat often stands on the back of its legs, drops itself to the ground and drives its horns into another animal.
Shaking	The animal is shaking its entire body in a very rapid motion, often followed by rapidly shaking its head for a brief moment. On a few occasions, the animal only shakes its head.
Climbing up	The animal is walking/jumping up onto an object. For example climbing into a shelter, or jumping onto a wooden bench.
Climbing down	The animal is walking/jumping down from an object. For example climbing out of a shelter, or jumping off a wooden bench.
Rubbing	The goat is pressing its body against a fence and walking while it keeps pushing itself towards the fence.
Scratch-Biting	The animal is using its teeth to nibble on its own skin. Sometimes the animal uses its hoofs.
Breast-Feeding	Standing still and allowing her kids to drink milk.
Standing-Up	Standing upright against an object (usually fence), with hind hoofs on the ground.
Food fight	This occurs when food is dropped in a group of animals. All animals are pushing each other trying to reach the food.

be recognized in the video (e.g. when the goat has moved behind an obstacle or other animals). All data that was not labeled is denoted as *null* in Table 3.7. The point cloud shown in Figure 3.10 shows that the activities are overlapping. One reason for the overlap is the fact that all data from 6 sensors and 5 goats is aggregated in the figure. Another

Figure 3.8: A 3D sketch of the collar with the attached sensor units seen from two angles. The red arrow denotes the front of the animal. The blue and green axis denote vertical and horizontal axis, respectively. The blue and red colored faces denote the bottom and top side of the sensor nodes, respectively. The sensor nodes have been labeled A to F clockwise.

Table 3.6: Sensor information and parameter settings of the multi sensor-orientation in Dataset 2

Parameter	Accelerometer	Gyroscope	Magnetometer	Barometer	Temperature
Unit	m/s^2	$^{\circ}/\text{s}$	μT	hPa	$^{\circ}\text{C}$
Sampling rate (Hz)	100	100	100	25	100
Full scale range	78.45 m/s^2 (8 g)	$2000 ^{\circ}/\text{s}$	$\pm 4912 \mu\text{T}$	$260 - 1260 \text{ hPa}$	$-40 - 85 ^{\circ}\text{C}$
Resolution	$62 \mu\text{g}$ @ $\pm 2\text{g}$ range	$0.007 ^{\circ}/\text{s}$ @ $\pm 250 ^{\circ}/\text{s}$ range	$0.15 \mu\text{T}$	0.02 Pa	n/a

reason for the overlapping samples from different gaits stems from the labeling process which is discussed in Section 3.5. We can only plot 3 dimensions and it is possible that the clusters are better separated in higher dimensional spaces. A full description of all the columns in the published data tables are described in Table 3.4.

Table 3.7: Amount of aggregated data samples per subject and activity for Dataset 2. Each sample denotes a 2 sec window of raw data.

Name / Activity	null	standing	eating	walking	grazing	lying	trotting	food_fight	running	scratch_biting	breast_feeding	standing_up	rubbing	fighting	climbing_up	climbing_down	shaking	total
G1	31110	55300	33965	26434	42690	1284	594	2420	510	1177	809	149	798	522	195	176	174	167197
G4	53297	62524	22572	25943	138	648	2674		2720	400		603		28	48	40	69	118407
G3	11161	35117	34825	13581	11394	5568	710	1733	316	709	150	6	114	148	37	93	26	104527
G2	19313	18420	17202	18703	21101	396	941	2004	298	862	396	373		6	12	31	106	80851
G5	1455	19194		6090	912		870		690	12				36	132	42		27978
total	116336	190555	108564	90751	76235	7896	5789	6157	4534	3160	1355	1131	912	740	424	382	375	615296
fraction	18,91%	30,97%	17,64%	14,75%	12,39%	1,28%	0,94%	1,00%	0,74%	0,51%	0,22%	0,18%	0,15%	0,12%	0,07%	0,06%	0,06%	100,00%
fraction of labeled		38,19%	21,76%	18,19%	15,28%	1,58%	1,16%	1,23%	0,91%	0,63%	0,27%	0,23%	0,18%	0,15%	0,08%	0,08%	0,08%

Figure 3.9: Labeled activity distribution for the multi sensor-orientation Dataset 2. Aggregated data from all subjects and sensors

3.4 HORSE MOTION DATA

This section describes a dataset that comprises motion data from horses. Motion data was collected at an equestrian facility over 7 days. The dataset comprises 1.3 million 2-second data samples from 18 individual horses, of which 93303 samples from 11 subjects have been labeled. Data from 11 out of 18 subjects was labeled but for 6 subjects the data was labeled more extensively for 6 activities. Data was collected during horse riding sessions and when the horses freely roamed the pasture. The sensor nodes were attached to the neck of the horses by means of a collar fabricated from hook and loop fastener in an orientation that was not strictly fixed. Figure 3.11 shows three horses during the outdoor collection process.

To study animal activity recognition from motion data a large dataset comprising motion data was required. In earlier data collection campaigns [76, 79], described in Sections 3.2 and 3.3, we found out that the observed animals spent most of the day eating and resting, and the activity dataset became unbalanced and skewed towards a few activities. Furthermore, motion data from a different species allowed us to verify our findings on a different species in Chapter 6. We chose to monitor horses and ponies that were ridden in an equestrian facility because they are exercising various activities dur-

Figure 3.10: Data distribution in 3D, aggregated data from all sensors and showing 3 statistical features (frequency entropy, largest magnitude in frequency spectrum, standard deviation) for Dataset 2

(a)

(b)

Figure 3.11: Horses in the outside pasture. (a) Two subjects standing still. (b) Subject grazing.

ing the day. Because of this, we could ease the task of collecting and labeling relatively large amounts of motion data from several activities which resulted in a more balanced dataset for different gaits and eating behavior. The dataset contains labeled data from activities that are very similar but slightly different, e.g. the difference in gait with- and without a rider on the horse. Ground truth was collected by placing cameras that could oversee most of the horse paddocks and outdoor pasture. The subjects were ridden in various gaits over the course of multiple days. More natural activity data was collected by observing the animals while they were left to roam freely in an outdoor pasture during their daily break. In total, 17 different activities performed by the horses were observed and annotated.

Most of this dataset is unlabeled (denoted as *null* and *unknown* in the dataset). The distinction between these two is that *null* data has never been seen by an annotator and essentially is unprocessed data and *unknown* data is data that has been seen by an annotator but the ground-truth was unclear or the activity did not fit into one of the predetermined categories. Because the dataset contains a relative large amount of unlabeled data along with labeled data for multiple subjects and activities, the dataset is particularly suitable for the benchmarking of unsupervised representation learning algorithms. Unsupervised representation learning is a set of machine learning (ML) technique that does not utilize data labels and aims to automatically discover a compact and descriptive representation of raw data from the data itself [16].

Furthermore, this dataset may be useful for research related to: gait analysis and comparison, feature selection for AAR, and transfer learning. For example, the dataset might be valuable to improve AAR methods for other quadruped animals within the *Equidae* family, such as zebras or donkeys. The dataset was publicly released and described to allow other researchers to improve AAR methods and benchmark novel approaches to unsupervised representation learning for AAR [75, 77, 83]. The complete dataset is available online with open access at the 4TU.Centre for Research Data [75].

3.4.1 METHODS

Motion data was collected from 18 individual horses and ponies over 7 days. The recordings were taken at different lengths of time, but usually were attached for most of the day. The animals were recorded on video from various angles during the day. The videos were later used as ground truth for labeling the data. The data was labeled according to the 17 activity categories listed in Table 3.8.

3.4.1.1 DATA ACQUISITION

A sensor device from Gulf Coast Data Concepts [52] was attached to the neck by means of a collar fabricated from hook and loop fastener. Figure 3.12 shows how the sensors were attached to horses. To be able to evaluate AAR approaches that are robust against the orientation, we did not fix the orientation of the sensor devices. In Chapter 2, we surveyed the state of the art and concluded that all studies which investigated AAR for land dwelling animals positioned the sensors around the neck of the animal. Moreover, this position is used in studies that monitor wildlife such as zebra [68]. Therefore, using the same position might increase the usability of our dataset for research related to other animals. Furthermore, by placing the sensors around the neck they could be worn with-

Table 3.8: Observed daytime activities exercised by horses in Dataset 3

Activity	Description
Standing	Horse standing on 4 legs, no movement of head, standing still
Walking natural	No rider on horse, the horse puts each hoof down one at a time, creating a four beat rhythm
Walking rider	Rider on horse, the horse puts each hoof down one at a time, creating a four beat rhythm
Trotting natural	No rider on horse, 2 beat gait, one front hoof and its opposite hind hoof come down at the same time, making a two-beat rhythm, different speeds possible but always 2 beat gait
Trotting rider	Rider on horse, 2 beat gait, one front hoof and its opposite hind hoof come down at the same time, making a two-beat rhythm, different speeds possible but always 2 beat gait
Galloping natural	No rider on horse, one hind leg strikes the ground first, and then the other hind leg and one foreleg come down together, the the other foreleg strikes the ground. This movement creates a three-beat rhythm
Galloping rider	Rider on horse, can be right or left leaning, one hind leg strikes the ground first, and then the other hind leg and one foreleg come down together, the the other foreleg strikes the ground. This movement creates a three-beat rhythm
Jumping	All legs off the ground, going over an obstacle
Grazing	Head down in the grass, eating and slowly moving to get to new grass spots
Eating	Head is up, chewing and eating food, usually eating hay or long grass
Head shake	Shaking head alone, no body shake, either head up or down
Shaking	Shaking the whole body, including head
Scratch biting	Horse uses its head/mouth to scratch mostly front legs
Rubbing	Scratching body against an object, rubbing its body to scratch itself
Fighting	Horses try to bite and kick each other
Rolling	Horse laying down on ground, rolling on its back, from one side to another, not always full roll
Scared	Quick sudden movement, horse is startled

out a saddle or halter. This was important because the horses wear various equipment at different locations in the facility throughout the day. For example, a saddle, bridle, and reins are required when horses are ridden, only a halter with rope is used when they are walked to the pasture, and horses wear nothing when walking freely outside or in the stable. Therefore, placing the sensor on the neck allowed us to use the same sensor on the subjects throughout the day without the need to switch them between different types of horse-equipment. When high quality gait analysis is required, it might be better to use multiple sensors locations simultaneously, including the legs [22, 170]. However, our focus is more on AAR that can be performed locally on the animal itself and use as little energy as possible. Different colors were used for the collars to ease the identification of the horses in the videos. The sensor devices contained a 3-axis accelerometer, gyroscope and magnetometer and were sampled with a sampling rate of 100 Hz. The sensor parameter settings are described in Table 3.9.

Figure 3.12: Sensor placement around neck of a horse. The sensors were attached with a collar made out of hook and loop fastener. The sensor was attached to the manes using elastic bands. The orientation of the sensor devices was not fixed. The collar and sensor did not bother the horses.

The sensors were attached to the horses while they were in their stable. This was done for all subjects during each day of monitoring. Horses were randomly ridden in turns, thus not all horses were either outside in the pasture or ridden the whole day. This means that in some cases part or most of the recorded data for that day can be of the horse standing or roaming around in her stable. Activities such as *eating*, *scratch-biting*

Table 3.9: Sensor information and parameter settings for the horse movement in Dataset 3

Parameter	Accelerometer	Gyroscope	Magnetometer
Unit	m/s^2	$^\circ/\text{s}$	μT
Sampling rate (Hz)	100	100	12
Full scale range	78.45 m/s^2 (8 g)	$2000^\circ/\text{s}$	$1200 \mu\text{T}$
Sensitivity	9.8 m/s^2 (1 g)	$1^\circ/\text{s}$	$1 \mu\text{T}$

and *rubbing* were also performed in the stable.

3.4.1.2 DATA LABELING

Overall, the data labeling procedure was identical to the one described in Section 3.2.1.2. The data was annotated with our labeling application that is described in Section 3.5. Data from 11 subjects was annotated according to the behaviors listed in Table 3.8.

To evaluate AAR methods through leave-one-subject-out cross-validation, it is desirable that the dataset from each subject contains sufficient labeled data for each activity within a set of activities that is identical for all subjects that are used in the cross-validation. Therefore, we chose to label a subset of activities for a subset of the subjects more extensively.

3.4.2 DATA DESCRIPTION

In this section, we describe the *labeled* part of the dataset. The raw sensor data D is stored in tables in which each row denotes one raw data sample as shown in Equation 3.1. Because we used a sampling rate of 100 Hz one second of data equals 100 rows. The columns of the data tables are described in Table 3.10. Figure 3.13 shows five two-second examples of accelerometer and gyroscope data that were recorded during different activities. The data was organized in segments of continuous raw sensor data. Segments can vary in length depending on how long the subject performed a given activity. Information leakage¹ may occur when overlapping windows are used and two overlapped windows are placed in both the training and test sets. To prevent information leakage, instead of the windows, the activity segments should be divided into training, tuning, and test sets prior to windowing [79]. Therefore, each continuous activity is marked with a unique segment identifier throughout the dataset. However, in Chapter 5 we show that some segments (activities) may have a long duration and the resulting training and test sets may be imbalanced with different ratios when the segments are divided instead of the windows, even when proportionate stratified sampling² is used [79]. Therefore, the segments have a maximum length of 10 seconds to maintain the same class balance ratio between the different subsets.

¹Explained in Section 2.2.6

²Sampling per activity. The sample size of each activity is proportionate to the population size of the activity. Each activity has the same sampling fraction.

Figure 3.13: Example of accelerometer and gyroscope data in Dataset 3. Data from several activities is concatenated

The composition and size of the dataset are shown in Table 3.11. The number of samples in this table were obtained by applying a 2 second window with 50 % overlap over the raw data segments. The number of samples per segment was calculated according to Equation 3.2. Table 3.11 is sparse because we initially did not concentrate on a subset of subjects and activities. To be able to use leave-one-subject out cross validation, we later focused our labeling effort on a subset of subjects and activities. Table 3.11 shows that most of the dataset is *null* (85.22 %) or was labeled as *unknown* (7.52 %). *null* is data that has never been seen by an annotator. *unknown* data represents motion that did not fit one of the known activities or data for which the ground truth was unknown. Figure 3.14 shows the distribution of labeled activities. During the monitoring in the paddock, the horses were mainly walking and trotting with a rider on their back. During the monitoring in the outside pasture, the horses were mainly grazing. Therefore, these activities represent the largest part of the labeled dataset.

Table 3.10: Column description of the horse movement in Dataset 3

Column name	Description
Ax	Raw data from accelerometer x-axis
Ay	Raw data from accelerometer y-axis
Az	Raw data from accelerometer z-axis
Gx	Raw data from gyroscope x-axis
Gy	Raw data from gyroscope y-axis
Gz	Raw data from gyroscope z-axis
Mx	Raw data from compass (magnetometer) x-axis
My	Raw data from compass (magnetometer) y-axis
Mz	Raw data from compass (magnetometer) z-axis
A3D	l2-norm (3D vector) of accelerometer axes
G3D	l2-norm (3D vector) of gyroscope axes
M3D	l2-norm (3D vector) of compass axes
label	Label that belongs to each row's data
segment	Each activity has been segmented with a maximum length of 10 seconds. Data within one segment is continuous. Segments have been numbered incrementally.
subject	Subject identifier

Table 3.11: Amount of data samples per subject and activity in Dataset 3. Each sample denotes a 2 sec window of raw data.

Name / Activity	null	unknown	walking_rider	trotting_rider	grazing	standing	galloping_rider	walking_natural	head_shake	scratch_biting	galloping_natural	trotting_natural	rolling	eating	fighting	shaking	jumping	rubbing	scared	total
Galoway	62155	23264	9653	6374	4315	1750	1030	1402	59	170	13	49	13	16	25	4				110292
Bacardi	92775	9850	1317	1981	1116	245	288	360		22	40					13		6		108013
Driekus	85468	11271	4024	2670	2465	341	310	270	55	14	13	3	23	31		4				106962
Patron	78536	15156	5150	3385	1951	1244	709	388	37		5	17	31							106609
Happy	68468	13606	8896	7032	5062	1186	689	746	238	8	7	6		1						105945
Zonnerante	90431																			90431
Duke	81885																			81885
Viva	69441	4413	1066	700		58	82	79	5	4									1	75849
Flower	75741																			75741
Pan	68628	1575	241			36		44												70524
Porthos	67080																			67080
Barino	66517																			66517
Zafir	38424	10349	5078	3546	1091	347	826	161	105	23	9	13					12			59984
Niro	43563	2740			85	20		2												46410
Sense	38823	1569			1977	39		157	120	44	15	6			6				2	42758
Blondy	31579																			31579
Noortje	17777	2878				31														20686
Clever	17696																			17696
total	1094987	96671	35425	25688	18062	5297	3934	3609	619	285	102	94	67	48	31	21	12	6	3	1284961
fraction	85,22%	7,52%	2,76%	2,00%	1,41%	0,41%	0,31%	0,28%	0,05%	0,02%	0,01%	0,01%	0,005%	0,004%	0,002%	0,002%	0,001%	0,000%	0,000%	100,00%
fraction of labeled			37,97%	27,53%	19,36%	5,68%	4,22%	3,87%	0,66%	0,31%	0,11%	0,10%	0,072%	0,051%	0,033%	0,023%	0,013%	0,006%	0,003%

Figure 3.14: Labeled activity distribution from all subjects for the horse motion in Dataset 3

Figure 3.15 shows the distribution of the labeled data using three summary statistics for each two-second window of data: frequency entropy, the frequency component with the largest magnitude, and standard deviation. More details regarding these features can be found in Chapter 5. The figure shows mixed data from 11 different subjects and all labeled activities. The different activity clusters are overlapping and activities such as *head-shake*, *walking-rider*, and *galloping-rider* are more scattered (they have a higher variability in the measurements).

3.5 DATA LABELING

This section describes the labeling framework developed and used to annotate the collected movement data of sheep [76], goats [79], and horses [81]. The framework was initially developed because at the time of data collection no framework was publicly available that could synchronize data from multiple sensor devices with a single video and annotate the data. The framework is based on a Matlab GUI [112] that displays the video along with a selection of data. Data is annotated by clicking in the data graph and selecting the appropriate label for that part of data. The code of the application is publicly available [72].

3.5.1 INTRODUCTION

Obtaining labeled data is a tremendously time consuming, tedious, and labor-intensive task. Nevertheless, most recent published papers in the field of machine learning and activity recognition (AR) heavily rely on the availability of labeled datasets. Ground truth is often collected using camera(s) that record subjects while wearing one or multiple data loggers that usually contain IMUs. The data is often displayed along with the recorded

Figure 3.15: Data distribution in 3D, using 3 statistical features (frequency entropy, largest magnitude in frequency spectrum, standard deviation) for Dataset 3

video so that a person can inspect segments of the data with corresponding video frames. This simultaneous display may make it easier to identify the particular ground-truth activity that belongs to that data segment. A screen capture of the developed labeling application is shown in Figure 3.16. Initially, clock timestamps from the camera and sensor nodes are used to obtain a coarse synchronization. The labeling application is then used to further synchronize videos with sensor data by adjusting the offset between the video and sensor data. The magnitude of the accelerometer vector is displayed to visualize the sensor data. A vertical led line in the center of the graph denotes the current time in the video. The data is labeled by clicking at the point representing a change in behavior on the graph. The activity that belongs to the data following the selected point in time can then be selected from a drop-down menu and added to the graph. A file with activity label and timestamp tuples is instantly updated when an annotation is added. The visualization of the sensor data along with the video, and the synchronization between them, allow the annotator to accurately label the activity associated with the sensor data. Keyboard shortcuts were added to the application and can be used to quickly jump forward and backward in the video to speed up the process. By looking at the visualized sensor data, the annotator can see when the same activity is performed for the rest of the window, and jump forward. Skipping though repeated activities significantly speeds up the labeling process.

Figure 3.16: Screenshot of the labeling application GUI

3.5.2 SYNCHRONIZATION BETWEEN SENSORS AND CAMERAS

The data have to be synchronized with the video prior to annotation so that it is clear which part of the sensor data belongs to a given activity segment. The synchronization accuracy that is required depends on the type of animal that is annotated. For example, an animal that performs rapid movements will require a higher accuracy than a slow moving animal. Furthermore, a higher accuracy is required when an animal rapidly changes between activities in short intervals. In the following we present different approaches to synchronize sensor data with video and discuss their advantages and disadvantages.

3.5.2.1 APPROACH A: SYNCHRONIZATION USING VISUAL KEY

To collect data using this approach, the annotator attaches the data logger somewhere on the subject. The annotator then records video of the subject in motion. Note that only one data logger and one video stream are captured. This approach has been used in data collection for Alpine skiing [67], hiking [66], and rock climbing [66]. Synchronization in this process involves capturing a red flash emitted by the data logger on video ten seconds after the data logger is turned on. In this approach, the annotator turns on the data logger, aims the video camera at the data logger, presses “record” on the camera, and waits to record the red flash. The data logger logs the time of the first red flash (in milliseconds elapsed since the processor was turned on). At the beginning of labeling, the annotator locates and marks the first video frame that contains the first red flash. The labeling application can then synchronize the video and data for as long as both continue recording. If either is stopped or turned off, synchronization must be repeated.

The accuracy of this approach is limited by the video camera frame capture rate. For example, if the video is captured at 30 frames per second then synchronization of the video and data is off by at most one-thirtieth a second or 33 ms. Cameras with higher frame rates can be used to synchronize the data with greater accuracy (up to the temporal resolution of the data logger sampling rate).

3.5.2.2 APPROACH B: SYNCHRONIZATION USING REAL-TIME CLOCKS

The approach proposed by us is as follows. During data collection multiple subjects simultaneously wear a data logger and appear in the same video(s). The framework assumes that each camera and data logger contains an internal real-time clock (RTC) that can be set prior to the data collection campaign. The RTCs are used to timestamp each video and sensor-data file. The framework uses the start-time information from the raw video files and sensor data files that is parsed during preprocessing of the files. The GUI is used subsequently to synchronize videos with sensor data more accurately.

Figure 3.17 shows a schematic diagram of the offset $\sigma_{m,n}^{(l)}$ between a given camera m and sensor n on day l . The offset σ is determined by using a distinctive event in the video and adjusting σ until $M(t + \sigma)$ aligns with the event shown in the video. In theory, the synchronization only needs to be done once. In practice, σ will probably need minor adjustments over time due to clock drift in the RTCs of the camera and sensors. Therefore, the camera-sensor offsets are stored per day and the annotator can update the offset when the synchronization becomes too coarse.

An easy way to synchronize multiple data loggers with one camera is to shake or tap all of them simultaneously in one video and follow the aforementioned procedure

Figure 3.17: Synchronization diagram. The blue signals denote the movement from the same event.

for each data logger. Because the synchronization is done visually, the accuracy of the synchronization mostly depends on the frame rate of the video plus a small error that depends on the level of difficulty in correlating the event in the video with $M(t)$. Thus, with a rate of 30 frames per second, the accuracy is maximum 33 ms. However, the timestamp for the label is determined by the annotation in the graph. It is often easier to observe when the activity pattern changes by looking at the visualized movement data and this accuracy is bounded by the sampling rate of the sensor.

3.5.3 DISCUSSION

Approach A can achieve a high accuracy in the synchronization due to the red flash that occurs in the video stream. The synchronization accuracy in our approach is lower because the annotator needs to determine how the movement of the subject correlates to the sensor data graph. However, a disadvantage to Approach A is that synchronization needs to be performed frequently each time a sensor or camera is restarted and the annotator must make sure to record the flash on the data logger. Our approach has a number of advantages:

1. Synchronization only needs to be done once, and slightly adjusted when collecting data over multiple days
2. It becomes easier to collect more data because multiple subjects can be recorded simultaneously
3. Because multiple cameras can easily be used, it is possible to track subjects from multiple angles and around corners
4. Data loggers are synchronized with each other after synchronizing to the same camera

3.5.4 FUTURE WORK

Because labeling is such a tedious task while it remains very important, there is a tremendous opportunity to improve the labeling process. Since the animals only perform a

finite set of activities, most of the data is a repetition of the main performed activities, such as standing, eating, and walking as we have observed in our goat, sheep, and horse datasets. Therefore, increased intelligence during the labeling process could significantly speed up the process by not having to label data that obviously belongs to a known category. Active learning [149, 163] is a form of machine learning that interactively queries the annotator for information during the learning process. An active learner can run in the background during the labeling process and pose queries in the form of unlabeled data instances to the human annotator. Because the video is synchronized with the sensor data in our framework, the active learner can show the annotator the ground-truth video along with the unlabeled instance and query the annotator for a label. One strategy to increase the performance of the active learner is to query the annotator with data that is dissimilar to the labeled dataset. An active learner might not only remove the necessity to label repetitive activities manually but more importantly, greatly support the creation of more balanced labeled datasets, which remains an open issue in AR [55, 65].

Computer vision techniques using deep learning (DL) are rapidly improving in performance. These techniques are popular in a wide range of application domains such as medical imaging and self-driving car technology. As DL techniques become more accurate, they might be used to extract meaningful information from the ground-truth videos. At first, this technique can be used as an assistant providing suggestions when it is confident about the extracted labels from the video(s). If it becomes possible to overcome many challenges in activity recognition from videos, the ground-truth videos can be used as an extra sensor-modality in a soft-labeling approach of the data, initially supplementing, and possibly replacing, human labeling.

For the synchronization between video and sensor-data, the best idea seems to be to combine the two approaches that we discussed in Section 3.5.2.1 and use visual keys on the data loggers to synchronize the RTC between cameras and sensors. The potential framework could be further optimized using automated pattern detection in the video instead of shaking or tapping the sensors. Each sensor can emit a unique n -bit blinking pattern. Computer vision can be used to interpret the blinking patterns in the recorded video(s) and identify the sensors. Time information can be added to the pattern so that the offset between camera and sensor can be calibrated automatically. The synchronization would only need to be performed once per camera in a dedicated recording where all sensors and the blinking LEDs are visible to the camera. If clock drift error accumulates over time, this can either be corrected manually by the annotator (adding a small offset), by the time information in the blinking pattern (if this is visible), or repeating the synchronization recording. A physical clock can be included in the video recordings to synchronize multiple cameras with each other.

3.6 CONCLUSIONS

We have introduced the datasets that were collected in order to conduct the research presented in this dissertation. Firstly, we collected a dataset that comprises data from goat and sheep and can be used to investigate AAR between different species. Secondly, we collected a dataset that comprises motion data from 5 goats that was recorded from 6 sensors at diverse positions and orientations around the neck of the animals simul-

taneously. Finally, we collected a dataset that comprises motion data from 18 horses, of which a subset of data was labeled for 11 horses that performed 17 activities. This dataset is particularly suitable for unsupervised representation learning. To annotate the data, a framework was developed that displays the data along the ground-truth videos and allow the annotator to add labels to the data. RTC clocks in the cameras and sensor devices were used to time-stamp the data and synchronize the ground-truth video and the sensor data.

4

MULTITASK LEARNING BASED ANIMAL ACTIVITY RECOGNITION ON COLLAR TAGS

Collaring technology has immense potential for research in the field of animal ecology [185]. One major challenge is the diversity between animals within one species and between species. On the one hand, an individualized animal activity recognition (AAR) system yields higher performance than a generalized classifier. On the other hand, collecting and labeling data for each animal and (sub)species is a daunting task. Therefore, we investigate the trade-off between AAR performance and the generalization capability of an AAR system. Specifically, we study the effect of multitask learning (MTL) on the performance of a single AAR system that classifies the activities of two species. We test and compare 7 classifiers in three scenarios: trained with individual data, trained with data from one species and tested on the other and vice versa, and trained with mixed data from both species. The results show that MTL has a significant positive effect on the generic AAR capability of the classifiers. Various AAR applications, such as wildlife monitoring studies, often require a long lifetime and lightweight design. Therefore, we take into consideration that our approach needs to be used locally on a collar that is attached to (wild) animals by evaluating the effect of the sampling rate of the sensor and comparing the CPU and memory usage of 7 classifiers.

4.1 INTRODUCTION

For many years, collaring technology with inertial measurement units (IMUs) and Global Positioning System (GPS) has been widely used to study animal behavior. In Chapter 2 we showed that most existing work on animal activity recognition (AAR) are offline and centralized approaches in which sensor data is stored on the tag and retrieved later or transmitted wirelessly [50]. However, to be useful for livestock and wildlife monitoring in widespread and remote areas, AAR needs to be executed online (while activities are being performed) and locally (on the collar tag) due to the following reasons. On the one hand, collar tags have limited energy supply, memory, processing power, and transmission bandwidth. Also, the re-capturing of animals for data retrieval and battery replacement is dangerous, expensive, stressful for the animal, and sometimes impossible. On the other hand, local AAR significantly prolongs battery life since it consumes less power for data transmission, which typically consumes more energy than data processing. For example, transmitting a string of activity codes instead of raw sensor data requires a relatively small number of data transmissions. Moreover, online AAR enables the monitoring system to efficiently adapt its resource usage to a situation (e.g., the device can sleep when the animal is sleeping).

A common challenge in activity recognition (AR) is the sensitivity of the classifiers to individual traits of the subjects. Individuals within a species, and even more so between different species, are physically different from each other. Thus, motion data for a group of animals can be heterogeneous, and it is challenging to train classifiers that generalize well over a larger population of subjects when training data is only available from a subset of the population. On the one hand, a classifier that is too specific performs well on training data, but poorly on test data, or during deployment. On the other hand, collecting a sufficient amount of training data for each individual or type of species is infeasible. To overcome this challenge, we envision a one-fits-all generic classifier, and a similar vision is shared in other research areas such as human activity recognition (HAR) [60] and computer vision [151]. In this chapter, we propose a framework that employs multitask learning (MTL) [28] for embedded platforms. We address online AAR with collar-based platforms for large heterogeneous groups of animals in real-world environments. Collected motion data from a fraction of animals are used for offline training at a central server using MTL, which performs classification tasks across individual animals to learn the significant commonalities. The trained classifier models can then be implemented on the collars for online AAR of other animals. The results of AAR, or a summary thereof, can be sent to a sink node using a low-cost and long-range communication link such as an low power wide area network (LPWAN).

To further reduce resource consumption while maintaining a high classification performance, we aim at minimizing the computational load and memory requirements of

This chapter is partly based on:

- [76] J. W. Kamminga, H. C. Bisby, D. V. Le, N. Meratnia, and P. J. M. Havinga. Generic Online Animal Activity Recognition on Collar Tags. In *Proceedings of the 2017 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2017 ACM International Symposium on Wearable Computers - UbiComp '17*, pages 597–606, New York, NY, 2017. ACM Press. doi:10.1145/3123024.3124407

the classification. Using less and simpler features lowers down the CPU load, and saves energy. Therefore, we extract and utilize only the most informative features from raw accelerometer data of the collar tags. The collars are likely to shift and rotate throughout the day. Therefore, we aim to select features that are robust against the sensor orientation to reduce the effects of orientation on classification accuracy. The extracted features can be used locally on the collar to classify the animal activities using a classification technique that possesses a lightweight inference.

As a result, the proposed approach can be employed for various (sub)families of species. Our approach supports the development of an application in which collars can be placed on a group of animals without the necessity of training the classifier and fine-tuning parameters for every individual. Collars can then be readily deployed on animals with a lower risk of system failure due to a mismatch between an animal and the collar or configuration.

The main contributions of this chapter are:

- We show that Multitask Learning significantly improves the performance of a generic classifier.
- We verify the classification performance of our approach among 7 types of classifiers.
- We show that a window size of 2 seconds and sampling rate of 30 Hz are sufficient for AAR of goats and sheep when discriminating 5 activities.

4.1.1 CHAPTER ORGANIZATION

The rest of the chapter is organized as follows. In the following section we briefly describe the dataset that was used for the experiments in this chapter and how it was preprocessed. Secondly, we introduce the concept of MTL in relation to AAR. Thirdly, we explain the methodology of the MTL experiments in Section 4.4. Subsequently, we evaluate and discuss the effect of multitask learning on AAR performance in Section 4.5. Fifth, we analyze the effect of window size and sampling rate on the classification performance in Section 4.6. To consider their suitability for embedded systems, we compare the resource usage of 7 classifiers in Section 4.7. Finally, we draw our conclusions in Section 4.8.

4.2 DATA DESCRIPTION AND PREPROCESSING

We used Dataset 2 that was described in Chapter 3 for the experiments described in Section 4.4. The dataset comprises data from four goats and two sheep. These animals differ in size, weight, and age but belong to the same subfamily *Caprinae*. We randomly placed the sensors in various orientations on each animal. The various orientations of the collars and the sensor positions on three animals are indicated in Figure 4.1. The collars were prone to rotation around the animal's neck during the day. In Chapter 2 we discussed that gyroscopes can consume up to 100 times more power than accelerometers. Therefore, we used the accelerometer data. The impact of gyroscope data on AAR is further discussed in Chapter 5. All sensors were sampled with 200 Hz. The size and composition of the used dataset are shown in Table 4.1. The activities that were discriminated shown in Table 4.2.

Figure 4.1: Sensor placements on various animals, the red arrows indicate the location of the sensors. (a) Sensor placement on a sheep. (b) Different sensor placements on two goats.

Table 4.1: Number of 2-second data samples per individual for each activity

	Stationary Eating		Walking	Running	Trotting
Sheep 1	3071	6039	974	432	409
Sheep 2	6376	5196	1714	386	478
Goat 1	4466	2552	1956	214	252
Goat 2	7346	2044	1850	224	66
Goat 3	7468	3998	1842	30	120
Goat 4	10418	1386	1398	6	69

4.2.0.1 PRE-PROCESSING

All sensor data was first segmented according to the labeling file generated by the labeling application described in Section 3.5. For the individual performance evaluations, the segments were split into a typical ratio of 60 % training, 20 % cross-validation, and 20 % test-sets for all animals. Subsequently, the segments were further segmented using a fixed-width sliding window to obtain more samples that also have uniform lengths. We evaluated several window lengths, which we discuss in Section 4.6. A window length of two seconds resulted in satisfactory AAR performance while retaining sufficient data points. Therefore, the data for the evaluation of the effect of MTL on AAR performance was windowed with a two-second window size and 50 % overlap.

Table 4.2: Used activities during evaluation

Activity	Description
Stationary	The animal is lying on the ground or standing still, occasionally moving its head or stepping very slowly.
Eating	The animal is eating fresh grass, hay from a pile or twigs on the ground.
Walking	The animal is walking. The pace of walking varies from very slowly to nearly trotting.
Trotting	This is the phase between walking and running. The animal is not galloping rapidly but walking very quickly and is therefore in a trot state.
Running	The animal gallops.

4.3 MULTITASK LEARNING

In the context of activity recognition, multitask learning (MTL) can be used to train a more generalized classifier to classify activities of multiple individuals [166]. More formally, MTL is an approach to inductive transfer that improves generalization by using the domain information from training data of related tasks as an inductive bias [28]. Inductive bias is anything that causes a classifier to prefer one hypothesis over others. In MTL, multiple tasks are learned in parallel while using a shared representation to exploit the deep, subtle connections among tasks [33].

Let us assume that the domain of an animals' or species data distribution is denoted by D . Specifically, D is a 2-tuple $(\chi, P(X))$, where χ is the feature space of D , and $P(X)$ is the marginal distribution where $X = x_1, \dots, x_n \in \chi$ [127]. A task T is a 2-tuple $(Y, f())$ for a given domain D , where Y is the label space of D and $f()$ is an objective predictive function for D . $f()$ is not given, but can be learned from the training data [127]. In our case, each species belongs to domain D , and T is the task of training an AAR classifier. Figure 4.2a shows a single-task learning scheme, where a single classifier is trained for each animal individually. Figure 4.2b shows a multitask learning scheme, in which the training samples of multiple animals are mixed, and a generic model is trained for multiple tasks in parallel.

4.4 METHODS

Figure 4.3 shows a graphical representation of our approach. Each double-edged colored box denotes an inner loop in the process. We use the accelerometer data described in Section 4.2 as input to the classifiers. In the following subsections, we discuss each step in more detail. Firstly, we extract features and apply feature selection which are discussed in Section 4.4.1. To investigate the effect of MTL on AAR performance, we examine three scenarios. In each scenario the set of source domains $D_S = D_{s1}, \dots, D_{sn}$ and target domains $D_T = D_{t1}, \dots, D_{tn}$ are different. Specifically, we train and evaluate the classifiers with individual data (individualized), with data from one species and tested on the other and vice versa, and with mixed data from two species. In doing so, we investigate not only the trade-off between AAR performance and generalization but also

the impact of sharing knowledge across two similar species. Moreover, we repeat and compare the aforementioned experiments for 7 classifiers.

For each scenario described above, we use k combinations of animals. The combinations of animals are further discussed in Section 4.5. For each combination, we mix the samples, using random shuffling, into 3 data sets: training, cross-validation, and test, respectively. The training set T_k is always used to train the classifier for combination k . The cross-validation set C_k is used to test the classifier performance during parameter optimization. The classifiers and parameter optimization are discussed in Sections 4.4.2 and 4.4.3, respectively. Finally, the tuned classifier and test set V_k are used to assess the AAR performance P_k for each data combination k . The performances of all combinations are averaged to obtain the results for each scenario.

Figure 4.2: **(a)** Single-task learning schematic. A machine learning model is trained as an AAR classifier for each animal individually. **(b)** Multitask learning schematic. A single model is trained for multiple animals simultaneously.

Figure 4.3: Training and testing with mixed data. Each colored box denotes an inner loop

4.4.1 FEATURE EXTRACTION AND SELECTION

Because the sensor orientation was not fixed and varied between different animals, we require data features that are robust against the sensor orientation. To acquire orientation-independent features, we calculated the 3D vector (the ℓ^2 -norm) from the sensors' axes. The orientation-independent magnitude of the 3D-vector is defined as:

$$M(t) = \sqrt{s_x(t)^2 + s_y(t)^2 + s_z(t)^2} \quad (4.1)$$

, where s_x , s_y , and s_z denote the three respective axes of the sensor. $M(t)$ was calculated from the accelerometer data and used as input for the feature extraction. We calculated time and frequency-domain features that are typically used for activity recognition [13, 154, 194]. The features that were calculated are shown in Table 4.3. If we had used all the listed features for each axis of the accelerometer, we would have needed to calculate $21 \times 3 = 63$ features, which is the number of features times the number of axes of the sensor. An additional benefit of the transformation to a 3D-vector is that the sensor modality dimension is reduced from 3 to 1, and we have to calculate fewer features. We used feature selection to reduce the number of features further. Another option to reduce the sensor modality dimension would be to use just one of the axes of the sensor [126] (essentially a 1D-accelerometer). Doing so would save energy because the sensor needs to sense fewer dimensions. Also, the computational load would be lower because the transformation to $M(t)$ does not have to be calculated. However, the sensitivity of the motion signal then becomes dependent on sensor alignment with the direction of motion that is exerted by the animal. Thus, this is only possible when the orientation of the sensor is fixed.

4.4.1.1 FEATURE SELECTION

To select the most contributing features, we utilized the Relief algorithm [85]. Relief assigns weights to features based on their relevance. The Relief algorithm estimates the quality and relevance of features according to how well they can classify and discriminate between similar activity classes. The algorithm compares the values of the current feature with both the closest samples of the same activity class and the nearest different activity classes. Each feature was weighted according to the separation of the samples. Subsequently, the weights were normalized so that the top contributing features could be extracted. The 3 best scoring features were the Minimum, Standard deviation, and the 25th percentile and were used to characterize the motion data of all animals. After the feature extraction and selection, the data was standardized utilizing a Z-transformation, obtaining a standard score of each feature value.

In Chapter 5, we present a more advanced feature selection procedure. We focus more on the sensor position and orientation and present a feature selection approach that selects sensor orientation-independent features using multi-orientation motion data from 5 goats. The generalization of these features to horses is discussed in Chapter 6

Table 4.3: Summary statistics that were calculated for each window of data

Domain	Feature	Description
Time	Maximum	Maximum value
	Minimum	Minimum value
	Mean	Average value
	Standard deviation	Measure of dispersion
	Median	Median value
	25 th percentile	The value below which 25 % of the observations are found
	75 th percentile	The value below which 75 % of the observations are found
	Mean low pass filtered signal	Mean value of DC components
	Mean rectified high pass filtered signal	Mean value of rectified AC components
	Skewness of the signal	The degree of asymmetry of the signal distribution
	Kurtosis	The degree of 'peakedness' of the signal distribution
	Zero crossing rate	Number of zero crossings per second
Frequency	Principal frequency	Frequency component that has the greatest magnitude
	Spectral energy	The sum of the squared discrete FFT component magnitudes
	Frequency entropy	Measure of the distribution of frequency components
	Frequency magnitudes	Magnitude of first six components of FFT analysis

4.4.2 ANIMAL ACTIVITY RECOGNITION CLASSIFIERS

Below we describe the classifiers that were implemented together with their most important parameter settings. All classifiers were implemented in RapidMiner [118]. We used the following parameter settings for 7 classifiers in the experiments. The classifiers were introduced in Section 2.2.

Decision tree (DT) The information gain ratio of features was used as the splitting criterion. The maximal depth of the decision tree was varied between 1 and 100. Pruning was enabled, with a confidence level varying between 1×10^{-7} and 0.5. Pre-pruning was enabled throughout with varying parameters. Firstly, the threshold feature gain value for splitting was varied between 1 and 100. Secondly, the minimum number of examples at a node for the node to be split was varied between 1 and 100. Lastly, the minimum number of examples at a leaf node was varied between 1 and 100.

Neural network (NN) The activation function used was *sigmoidal*. The number of hidden layers necessary depends on the size of the data set. Since we are dealing with a relatively small data set, only one hidden layer was used. The number of neurons in each hidden layer was defined by:

$$\psi = \frac{\gamma + \rho}{2} + 1 \quad (4.2)$$

, where ψ is the amount of neurons in a layer, γ the number of features, and ρ the number of classes. The learning rate was varied between 4.9×10^{-324} and 1, while

the momentum was varied between 0 and 1. The error epsilon was set to 1×10^{-5} , and a maximum of cycles used for training was 500.

Support vector machine (SVM) A LibSVM C-SVC [86] model was used with linear kernel throughout. The epsilon value was fixed at 0.001, while the cost function was varied between 0 and 100.

Naive Bayes (NB) We used the traditional Naive Bayes algorithm that does not use adjustable parameters.

Linear discriminant analysis (LDA) LDA typically has no adjustable parameters.

K-nearest neighbors (k-NN) The measure of distance was Euclidean space, and the value of k was varied between 1 and 100.

Deep neural network (DNN) We used an implementation of the H2O 3.8.2.6 algorithm [27]. The DNN was used with 10 hidden layers which each contained 50 neurons. The start, ramp, and stable momentum values, as well as the number of epochs, were varied between 0 and 100. The annealing and decay learning rates, as well as L1 and L2 parameters, were varied between 0 and 1. The value of epsilon was set at 1.0×10^{-8} and the value of rho at 0.99. A multinomial distribution function and a cross-entropy loss function were used throughout.

4.4.3 PARAMETER OPTIMIZATION

To make a fair comparison between different classifiers, we performed parameter optimization before the performance assessment. Parameter optimization attempts to find optimal values for a parameter set of the classifiers. The classifier was embedded in a loop where various combinations of parameter settings were evaluated based on the classification performance of each configuration. We used an evolutionary approach that iteratively adjusted the various parameters of the classifiers until an optimal configuration was found. The approach used a genetic algorithm that aims to mimic the process of natural evolution. We used a maximum of 100 generations and the population size was set to 2. We used Gaussian mutation with tournament selection and a tournament fraction of 0.25. The crossover probability was set to 90 %. The optimal configuration of each classifier was used subsequently to assess the performance for each combination k in the experiments described in Section 4.5.

4.5 EFFECT OF MULTITASK LEARNING ON ANIMAL ACTIVITY RECOGNITION PERFORMANCE

In the following subsections we evaluate three scenarios: individualized AAR, MTL within a species, and MTL between species. Figures 4.4a and 4.4b show the accuracy and F_1 scores of each scenario per classifier. We discussed these evaluation metrics in Chapter 2.

4.5.1 SCENARIO 1: INDIVIDUAL ANIMAL ACTIVITY RECOGNITION

In this scenario, we used only individual data for training and testing the AAR classifiers. Thus, the training data was within the same domain as the test data ($D_S = D_T$). Therefore, no MTL takes place and the classifiers are trained with a single-task learning scheme (Figure 4.2a). We split data from each individual into 60 % training, 20 % cross-validation and 20 % training.

Because both training and testing data belong to the same domain (same individual), each classifier performed the best in this scenario. Thus, an individualized classifier always yields the best performance. The k-nearest neighbors (k-NN) classifier obtained the highest performance. There were insufficient samples for some animals in some classes. For example, Table 4.1 shows that *running* for Goat 3 and Goat 4 contained only 30 and 6 samples, respectively. Therefore, the performance may be improved by collecting more data for each individual.

4.5.2 SCENARIO 2: MULTITASK LEARNING WITHIN SPECIES

Grouping the data causes the classifier to be subject to individual traits, which may affect the performance. To see how much activity recognition accuracy is affected by grouping the animals per species, we aggregated data into two groups, i.e., one group consisting of two sheep and one group consisting of four goats. The classifiers were trained with mixed data from animals in one species simultaneously and tested with mixed data from the other species, thus ($D_S \neq D_T$). Here, MTL was utilized within each species, but not yet between species.

Table 4.4 shows the combinations of data used to train and test the classifiers. For each combination k , two animals from one species were divided into 60 % training and 40 % cross-validation, while data of two animals from the other species were used for testing.

Table 4.4: Scenario 2: Non-mixed training and testing combinations. G_i and S_i denote a goat and sheep, respectively.

Animals in 60% training and 40% CV		Animals in 100% testing			
G1	G2	S2	S1		
G1	G3	S2	S1		
G1	G4	S2	S1		
G2	G3	S2	S1		
G2	G4	S2	S1		
G3	G4	S2	S1		
S1	S2	G1	G2	G3	G4

Figure 4.4 shows that all classifiers performed significantly worse than the individual AAR scenario. The difference between the two species is too large to use a shared feature

representation only. The support vector machine (SVM) classifier performed the best in this scenario.

4.5.3 SCENARIO 3: MULTITASK LEARNING BETWEEN SPECIES

Grouping the data from multiple species causes the model to be subjected to not only individual traits but also species-specific traits, which may affect the performance. By mixing the data samples from all domains, the classifier can fit a model to a wider distribution. The classifiers were trained and tested with mixed data from multiple animals from two species, thus ($D_S \approx D_T$). Here, MTL was utilized between the two species (Figure 4.2b).

Table 4.5 shows the combinations of data for training and testing. For each combination k , 4 animals' data were mixed and divided into 60 % training and 40 % cross-validation, while 2 animals' data of both species were mixed and used for testing.

Table 4.5: Scenario 3: Mixed training and testing combinations. G_i and S_i denote a goat and sheep, respectively.

Animals in 60% training and 40% CV				Animals in 100% testing	
G1	G2	G3	S2	G4	S1
G1	G2	G4	S2	G3	S1
G1	G3	G4	S2	G2	S1
G2	G3	G4	S2	G1	S1
G1	G2	G3	S1	G4	S2
G1	G2	G4	S1	G3	S2
G1	G3	G4	S1	G2	S2
G2	G3	G4	S1	G1	S2

Figure 4.4 shows that mixing data from both species, in both training and testing sets, yields a significant improvement in the performance of the classifiers. The average increase in F_1 performance is 11.11 %. The performance is similar to that of the individual scenario, except for the k-NN classifier's F-score. The SVM classifier outperforms the other classifiers, closely followed by the deep neural network (DNN) classifier. The big gap in performance between the unmixed and mixed instance scenarios shows that the two species share sufficient characteristics so that a generic classifier can be trained.

4.6 ANALYZING IMPACT OF WINDOW SIZE AND SAMPLING RATE

In this section, we evaluate the effect of the window size and sampling rate on the AAR performance. To minimize the impact of the classification system, we used the same

Figure 4.4: Performances per classifier. The performances are averaged over all individuals or combinations. (a) Accuracies. (b) F_1 scores.

classifier for all experiments. We used a k-NN classifier with $k = 1$. k-NN determines the class of a feature vector based on the majority vote of the values of the k -nearest neighbors in the example set.

4.6.1 EFFECT OF WINDOW SIZE ON CLASSIFICATION PERFORMANCE

To evaluate the effect of the window size on the classification performance, we repeated the AAR process with various window sizes. The window size of the raw data was varied between $\{0.5, 1, 2, 3\}$ seconds. Because our labeled dataset is small, especially the minority classes *trotting* and *running*, too many data samples are lost when larger window sizes are used due to two reasons. Firstly, when a continuous activity segment is shorter than the window size, it is discarded. In longer segments, the tail at the end of each segment is discarded when it is smaller than the window size. Secondly, Equation 3.2 in

Section 3.2 denotes that a larger window size results in fewer samples (each window is denoted as a sample).

The sampling rate of the data was retained at 200 Hz for each of these window sizes, and AAR was performed in two scenarios, for each animal individually, and using MTL within the same species.

Figure 4.5a shows the classification performance for each animal and different window sizes. Figure 4.5b shows that, on average, the classification accuracy is highest at a three-second window size. However, the relative difference between one and two-second window sizes is marginal (0.81 %). Because a window size larger than 2 seconds did not yield a sufficient amount of samples for the minority classes while it did not significantly increase the performance, we used a window size of two seconds for the rest of our evaluations.

To see the effect of window size in a MTL scenario, we mixed the data within the same species and repeated the AAR classification using different window sizes. The results are shown in Figure 4.5c from which can be seen that a window size of three seconds has the highest average accuracy of 98 %. This performance is comparable to the average accuracy for individual animal's accuracy, shown in Figure 4.5b. Besides the effect of the window size on the performance of the classifier, these results show that it is possible to train a model with mixed data from multiple individual animals without experiencing a significant loss of classification accuracy. We investigate this effect of MTL in more depth in Section 4.5.

4.6.2 EFFECT OF SAMPLING RATE ON CLASSIFICATION PERFORMANCE

The data was down-sampled to study the effects of a lower sampling frequency. Our goal was to find the frequency where the performance of the classifier starts to decrease. In signal processing, the Nyquist rate is known as a lower bound for the sample rate for alias-free signal sampling. The lower band denotes that the sampling frequency should be at least double the frequency band of interest. We expect that some activities, such as eating, involve frequencies in the motion signal that are at least 5 Hz. Thus, a minimum sampling frequency of 10 Hz is required to detect these activities reliably. The sampling rate was varied between {10, 30, 60, $\dots$, 200} Hz for each window. A window size of 2 seconds was used. AAR was performed for all animals and each sampling rate.

The individual and average AAR performance for various sampling rates are shown in Figure 4.6a and Figure 4.6b, respectively. It is clear that between 30 and 200 Hz, the average performance curve is almost flat. These results show that higher sampling rates do not increase the performance for activity recognition of goats and sheep. This can be explained by the fact that the frequencies of the acceleration vector for most activities are low. We did try to classify the behaviors using a sampling rate below 10 Hz, but due to the small labeled dataset, some classes never received any predictions; this made the performance results too unreliable to include here. Future work entails a low-sampling rate experiment with a larger dataset.

4.7 RESOURCE USAGE

While most machine learning studies focus on the performance of a technique, other criteria should be considered when selecting a classifier [86], especially when selecting a classifier to be used on an embedded platform. Here, we focus mainly on the CPU execution time and memory usage. To reflect on the trade-off between accuracy and resource consumption, we measured the CPU run-time and memory usage for all 7 classifiers. Memory and CPU measurements were taken using a PC with an Intel core i7-2600 with 4GB of RAM and a clock speed of 3.40GHz running Windows 7 64-bit. An embedded system most likely uses a different CPU and memory architecture, which affects the comparison. Therefore, our results are an indication, and no hard conclusions can be drawn from these measurements. Using only 3 features made the inference phase too fast on a PC to be able to take high-resolution measurements. Therefore, we decided to use higher-dimensional data during the comparison of the classifiers. We used the principal components that account for the top 99 % of the variability in the data, resulting in 109 components (features). Memory consumption was measured using JProfiler v10.0 [39]. The memory usage was measured by running the same task (training or inferring a model) 5 times while forcing the garbage collection operation before and after the performed task in order to measure the amount of heap memory consumed by the algorithm. The value of memory usage includes the memory used by the software. Therefore we evaluate relative memory usage. The average of these 5 measurements was taken in order to account for anomalous fluctuations. The CPU execution times were measured using the log operator in RapidMiner Studio v7.4 [118]. The training and inference CPU execution times were measured and averaged across 20 runs for each of the algorithms.

Figures 4.7 and 4.8 show the memory usage and CPU execution time, respectively. The most important comparison should be made in the inference phase because this is the phase to be implemented and executed on the embedded system. It can be seen that the decision tree (DT), naive Bayes (NB), neural network (NN), and DNN classifiers all consumed the lowest amount of memory in the inference phase, which makes them good candidates for embedded platforms. The results show that the SVM, k-NN, and linear discriminant analysis (LDA) are not the most suitable candidates for an embedded system because they consumed the most memory and had the longest CPU execution times. The NB classifier was the best performing in terms of CPU usage, closely followed by the NN, DNN, and DT classifiers. Overall, the NB classifier consumed the least amount of resources. In the scenario where we mixed data from two species, the relative difference in F_1 performance between NB and the best performing classifier (SVM) was 5.04 % (4.26 % absolute difference). The SVM required 9 times more memory and had 200 times longer execution time. This means that a classifier with a higher resource efficiency does not perform significantly worse than a classifier which uses a lot more resources.

Figure 4.5: Classification performance versus window size (a) Performance for individual animals. (b) Average performance. The error bars denote the standard deviation over the various animals. (c) Performance using grouped data of goats and sheep.

(a)

(b)

Figure 4.6: Performance versus sampling rate. (a) Individual performances versus sampling rate. (b) Average performance for various sampling rates. The error bars denote the standard deviation over multiple animals.

Figure 4.7: Memory usage for training and inference phases of various classifiers

Figure 4.8: CPU execution time for training and inference phases of various classifiers

4.8 CONCLUSIONS

In this chapter, we discussed the trade-off between AAR performance and the generalization capability of an AAR system. We used real-world motion data from goats and sheep to evaluate AAR in three scenarios. We showed that an individualized AAR system always performs best. Training a classifier with data from one species, and using that classifier to predict activities of another similar species, yielded relatively bad AAR performance. We have shown a significant increase in performance when MTL is utilized between species by using data from two species and a shared feature representation to train a classifier. On average, the F_1 performance increased with 11.11 %. The performance approached that of the individualized scenario, where data was used per individual.

We analyzed the resource usage in terms of memory and CPU usage between 7 classifier types. In our comparison, the NB classifier used the least amount of resources while the attained F_1 score was 5 % lower relative to the best performing classifier (SVM). However, NB used 9 times less memory and executed 200 times faster. Thus, more resource-efficient activity recognition with MTL has a small trade-off in terms of performance. A robust comparison between actual resource usage of classifiers on embedded systems requires further investigation.

Besides the training of a generic classifier, our results indicate that data from similar species may be mixed to improve the classification of one of the species. For example, it can be difficult to obtain labeled data from a wild animal (e.g., zebra), while it is usually easier to collect data from a similar domesticated animal (e.g., horse). A small labeled dataset for the zebra can be mixed with data from the horse to complement the training of the classifier. This is under the assumption that the sensor location of the collected data is somewhat similar. For example, we always attached the sensors around the neck of the goats and sheep, but not in fixed positions and orientations.

One reason for declined AAR performance could be the position and orientations of the sensors around the neck of the animals. Simultaneously, the Relief algorithm may not be the most elaborate feature selection method. The dataset that we used for the research in this chapter proved insufficient to study the effect of the sensor position and orientation on the performance. Therefore, we performed a follow-up study to address the sensor position and orientation using a better dataset and elaborated feature selection method. This study is presented in Chapter 5.

5

SENSOR ORIENTATION-INDEPENDENT FEATURE SELECTION

Motion sensors placed around the neck of an animal can be displaced over time by the animal itself (e.g., scratching or biting), its environment (e.g., other animals or vegetation), and misalignment during manufacturing or collaring. The animal activity recognition (AAR) performance degrades significantly in these cases when a classifier is sensitive to the orientation and position of the sensor around the neck. Additionally, collar tags often have limited energy, memory, and processing resources. In this chapter, we aim at finding small optimal feature sets that are lightweight and robust to the sensor's orientation. Our approach comprises four main steps. First, 3D feature vectors are selected since they are theoretically independent of orientation. Second, the least contributing features are suppressed to speed up computation and increase robustness against overfitting. Third, the features are further selected through an embedded method, which selects features through simultaneous feature selection and classification. Finally, feature sets are optimized through 10-fold cross-validation. We show that the performance is robust to sensor orientation and position. Furthermore, the results show that activities can be accurately recognized using only accelerometer data and a small number of lightweight features. A simple Naive Bayes classifier using only a single feature achieved an accuracy of 94 % with our empirical dataset. Moreover, our optimal feature set yielded an average of 94 % accuracy when applied with six other classifiers.

5.1 INTRODUCTION

Collaring technology has immense potential for research in the field of basic and applied animal ecology [34]. Animals have been collared in many studies for varying research purposes, including animal identification, tracking, and health monitoring. Figure 5.1 shows a collared lion. The battery pack, which is usually the heaviest component, is not hanging at the bottom of the neck but is rotated 90°. Thus, although the battery pack is often expected to be at the bottom, the collar can still rotate around the neck because they are subjected to violent movements and displacement by the animals. The collar may also be displaced by other animals or elements in the environment, such as thick vegetation. Furthermore, because it is essential to keep collar tags as lightweight as possible, this minimizes the counter-weight effect of heavy components. Therefore, collars used for AAR must be robust against the orientation of the sensor.

Figure 5.1: A lion wearing a collar that is rotated around the neck from its intended orientation. The encircled battery is supposed to be located at the bottom of the neck. Credit:

Long lifetime and smaller size of a monitoring collar require a design with minimal complexity without compromising accuracy. The objective of this work is to meet

This chapter is mainly based on:

- [79] J. W. Kamminga, D. V. Le, J. P. Meijers, H. Bisby, N. Meratnia, and P. J. Havinga. Robust Sensor-Oriented-Independent Feature Selection for Animal Activity Recognition on Collar Tags. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies* IMWUT, 2(1):1–27, 2018. doi:10.1145/3191747

these requirements by discovering a small subset of features that can be used for online, energy-efficient, and orientation-independent activity recognition of animals.

When we speak about orientation throughout this chapter, we often implicitly talk about the orientation and position of the sensor. Because sensors attached to a collar rotate around the neck, the orientation and position are both changing simultaneously. In Chapter 2 we showed that many studies assume that the orientation of a sensor on a body is fixed when classifying activity [84, 133, 194]. However, the variability in sensor-orientation causes significant errors if activity classifiers are sensitive to sensor orientation. Several studies in the state of the art mention sensors that get displaced unintentionally [87, 126, 174]. One study [174] added extra weight to counterbalance the collar in an attempt to fix the orientation. However, doing so does not ensure the orientation, and adding extra weight could be harmful to the animal [8, 24]. For example, when wildlife is collared, a general rule of thumb for the weight of an animal collar is usually 5 % of their body weight [8]. Brooks et al. [24] found a significant effect of collar weight and its fit on the travel rate of zebra females. The authors compared two types of Global Positioning System (GPS) collars. Although both types were well within accepted norms of collar weight, the slightly heavier collars (0.6 % of the total body mass) reduced the rate of travel by more than 5 % when foraging compared with the collar that was 0.4 % of total body mass. Instead, it may be better to use sensor-orientation-independent AAR. Therefore, activity classifiers must be insensitive to sensor orientation.

5.1.1 ORIENTATION-INDEPENDENT FEATURES

Due to the resource limitations of collar tags, it is essential to calculate only those features that are both sensitive to changing behaviors and robust to sensor orientation. Therefore, to save computational load and memory usage, the complexity of an AAR system must be kept to a minimum, and the trade-off between classification performance and resource efficiency carefully evaluated. Complexity can be found in two parts of the application; first, in the feature extraction from the sensor data, and second in the classifier. It is our challenge to find an optimal combination of the two, which both minimizes computational expense and maximizes performance.

Robustness to sensor orientation has been widely researched in the field of human activity recognition (HAR). Sensor orientation independence can be tackled in two ways [154]: (i) using orientation-independent features: to only use those features that are insensitive to orientation [137, 155]; (ii) transformation of the input signal: for which in most cases – for all input data – the coordinate system of the mobile device is transformed into a global coordinate system before activity classification [45, 124]. However, the continuous transformation of raw measurement data is computationally intensive and, as aforementioned, should be avoided for animal tags. Studies on HAR, which claim to use orientation-independent features, often make use of the magnitude of the 3 axes of the accelerometer [137, 155]. However, multiple features can be derived from the 3D vector of a 3D accelerometer or 3D gyroscope. To the best of our knowledge, an extensive analysis of the 3D vector has not yet been performed.

5.1.2 AN OVERVIEW OF OUR APPROACH

Our main objective is to discover a small optimal set of features that are orientation-independent and can discriminate between various activities using a low-complexity classifier. Therefore, from the raw data collected by collar tags, we propose the extraction of only the most informative orientation-independent features.

We select features through a combination of filtering and wrapping techniques – the so-called embedded method. The filter is based on the Chi-squared Test [130], while the wrapper is based on sequential forward selection (SFS) [54]. The selection yields small, efficient subsets of features that are lightweight and robust to sensor orientation, while still providing a very high accuracy value, i.e., above 95 %.

Extracted features are used locally – by the collar tag – to classify the animal activities using a lightweight classification approach such as the Decision Tree. Summary results of activity recognition are then sent to a sink node, using a low-cost and long-range communication link such as a low power wide area network (LPWAN), that has recently become popular in the internet of things (IoT) paradigm. By doing so, we aim to resolve the problem of energy consumption and communication constraints.

The approach is evaluated by analyzing a total of 126 features, captured by six 3D accelerometers and 3D gyroscopes in different orientations on five farm animals. As a result, the global behavior of multiple individuals can be analyzed by a central server using an advanced inference approach that utilizes the characteristics which were derived locally on the tags.

Additionally, we test the subsets of selected features on other classifiers such as neural network (NN), support vector machine (SVM), linear discriminant analysis (LDA), and k-nearest neighbors (k-NN). The results show that the average accuracy is at least 80 % for typical activities such as being stationary, walking, eating, running, and trotting. The high performance signifies that even though the features set was optimized for the decision tree (DT) or naive Bayes (NB) classifiers, the features presented in this chapter can be reused with other classifiers while maintaining good accuracy.

5.1.3 CHAPTER ORGANIZATION

The rest of the chapter is organized as follows. Firstly, related work is discussed in Section 5.2. Secondly, the proposed feature selection methodology is detailed in Section 5.3. Thirdly, the dataset and pre-processing are described in Section 5.4. Subsequently, the results of various evaluations are presented in Section 5.5. Finally, conclusions are drawn in Section 5.6.

5.2 RELATED WORK

In the following two subsections we discuss the related work in feature extraction and sensor orientation-independent activity recognition, respectively.

5.2.1 FEATURE EXTRACTION AND CLASSIFICATION

Smith et al. [156] studied features in cattle behavior models, using a greedy search to identify feature subsets that were most effective in classifying activities of steers. The authors elaborated on this work [157] and classified five general activities of dairy cows.

By means of an ensemble method, the authors trained multiple binary classifiers for each activity independently. Embedded feature selection was used to select a subset of features that produced the best performance for each activity. The orientation of the sensor attached to the cows was fixed in both studies [156, 157] and the authors did not consider orientation-dependency.

Real-time activity recognition systems with wearables have been widely studied for humans, and have a certain overlap with animal activity recognition. Yang et al. [191] consider only time-domain features and disregard frequency-domain methods such as FFT and wavelet analysis in order to limit time and processor consumption in their implementation of a real-time activity recognition system. They state that *Mean*, *Root Mean Square (RMS)*, and *Standard Deviation* are the most common and practical time-domain features to be used for activity recognition. They state that *mean* offers both the highest accuracy and the easiest implementation. By calculating only the *mean* value of the accelerometer data, 87.55 % accuracy in the classification of five activities was achieved using a naive Bayes (NB) classifier. Liang et al. [103] built on this by applying a 'two-step feature extraction' method for classifying 11 activities using data from a smartphone's onboard tri-axial accelerometer. Although the aforementioned papers describe the extraction of basic features such as *mean*, *standard deviation*, and *magnitude* in order to reduce the feature dimension, feature selection remains a useful, yet unexplored, issue to distinguish the most prominent of a large array of features. Zhang et al. [194] investigate feature selection for human activity recognition, stating that high-quality feature selection is 'essential' for the improvement of classification accuracy. They discussed three methods: Sequential Forward Selection (SFS), Relief-F, and Single Feature Classification (SFC). SFS, which was found to deliver the best performance, adds features one by one sequentially, evaluating the accuracy for each sequential combination. This method is the simplest form of greedy feature selection, which is employed by Marais et al. [108] to classify sheep behavior, finding the maximum and minimum values for each axis in a frame as the most important feature out of *mean*, *standard deviation*, *variance*, *skewness*, *kurtosis*, *energy*, *frequency-domain entropy*, *correlation between axes*, and *average signal magnitude*. This combination of features is widely used in activity classification [11, 13, 109, 135]. Previous approaches either select features by using randomly selected training and test data from the full dataset [108], providing similar proportions of each specimen's data in both the training and the test set by visual or statistical analysis [128], or by comparing various feature combinations found in the literature to reach the highest performing combination [62, 133]. However, these methods do not aim to optimize feature sets for robust orientation-independent classification. Lester et al. [100] address the problem of creating a generic algorithm suited to an individual 'out-of-the-box' by training and testing their algorithm on a dataset that contains activity data from a large and diverse group of individual animals. However, they do not address robustness of the selected features.

5.2.2 SENSOR-ORIENTATION INDEPENDENT ACTIVITY RECOGNITION

A number of works have reported the effects of various placements of sensors on the human body [9, 111, 116]. Error in activity recognition due to sensor orientation is often tackled by ensuring that the device orientation is defined in advance relative to the

subject's orientation [20, 174, 186]. Ngo et al. [124] use a tilt-correction method and an orientation-compensative matching algorithm is applied in order to solve the remaining relative sensor orientation angle between training and test data. Florentino-Liano et al. [45] transform the measurements from the device's frame into a fixed frame using a rotation matrix. However, these approaches require undesirable additional computational expense. Another solution to this problem is to use orientation-independent features such as the magnitude of an accelerometer as implemented in [155] and [137]. Fixing a device to an animal's body in a particular orientation is impractical and orientation compensating techniques are not always efficient. Therefore, we aim to find features that are orientation-independent and efficient, yielding accurate activity recognition.

5.3 METHODOLOGY

This section details the proposed approach to find orientation-independent features. During the feature selection process, the data from goat G4 were used because this dataset contains both the largest quantity of data and the best balance between the activities. A graphical representation of the approach is shown in Figure 5.2, wherein each colored box represents an inner loop in the process. First, we select only 3D-vector features since they are theoretically robust to sensor orientation [155]. Second, for each fold k of the data with selected 3D-vector features, a filter method is applied in order to suppress the least interesting features. The core of our feature selection is an embedded method, which selects features through simultaneous feature selection and classification [54]. The embedded method comprises a wrapper that uses classification performances as criteria to select the most informative features. The classifier is used within the wrapper as a black box to weight feature subsets based on their recognition performance. The embedded method was executed with the Forward Selection scheme for all 10 folds with various maximum feature set sizes denoted by n in the range of $\{1, \dots, 10\}$ so that a total of 100 instances of $F_{k,n}$ were obtained. Finally, the feature selection results of 10 folds were used to select the most optimal feature set for each size n . The aforementioned steps are described in more detail in the following subsections.

Figure 5.2: Embedded feature selection process. Each colored box denotes an inner loop

5.3.1 FEATURE EXTRACTION

A selection was made consisting of time and frequency-domain features that are typically used for activity recognition [13, 154, 194]. Although frequency-domain features are more complex to calculate than time-domain features [43], no features were excluded because of their higher complexity because this study aims to perform exploratory analysis and to find those features that are most robust to sensor orientation. Table 5.1 denotes the features that were calculated for each window of data. The total number of 126 features is calculated by multiplying the number of derived features with the number of sensors and axes used in the selection process.

Table 5.1: Features that were calculated for each window of data from all sensors and all their axes

Feature	Description	Number of features
Maximum	Maximum value	6
Minimum	Minimum value	6
Mean	Average value	6
Standard deviation	Measure of dispersion	6
Median	Median value	6
25 th percentile	The value below which 25 % of the observations are found	6
75 th percentile	The value below which 75 % of the observations are found	6
Mean low pass filtered signal	Mean value of DC components	6
Mean rectified high pass filtered signal	Mean value of rectified AC components	6
Skewness of the signal	The degree of asymmetry of the signal distribution	6
Kurtosis	The degree of 'peakedness' of the signal distribution	6
Zero crossing rate	Number of zero crossings per second	6
Principal frequency	Frequency component that has the greatest magnitude	6
Spectral energy	The sum of the squared discrete FFT component magnitudes	6
Frequency entropy	Measure of the distribution of frequency components	6
Frequency magnitudes	Magnitude of first six components of FFT analysis	36
Total		126

Our goal is to find orientation-independent features; therefore, a 3D vector was calculated from the sensors' axes. The orientation-independent magnitude of the 3D vector is defined as:

$$M(t) = \sqrt{s_x(t)^2 + s_y(t)^2 + s_z(t)^2}, \quad (5.1)$$

where, s_x , s_y , and s_z are the three respective axes of the sensor. $M(t)$ was calculated from both the gyroscope and accelerometer data. All data were standardized through a Z-transformation, obtaining a standard score of each feature value. Standardization does not affect the performance of decision tree (DT) and naive Bayes (NB) classifiers.

5.3.2 FILTER: CHI-SQUARED TEST [130]

Since filters are faster than wrapper methods, they can be used as a pre-processing step to reduce space dimensionality and overcome over-fitting. Moreover, filters can provide a more generic feature set that is not specifically tuned for a given classifier [54]. To determine the relevance of each feature concerning the activity label, the Chi-Squared test [130] was applied to the feature set. The Chi-Squared test is a statistical technique to determine the independence between features. The test determines if a distribution of observed frequencies differs from the theoretically expected frequencies [130]. The Chi-Squared statistic is expressed as

$$\chi^2 = \sum_{i=1}^n \frac{(O_i - E_i)^2}{E_i} \quad (5.2)$$

, where O_i is the observed frequency and E_i is the expected frequency. A weight was calculated for each feature, and the 30 % lowest-scoring features were filtered to speed up the embedded forward selection.

5.3.3 EMBEDDED FORWARD SELECTION

After applying the Chi-Squared filter, the remaining features were used as the input for the embedded forward selection [54] method. Forward selection starts with an empty set of features F , retrains, and tests the performance of the classifier with each isolated feature of the given dataset. Only the feature that gives the highest increase in performance is added to the subsequent feature set F . This set is then used as the basis for the next round of adding features until one of the stopping criteria, detailed in the following paragraph, was met.

In Chapter 4 we compared the CPU execution times and memory usage of 7 classifiers. The NB classifier used the least amount of resources in both the training and inference stage and is a suitable candidate for implementation in a collar tag. The next classifier with short execution times in both stages was the decision tree (DT). The NN-based classifier also attained good performance and low resource use in the inference phase. However, the design space for NN is relatively large, and each design choice can have a significant effect on the performance. Additionally, the resource usage measurements in Chapter 4 show that the CPU execution time for training a NN was 10000 times higher than NB. Because the embedded classifier is retrained in each iteration of the algorithm, embedding a NN resulted in very long runtimes. The number of design choices for NB and DT is much lower, they are trained much faster, and they have low processing and memory requirements for implementation in a collar. Therefore, we performed forward selection separately twice, first a DT was used within the embedded method and second a NB classifier, resulting in two feature sets.

In order to investigate the effect of the number of features used, denoted as n , on the recognition performance, we used a maximum number of features as the first stopping criterion. By incrementing the maximum number of features from 1 to 10, 10 feature sets with incremental sizes were obtained for both the DT and NB classifier. The second stopping criterion was defined as a minimum increase in performance. The iteration was terminated when the absolute performance did not increase at all, so that the first

criterion was enforced as much as possible. Three speculative rounds were implemented in order to avoid getting stuck in local optima.

During the forward selection process, the classifier was trained using merged training data from all 6 sensors with various orientations. Simultaneously, the classifier was tested with merged cross-validation data from all 6 sensors. The samples were always shuffled after merging to prevent bias of the classifier towards a single orientation. Due to the fact that the classifier was trained with mixed data from all orientations, orientation-dependent features would not perform well. Therefore, the result of the feature selection process is a feature set that is robust against sensor-orientation.

The process described above was repeated ten times by using a 10-fold cross-validation of our sensor datasets, leaving out a test set for each fold. This approach resulted in 10 feature sets F for both the DT and NB classifiers and for each size n of F in a range of $\{1 \dots 10\}$. Ultimately, the test sets were only used in order to assess the performance of the final feature set.

5.3.4 OPTIMAL FEATURE SET SELECTION

Finally, the optimal feature set was selected from the results of the 10 folds. In order to study the effect of the number of features (size of n) on the classification performance we selected 10 optimal feature sets incremental in sizes $n = \{1 \dots 10\}$ for both the DT and NB classifier. The optimal feature set selection algorithm is shown in Algorithm 1. The embedded selection process resulted in a 3-dimensional binary feature weight map. The 3 dimensions are all features H , feature-set-sizes n , and folds k . For every set-size n in the binary map F , Algorithm 1 selected the features that were most often selected over 10 folds and included them in the final optimal feature set $Uopt_{1\dots n}$.

ALGORITHM 1: Optimal feature set selection

Data: $F_{1\dots H, 1\dots n, 1\dots k}$, F is a binary feature weight map for all features H , set-sizes n , and folds k

Result: $Uopt_{1\dots n}$, the optimal feature sets for all sizes n

```

for  $n = 1$  to 10 do                                /* where  $n$  is the feature set size */
    for  $k = 1$  to 10 do                              /* where  $k$  is the fold */
        for  $i = 1$  to  $H$  do /* where  $H$  is the total number of features */
            if  $F_{i,n,k}$  then
                 $S_{i,n} = S_{i,n} + 1$ ;                /* count selections for feature  $i$  in
                feature-set-size  $n$  over folds  $k$  */
            end
        end
    end
end
for  $n = 1$  to 10 do
    sort( $S_{1\dots H,n}$ , descending);                    /* sort the feature scores */
     $Uopt_n = S_{1\dots n,n}$ ;                          /* pick the  $n$  best scoring features */
end

```

5.4 DATA DESCRIPTION AND PREPROCESSING

For this research, we used a dataset that comprises motion and orientation data from 3D accelerometers and 3D gyroscopes. The dataset and collection process are described in more detail as Dataset 2 in Chapter 3.3. Figure 5.3 shows a 3D sketch of the collar that was used during data acquisition and the sensor positions with their respective x , y , and z axis. All efforts were put in to maximize the difference in positions and orientations between the six sensors for all three x , y , and z axis. Since a sensor node placed on the left would give similar data to one placed on the right, due to the symmetry, we allocated sensor nodes on one side of the goat's neck as much as possible. An identical configuration was used for each animal. Table 5.2 shows the amount of data per animal that was used for this research. The *other activities* class comprises the activities: *fighting*, *shaking*, *climbing-up*, *climbing-down*, *rubbing*, and *food-fight*.

Table 5.2: Composition of the dataset per goat. The columns denote the number of 2-second samples and proportions of data from 6 sensors per (grouped) activity

Name	G1		G2		G3		G4		G5	
Activity	samples	fraction	samples	fraction	samples	fraction	samples	fraction	samples	fraction
Stationary	56584	28.5%	18816	18.8%	40685	35.2%	63172	36.8%	19194	65.2%
Walking	26434	13.3%	18703	18.7%	13581	11.7%	25943	15.1%	6090	20.7%
Trotting	594	0.3%	941	0.9%	710	0.6%	2674	1.6%	870	3.0%
Running	510	0.3%	298	0.3%	316	0.3%	2720	1.6%	690	2.3%
Eating	76655	38.7%	38303	38.2%	46219	40.0%	22710	13.2%	912	3.1%
Other activities	6420	3.2%	3790	3.8%	3016	2.6%	1188	0.7%	222	0.8%
Null	31110	15.7%	19313	19.3%	11161	9.6%	53297	31.0%	1455	4.9%
Total	198307		100164		115688		171704		29433	

5.4.1 DATA PARTITIONING FOR TRAINING, VALIDATION, AND TESTING

To prevent information leakage, segments, instead of windows, were divided into training, cross-validation, and test sets for all sensor orientations. The cross-validation sets were used during the feature selection process. The test sets were only used at the end to assess the performance of the final feature set.

K-fold cross-validation [148], also referred to as rotation estimation, ensures that each data sample has been used at least once as training, cross-validation, and test data. In each iteration k , we divided the labeled segments into three respective datasets, rotating over the whole dataset. 10-fold cross-validation was used to obtain 10 training, cross-validation, and test sets. This method divides the data into 80 % training, 10 % cross-validation, and 10 % test data. Both the feature selection process and performance assessment were repeated 10 times.

Since some activities may have a long duration, the data among the activities may be unbalanced, which results in a significant bias for the activity learning and testing phase. For example, a *stationary* activity can last either 20 minutes or 5 seconds; if the longer duration is used as training and the shorter as testing, then the activity *stationary* might have a larger ratio of training/testing than other activities. To eliminate this imbalance,

Figure 5.3: A 3D sketch of the collar with the attached sensor units seen from two angles. The red arrow denotes the front of the animal. The blue and green axis denote vertical and horizontal axis, respectively. The blue and red colored faces denote the bottom and top side of the sensor nodes, respectively. The sensor nodes have been labeled A to F clockwise.

we recursively split each segment into smaller ones until each segment had a maximum length of 10 seconds. The segments were split before dividing them into training, cross-validation, and test sets.

The effect of the splitting is shown in Figure 5.4. It can be seen in Figure 5.4a that the ratios between the 3 sets vary for each activity when the data are not recursively split to segments with a maximum length of 10 seconds. Figure 5.4b shows the proportions when the data was split; it can be seen that the ratios are more balanced between the activities.

After the division of segments into three groups, the segments were further segmented using a fixed-width sliding window to obtain more samples that also have uniform lengths. In Chapter 4, we discussed the trade-off between window size and AAR performance. We showed that a window length of two seconds resulted in satisfactory AAR performance while retaining sufficient data points. Therefore, we used a window size of two seconds and a 50% window overlap. For each window, calculation of the features described in Section 5.3.1 was performed.

5.5 EVALUATION

In this section, the results of the feature selection are presented, and subsequently, the orientation-independent activity recognition performance of the DT and NB optimal feature sets.

Figure 5.4: Distribution of data over training, cross-validation, and test sets. (a) No recursive splitting of segments. (b) Recursive splitting of segments to maximum length of 10 seconds

All classifiers were implemented in RapidMiner [118], and no performance fine-tuning was performed for any of the classifiers. We used *information gain* as the splitting criterion for the DT, with a maximal tree depth of 10 and the application of both pruning and pre-pruning. The NB classifier used Laplace smoothing to prevent the strong influence of zero probabilities. For the remaining classifiers, we used generic parameter settings.

5.5.1 EVALUATION OF FEATURE SELECTION

Figure 5.5 shows the selected features when the DT classifier is used within the wrapper. Each color represents a feature, and the size of the box represents the number of times that the feature is selected over 10 folds. When a feature is selected less than 10 times over all 10 folds and feature set sizes n , it is considered to be insignificant and is not shown in Figures 5.5 and 5.6.

Forward Selection with the DT classifier selects various features over 10 folds when the size of the feature set is $n > 1$; this means that the DT classifier is less sensitive to the variety of features. Figure 5.5 shows that the 6th magnitude in the norm of the accelerometer's 3D vector is the best-performing feature to use with the DT classifier if a single feature is used. The optimal feature set comprises the features that are most often selected over 10 folds and is shown in Table 5.3, in which each column denotes the feature set with size n . When a box in Figures 5.5 and 5.6 is similar in size to the largest box, this means that interchanging some of the features in our optimal set (Table 5.3) with these other high-scoring features in Figures 5.5 and 5.6 will not significantly degrade the performance. For example, the standard deviation of the accelerometer's 3D vector performs equally well as the frequency entropy feature. The optimal feature sets were used

Figure 5.5: Optimal feature sets for each number of features that are included using Decision Tree classifier. The size of each box denotes the number of times that feature is included in the feature set over 10 folds.

Figure 5.6: Optimal feature sets for each number of features that are included using Naive Bayes classifier. The size of each box denotes the number of times that feature is included in the feature set over 10 folds.

Table 5.3: Optimal feature sets for DT and NB classifiers. *acc* and *gyro* are abbreviations for *accel_3dvector_norm* and *gyro_3dvector_norm*, respectively

Size(<i>n</i>)	1	2	3	4	5
DT	accel_mag_6	accel_mag_6	accel_mag_6	accel_mag_6	accel_mag_6
		accel_std	accel_freqEntropy	accel_freqEntropy	accel_freqEntropy
			accel_std	accel_std	accel_std
				accel_twenty_fith_p	accel_mag_1
					accel_twenty_fith_p
NB	accel_std	accel_std	accel_std	accel_std	accel_std
		accel_freqEntropy	accel_freqEntropy	accel_freqEntropy	accel_freqEntropy
			gyro_twenty_fith_p	gyro_twenty_fith_p	gyro_twenty_fith_p
				accel_median	accel_twenty_fith_p
					accel_median

5

to assess the performance per sensor and all sensors combined. These performance results are presented in Section 5.5.2.

The same feature selection is performed when the NB classifier is used within the embedded method. The selection results are shown in Figure 5.6. The results show that NB is more sensitive to the selected features than DT because the same features are selected more consistently over the 10 folds. It is well known that NB is sensitive to irrelevant features [63]. Therefore, the embedded approach selects features more consistently for NB than for DT. The optimal feature set with the NB classifier is shown in Table 5.3. The gyroscope’s 25th percentile outperforms the accelerometer features with a minor difference. Thus, the performance will degrade minimally, if any, when the gyroscope is not used for activity recognition. Figure 5.6 shows that the *gyro_twenty_fith_p* feature can be exchanged with either the *accel_twenty_fith_p* or *accel_median*.

5.5.2 OPTIMAL FEATURE SET PERFORMANCE

In this section, we present the classification performances when the data were characterized by the feature sets shown in Table 5.3.

5.5.2.1 EVALUATION OF INDIVIDUAL ORIENTATIONS AND POSITIONS

The evaluation presented here aims to investigate the difference in classification performance when a single 3D accelerometer is used on a collar at different positions and in diverse orientations. Moreover, the results presented here not only show the impact of different feature subset sizes, but they also give an insight into the effect of individual features in these optimal subsets.

In this evaluation, we used the data from goat G4 because this dataset contains the most substantial quantity of data as well as the most balanced activities. The performance evaluation on the other goats is discussed in Section 5.5.2.4. The performance of the classifier was assessed with data from each sensor node individually to show that the selected features are indeed orientation-independent. All sensor nodes simultaneously

recorded the same number of activities but did so from diverse orientations and positions, as shown in Figure 5.3. Both DT and NB feature sets were used to characterize the training and test sets of each sensor's data. Both the DT and NB classifiers were trained and tested with data from each individual sensor. The performances of both classifiers, shown in Figures 5.5 and 5.6, are very high and the variance among the sensors is low. The minor difference between the sensors' performances may be explained by the different positions of the sensors. Figure 5.7 shows that position E and C benefited from the *accel_median* feature that was included in the subset with 6 features. This feature is not included in the smaller subset sizes because the feature selection was optimized for all orientations simultaneously and not for individual position performance. Figure 5.8 shows that the NB classifier selected features that perform more consistently throughout all positions. Because NB classifiers are known to be very sensitive to the presence of redundant and irrelevant attributes [19], they typically select more consistent features that perform well on average for all positions. For both classifiers, sensors C and F are the best overall performing sensors. These sensors were mostly positioned at the bottom and top of the goat's neck, respectively. Thus, the best position on the neck for activity recognition of goats may be either at the top or bottom of the neck. The difference in performance among various orientations and positions is small ($\pm 2\%$ with 3 features), and activity recognition is robust against the rotation of the animal tag around the animal's neck.

Figure 5.7: Performance for each sensor orientation using DT classifier and DT feature set. Error bars denote standard deviation over 10 folds.

Figure 5.8: Performance for each sensor orientation using NB classifier and NB feature set. Error bars denote standard deviation over 10 folds.

5.5.2.2 EVALUATION OF DT AND NB CLASSIFIERS WITH DATA FROM DIFFERENT SENSOR ORIENTATIONS

The goal of this evaluation is to assess and compare the performance of DT and NB classifiers which were tested with data from diverse orientations. A single DT and NB classifier were trained with mixed data from all six sensor orientations (A-F) with diverse orientations. The optimal feature sets were used to characterize the mixed training and test sets. The results are presented in Figure 5.9, which shows that both classifiers are able to classify activities with high accuracy using just a single feature. Figure 5.9 shows that the optimal feature subset size is 3 and adding more than 3 features does not increase the performance of the classifiers. NB performs slightly better than DT for all feature set sizes.

In order to evaluate the validity of our feature sets, they were compared with randomly-drawn feature sets, excluding the optimal set. The results are shown in Figure 5.10. The performances of the random feature set are always lower than the optimal feature set which shows that our feature sets are indeed optimal. The difference in performance between the optimal and random feature set is larger for the NB classifier. This is as expected because NB is more sensitive to irrelevant features than DT.

5.5.2.3 ASSESSING THE PERFORMANCE OF THE FEATURES WITH VARIOUS CLASSIFIERS

The aim of this evaluation is to evaluate the performance of various classifiers other than DT and NB. We used our optimal feature sets to characterize the mixed-orientation activity data and assessed the performance of the features and the effect of the subset size

Figure 5.9: Performance for mixed data set with DT algorithm using DT feature set and NB algorithm using NB feature set. Error bars denote standard deviation over 10 folds

Figure 5.10: Performances of optimal feature set and randomly selected feature sets. The mixed data set was used. Error bars denote standard deviation over 10 folds

for the following classifiers: i. decision tree (DT), ii. neural network (NN), iii. support vector machine (SVM), iv. naive Bayes (NB), v. linear discriminant analysis (LDA), and vi. k-nearest neighbors (k-NN).

Figures 5.11 and 5.12 show the performance of 5 classifiers for different sizes of the feature sets. The results in Figure 5.11 are obtained with the DT best selected feature sets and in Figure 5.12 are obtained with the NB best selected feature sets.

The fact that performance increases with the use of more features signifies that the feature set is not optimal for these classifiers. An optimal feature set can only be found when feature selection is tuned for that specific classifier. Figures 5.11 and 5.12 show that the optimal sets perform at least as good on a neural network (NN) than on the classifiers they were selected with in the embedded method. Figures 5.11 and 5.12 show that the genericity of both feature sets is very similar except when $n = 1$. The NB feature set includes more generic features than the DT feature set (both LDA and SVM perform better with 2 features because the *accel_freqEntropy* is included).

The general performance does not significantly increase when more than 3 features are included. For all the classifiers, except LDA and SVM, the performance is already 93 % with just 1 feature.

5

Figure 5.11: Performances of multiple algorithms using the mixed data set and DT feature set. Error bars denote standard deviation over 10 folds

5.5.2.4 EVALUATION OF FEATURE SETS ON UNSEEN GOATS

The aim of this evaluation is to assess the genericness of the feature sets to other goats. We evaluate the performance of the optimal feature sets on the data from goats that were not used in the feature selection process.

Figure 5.12: Performances of multiple algorithms using the mixed data set and NB feature set. Error bars denote standard deviation over 10 folds

Figure 5.13: Average performances of multiple algorithms with DT and NB feature feature sets. Error bars denote standard deviation over 6 algorithms

The optimal feature sets were tested on 4 other goats that wore the collar. The optimal feature sets were also tested with unseen data of the goat that were used for our feature selection. The activities of each goat were recorded concurrently from 6 positions in various orientations, as shown in Figure 5.3. For each animal, the classifiers were trained and tested with data from that animal, using the optimal feature sets. Training and testing a classifier with data from various individuals would be possible through methods such as leave-one-subject-out cross-validation. However, such an assessment brings up a range of issues, such as sensitivity to personal traits, and was addressed in Chapter 4. Here, we focus on orientation independence, specifically.

The performance of the DT and NB classifiers can be seen in Figures 5.14 and 5.15, respectively. Because the data from G4 was used for the feature selection process, the features are most optimal for this animal. G5 is physically most similar to G4 and Figure 5.14 shows that the performance of G5 is even a little higher than G4. Table 3.7 shows that the *eating* activity is better balanced for G5 and has a 6 % higher accuracy (shown in Table 5.9). The difference in accuracy for the *eating* activity of G5 explains the overall, although minor, higher performance for G5. G1, G2, and G3 are all three goats from a different family. They are smaller, have shorter legs, and do not trot and run as much as the more wild goats. We believe these physical differences to be the main reason of the drop in performance for goats G1, G2, and G3. However, the accuracy of activity recognition of these goats is still above 89 % while the classifiers' parameters and data were not tuned or optimized for multiple subjects. The results in Figures 5.14 and 5.15 show that the NB subset was able to find an optimal set for all animals with 3 features as the performance does not significantly increase with more features. Figure 5.14 shows that with the DT subset the performance of goat G1 and G2 increased with 3 % at $n = 8$. The *gyro_3dvector_norm_median* feature was included at $n = 8$. As we discussed in Chapter 2, a gyroscope consumes up to 100 times more energy than an accelerometer. However, the performance results of the other goats show that using a gyroscope is not necessary if the classifier is correctly tuned for a given or multiple individuals. Power consumption and other considerations for real-time implementation are further discussed in Section 5.5.2.5.

We further evaluate the performance of 6 classifiers with test-data from all 5 goats. The classifiers were evaluated with the optimal feature subsets selected by DT and NB. Figures 5.16 and 5.17 show that the relative differences in performance is similar for all goats. The best overall performance was obtained with data from G4 because the feature sets were selected with cross-validation data from this animal. For all the goats other than G4 the classifier that was used during feature selection performed the best, closely followed by the NN classifier. The results show that the NN classifier generalizes well over multiple animals. The highest overall accuracy for all classifiers and animals was obtained with the NB feature set.

In the following, we discuss the confusion matrices for the two best performing AAR scenarios of G4 and G5. The results were obtained through classification with the DT classifier using the DT selected optimal features, and the NB classifier using the NB optimal selected features. The confusion matrices of the DT and NB classifiers for goat G4 are shown in Tables 5.4 and 5.5, respectively. The AAR performances in terms of accuracy, recall, precision, and F_1 scoring are presented in Table 5.6. The confusion matrices

5

Figure 5.14: Performances of DT classifier using the mixed data set of 5 different goats and DT feature set. Data from goat G4 was used exclusively during the feature selection process

Figure 5.15: Performances of NB classifier using the mixed data set of 5 different goats and NB feature set. Data from goat G4 was used exclusively during the feature selection process

Figure 5.16: Performances of multiple algorithms using the mixed data set of 5 different goats using 3 features from the DT feature set

Figure 5.17: Performances of multiple algorithms using the mixed data set of 5 different goats using 3 features from the NB feature set

for goat G5 are shown in Tables 5.7 and 5.8. The AAR performances for G5 are shown per activity in Table 5.9. The optimal feature sets with $n = 3$ were used to characterize the data. The values in the confusion matrices are summed up over 10 folds. The numbers in Tables 5.4, 5.5, 5.7, and 5.8 express the number of test data points that have been classified as that activity. Each data point represents a 2-second window of raw sensor input data. The sum of each column denotes the total number of true data points for that activity over 10 folds.

The results in Table 5.6 show that both classifiers perform similar with average accuracies of 93.90 % and 94.78 %, respectively. For both goats there is no overall significant difference in performance between the two classifiers other than NB performing slightly better (0.8 % higher F_1 score). The DT outperforms NB for the activities *walking*, *eating*, and *trotting*, as is reflected in the higher F_1 score. For the activity *eating* DT has a higher recall and lower precision than NB; this means that more data points of this activity were recognized by the DT, but the ratio of correctly classified data points was higher with NB.

Because the classifiers' performances are very similar for both goats, in the following we combine the evaluation of individual activities. Overall, all activities are well detected, except for the *other activities* activity. The activities *stationary* and *walking* have the best F_1 scores and are well detected and distinguished from other activities. It can be seen from Tables 5.4 and 5.5 that *trotting* is mostly confused with *running* and vice versa. The confusion is as expected because these two activities are similar, and distinguishing them is often very difficult during labeling because the animal is often rapidly changing from *trotting* to *running* and vice versa. The activities *stationary*, *walking*, and *eating* are mostly confused with each other. This can be explained by the fact that the goat often performs these activities simultaneously; e.g., during *eating* the goat can be *stationary* while chewing, and often is *walking* while *eating*. The activities in the *other activities* activity are mostly classified as either *trotting* (G4) or *walking* (G5). Tables 5.6 and 5.9 both show that the NB classifier discriminates *other activities* activity data points better than DT. Improved discrimination between the activities can be achieved with more tuning of the classifiers and is outside the scope of this research.

Table 5.4: Confusion matrix of DT classifier using 3 features for goat G4. The values are summed up over 10 folds.

Predict \ True	True Stationary	True Walking	True Eating	True Running	True Trotting	True Other Activities
Predict Stationary	93807	22	5471	0	0	0
Predict Walking	372	50773	914	22	187	654
Predict Eating	32028	876	39000	0	0	7
Predict Running	0	0	0	4622	463	292
Predict Trotting	0	158	0	794	4684	891
Predict Other Activities	0	5	0	0	8	6

5.5.2.5 CONSIDERATIONS FOR REAL-TIME ACTIVITY RECOGNITION ON A COLLAR TAG
 Executing activity recognition in real-time (while performing the activities) and locally (on the collar tag) supports numerous applications. Local processing faces the challenge of limited energy supply, processing power, and transmission bandwidth on collar

Table 5.5: Confusion matrix of NB classifier using 3 features for goat G4. The values are summed up over 10 folds.

Predict \ True	True Stationary	True Walking	True Eating	True Running	True Trotting	True Other Activities
Predict Stationary	113204	24	17792	0	0	0
Predict Walking	401	50038	1143	18	101	564
Predict Eating	12581	630	26404	0	0	0
Predict Running	0	0	0	4814	599	132
Predict Trotting	0	899	0	447	4500	1039
Predict Other Activities	21	243	46	159	143	115

Table 5.6: Performance of both DT and NB classifiers for goat G4

	Classifier	Stationary	Walking	Eating	Running	Trotting	Other Activities	Average Performance
Accuracy	DT	83.95%	98.64%	83.35%	99.33%	98.94%	99.21%	93.90%
	NB	86.94%	98.30%	86.36%	99.43%	98.63%	99.01%	94.78%
Recall	DT	74.33%	97.95%	85.93%	84.99%	87.68%	0.32%	71.87%
	NB	89.70%	96.54%	58.18%	88.53%	84.22%	6.22%	70.56%
Precision	DT	94.47%	95.94%	54.23%	85.96%	71.76%	31.58%	72.32%
	NB	86.40%	95.74%	66.65%	86.82%	65.36%	15.82%	69.46%
F1	DT	83.20%	96.94%	66.50%	85.47%	78.93%	0.64%	68.61%
	NB	88.02%	96.14%	62.13%	87.66%	73.60%	8.93%	69.41%

Table 5.7: Confusion matrix of DT classifier using 3 features for goat G5. The values are summed up over 10 folds.

Predict \ True	True Stationary	True Walking	True Eating	True Running	True Trotting	True Other Activities
Predict Stationary	41528	1	2733	0	0	0
Predict Walking	149	21920	898	12	72	3571
Predict Eating	6870	693	20445	0	0	341
Predict Running	0	3	0	1923	595	401
Predict Trotting	0	181	0	723	2113	410
Predict Other Activities	1	26	5	0	21	17

tags. However, local activity recognition will significantly prolong the battery life because large amounts of data do not have to be transmitted, which typically consumes more energy than local data processing. Moreover, online activity recognition enables the collar tag to efficiently adapt its resource usage to a situation (e.g. the device can sleep when an animal is sedentary). A long lifetime and smaller size of a monitoring collar require an activity recognition system with minimal complexity. Three components that contribute to the energy consumption of an activity recognition system are: (i.) the quantity and type of sensors that are utilized, (ii.) the complexity of the classifier's inference phase, and (iii.) the complexity and quantity of the features. In the following we will

Table 5.8: Confusion matrix of NB classifier using 3 features for goat G5. The values are summed up over 10 folds.

Predict \ True	True Stationary	True Walking	True Eating	True Running	True Trotting	True Other Activities
Predict Stationary	42490	28	3329	0	0	40
Predict Walking	143	21596	915	10	28	3462
Predict Eating	5909	770	19780	0	0	236
Predict Running	0	0	0	1852	424	217
Predict Trotting	0	332	0	572	2133	656
Predict Other Activities	6	98	57	224	216	129

Table 5.9: Performance of both DT and NB classifiers for goat G5

	Classifier	Stationary	Walking	Eating	Running	Trotting	Other Activities	Average Performance
Accuracy	DT	90.77%	94.69%	89.08%	98.36%	98.11%	95.48%	94.41%
	NB	91.05%	94.52%	89.38%	98.63%	97.89%	95.07%	94.42%
Recall	DT	85.54%	96.04%	84.90%	72.35%	75.44%	0.36%	69.10%
	NB	87.52%	94.62%	82.14%	69.68%	76.15%	2.72%	68.81%
Precision	DT	93.82%	82.34%	72.12%	65.81%	61.66%	24.29%	66.67%
	NB	92.60%	82.57%	74.10%	74.29%	57.76%	17.67%	66.50%
F1	DT	89.49%	88.66%	77.99%	68.92%	67.85%	0.71%	65.60%
	NB	89.99%	88.19%	77.91%	71.91%	65.69%	4.72%	66.40%

discuss these three components.

Gyroscopes continuously vibrate at a certain frequency in order to measure the angular velocity [176]. Thus, they consume up to 100 times more energy than other sensors [104] and it is better to not use this sensor. The results in Tables 5.3 show that the optimal DT subset does not include any gyroscope features and the NB selects only one gyroscope-dependent feature, which can be swapped out for an accelerometer feature with a minor drop in performance. Therefore, simple and orientation-independent activity recognition can be done without using a power-hungry gyroscope sensor.

During runtime, a classifier infers each new window of data. With a window size of 2 seconds and 50 % overlap there will be a new data point every second. For each data point, the CPU and memory are engaged in order to calculate the features and classify the data point; thus, minimizing the complexity of these steps will save large amounts of energy over longer runtime periods. The results in this section have shown that lightweight classifiers, such as Decision Tree and Naive Bayes, can obtain good performance when tested with data from diverse orientations. The monitoring system is more energy efficient with a lower quantity and complexity of features. Previous works on HAR [45, 124] have tried to obtain orientation independence through transformations of the input data. However, this requires a significant amount of additional computation for every window of data [154]. Therefore, we propose to use only a few orientation-independent features that have low complexity.

There are two main types of features: time and frequency-domain features. Figo et al. [43] performed an extensive complexity analysis of features that are commonly used. Time domain features require less computational resources than frequency domain features. The results in Figures 5.16 and 5.17 show that most classifiers considered here have good performance with only a single feature. Figure 5.13 shows that using more than 3 features does generally not improve the performance of the classifiers. The optimal sets with 3 features do contain frequency domain features (*frequency entropy* and *6th magnitude of FFT*). When energy efficiency is more important than accuracy, time domain features should be preferred, which results in a small drop in accuracy. Figure 5.17 shows that classifiers with a lightweight inference phase (NB, DT, and NN) obtain high accuracy (>92 %) using only the accelerometer 3D vector standard deviation, which is a time domain feature with low complexity [43].

Because we use 2-second observation windows with 50 % overlap, the delay of an actual implementation would therefore be 1 second plus the required time for classification. The classification time varies for different classifiers and can, in theory, be done in milliseconds. Therefore, the total delay for the activity to be recognized in real time is more or less 1 second. However, transmitting an update to a central location would be quite expensive in terms of energy. Therefore, we propose to aggregate a log file with change points and transmit the information each time period T , or use conditional rules regarding the local context (e.g. transmit log file when $\tau > K$, where τ denotes the total duration of activity α within a time period U , and K denotes a maximum duration).

5.6 CONCLUSIONS

We have shown that it is possible to obtain optimal orientation-independent features by training a classifier with mixed data from various orientations. Accurate activity recognition is achieved using just one feature and can be slightly improved by using up to 3 features selected by the decision tree (DT) and naive Bayes (NB) classifiers. Using a larger feature set does not improve the performance. The best scoring features are: *accel_3dvector_std*, *accel_3dvector_norm_mag_6*, *accel_3dvector_freqEntropy*, and *gyro_3dvector_twenty_fith_p*; this is a promising list because most features are accelerometer-dependent, which is a low-power sensor. With a minor drop in the accuracy, the frequency-domain features can be swapped out for time-domain features. Our results have shown that the accelerometer is the best sensor to use for activity recognition. A gyroscope will not significantly contribute to performance and consumes more energy than accelerometers. The optimal feature sets that have been revealed in this chapter are orientation-independent, consist of mostly time-domain features, and are used with simple classifiers; these properties support real-time, energy-efficient, and robust activity recognition for animals.

NB slightly outperforms DT in feature selection and the feature set selected by NB generalizes a little better over other classifiers. Our results indicate that the best position for AAR, on the neck of a goat, is at the top or bottom of the neck.

We have shown that the distribution of data between training, cross-validation, and test sets is more balanced when long segments of activities are recursively broken up into shorter segments. This method maintains the original balance ratios of activities in all train and validation sets.

We argue that the activity of an animal is accurately recognized by placing only an accelerometer and a simple processing unit around its neck – in any orientation or position – with a NB classifier that only requires one feature, the standard deviation of $M(t)$ (5.1), over a 2-second window of data. When using a classifier other than DT or NB, our approach can be repeated to select an optimal feature set for that classifier.

6

FACTORS THAT INFLUENCE ANIMAL ACTIVITY RECOGNITION PERFORMANCE

Up to this point, we have discussed generic activity recognition and orientation independence using various classifiers. Besides the sensitivity to individual traits and sensor-orientation, there are essential factors of the AAR process that influence the performance of AAR classifiers. Therefore, we evaluate the impact of factors that are often used differently. We compare the performance of 7 classifiers by training and evaluating them with motion data from horses using supervised machine learning techniques. Firstly, we evaluate the effect of the feature types to investigate the trade-off between feature complexity and performance. We compare the performance utilizing only time-domain features, frequency-domain features, and the orientation-independent set from Chapter 5. Secondly, we investigate the effect of the evaluation partitioning method by comparing leave-one-subject-out cross-validation with k -fold cross-validation. Finally, we investigate the effect of hyperparameter tuning by training the classifiers with and without hyperparameter tuning.

6.1 INTRODUCTION

Various factors impact the performance of animal activity recognition (AAR). In Chapter 2, we introduced the steps of the AAR pipeline. In the previous chapters, we discussed the first steps of the pipeline: data acquisition, preprocessing and segmenting, and feature selection. In this chapter, we investigate the impact of factors in the feature extraction, training, and evaluation steps of AAR using supervised machine learning (ML) techniques.

In Chapter 2, we showed that related work used a variety of settings for several factors. The analysis presented in this chapter is motivated by the fact that it is not clear to what extent each factor may impact the AAR performance. It can be challenging to compare related work when they use different settings for these factors without explaining their impact. For example, a labeled dataset has to be partitioned into multiple sets to evaluate machine learning methods. Table 2.1 shows that the surveyed works use three different methods to partition the labeled data into train and test sets. Hyperparameters are parameters that are given a value before the training process. Most classifiers have multiple hyperparameters, and finding the right combination of values that give the best performance can be challenging. Some related works used hyperparameter tuning [51, 121] while most others did not. When factors such as the partitioning method or hyperparameter tuning have a significant effect on the performance results, it becomes problematic to compare related works in AAR. Therefore, we evaluate the following factors that potentially have a significant effect on the AAR performance: the type and number of features, data partitioning methods, and hyperparameter tuning. Because the impact of each factor may be dependent on the classifier type, we evaluate the effect of each factor for 7 classifiers.

6.1.1 TYPE AND NUMBER OF FEATURES

Feature extraction is an essential step in the AAR pipeline. Using a large amount of irrelevant and redundant features may degrade the performance of the classifiers. In Chapter 5, we utilized an embedded forward selection scheme to select features that are insensitive to the orientation using motion data from goats. Our results showed that for some goats using more than 3 features did not significantly improve the performance, and in some cases, the performance degraded (especially with the naive Bayes (NB) classifier, shown in Figure 5.17). We also showed that the subset that was selected generalized over other subjects that were not used for the feature selection process. Although we assessed the genericity of the feature set to other subjects within the goat species (Caprinae), we did not verify the set on another species. To validate the feature subset from Chapter 5 on a different species, we use the selected subset of features from the accelerometer to classify the activities on data from the horses. The sensor devices that were used for the goat and sheep dataset were different than those used for the horse dataset. Horses are much larger than goats, but the differences between the gaits might be similar between the two species. Therefore, we assume that the feature set that generalized well over multiple goats might also perform well on the horses.

Furthermore, as we discussed in Chapter 1, one of the major challenges in online AAR is power consumption. One part of the solution is to minimize the computational complexity of the AAR system components so that energy is saved. It is important for ap-

plications that use online AAR to keep the required computational and memory load low due to limited battery power. Energy consumption is reduced by using simpler features that are computationally less expensive and require little memory. Some of the features in the orientation-independent set are frequency domain features. Here, we compare the AAR performance when using only time-domain or feature-domain features to show the trade-off between feature complexity and AAR performance in AAR of horses. We evaluate the performance of the classifiers in three scenarios: using all 20 features, only time-domain features, and only frequency domain features.

6.1.2 DATA PARTITIONING METHODS

A labeled dataset has to be partitioned into multiple sets to evaluate machine learning methods. The labeled dataset must be partitioned into training, tuning (also referred to as cross-validation), and test (also referred to as holdout) sets. The training data is used to train a model, the tuning set is used to tune the model-hyperparameters, and subsequently, the test set is used to evaluate the performance of the model. Three conventional methods to partition the data are holdout, k -fold cross-validation, and leave- n -subject-out cross-validation. When the holdout method is used, the data points are shuffled and randomly sampled with a relatively large ratio for the training set (e.g., 60 %), and smaller ratio for the tune (e.g., 20 %) and test sets (e.g., 20 %). This holdout can be repeated k times; however, k is often set to 1. Holdout can be used when the dataset is large, or the training time of a model is very long. However, the dataset is not optimally used with this method because each data point is only considered k times, and the variability of the whole dataset is not optimally assessed. A different composition of the datasets may lead to different performance results. A more elaborate partitioning method is k -fold cross validation [148] (also referred to as rotation estimation), which ensures that each data point has been used at least once as training, cross-validation, and test data. However, data from all subjects is mixed in both training and testing data, which can cause a bias of the trained model to the subjects present in the training set. Leave- n -subject-out cross-validation aims to overcome the bias by partitioning all data from n subjects as the test (holdout) set. The remaining data of the other subjects is used for training and tuning, and the tuning can be partitioned using the leave- n -subject-out or k -fold cross-fold validation.

The generalization to unseen subjects in the population is essential for most AAR related studies, especially when a system must be deployed on animals for online AAR. In Chapter 2, we surveyed the state of the art and showed that most studies use either a holdout partitioning method or k -fold cross-validation. Only a few surveyed studies used leave-one-subject-out cross-validation. Often, the reason was not mentioned, or there was not a sufficient amount of labeled data from multiple subjects for all activities to use leave-one-subject-out validation.

6.1.3 HYPERPARAMETER TUNING

Hyperparameters are parameters that are given a value before the training process. Most classifiers have multiple hyperparameters. Finding the right combination of values that give the best performance can be challenging. Hyperparameter tuning aims to automatically discover a set of parameter settings that yield the best performance. Four

commonly used hyperparameter tuning algorithms are: (i) Manual search [59], (ii) Grid search [96], (iii) Random search [18] and, (iv) Bayesian optimization [160].

Hyperparameter tuning can be a time-consuming process and is generally a trade-off between the amount of available development time and the required performance of the classifier. The manual search method entails the practitioner choosing the hyperparameters from either common knowledge or a process of trial and error. Grid search combines all combinations of parameter settings from a predefined range of values for each hyperparameter. Random search selects random values within a given range for each hyperparameter. Bayesian optimization is less exhaustive but does not require the exploration of the entire hyperparameter space and requires less computational resources. Although grid and random searches are more exhaustive and may yield higher AAR performances, they take a long time to complete. Because we compare many classifiers, we use Bayesian optimization. To evaluate the effect of hyperparameter tuning on the AAR performance, we evaluated all classifiers in two scenarios: (i) using default hyperparameter settings and (ii) using Bayesian optimization as hyperparameter tuning.

6.1.4 CHAPTER ORGANIZATION

The rest of this chapter is organized as follows. In the following section, we discuss the methodology of this chapter. Subsequently, we discuss the results of the various experiments in Section 6.3. Finally, we conclude this chapter in Section 6.4.

6.2 METHODOLOGY

All experiments were executed using Matlab [113]. To investigate the impact of the factors, we repeatedly performed AAR in several experiment scenarios. In each scenario, we varied a different factor that impacts the performance while we fixed the settings of other factors. The fixed settings were chosen to provide the most objective results. Therefore, when not investigating these factors specifically, we used hyperparameter tuning and leave-one-subject-out cross-validation by default. We did not explore the whole space of combinations of settings because that would be intractable.

We classified activities of horses, using motion data that was derived from inertial measurement units (IMUs) that were attached around the neck in an orientation that was not strictly fixed. Each experiment scenario was repeated for 7 classifiers. In each scenario, we separated identical type and number of activities for the horses and used the same preprocessing steps. Although they may be performed differently, the classified activity types are commonly performed by sheep, goats, and horses. To be consistent with the analysis that was performed with the goat and sheep datasets in Chapters 4 and 5, we used the same set of classifiers and activity types in this chapter. The results were aggregated in a database and are discussed in Section 6.3.

In the following subsection, we discuss how we used the horse data. Subsequently, we briefly describe the classifiers and the parameters that were tuned during hyperparameter tuning in Section 6.2.2.

6.2.1 DATASET AND PREPROCESSING

We used data from 6 horses and 5 activities. Figure 6.1 shows two subjects in a pasture during the data collection. The sensors were attached around the neck of the horses in an orientation that was not fixed. The used dataset and its collection process are described in more detail in Chapter 3.

Figure 6.1: Two subjects during the outdoor collection process

The activities that were classified are listed in Table 6.1. The composition of the used data is shown in Table 6.2. Because the horses were being ridden, this dataset is more balanced over the different gait types than the goat dataset. During the experiments, we did not balance the datasets.

Table 6.1: Classified horse activities

Activity	Description
Standing	Horse standing on 4 legs, no movement of head, standing still
Walking	The horse puts each foot down one at a time. Walking with and without rider on back.
Trotting	One front foot and its opposite hind foot come down at the same time, making a two-beat rhythm. Trotting at different speeds but always 2 beat gait. With and without rider on back.
Galloping	One hind leg strikes the ground first, and then the other hind leg and one foreleg come down together, finally the other foreleg strikes the ground. This movement creates a three-beat rhythm. With and without rider on back.
Eating	Head down in the grass, eating and slowly moving to get to new grass spots or head is up, chewing and eating food, usually eating hay or long grass.

Because the gyroscope consumes more energy and did not contribute significantly to the AAR performance in Chapter 5, we do not use features from the gyroscope. We used only the magnitude of the 3D vector (ℓ^2 -norm) of the accelerometer because it is orientation-independent and energy efficient [79]. We used 20 summary statistics that are commonly used for activity recognition (AR) [79] to describe the data. The features are shown in Table 6.3. Each segment of activity data was separated into windows with a window size of 2 seconds, and 50 % overlap. Most classifiers perform better with scaled data [4]. Therefore, we scaled the data through a Z-transformation, obtaining a standard

Table 6.2: Composition of the horse dataset. Number of 2-second samples per subject

Subject Activity							Total	
	1	2	3	4	5	6	samples	fraction
Standing	1750	1186	1244	347	341	245	5113	6%
Walking	11055	9642	5538	5239	4294	1677	37445	43%
Trotting	6423	7038	3402	3559	2673	1981	25076	29%
Galloping	1043	696	714	835	323	328	3939	4%
Eating	4331	5063	1951	1091	2496	1116	16048	18%
Total	24602	23625	12849	11071	10127	5347	87621	
Balance score	0,83	0,81	0,86	0,78	0,8	0,85	0,83	

score with zero-mean and unit variance. The standard score is calculated as:

$$x' = \frac{x - \bar{x}}{\sigma}$$

(6.1)

, where x is the training data, $\bar{x} = \text{mean}(x)$ is the mean of the training set, and σ is its standard deviation. Data in the test set was not used to calculate the mean and standard deviation.

Table 6.3: Summary statistics that were calculated for each window of data

Domain	Feature	Description
Time	Maximum	Maximum value
	Minimum	Minimum value
	Mean	Average value
	Standard deviation	Measure of dispersion
	Median	Median value
	25 th percentile	The value below which 25 % of the observations are found
	75 th percentile	The value below which 75 % of the observations are found
	Mean low pass filtered signal	Mean value of DC components
	Mean rectified high pass filtered signal	Mean value of rectified AC components
	Skewness of the signal	The degree of asymmetry of the signal distribution
	Kurtosis	The degree of 'peakedness' of the signal distribution
Frequency	Principal frequency	Frequency component that has the greatest magnitude
	Spectral energy	The sum of the squared discrete FFT component magnitudes
	Frequency entropy	Measure of the distribution of frequency components
	Frequency magnitudes	Magnitude of first six components of FFT analysis

6.2.2 CLASSIFIERS

The hyperparameters that were tuned were similar to those described in Section 4.4.2, and we used default values where possible. The most common hyperparameters of all classifiers were tuned using Bayesian optimization. We implemented the following classifiers:

Deep neural network (DNN) The deep neural network (DNN) consists of several fully connected layers. Each layer contains 50 rectifier (ReLU) activations. The number of layers to be optimized is set in a range of 1 to 15 layers, as most DNN architectures have several layers below 15.

Decision tree (DT) A decision tree consists of branches and leaves which are navigated depending on feature values [86]. The minimum number of leaf node observations was tuned.

K-nearest neighbors (k-NN) k-nearest neighbors (k-NN) determines the class of a feature vector based on the majority vote of the values of the k -nearest neighbors in the example set. The measure of distance was Euclidean space, and the value of k was varied between 1 and 100.

Linear discriminant analysis (LDA) LDA [86] aims to discover the combination of features which best distinguish classes. The *amount of regularization (gamma)* and the *"linear coefficient threshold (delta)"* were tuned.

Naive Bayes (NB) Naive Bayes uses Bayes theorem to build a model that determines the

probabilities of each outcome [86]. The *data distribution* and *Kernel smoothing window width* were tuned.

Neural network (NN) We implemented a feed-forward neural network that maps input data to output classes using several hidden layers [86]. In this case, the activation function used was *sigmoidal*. One hidden layer was used. The default number of neurons in the hidden layer was defined by:

$$\psi = \frac{\gamma + \rho}{2} + 1, \quad (6.2)$$

where ψ is the amount of neurons in a layer, γ the number of features, and ρ the number of classes. During hyperparameter tuning, we varied the number of neurons.

Support vector machine (SVM) A LibSVM C-SVC [86] model was used with a Gaussian radial basis function kernel throughout. The hyperparameters C and γ were tuned.

6.3 EVALUATION

Unless otherwise noted in a specific experiment, we used leave-one-subject-out cross-validation and hyperparameter tuning for all the experiments by default. For all results we report the F_1 (%) and Accuracy (%) performances.

6.3.1 EFFECT OF FEATURE SELECTION

To validate the feature subset from Chapter 5 on a different species, we used the selected subset of features from the accelerometer to classify the activities on data from the horses. We used the following three summary statistics *accel_3d_vector_norm_freqEntropy*, *accel_3d_vector_norm_std*, and *accel_3d_vector_norm_median*. The F_1 and accuracy performances are shown in Figures 6.2a and 6.2b, respectively.

Figure 6.2: Impact of the feature selection on the performance of 7 activity recognition classifiers in terms of (a) F_1 and (b) Accuracy

The results show that the feature-subset yields sufficient AAR performance on horses. Moreover, the subset of features performs better than using all features with an average 2.52 % increase in F_1 performance. The decision tree (DT), linear discriminant analysis (LDA), and neural network (NN) show a slight improvement in terms of genericity (lower standard deviation) when using the subset. Therefore, using a subset of features is not only more energy-efficient, but also improves the performance, and in some cases, the genericity performances of the classifier. Although the feature set from Chapter 5 generalizes well to horses, higher performance may be obtained when the framework from Chapter 5 is used for the horse data.

6.3.2 EFFECT OF TIME AND FREQUENCY DOMAIN FEATURES

To be able to show the performance versus energy usage trade-off, we evaluated the classifiers' performance in three scenarios: using all 20 features, only time-domain features, and only frequency domain features. The features are shown in Table 6.3. The F_1 and accuracy performances are shown in Figures 6.3a and 6.3b, respectively.

Figure 6.3: Comparison between the impact of frequency and time domain features on the performance of 7 activity recognition classifiers in terms of (a) F_1 and (b) Accuracy

The results show that some classifiers are more sensitive to frequency-domain features than others. When we used only the frequency-domain features, the performance was higher for 5 out of 7 classifiers compared to using all the features. On average, frequency-domain features increased F_1 performance with 2.43 %, ranging from -3 % (LDA) to 4.94 % (DT). Thus, the trade-off between complexity and performance is different for each classifier, but overall most classifiers did yield higher performance using frequency features. Except for the LDA, it is better to use only frequency-domain features than all features. Except for the support vector machine (SVM), using only time-domain features results in the same performance as using all features, which on average less than using only frequency domain features. The F_1 performance difference between time-domain and frequency-domain features was 0.76 % for the NB classifier. Thus, the NB classifier was indifferent to the type of features. The standard deviation is similar between all scenarios, which shows that the genericity performance of the classifiers did not improve when using frequency-domain features, except for LDA.

The results in Figure 6.3 indicate that, for this particular set of activities in horse data,

the frequency features contain more information than time-domain features. Because the number of time-domain features was 11 and frequency-domain features were 4, the difference in dimensionality between the two feature sets may have an impact on the result. In future work, the analysis can be improved by repeating the experiment using subsets of time-domain features and calculating the average performance.

6.3.3 EFFECT OF THE DATA PARTITIONING METHOD

To investigate the impact of the evaluation method on various classifiers, we trained and tested the classifiers with both the mixed k -fold cross-validation and leave-one-subject out method. We set k to 5 because this yielded a satisfactory proportion of training, tuning, and testing data. The F_1 and accuracy performances are shown in Figures 6.4a and 6.4b, respectively.

Figure 6.4: Impact of the partitioning method on the performance of 7 activity recognition classifiers in terms of (a) F_1 and (b) Accuracy. The error bars denote the standard deviation over multiple folds.

The difference in performance between the two methods is the largest for DT, k-NN, and NB. It can be seen that for all classifiers, the performance is higher with the mixed k -fold cross-validation method. On average, the F_1 performance was 2.23 % higher for the k -fold cross-validation method. The standard deviation for the k -fold validation is significantly lower, indicating that the performance is consistent over the folds. This can be explained by the fact that in each fold, data from all subjects is present in both train and test sets. The leave-one-subject-out method shows a higher standard deviation in the results. With this method, the data from one subject was left out in each fold. Therefore, the degree of standard deviation reflects the bias of the trained classifier towards the subjects in the training data. Using k -fold cross-validation does not capture the genericity performance of the classifiers. This means that the classifier performance is over-optimistic when k -fold cross-validation is used. In a practical scenario where an AAR classifier is used on unseen animals from outside the training data, the performance is reflected more precisely using leave-one-subject-out validation. To improve the evaluation of the generic property of the classifier to unseen data from subjects that were not in the training data, all data from one or more subjects should be left out of the training set. However, this is often difficult due to limited labeled data availability.

6.3.4 EFFECT OF HYPERPARAMETER TUNING

To investigate the effect of hyperparameter tuning, we evaluated all classifiers with both default and tuned hyperparameter settings, as described in Section 6.2.2. Because we compared many classifiers, we used Bayesian optimization since this method does not evaluate the whole parameter space and is faster. As such, the results presented here are not exhaustive because the optimization is prone to local minima in the parameter space. We used the auto-tuning functionality embedded in Matlab as much as possible. The F_1 and accuracy performances are shown in Figures 6.5a and 6.5b, respectively.

Figure 6.5: Impact of hyperparameter optimization on the performance of 7 activity recognition classifiers in terms of (a) F_1 and (b) Accuracy. The error bars denote the standard deviation over multiple leave-one-subject-out folds.

Overall, the results show that hyperparameter tuning did increase the performance of most classifiers with an average of 1.6 %. For the LDA, and NN, and SVM classifiers the improvements were 0.07 %, 0.43 %, and 0.44 %, respectively. These improvements are small and can be explained by the type of parameters that were tuned or the default value for those parameters that were used in our comparison, e.g., the default parameters may have coincidental been near the optimized value. LDA typically does not have any parameters that significantly affect the performance. In this case, hyperparameter tuning for NN tuned the number of neurons in the hidden layer. The number of optimal neurons was either the same as Equation 6.2, or the number of neurons did not affect the performance in this scenario. Hyperparameter tuning decreased the standard deviation in the performance of the DNN classifier, showing that the learned model generalized better to unseen subjects after tuning. Based on these results we can conclude that the performances in Chapter 5 are somewhat pessimistic because we did not use hyperparameter tuning.

6.3.5 OVERALL OBSERVATION

Figure 6.6 shows the AAR performances of the classifiers from Chapters 4, 5, and 6 side by side. In the following, we list the similarities and differences between the evaluations shown in Figure 6.6.

- Similarities:

- Accelerometer data was used in all evaluations and was collected from a tag attached to the neck of the animal
 - 5 identical activity classes were classified in all evaluations (i.e., *standing, walking, trotting, running, eating*), only evaluations in Chapter 5 also separated the class *other activities*
 - The number of features was 3 in all evaluations
 - The same subset of selected features was used in Chapters 5 and 6, and Chapter 4 used a different subset
 - Chapter 4 and 6 both used hyperparameter tuning, and 5 used default parameters
- Differences:
 - The size of datasets in the three evaluations were different. Chapter 4 used the smallest dataset per subject (Movement Data of Goats and Sheep [70]), Chapter 5 used the largest dataset (Multi Sensor-Orientation Movement Data of Goats [71]), and Chapter 6 used a middle-sized dataset that was the most balanced (Horse Movement Data [75]). Please refer to the Chapters for the respective sizes and compositions of the datasets.
 - For evaluations of Chapters 4 and 5, the classifiers were trained and tested with data from each subject individually, but in Chapter 6 we used leave-one-subject-out cross-validation.

Figure 6.6: Activity recognition performance comparison between Chapters 4 (Goats and Sheep), Chapters 5 (Goats), and Chapter 6 (Horses), for 7 classifiers in terms of Accuracy

Figure 6.6 shows that accelerometer data performs adequate for all classifiers and species. The location around the neck is adequate and generic for these species, at least for the set of activities that were classified; activities other than those considered here may benefit from different sensor locations on the animal. The results show that 3 features are sufficient for all species. Although the subset of features was different for Chapter 4, the performances are still good, which can be explained because the features were selected for that specific dataset. The feature subset from Chapter 5 (selected for goats) generalizes well to horses.

The results from Chapter 4 are mostly higher than the other two. The increased performance in Chapter 4 may be caused by the fact that both the evaluation was done per subject and hyperparameter tuning was used, which increase the performance. Figure 6.6 shows that the performances from this chapter and the previous chapter are very similar for DT, k-NN, and NN. The LDA classifier had the lowest average accuracy of the chapters. The NN classifier performed the best overall (2nd highest average and lowest standard deviation over the three evaluations). Thus, the NN appears less sensitive to the specifics of each evaluation and capable of adapting to species-specific traits and methods used.

6.4 CONCLUSION

We have shown the impact of the number and type of features, two data partitioning methods, and hyperparameter tuning on animal activity recognition (AAR) performance using motion data from horses. We compared the impacts between 7 classifiers: deep neural network (DNN), decision tree (DT), k-nearest neighbors (k-NN), linear discriminant analysis (LDA), naive Bayes (NB), neural network (NN), and support vector machine (SVM).

6.4.1 CLASSIFIER

Overall, the SVM was the best performing classifier. The classifier obtained 92.8 % accuracy and 89.5 % F_1 score using the feature set comprising 3 features, hyperparameter tuning, and leave-one-subject-out cross-validation. Similar performance was obtained by the NN and DNN (92.7 % and 92.6 % accuracy, and 89.2 % and 88.8 % F_1 , respectively) when the orientation independent subset from Chapter 5 was used.

6.4.2 FEATURE TYPE

The trade-off between feature complexity and AAR performance was different for each classifier, but overall most classifiers did yield higher performance using frequency-domain features. Except for the LDA, it was better to use only frequency-domain features than all features. Using only time-domain features resulted in slightly lower performance. When we used the orientation-independent feature subset from Chapter 5, the classifiers obtained similar performance to using frequency features. The only frequency feature in the subset is the *accel_3d_vector_norm_freqEntropy*. In future work, a feature subset can be selected using the framework from Chapter 5 with the horse data to compare its composition and performance with the goat feature set.

6.4.3 DATA PARTITIONING METHOD

The standard deviation in the results was lower for k -fold cross validations than leave-one-subject-out cross-validation. k -fold cross validation does not capture the genericity performance of the classifiers because data from all subjects is mixed. Therefore, the performances are over-optimistic. In a practical scenario where an AAR classifier is used on unseen animals, the performance is reflected more precisely using leave-one-subject-out validation.

6.4.4 HYPERPARAMETER TUNING

Hyperparameter tuning improved the performance of most classifiers. Hyperparameter tuning decreased the standard deviation in the performance of the DNN classifier, showing that the learned model generalized better to unseen subjects after tuning.

7

DEEP UNSUPERVISED REPRESENTATION LEARNING TECHNIQUES FOR ANIMAL ACTIVITY RECOGNITION

Good feature representations are essential to effective animal activity recognition (AAR). In the previous chapters, we focused on summary statistics. These have been used in many activity recognition (AR) studies and are relatively simple to compute. In this chapter, we zoom in on unsupervised learning techniques. The most compelling reason to use unsupervised representation learning as a feature extraction method is the ability to learn from *unlabeled* data. Obtaining labeled data is a tremendously time consuming, tedious, and labor-intensive task. It is much easier to obtain raw unlabeled data. In this chapter, we compare three unsupervised representation learning techniques with three conventional feature extraction methods that are simple and have excellent performance. To investigate the effect of the size of both *labeled* and *unlabeled* part of the dataset on the quality of the representations, we train the representations and classifier using various sample sizes. Furthermore, we evaluate the effect of depth in feature architectures on the performance of the representation learning techniques. Finally, we analyze and discuss the effect of class imbalance in the dataset on the AAR performance of the representation architectures. All evaluations are performed on two different datasets that are diverse in terms of species, subjects, sensor-orientations, and sensor-positions.

7.1 INTRODUCTION

An AR system is often trained through supervised machine learning methods that generally follow three steps: Firstly, movement data is collected through motion sensors and annotated through a labeling process. Secondly, the low-level sensory data is transformed into a more compact and discriminative representation. This step is called feature extraction and is one of the most critical steps. Finally, the representations and their corresponding labels are used to train a classifier to separate various activities, given the differences in the sensor data. In this chapter, we do not focus on the classification step, but rather on the second step, representation of data and feature extraction. The performance of AR – or any machine learning algorithm – heavily depends on the type and quality of the features that describe the data [16]. In the state of the art, much effort has been put into preprocessing and transformation of low-level sensory data into informative features. Manually finding the optimal transformation is referred to as feature engineering and relies on expert domain knowledge of the data. In the majority of cases, carefully selected features (engineered features) and supervised machine learning approaches are used. However, extracting engineered features requires expert domain knowledge, and these features do not always generalize well to data outside the training set [101]. Although feature engineering often results in excellent features that work well for the specific task at hand, there are two main drawbacks. Firstly, engineered features do not allow a system to extract and organize the discriminative information from the raw data itself, limiting it to the boundaries of human knowledge at the moment it was developed [16]. The second drawback and the most important one is that a feature engineering approach does not exploit the vast amount of unlabeled data that is often collected, before development and during deployment of an AR system. It is a lot easier to collect unlabeled data than labeled data. Observations are required during the data collection process to obtain labeled data; subsequently, the data must be annotated, which both are tremendously labor-intensive, challenging, and tedious tasks.

In recent years, deep neural networks (DNNs) emerged from neural networks (NNs). DNNs are similar to NNs, but contain more than one hidden layer and introduce hierarchy so that they can learn hierarchical features. convolutional neural networks (CNNs) perform convolutional and pooling operations between consecutive layers [95] and have demonstrated good performance over other models. Therefore, they have been a popular choice to use in a supervised setting for human activity recognition (HAR) tasks [6, 31, 125, 143, 190, 192]. Recently, deep learning (DL) has also become known as end-to-end learning systems. End-to-end learning denotes that no human ingenuity is required in the training process (AR pipeline) from raw data to activity predictions. Many researchers have used end-to-end DL approaches, where the data input is directly mapped through a deep network to the output, bypassing all the intermediate steps. In end-to-end learning approaches, the feature extraction occurs implicitly between the layers in the network. Such approaches are known to require a vast amount of data and have proven to work well when these amounts of data are available [12, 123, 165].

The advancement of DL [93] introduced the opportunity to learn features from raw data without domain-specific knowledge and has proved to be promising for improving the performance of both animal and human activity recognition [6, 31, 101, 134, 143, 178, 190]. Two recent surveys [46, 178] both identified unsupervised AR through DL as

an urgent open research question. Therefore, we investigate the opportunity to exploit the large unlabeled part of sensor-data to improve the feature extraction for AAR through representation learning. Representation learning is a set of techniques that aim to automatically discover a compact and descriptive feature representation of raw data from the data itself. Effectively, less labeled data is required when the features are improved and better able to separate the classes in feature space. Researchers in the field of HAR have investigated unsupervised feature learning with small datasets and demonstrated promising performances [46, 101, 102]. Although our results are also applicable to the HAR field, we mainly analyze and compare the effect of various feature representations on AR performance for animals. The most significant difference between HAR and AAR is the sensor location and movement patterns between the activities in humans and quadruped animals. In animal monitoring applications, the sensors are mostly worn by animals on collars around the neck, and the sensor orientation is not fixed. There are only a few recent papers on the subject of DL in relation to AAR. Browning et al. utilized a DNN to predict diving activities from only GPS data [25]. A DNN, and more recently, a CNN were utilized successfully to identify animals in camera-trap images in [145] and [167], respectively. To the best of our knowledge, DL, and more specifically, unsupervised representation learning using inertial measurement unit (IMU) data, has not been researched for AAR so far. Eventually, unsupervised representation learning is not only useful for AR at a lower sensory level. The same techniques can potentially be used to extract essential features from higher-level information using multi-modal data sources, such as activities combined with location data.

In this chapter, our primary goal is to compare and analyze the quality of unsupervised representation learning techniques and evaluate their effect on the performance of AAR. Specifically, our main objective is to compare learned representations, from unlabeled data, that are expressive, orientation-independent, and discriminate various activities. Lee et al. introduced convolutional deep belief network (CDBN) in [98] for efficient hierarchical feature detection in images. In a later work, the authors applied CDBN to audio data and empirically evaluated them on various audio classification tasks [99]. The authors showed that the learned features corresponded to phonemes and demonstrated that the feature representations learned from unlabeled audio data had an excellent performance for multiple audio classification tasks. Their work inspired us because we expect that there must be components in movement data that built up to a given activity, similar to how phonemes build-up to words. In total, we evaluate and compare six feature extraction methods. These methods include traditional summary statistics and the following representation learning techniques: principal component analysis (PCA), a deep net consisting two stacked sparse auto encoders (SAEs), and a convolutional deep belief network (CDBN). As a baseline, we compare the learned representations with conventional engineered time- and frequency-domain summary statistics. We assess the performance by training and testing a multi-class support vector machine (SVM) with the features derived using each extraction method.

Furthermore, the quality of the aforementioned feature extraction methods is affected by various factors. In this chapter, we investigate three: (i.) the size of the labeled and unlabeled dataset, (ii.) the number of layers (depth) of the representation learning architectures, and (iii.) the effect of imbalanced data.

7.1.1 CHAPTER ORGANIZATION

The rest of the chapter is organized as follows: Firstly, we present our experiment methodology in Section 7.2. Secondly, we briefly describe the used datasets, their composition specific to this chapter, and preprocessing in Section 7.3. Subsequently, we discuss the evaluation of the experiments in Section 7.4, followed up with a discussion in Section 7.5. Finally, we conclude the chapter in Section 7.6.

7.2 METHODOLOGY

In this section, we describe how the feature extraction methods were compared in several different scenarios. In the following, we describe how we investigated the effect of both the size of the amount of available labeled and unlabeled data on the performance of AAR and compared this effect between traditional and various types of deep representations that were learned. The quality of different representation learning architectures was compared through two experiments within which (i.) the size of the labeled dataset, and (ii.) the size of the unlabeled dataset were varied. The methods of these experiments are discussed in Section 7.2.2. For each dataset size, we compared two engineered representations and three unsupervised representation learning methods. The overall structure of the experiments is shown in Figure 7.1. To minimize the influence of the classifier, we use the same type of classifier throughout our evaluations.

First, raw annotated data from the accelerometer was pre-processed and transformed into an orientation independent 3D acceleration vector. The dataset acquisition and preprocessing are discussed in more detail in Section 7.3. Second, various representations were extracted from the 3D vector. We discuss each representation architecture in more detail in Section 7.2.1. The different representations were used separately and subsequently to describe the data that were used to train and test a SVM classifier. We used SVM because this classifier is generally robust to the higher dimensionality of the data [86]. We did not use the test data for representation learning because we assumed that this would not be available when AAR is deployed on unseen animals. We sampled our dataset with increasing sample sizes by means of stratified random sampling and random under-sampling. Both techniques are discussed in more detail in Section 7.2.4. In order to take variability into account, the experiments were repeated multiple times for each subsample (batch) of training data. For each sample size, the trained representation architecture was used to extract features from the training data and train the SVM as a supervised learning algorithm. Finally, the performance of the SVM was assessed using the test data. We evaluated the performance using the F_1 measure.

In order to address heterogeneity, we used leave-one-subject-out cross-validation, thus for each fold, all data from one subject was only used as test data, while data from the remaining subjects was used as training data. Through leave-one-subject-out cross-validation, we assessed the generalization ability for each architecture. This procedure was repeated for various sizes of labeled and unlabeled data.

7.2.1 FEATURE EXTRACTION METHODS

In this section, we briefly describe each feature extraction method and the settings that were used in their implementation. More detailed background information regarding

Figure 7.1: Experiment methodology

the unsupervised representation learning algorithms is provided as Appendix A.

7.2.1.1 STATISTICAL FEATURES

The statistical features do not utilize the unlabeled part of the data because they cannot be learned. For each window of both training and test data, the features described in Table 7.1 were calculated. A selection was made that consisted of time and frequency-domain features that are typically used for activity recognition [13, 79, 154, 194].

Table 7.1: Summary statistics that were calculated for each window of data

Domain	Feature	Description
Time	Maximum	Maximum value
	Minimum	Minimum value
	Mean	Average value
	Standard deviation	Measure of dispersion
	Median	Median value
	25 th percentile	The value below which 25 % of the observations are found
	75 th percentile	The value below which 75 % of the observations are found
	Mean low pass filtered signal	Mean value of DC components
	Mean rectified high pass filtered signal	Mean value of rectified AC components
	Skewness of the signal	The degree of asymmetry of the signal distribution
	Kurtosis	The degree of 'peakedness' of the signal distribution
	Zero crossing rate	Number of zero crossings per second
Frequency	Principal frequency	Frequency component that has the greatest magnitude
	Spectral energy	The sum of the squared discrete FFT component magnitudes
	Frequency entropy	Measure of the distribution of frequency components
	Frequency magnitudes	Magnitude of first six components of FFT analysis

7.2.1.2 PRINCIPAL COMPONENT ANALYSIS (PCA)

Principal component analysis (PCA) [153] is a commonly used and well-established dimensionality reduction and decorrelation technique that is often used in activity recognition [131]. PCA is a basic form of representation learning since it automatically discovers a compact and descriptive subset of representation from the raw data without relying on domain or expert knowledge [131]. Further background information is provided in Appendix A.1.

The 21 most significant components identified in the training data were retained and used to describe the training and testing data.

7.2.1.3 DEEP NET OF SPARSE AUTO ENCODERS

An autoencoder (AE) [122] is a type of neural network with a single hidden layer that is used for representation learning. The activation rate of the hidden neurons can be lowered by imposing a constraint called the sparsity constraint [122], from which the name

sparse auto encoder (SAE) is derived. It is an unsupervised learning algorithm that is trained using backpropagation. A SAE learns to compress data from the input layer into a shortcode and then decompresses that code into something that resembles the original data. The encoder part of the SAE is trained with unlabeled training data during the training phase. In order to obtain the feature vector used for classification, the training and test sets are given as inputs to the decoder part of the network and transformed with the learned code $h_{W,b}(x)$. The output of the network, along with the respective labels, are used as a feature vector for the classification algorithm. Further background information is provided in Appendix A.2.

We implemented the SAE class from the Matlab Deep Learning Toolbox [112]. The number of neurons in the first and second layers was 150 and 100, respectively. The number of hidden neurons was initially determined by a grid search over the training data. It was fixed during the experiments to keep the parameter search space feasible. Both layers were trained with 100 epochs. The activation function σ was set to the logistic sigmoid function. All other parameters were found using a grid search during each experiment iteration. The sum of mean squared reconstruction errors from both layers was used as the selection criteria for the parameters. The regularization parameter was varied between $\lambda \in [0.1, \dots, 2]10^{-3}$ with steps of 0.5×10^{-3} . The sparsity parameter was varied between $\rho \in [0.05, \dots, 0.4]$ with steps of 0.05. The sparsity coefficient was varied between $\beta \in [1, 3, 9]$. Because parameter optimization had to be performed for each experiment with a new subset of training data, the computational overhead for the grid-search with larger dataset sizes became problematic due to long run times. Therefore, for dataset sizes > 40000 samples we sampled the dataset 4 times with 12000 samples, of which 20% was used as validation to compute the mean squared reconstruction error for each set of parameters.

7.2.1.4 CONVOLUTIONAL DEEP BELIEF NETWORK (CDBN)

CDBNs are generative probabilistic models composed of one visible layer and multiple hidden layers [98]. Each hidden neuron learns a statistical relationship between the neurons in the lower layer; the higher layer representations usually become more complex [99]. Further background information is provided in Appendix A.3.

The CDBN was implemented by adopting the code that was available from [98] and [99] so that it could be used with our activity datasets. Parameter tuning was performed once using the unlabeled training data. The reconstruction error of both layers was used as a selection criterion – no labeled information was used for parameter tuning. The number of hidden bases in the first and second layer was varied between [50, 125, 200]. The sparsity regularization parameter was varied between $\beta \in [0.01, 0.05, 0.1]$. For both layers, the filter length was varied between $N_W \in [3, 5, 7]$, and the pooling ratio was varied between $C \in [2, 4, 6, 8]$. After the grid search, we fixed the parameters to the following settings. For the goat dataset, we used 150 and 50 bases in the first and second layers, respectively. The filter length N_W was set to 10 and 3 for the first and second layer, respectively. β was set to 0.05; For the horse dataset we used 100 and 150 bases in the first and second layer, respectively. The filter length N_W was set to 15 and 3 for the first and second layer, respectively. β was set to 0.1 and C was set to 2 for both datasets.

7.2.1.5 SUPPORT VECTOR MACHINE (SVM)

The SVM was implemented with the LibSVM library (version 3.23) [29] using a radial basis function. During each experiment iteration a grid search was performed to find optimal values for the parameters $C \in \{2^{-5}, 2^{-3}, 1, 2^3, 2^5\}$ and $\gamma \in \{2^{-4}, 2^{-2}, 2^{-1}, 1, 2^2, 2^4\}$.

7.2.2 EFFECT OF SIZE OF THE LABELED AND UNLABELED DATA

In machine learning, the use of more training data generally improves the performance of a learning task such as AR [12, 165]. Figure 7.2 [123] sketches the relation between the amount of available training data, and performance for both traditional supervised algorithms and newer algorithms that utilize deep learning.

Figure 7.2: Deep Learning algorithms increase in performance as more data is available. Based on figure from [123]

The curve in Figure 7.2 illustrates the notion that initially adding more training data significantly improves the task performance. However, at some point, the performance improvement becomes smaller, and other factors such as the number of layers, number of training epochs, and number of classes to separate, have a more significant effect on performance than the amount of available training data. Generally, newer deep learning algorithms have demonstrated that adding more data improves performance up to a large extent [123, 165]. Specifically, end-to-end learning approaches require vast amounts of *labeled* data, opposed to unsupervised representation learning that uses *unlabeled* data [12, 123, 165]. Obtaining labeled data is a tremendously time consuming, tedious, and labor-intensive task. Therefore, using unsupervised representation learning in a pipeline approach has multiple advantages. Most importantly, features can be learned from unlabeled data. Furthermore, separating (part) of the feature learning allows for more flexibility because generic parts of such an approach can be separated from specific parts. There is no consensus on the amount of data that is required for deep architectures to work well, and this depends on a number of factors [12, 123, 165].

Therefore, we evaluate the effect of the size of both *labeled* and *unlabeled* data on the performance of the classifier for each feature extraction method.

7.2.2.1 EFFECT OF SIZE OF THE LABELED DATASET ON REPRESENTATION QUALITY

First, we analyzed the effect of the amount of available *labeled* data on the classifier performance. We investigated the quality of the representations using different amounts of labeled data. Figure 7.3 shows the methodology of this experiment. During each fold, 100 % of available training data was used for representation learning. In theory, good representations allow a classifier to separate activities with only a small amount of labeled training data.

Figure 7.3: Overview of experiments where the size of the labeled data was varied. All available unlabeled data was used for representation learning.

7.2.2.2 EFFECT OF SIZE OF THE **UNLABELED** DATASET ON REPRESENTATION QUALITY

We fixed the size of the labeled dataset and analyzed the effect of the amount of available *unlabeled* data on the quality of the representation learning techniques. We compared the effect of the unlabeled data to investigate its prospective benefit to unsupervised learning techniques. We used the increasingly larger sample size to verify that the representation learning techniques are learning and improving as more data became available.

We investigated the effect of the size of the unlabeled dataset on representation quality by fixing the amount of labeled data to 50 samples per class and utilizing the rest of the data in incremental subset sizes as unlabeled data. Figure 7.4 shows the methodology of this experiment. With each subset size, the amount of sampled unlabeled data was combined with the labeled data, without using the label information, and the combined data was used to train the representations.

Figure 7.4: Overview of experiments where the size of the unlabeled data used for representation learning was varied. The size of the available labeled data used for training the SVM was fixed.

7.2.3 EFFECT OF DEPTH

In end-to-end learning approaches, the feature extraction occurs implicitly between the layers in the network. Depth – a hierarchical order in the features – is a crucial aspect in feature learning strategies. Deep architectures promote the re-use of features and can potentially lead to increasingly more abstract features at higher layers [16]. Depth in deep learning techniques is obtained by adding more layers in a NN architecture. To analyze to what degree the additional depth in the representation learning techniques contributes to the AR performance, we repeat the classification evaluations using features derived from intermittent layers of the representation learning techniques.

The SAE deep net and CDBN are both hierarchical DL representation architectures. Both architectures consist of two layers of representations. The output of the first layer is the input for the second layer, introducing hierarchy to learn more abstract features in the second layer. We evaluated the classification performance for each intermediate layer to investigate the effect of depth. In each experiment, we trained the SVM classifier three times using different representations of the data. Firstly, using the representation from the first (pooling) layer activations $L1$. Secondly, using the representations from the second (pooling) layer $L2$. Finally, using the concatenation of both layer activations $L1 + L2$.

7.2.4 EFFECT OF IMBALANCED DATA

A common problem in AR is the significant difference between the size of small minority classes and bigger classes. The imbalance occurs in AAR because some activities are not performed or observed as frequently as others. Examples of minority classes are the *running* activity in the goat dataset, because goats do not run much, and the *eating* activity in the horse dataset because they were mostly observed during riding hours. Dealing with imbalanced classes is an ongoing and essential area of research in machine learning [55, 65]. The class imbalance has a significant impact on the performance of AAR, especially with small dataset sizes. The degree to what makes a dataset 'small' depends on many factors including the type of dataset, the number of different activities than need to be classified (fine or coarse-grained AR), the number of sensors, the sensor position and orientation (were these fixed?), the sampling rate, and the window size. We investigate the effect of imbalanced data in this chapter because we use two different datasets that have different imbalance properties between the activities.

The imbalance in a dataset can be quantified using Shannon's diversity index [162]. Shannon's diversity index can be normalized between 1 and 0 to obtain a balance score, where 1 denotes a balanced and 0 an imbalanced dataset as follows [142]:

$$Balance = \frac{H}{\log k} = \frac{-\sum_{i=1}^k \left(\frac{c_i}{n} \log \frac{c_i}{n} \right)}{\log k} \quad (7.1)$$

, where H is the Shannon entropy, n is the total number of data samples, k the number of classes, and c_i the size of class i . Because some recorded activities were not exercised often enough by all subjects, we chose to use only data from 6 subjects and 5 classes. We had sufficient data of these classes for each subject to be able to assess the performance with leave-one-subject-out validation. Overall, the class imbalance in the horse dataset was 0,94 versus 0,71 in the goat dataset. The imbalance was a bit different for each fold

because we used leave-1-subject-out cross-validation, which results in varying balance scores in the training and test sets. It is important to note here that we learned that the accuracy measure does not report the situation where the classifier never classifies one of the activities. When a minority class never receives either a true or false positive classification, the accuracy measure still reports high performance. On the other hand, the F_1 score is not able to report a performance measure in such a case due to a division by 0.

To demonstrate the effect of imbalanced classes on the performance of the representations, we report two sets of results that reflect two scenarios. Firstly, we maintained a fixed imbalance ratio for all dataset sizes using stratified sampling. This scenario shows the effect of collecting little labeled data, which often results in minimal minority classes for small dataset sizes. Secondly, we obtained a balanced dataset at small dataset sizes using random under-sampling [65] on the majority classes. This scenario reflects one solution to the imbalance problem where data from the majority classes is discarded, or more data from the minority class is collected.

7.3 DATA DESCRIPTION AND PREPROCESSING

We used the multi-orientation goat dataset and the horse dataset, comprising multiple subjects, diverse sensor-orientations, and various activities. We did not use the goat and sheep dataset because this dataset did not contain sufficient unlabeled data. Many datasets that are available online were collected with multiple sensors at fixed positions in fixed orientations. Having multiple sensors in fixed orientations dramatically improves the ease of obtaining good AR performance. The datasets we use contain data collected from a diverse set of animals, e.g., some goats were from a different subspecies than others, and our horse dataset contains data from large horses and smaller ponies from different breeds. Moreover, we used a single sensor of which the position around the neck and orientation was not fixed.

7.3.0.1 GOAT MOVEMENT DATA

This dataset was collected at two farms over 5 days [71]. The dataset comprises data from 5 different goats that performed various activities. Two goats were from a different species than the other three. Thus the subjects are quite different from each other (mostly in size), and there is variability in the data. The ProMove-mini [169] sensor nodes from Inertia Technology were used, which contained a 3-axis accelerometer, gyroscope, and magnetometer and were sampled at 100 Hz. We used data from sensors located at various positions and orientations around the goats' neck. The activities that were used in this research are listed in Table 7.2. The composition of the dataset is shown in Table 7.3. The observed goats mostly spend their time stationary or eating, and the dataset is imbalanced. More information regarding this dataset can be found in Chapter 3.

7.3.0.2 HORSE MOVEMENT DATA

Movement data was collected at a riding stable over 7 days. The dataset comprises data from 6 individual horses that performed 13 different activities. Data was collected when the horses were being ridden and when they were able to move about the paddock freely. We used the Human Activity Monitor [52] sensor nodes from Gulf Coast Data Concepts,

Table 7.2: Observed goat activities

Activity	Description
Stationary	Lying on the ground or standing still, occasionally moving the head or stepping very slowly.
Walking	The goat puts one foot down at the time. The pace of walking varies from very slowly to nearly trotting.
Trotting	The phase between walking and running. One front foot and its opposite hind foot come down at the same time. Trotting at different speeds but always 2 beat gait.
Running	One hind leg strikes the ground first, and then the other hind leg and one fore-leg come down together, finally the other foreleg strikes the ground. This movement creates a three-beat rhythm.
Eating	Pulling fresh grass out of the ground, eating hay from a pile or twigs/grains on the ground.

Table 7.3: Composition of the goat dataset. Number of samples per subject

Activity	Subject					Total	
	1	2	3	4	5	samples	fraction
Stationary	9879	10597	7275	3415	3199	34365	41%
Walking	4526	4737	2381	3339	1015	15998	19%
Trotting	100	526	120	154	145	1045	1%
Running	88	497	56	40	115	796	1%
Eating	12973	3811	8129	6781	152	31846	38%
Total	27566	20168	17961	13729	4626	84050	
Balance score	0,66	0,73	0,65	0,69	0,56	0,71	

which contain a 3-axis accelerometer, gyroscope, and magnetometer. Identical to the goat dataset, the sensors were sampled at 100 Hz. The sensor nodes were attached to the neck of the horses using a collar fabricated from hook and loop fastener. The activities that were observed during the day are listed in Table 7.4. The composition of the dataset is shown in Table 7.5. Because the horses were being ridden, this dataset is more balanced over the different types of gait than the goat dataset. This dataset has been made publicly available [75, 77, 83]. More information regarding this dataset can be found in Chapter 3.

Table 7.4: Observed horse activities

Activity	Description
Standing	Horse standing on 4 legs, no movement of head, standing still
Walking	The horse puts each foot down one at a time. Walking with and without rider on back.
Trotting	One front foot and its opposite hind foot come down at the same time, making a two-beat rhythm. Trotting at different speeds but always 2 beat gait. With and without rider on back.
Galloping	One hind leg strikes the ground first, and then the other hind leg and one fore-leg come down together, finally the other foreleg strikes the ground. This movement creates a three-beat rhythm. With and without rider on back.
Eating	Head down in the grass, eating and slowly moving to get to new grass spots or head is up, chewing and eating food, usually eating hay or long grass.

7

Table 7.5: Composition of the horse dataset. Number of samples per subject

Subject Activity							Total	
	1	2	3	4	5	6	samples	fraction
Standing	1750	1186	1244	347	341	245	5113	6%
Walking	11055	9642	5538	5239	4294	1677	37445	43%
Trotting	6423	7038	3402	3559	2673	1981	25076	29%
Running	1043	696	714	835	323	328	3939	4%
Eating	4331	5063	1951	1091	2496	1116	16048	18%
Total	24602	23625	12849	11071	10127	5347	87621	
Balance score	0,83	0,81	0,86	0,78	0,8	0,85	0,83	

7.3.0.3 PRE-PROCESSING

Energy consumption is a challenge because AAR systems need to run on an embedded tag. Our analysis is mainly different from the state of the art due to the type of animal data and the preprocessing. We aim to focus our analysis on AAR systems that have the opportunity to work highly energy-efficient on an embedded system in the wild. We do so by applying two primary preprocessing steps: Firstly, we use only data from the accelerometer as our input because a gyroscope consumes more energy [79]. Secondly, to be robust against the orientation, we transform the data from 3 axes of the accelerometer into one 3d-vector that is orientation-independent. Thus, we use a low dimensional ($1 \times n$) vector as input for the representation learning frameworks, where n is the size of the window. The transformation effectively reduces the input dimensionality with a factor of 3, reducing computational load due to the lower dimension.

The magnitude of the 3D vector (ℓ^2 -norm) of IMU data is theoretically orientation-independent [79]. This vector is defined as:

$$M(t) = \sqrt{s_x(t)^2 + s_y(t)^2 + s_z(t)^2}, \quad (7.2)$$

where, s_x , s_y , and s_z are the three respective axes of the sensor. To achieve robustness against the rotation of the sensors, we calculated $M(t)$ from the 3-axis of the accelerometer, before calculating the features.

Each segment of activity data was separated into windows with a window size of 2 seconds, and 50 % overlap. Most algorithms, like PCA, perform better with scaled data [4]. Therefore we scaled the data through a Z-transformation obtaining a standard score with zero-mean and unit variance. The standard score is calculated as:

$$x' = \frac{x - \bar{x}}{\sigma}, \quad (7.3)$$

where x is the training data, $\bar{x} = \text{mean}(x)$ is the mean of the training set, and σ is its standard deviation. Data in the test set were not used to calculate the mean and standard deviation.

7.4 EVALUATION

In this section, we present the evaluation results. All analysis was done in Matlab [112]. The F_1 measure was used as the evaluation metric. More details regarding the F_1 measure were discussed in Chapter 2.

7.4.1 VARYING SIZE OF THE LABELED DATASET

We used two sampling methods to vary the amount of labeled data that was used for training: (i.) random under-sampling, which balances the data, and (ii.) stratified sampling, which maintains the imbalance in the dataset. We discuss both experiment results in the following two subsections.

7.4.1.1 BALANCED DATA: RANDOM UNDER-SAMPLING

When sampling a larger labeled dataset, it is possible to balance the subsample by sampling each class with an absolute number of samples per class using random under-

sampling. In a practical scenario, the small labeled dataset can be balanced by discarding data from the majority classes or collect more data for the minority class. The balance score (7.1) for the subsample will be 1 when $c_i \leq c'$, where c_i is the size of class i and c' the desired size per class.

Figures 7.5 and 7.6 show the experiment results of each feature extraction method for the goat and horse dataset, respectively. With small dataset sizes, the performance of all representations increases rapidly and flattens out as the labeled dataset size becomes approximately 1000 samples. The performance did not change much between 1 % and 20 %, and these were therefore not included in the figures for clarity. For both datasets, the sampled dataset ranging from 0.01 % to 2 % size had a balance score of 1 due to random under-sampling. When the dataset is more balanced for smaller sizes, the PCA and SAE representations also result in a valid F_1 -score, which means that for at least one subject in the test set the classifier was able to predict all activities positively. The larger sample sizes had average balance scores of 0.71 and 0.83 for the goat and horse datasets, respectively. Most likely the imbalance is the cause for the dip in performance and high standard deviation for the SAE and PCA representations at the 20 % - 80 % sample sizes in the goat dataset.

7.4.1.2 IMBALANCED DATA: STRATIFIED SAMPLING

Stratified sampling ensures that the class distribution of each subsample roughly remains identical to the distribution in the whole dataset. In this scenario, the minority class contained only one or a few data samples at the smallest dataset size. Figures 7.7 and 7.8 show the experiment results of each feature extraction method for the goat and horse dataset, respectively. When the labeled dataset was minimal, there was a significant difference in performance between the goat and horse datasets. The difference is most likely caused by the higher imbalance of the goat dataset. Sufficient labeled data may have been unavailable for some classes during training, which results in lower performance, or an invalid F_1 measurement. An invalid F_1 measurement occurs when the classifier never predicts an activity class because a division by 0 occurs.

The results show that the PCA and deep net SAE representations were not discriminative enough so that the SVM could separate the activities with small labeled imbalanced datasets. The SVM can deal with the imbalance using these representations as the labeled dataset gets bigger. The results show that when the labeled dataset size is small, the CDBN architecture produces representations that still discriminate activities, even when all test data is from an unseen subject (no data from this subject was used for training). Figure 7.5 shows that the second layer does significantly contribute to the performance of the CDBN representation in small more imbalanced labeled datasets. In larger or more balanced datasets, the depth contributes when the first and second layers are concatenated. The difference in performance between representation algorithms in an imbalanced dataset becomes smaller as more labeled data is used.

Figure 7.5: AAR performance for goats using different sizes of labeled data. The performance for each feature extraction method is shown where the labeled data was varied. Random under-sampling was used for smaller datasets ($\leq 2\%$). The error bars denote the standard deviation over multiple folds and batches. Because the size of the training dataset size varies per fold, the shown sample sizes are averages of the whole dataset size.

Legend: CDBN: convolutional deep belief network, PCA: principal component analysis, SAE: sparse auto encoder, **stat_{freq}**: spectral features, **stat_{time}**: temporal features, **stat_{combined}**: spectral + temporal features, **L1**: first layer, **L2**: second layer, **L1L2**: first and second layer concatenated

Figure 7.6: AAR performance for horses using different sizes of labeled data. The performance for each feature extraction method is shown where the labeled data was varied. Random under-sampling was used for smaller datasets ($\leq 1\%$). The error bars denote the standard deviation over multiple folds and batches. Because the size of the training dataset size varies per fold, the shown sample sizes are averages of the whole dataset size.

Legend: CDBN: convolutional deep belief network, PCA: principal component analysis, SAE: sparse auto encoder, **stat_{freq}**: spectral features, **stat_{time}**: temporal features, **stat_{combined}**: spectral + temporal features, **L1**: first layer, **L2**: second layer, **L1L2**: first and second layer concatenated

Figure 7.7: AAR performance for goats using different sizes of labeled data. The performance for each feature extraction method is shown where the labeled data was varied. Stratified sampling was used and no balancing was applied. The error bars denote the standard deviation over multiple folds and batches. Because the size of the training dataset size varies per fold, the shown sample sizes are averages of the whole dataset size.

Legend: CDBN: convolutional deep belief network, PCA: principal component analysis, SAE: sparse auto encoder, **stat_{freq}**: spectral features, **stat_{time}**: temporal features, **stat_{combined}**: spectral + temporal features, L1: first layer, L2: second layer, L1L2: first and second layer concatenated

Figure 7.8: AAR performance for horses using different sizes of labeled data. The performance for each feature extraction method is shown where the labeled data was varied. Stratified sampling was used and no balancing was applied. The error bars denote the standard deviation over multiple folds and batches. Because the size of the training dataset size varies per fold, the shown sample sizes are averages of the whole dataset size.

Legend: CDBN: convolutional deep belief network, PCA: principal component analysis, SAE: sparse auto encoder, **stat_{freq}**: spectral features, **stat_{time}**: temporal features, **stat_{combined}**: spectral + temporal features, L1: first layer, L2: second layer, L1L2: first and second layer concatenated

7.4.2 VARYING SIZE OF THE UNLABELED DATASET

The performance of the representation learning architectures in the previous section is dependent on the amount of available unlabeled data. This experiment aims to investigate the effect of unlabeled dataset size on feature learning performance. We chose a labeled dataset size where the F_1 performance of all architectures was above 50 % in the previous experiments. This size is not too big so that the effect of additional unlabeled size would become insignificant against the large labeled dataset. We used 50 labeled samples per class during each experiment iteration as the training set for the SVM classifier and gradually increased the size of the additionally available unlabeled data to train the representations in an unsupervised manner. Not all architectures were able to deal with the imbalance with this sample size of labeled data. Therefore, we used random under-sampling for the smaller labeled dataset sizes. The methodology for this experiment was discussed in more detail in Section 7.2.2.2.

Figures 7.9 and 7.10, and Tables 7.6 and 7.7, show the experiment results for the Goat and Horse datasets, respectively. The results show that the overall performance of the learned representations gradually increases with the size of the unlabeled dataset. The performance over sample size increased mostly in the Goat dataset and more slowly in the Horse dataset. The results are further discussed in the following section.

Table 7.6: AAR performance (%) for goats using different sample sizes of unlabeled data. Each second column denotes the standard deviation σ over multiple folds and batches.

sample size	0,4% (250)		2% (1000)		20% (13398)		85% (55510)		100% (74623)	
representation	F_1	σ	F_1	σ	F_1	σ	F_1	σ	F_1	σ
CDBN ^{L1}	67.19	6.18	66.30	5.66	72.56	9.63	73.56	5.72	79.55	10.87
CDBN ^{L1L2}	68.10	4.96	67.02	5.20	76.28	8.51	75.40	5.56	79.46	11.33
CDBN ^{L2}	53.20	5.07	47.19	17.04	74.19	5.26	72.29	7.08	77.80	10.95
PCA	59.23	5.72	62.14	6.50	60.57	5.39	61.65	5.57	62.03	0.18
SAE ^{L1}	65.62	6.20	62.07	8.14	61.79	5.49	60.43	7.47	67.89	6.23
SAE ^{L1L2}	62.63	7.92	61.13	8.63	59.40	6.63	59.61	7.09	65.31	8.56
SAE ^{L2}	57.90	6.53	60.90	8.66	59.57	8.48	60.71	7.55	64.34	7.64

7.5 DISCUSSION

Overall, the classification performance was higher using the horse dataset. Plausible reasons for this are the fact that the horse dataset is more balanced than the goat dataset (see Section 7.2.4), the goat subjects are more diverse than the horse subjects, and the sensor locations did vary more in the goats than the horses. Therefore, we consider the goat dataset harder to classify than the horse dataset. In smaller labeled dataset samples, the statistical features generally outperformed the learned representations. These are engineered features and have been proven to work well for AAR [79] and seem to

Table 7.7: AAR performance (%) for horses using different sample sizes of unlabeled data. Each second column denotes the standard deviation σ over multiple folds and batches.

sample size	0,4% (250)		2% (1000)		20% (14553)		85% (58935)		100% (77523)	
representation	F_1	σ	F_1	σ	F_1	σ	F_1	σ	F_1	σ
CDBN ^{L1}	65.17	4.40	66.78	5.71	72.14	5.11	72.62	5.69	70.01	6.86
CDBN ^{L1L2}	76.45	6.81	76.16	5.90	75.30	6.12	76.87	5.48	78.00	7.90
CDBN ^{L2}	60.59	10.83	61.15	10.20	62.43	7.64	63.24	9.98	65.79	9.57
PCA	59.18	4.78	59.13	4.48	58.96	3.62	58.99	3.68	56.30	5.06
SAE ^{L1}	78.47	4.83	77.63	5.71	75.14	4.53	76.39	6.70	74.19	5.75
SAE ^{L1L2}	80.01	5.09	78.74	5.56	76.40	4.91	80.05	4.68	79.77	6.90
SAE ^{L2}	76.45	4.70	76.04	4.71	77.26	4.63	81.50	5.24	80.86	9.71

Figure 7.9: AAR performance for goats using different sizes of unlabeled data. The performance for each feature extraction method is shown where the unlabeled data was varied. The grouped bar plots on the x-axes show the average amounts of additional unlabeled data. The error bars denote the standard deviation over multiple folds and batches.

Legend: CDBN: convolutional deep belief network, PCA: principal component analysis, SAE: sparse auto encoder, L1: first layer, L2: second layer, L1L2: first and second layer concatenated

Figure 7.10: AAR performance for horses using different sizes of unlabeled data. The performance for each feature extraction method is shown where the unlabeled data was varied. The grouped bar plots on the x-axes show the average amounts of additional unlabeled data. The error bars denote the standard deviation over multiple folds and batches.

Legend: CDBN: convolutional deep belief network, PCA: principal component analysis, SAE: sparse auto encoder, L1: first layer, L2: second layer, L1L2: first and second layer concatenated

perform well in smaller samples too. With larger dataset sample sizes, representation learning techniques slightly outperformed summary statistics. Figures 7.5 and 7.6 show that using only the time domain features ($\text{stat}_{\text{time}}$) on average performed just as well as combining them with frequency domain features ($\text{stat}_{\text{combined}}$). Overall, when using only frequency domain features, the performance was worse. This result confirms previous findings [79] and shows that activity recognition can be performed with high performance and simple features that do not require much computation. However, in the case of the Goat dataset (which is more challenging to classify), the difference in performance between the statistic features and the CDBN was small. At the same time, there is much room for improvement in CDBN development and training with additional unlabeled data. Moreover, in larger dataset samples, the statistical features were outperformed by the CDBN and SAE deep net in most scenarios.

The results for both datasets show that PCA features had excellent performance when the labeled dataset sample size was big, and it performed poorly with smaller labeled dataset sizes. The results show that the PCA and SAE representations could not deal with more imbalanced datasets at first but improved as the labeled dataset sample size grew bigger than 20 %. For smaller dataset sample sizes, and mostly with the horse dataset, the second layer representation in the SAE deep net did extract meaningful information because the performance was higher than when using only a single layer. The second layer in the SAE deep net did not contribute much to the performance as the labeled dataset size grew in size. In a more balanced dataset, it seems better to use a single layer representation, thus reduce complexity when there is a large amount of labeled data. However, in practical scenarios, this is usually not the case as there is often a small amount of labeled data, which is (highly) imbalanced.

Our results show that when the labeled dataset size is small, the CDBN architecture outperforms the other representation learning algorithms. The CDBN is more robust to smaller dataset sizes and a higher imbalance in the dataset than the other representation learning architectures. In both scenarios with the small goat dataset sizes, the 2nd layer representation performed better than using only the 1st layer. In the horse dataset and larger sizes of the labeled goat dataset, the concatenation of both layers ($L1 + L2$) performed the best. On average, the concatenation of the 1st and 2nd layer yielded a performance increase of 13.78 % F_1 performance over all experiments, relative to using only the 1st or 2nd layer representations. Thus, even when the second layer by itself did not perform better than using only the first layer, the concatenation often resulted in better representations. The CDBN representations outperformed statistical features for the goat dataset and performed slightly worse with the horse dataset.

Figures 7.9 and 7.10 show that when increasing the amount of unlabeled data, the rate of improvement was the largest for the CDBN and the smallest for PCA representation. When only a small amount of unlabeled data was available, the extra layers did not seem to contribute much. For the horse dataset, the concatenation of both CDBN layers gained in performance as more unlabeled data became available. The PCA representations did not benefit from more unlabeled data and seemed to be restricted in performance due to the size of the labeled dataset sample. The results in the Section 7.4.1 show that the performance of PCA improved with more labeled data.

Although the performance increased very slowly with dataset size, our results indi-

cate that the idea presented in Section 7.2.2 (Figure 7.2) also holds for AAR – DL representations for AAR increase in performance as more unlabeled data becomes available. The performance of the learned representations is excellent, especially given the fact that both architectures were only trained with unlabeled data from limited sensor modalities without fine-tuning to the datasets (unsupervised representation learning). We expect that fine-tuning using a small amount of the labeled data improves the performance of the representations even more.

7.6 CONCLUSION

AAR can obtain excellent performance with only engineered time-domain features. However, we have demonstrated that unsupervised representation learning techniques can approach and outperform the performance of engineered features. This finding is important, especially given the fact that the representation learning architectures were only trained with unlabeled data without fine-tuning to the datasets (unsupervised representation learning). When fixing the amount of labeled data and varying the size of the unlabeled dataset, our results show that the CDBN architecture benefited the most from an increasing amount of unlabeled data, especially in the more diverse and imbalanced dataset. The most significant difference between the CDBN and other architectures is that it is a generative model. Based on our findings, we believe that generative models, such as the CDBN, are compelling research directions in unsupervised representation learning for AR. We demonstrated that concatenating the 1st and 2nd layer representations often yields better classification performance with an average performance increase of 13.78 % F_1 performance over all experiments, relative to using only the 1st or 2nd layer. Furthermore, the results indicate that deep representations provide more robustness to the imbalance in smaller labeled datasets.

Our results confirmed the general knowledge that an imbalance in datasets has a significant effect on AR. The difference in performance between representation algorithms in an imbalanced dataset becomes smaller as more labeled data is available from the majority classes. We believe that the effect of class imbalance in datasets is not only crucial in labeled data but also affects the performance of unsupervised representation learning, especially as the unlabeled dataset grows. Therefore, class imbalance in representation learning is an important research topic in HAR and AAR to make deep unsupervised representation learning a reality for many application domains.

Unsupervised deep representation learning for AAR is hard and has not yet been thoroughly explored. These architectures come with many design choices and tuning parameters that have a high impact on their performance. Most importantly, the performance of the SAE deep net and CDBN kept increasing in performance up to 100 % of the unlabeled dataset opposed to engineered features, which can not improve by learning from unlabeled data.

Although 'simple' – engineered – time-domain features match or even outperform *unsupervised* representation learning algorithms at this point, we believe that representation learning structures outperforms engineered representations as the task becomes increasingly difficult, we find better design solutions, and the unlabeled dataset size grows.

8

CONCLUSIONS AND FUTURE WORK

In this thesis, we investigated multitask learning, orientation-independence, and unsupervised representation learning for animal activity recognition (AAR). Specifically, we focused on AAR using inertial measurement units that are attached to collars around the neck of animals. Throughout the chapters in this thesis, we presented various evaluations that provide insight into the impact of different factors on the performance. In this chapter, we review our contributions, lessons learned, and future directions for AAR.

8.1 RESEARCH SUMMARY

The focus of this thesis is on AAR using inertial measurement units (IMUs) that are attached to collar tags around the neck of animals in combination with machine learning (ML) classifiers. The performance of AAR is impacted by various factors such as heterogeneity of animal populations, sensor position and orientation, and the classification method. In this thesis, we investigated these and other factors through the following main research question:

How can we recognize various animal activities using motion data while considering resource-efficiency, orientation-independence, and genericity so that it can be executed online and easily deployed across a wide variety of species?

In this thesis, we have provided answers to this question through the following seven contributions.

CONTRIBUTION 1: LITERATURE STUDY OF THE STATE OF THE ART

In Chapter 2, we explained the AAR pipeline and its parts. We discussed the different sensor modalities used for AAR and motivated the use of accelerometers over other modalities. We surveyed the state of the art in AAR and compared properties such as the dataset size and composition, number and type of discriminated activities, sensors, features, and classifiers. The survey showed that there is a need for open access datasets that contain data from multiple subjects. Through this thesis, we published three open-access datasets, which are further discussed in Contribution 2. The survey showed that no studies addressed and compared the genericity performance of classifiers sufficiently. We evaluated genericity of the classifiers through multitask learning (MTL) in Contribution 4. Furthermore, multiple studies reported varying sensor orientations during data acquisition, while sensor-orientation-independent AAR has not been studied. We addressed sensor orientation and position independent AAR in Contribution 5. In the survey, we provided an overview of all the elements that are essential for effective AAR and the different factors that influence the performance. Four essential factors are investigated in Contribution 6. Finally, none of the surveyed works investigated unsupervised representation learning for AAR, which we addressed in Contribution 7.

CONTRIBUTION 2: DATASETS

Different types of motion data from animals were required to answer the research questions. Because the required types of data were not available at the start of this research, it was collected from goat, sheep, and horses. All of the collected data has been made available online with open access. The dataset descriptions were presented in Chapter 3. The composition and collection process has been described in detail so that other researchers can use the data for their research. In total, three datasets were collected and annotated. Dataset 1 is the smallest dataset out of three and comprises motion data from 4 goats and 2 sheep and was used to study the effect of MTL across individuals and between goats and sheep. The main feature of this dataset is that identical activities were annotated for two different but similar species; this makes this dataset particularly suitable for research regarding generic AAR or transfer learning. Dataset 2 comprises motion data from 5 goats that was collected from 6 diverse positions and orientation around the neck. The dataset was used to study orientation-independent feature selection for AAR. The diverse sensor position and orientations around the neck of

each subject make this dataset particularly suitable for sensor-orientation independent AAR research. Dataset 3 is the largest dataset of the three and comprises motion data from 18 horses that was collected at an equestrian facility. Data from 11 subjects was labeled, but for 6 subjects, the data was labeled more extensively for 6 activities. The dataset is particularly suitable for unsupervised AAR research because it contains a large amount of additional unlabeled data.

CONTRIBUTION 3: SENSOR-VIDEO SYNCHRONIZATION AND LABELING TOOL

We presented a synchronization method to synchronize videos with sensor data. The method has been used to develop a labeling application described in Section 3.5. The application can be used to synchronize videos with sensor data. Subsequently, annotations can be added to the data, and a labeled dataset can be exported.

CONTRIBUTION 4: MULTI-TASK LEARNING ANALYSIS

In Chapter 4, we investigated the trade-off between the generalization capability of various classifiers and AAR performance using MTL for embedded platforms. We used real-world motion data from goats and sheep to evaluate AAR in three scenarios: (i.) individual AAR. We showed that an individualized AAR system always performs best with an average F_1 performance of 86.1 %. (ii.) training a classifier with data from one species, and using that classifier to predict activities of another similar species, yielded relatively bad AAR performance (69.77 %). (iii.) we have shown a significant increase in performance when MTL is utilized between species by using data from two species and a shared feature representation to train a classifier (80.88 %). On average, the relative increase in F_1 performance was 15.92 %. The performance approached that of the individualized scenario, where data was used per individual.

Furthermore, our results indicate that data from similar species can be mixed to improve the classification of one of the species. This result is prospective because obtaining labeled data from a wild animal (e.g., zebra) is difficult, while it is easier to collect data from a similar domesticated animal (e.g., horse). A small labeled dataset for the zebra may be mixed with data from the horse to complement the training of the classifier.

CONTRIBUTION 5: SENSOR ORIENTATION-INDEPENDENT FEATURE SELECTION

In Chapter 5, we presented a framework that finds small optimal feature sets that are lightweight and robust to the sensor's orientation. Robustness against position and orientation is essential because motion sensors placed around the neck of an animal can be displaced over time by the animal itself (e.g., scratching or biting), its environment (e.g., other animals or vegetation), and misalignment during manufacturing or collaring. The AAR performance degrades significantly in these cases when a classifier is sensitive to the orientation and position of the sensor around the neck. We have shown that it is possible to obtain optimal orientation-independent features by training a classifier with mixed data from various orientations.

Using a single feature sufficed for excellent performance (90.8 %), and this can be improved by using up to 3 features (93.5 %) selected by the decision tree (DT) and naive Bayes (NB) classifier; using a larger feature set did not improve the performance. The best scoring features were: *accel_3dvector_std*, *accel_3dvector_norm_mag_6*, *accel_3dvector_freqEntropy*, and *gyro_3dvector_twenty_fith_p*. Most of these features are accelerometer features. Excluding the gyroscope did not significantly degrade the per-

formance. Additionally, the accelerometer consumes significantly less power. Therefore, the accelerometer is the best sensor to use for AAR. With a small loss of accuracy, the frequency-domain features can be swapped out for time-domain features, lowering the computational requirement.

CONTRIBUTION 6: ANALYSIS OF FEATURE TYPE, HYPERPARAMETER TUNING, AND DATA PARTITIONING

Besides the classifier, various other choices in the design and evaluation method impact the AAR performance. In Chapter 6, we analyzed the impact of the number and type of features, two data partitioning methods, and hyperparameter tuning on AAR performance using supervised ML techniques. We compared the performance of 7 classifiers by training and evaluating them with motion data from 6 horses in four scenarios: (i.) We evaluated the performance of the orientation-independent feature set from Contribution 5 on horses and showed that using the feature-subset yields an average 2.95 % relative increase in F_1 performance compared to using all features. (ii.) We compared the difference in performance between time-domain and frequency-domain features to investigate the trade-off between feature complexity and AAR performance. On average, spectral features increased F_1 performance relatively with 2.81 %, ranging from -3 % (linear discriminant analysis (LDA)) to 4.94 % (decision tree (DT)). Thus, the trade-off between complexity and performance is different for each classifier, but overall most classifiers did yield higher performance using frequency features. (iii.) We investigated the effect of the evaluation partitioning method by comparing leave-one-subject-out with k -fold cross-validation. k -fold cross-validation does not capture the genericity performance of the classifiers because data from all subjects is mixed. Therefore, the performances are over-optimistic. On average, the relative F_1 performance was 2.6 % higher for the k -fold cross-validation method. In a practical scenario where an AAR classifier is used on unseen animals, the performance is reflected more precisely using leave-one-subject-out validation. (iv.) We demonstrated that hyperparameter tuning had a positive effect on most classifiers, and was minimal for a few. On average, hyperparameter tuning increased the F_1 performance with 1.91 % relative to default parameters. Hyperparameter tuning decreased the standard deviation in the performance of the deep neural network (DNN) classifier, showing that the learned model could generalize better to unseen subjects after tuning.

CONTRIBUTION 7: DEEP UNSUPERVISED REPRESENTATION LEARNING

We investigated the opportunity to exploit the large unlabeled part of sensor-data to improve the feature extraction for AAR through unsupervised representation learning. We compared three unsupervised representation learning techniques with three conventional feature extraction methods. To investigate the effect of the size of both *labeled* and *unlabeled* part of the dataset on the quality of the features, we trained the unsupervised representation architectures and classifier using various sample sizes. Furthermore, we evaluated the effect of depth in the architectures on the performance. Finally, we investigated the effect of class imbalance in the dataset on the AAR performance using the different features. In Chapter 7, we demonstrated that the performance of unsupervised representation learning could approach and, in some cases, outperform conventional features (85.17 % vs 82.52 % in the goat dataset). This result is essential, especially given the fact that the representation learning architectures were only trained

with unlabeled data without fine-tuning to the datasets (unsupervised representation learning). When fixing the amount of labeled data and varying the size of the unlabeled dataset, our results showed that the convolutional deep belief network (CDBN) architecture benefited the most from an increasing amount of unlabeled data, especially in the more diverse and imbalanced dataset. We demonstrated that concatenating the 1st and 2nd layer representations often results in better classification performance with an average performance increase of 13.78 % F_1 performance over all experiments, relative to using only the 1st or 2nd layer. Furthermore, our results indicate that deep representations provide more robustness to the imbalance in smaller labeled datasets.

Unsupervised deep representation learning for AAR is hard and has not yet been thoroughly explored. These architectures come with many design choices and tuning parameters that impact their performance. Most importantly, the performance of the sparse auto encoder (SAE) deep net and CDBN kept increasing in performance up to 100 % of the unlabeled dataset opposed to engineered features, which can not improve by learning from unlabeled data.

8.2 LESSONS LEARNED

In this section, we summarize the most important lessons that were learned during this dissertation.

- DATA ACQUISITION REQUIRES PATIENCE, DELIBERATION, AND STAMINA

For this thesis, we collected 3 datasets, and we learned that collecting and annotating data is laborious and time-consuming. The total time required to collect movement data is easily underestimated. Each experiment requires a long preparation phase that includes planning, ethical soundness, hardware choice, testing, and finding a location. During the experiments, sensors broke down, data got corrupted or lost and had to be organized and logged carefully. Hard drives quickly became too small. Unlike human subjects, it is not always possible to ask an animal to perform a particular activity. Each experiment has to be performed in an ethically sound manner that puts the animals' well-being first. Therefore, it is not straightforward to obtain a rich and balanced dataset that contains a sufficient amount of labeled data for multiple activities. From first-hand experience, we learned that data labeling could not be performed for long consecutive periods without corrupting the mind.

- DATA COLLECTED FOR A SPECIFIC PURPOSE MAY HAVE THE POTENTIAL TO BE USED IN RESEARCH BEYOND THE CONTEXT ORIGINALLY ENVISIONED

We observed that a dataset that was collected for one specific purpose proved to be very useful for a very different purpose. At the same time, to be fully applicable for the originally “not envisioned” research purpose, the data may lack some modality. For example, one might not need the local outside temperature for the current research scope, but others may later want to study a correlation between the weather and your data. The same applies to the annotation and synchroniza-

tion of datasets. Therefore, it may be useful to consider the applicability of the “to be collected” data beyond the scope of the current research.

- ACTIVITY RECOGNITION PERFORMANCE IS EASILY OVERESTIMATED

To prevent over-optimistic performance results, AAR and human activity recognition (HAR) systems should be evaluated with leave- n -subject-out cross-validation. This validation method should primarily be used in the case of research that aims to deploy AAR in real-world scenarios, in which the AAR system is used on unseen subjects, outside the training population. When k -fold cross-validation is used, data from all subjects is present in the training *and* test sets. This fact allows the classifier to fine-tune on the distribution that best fits the used dataset. The performance may be significantly lower with data from unseen subjects, that might have a different distribution. Because it is difficult to obtain sufficient labeled training data, most research uses k -fold cross-validation, and when leave- n -subject out validation is used, n is usually not larger than 1. This choice is made because not all activity classes for all subjects always contain a sufficient amount of data. For example, if there is one subject in the set that only has labeled data for 2 activities and the other subjects have data from 5 activities, there is no correct way to assess the performance for this subject.

- INCORRECT DESIGN CHOICES ARE EASILY MADE DURING DATA PREPROCESSING

Preprocessing data is an essential step in the AAR pipeline. The choices made during this step can have a significant effect on performance. We learned that it is quite easy to make incorrect design choices that quickly go unnoticed because they do not immediately result in an error. For example, feature scaling, such as standardization, should only use the *training* data for properties. On one occasion, we mistakenly used the dataset for standardization in a preprocessing step, before dividing the data into training and testing sets. In doing so, we used information from the test set, and the performance was over-optimistic. Other mistakes that easily go by unnoticed include: dividing overlapped segmented data into both training and testing data (information leakage), not shuffling data before sampling, and incorrectly (re)mapping labels (e.g., when converting a string-type to integer-type and vice versa).

- SPLITTING LONG ACTIVITY SEGMENTS YIELDS MORE BALANCED DATASETS

We defined a segment as a continuous recording of an activity exercised by a subject. Segments should be divided into train and test sets before windowing (usually with overlap) to prevent information leakage. Because some segments are short while others can be long, merely sampling segments and dividing them into training and test sets causes a difference in the balance ratio of the train and test sets between training, tuning, and test sets. We learned that recursively shortening activity segments to a maximum length minimizes the imbalance in the ratio of sample data for some activity categories between the different datasets.

- ACCURACY IS NOT ALWAYS THE BEST EVALUATION METRIC

Accuracy is used in virtually all AAR research. The accuracy measure is commonly defined as the total number of correct predictions divided by the total number of predictions: $\frac{tp+tn}{tp+fp+tn+fn}$. Although we did argue in this thesis that accuracy is a good measure because it takes into account the true negatives (tn), it is not always a good measure for activity recognition, especially not in imbalanced datasets. The F-measure does not include tn . When a classifier fails to classify *any* positive prediction for one of the activity classes, this is not reflected in the accuracy measure. However, in such a case, the F-measure cannot be computed due to a division by 0, reflecting poor performance. The severeness of this lesson depends on the AAR situation and should be considered in situ.

8.3 FUTURE WORK

In this section, we present prospective ideas that can be addressed to extend our work in future work.

- UNSUPERVISED REPRESENTATION LEARNING

In Chapter 7, we compared three unsupervised representation learning techniques and demonstrated their potential to exploit the benefits of the unlabeled part of the data. Numerous newer and improved versions of unsupervised and supervised representation learning techniques have been proposed and are worth investigating.

Furthermore, we showed the performance of the SAE deep net and CDBN kept increasing in performance up to 100 % of the used unlabeled dataset. However, our results show that the imbalance in the labeled dataset has a significant impact on the performance of AAR, especially in smaller datasets. One analysis that was not included in this work is a focused investigation on the effect of class imbalance in the *unlabeled* data. We only demonstrated the effect of imbalance using the *labeled* data. Significant challenges that need to be tackled include an imbalance in both the labeled and unlabeled data. Future work can sample significant amounts of additional unlabeled data that are available in our horse dataset. Future research should find the rate of improvement in the quality of the representations as more unlabeled data is used or the rate of deterioration and its causes. Because this data is unlabeled, we cannot use under- or upsampling to balance the unlabeled dataset. The large volume of unlabeled data should be sampled in a way so that it contributes to the representation quality. A new framework for unsupervised learning may simultaneously guide the policy of a reinforcement learning agent while shaping the representations. The framework should learn what parts of the unlabeled dataset to use for representation learning, and what part to 'forget' or exclude. The framework requires a form of curiosity and discovery.

- GENERIC ACTIVITY RECOGNITION

In Chapter 4, we demonstrated that MTL has a significant effect on the genericity performance of the classifiers. Recently, many end-to-end (deep) learning frame-

works have been proposed for transfer learning in HAR. Similar frameworks could be useful for AAR and can be investigated using our datasets. For example, (deep) representations learned from one species's data might be beneficial to improve those of another species.

- ACTIVE LEARNING EMBEDDED IN LABELING FRAMEWORK

Naturally, animals exhibit activities in an imbalanced manner. For example, in Chapter 3, we learned that goats spend most of their time standing and eating. When the data annotation is performed chronologically, this results in an equally imbalanced labeled dataset. Random under-sampling is often used during pre-processing to improve the balance between the activity classes. Random under-sampling discards labeled data from the majority classes, which is wasteful – why label that data if it is discarded later?

Active learning may be able to balance the dataset during the data annotation process and prevent wasteful work on labeling data that is later discarded due to the imbalance. Active learning promises to not only obtain a more balanced dataset but also speed up the process. Active learning aims to select raw data that is dissimilar to the data that is already labeled. For example, when most of the data consists of the animal grazing, then it might be beneficial to have an active learner select data that is different from grazing and query the annotator for a label, opposed to manually scanning all the footage to find other behavior.

- QUATERNION FEATURES

A quaternion [49] is a four-part hyper-complex number used in 3D rotations and orientations. Although our results have shown that summary statistics derived directly from gyroscope data did not significantly contribute to AAR performance, the sensor can be used to engineer features that have not been explored in the state of the art or this dissertation. In situations where energy constraints are less critical, the accelerometer data can be fused with the gyroscope data to estimate the device's orientation at each point in time. The fusion is different than using the accelerometer and gyroscope as two separate data streams and extracting summary statistics from them individually. The valuable property is not the orientation because we assume that this is not fixed. What may be interesting to explore is the relative angular velocity. The accelerometer can only capture the squared summed motion in 3D, which is one dimensional. The rotations of the device are 3 dimensional and could be very specific for different activities. The main question that arises is the sensitivity to the orientation of the collar. The quaternion fusion can be explored in future work using our multi-orientation goat movement dataset.

- AUTOMATIC SYNCHRONIZATION OF DATA-LOGGERS WITH CAMERAS

During and after the collection of data that has to be labeled, it is a tedious task to synchronize the sensor data with the ground-truth videos. One solution would be to use dedicated cameras that communicate and exchange time information with

the sensor. However, this would be a limitation because every situation requires a different camera setup. In Chapter 3, we proposed an approach with a more advanced datalogger that allows the use of any camera. In future research, a data logger can be developed that encodes identification and time information into a shortcode that is transmitted through a visual pattern (e.g., a flashing LED), which is recorded by the camera. The labeling framework can then interpret the flashing pattern back to identify each sensor in the video-frame and synchronize with it accordingly.

REPRESENTATION ARCHITECTURES

This appendix provides the basic principles of the following 3 representation learning architectures that were used in Chapter 7: (i.) principal component analysis (PCA), (ii.) a deep net with sparse auto encoders (SAEs), and (iii.) the convolutional deep belief network (CDBN).

A.1 PRINCIPAL COMPONENT ANALYSIS

Principal component analysis (PCA) [153] is a commonly used and well established dimensionality reduction and decorrelation technique that is often used in activity recognition [131]. principal component analysis (PCA) is a basic form of representation learning since it automatically discovers a compact and descriptive subset of representation from the raw data without relying on domain or expert knowledge [131]. Essentially, PCA obtains a linear transformation $f(x) = W^T x$ that maps raw data into a feature vector [102]. PCA identifies components in the input data which have the largest variance [153, 158]. The significance of the components is reflected in their eigenvalues, obtained from the covariance matrix.

A.2 DEEP NET COMPRISING 2 STACKED SPARSE AUTO ENCODERS

An autoencoder (AE) [122] is a type of neural network with a single hidden layer that is used for representation learning. It is an unsupervised learning algorithm that is trained using backpropagation. An AE learns to compress data from the input layer into a short code, and then decompresses that code into something that resembles the original data. Figure A.1 shows a schematic overview of an AE. The encoder part of the AE, shown in Figure A.1, is trained with unlabeled training data during the training phase. In order to obtain the feature vector used for classification, the training and test sets are given as inputs to the decoder part of the network and transformed with the learned code $h_{W,b}(x)$. The output of the network, along with the respective labels, are used as a feature vector for the classification algorithm.

Figure A.1: Schematic overview of an autoencoder, showing the encoder and decoder parts.

During training of the AE, the target values are set to be equal to the input $y^{(i)} = x^{(i)}$, for each i -th training sample. An AE tries to learn a function $h_{W,b}(x) \approx x$; in other words, to learn an approximation of the identity function ($f(x) = x$) so that the network outputs $\hat{x}$, as similar as possible to x . The hidden layer is usually smaller than the in- and output layers, so that the AE is engaged in dimensionality reduction and learns a compressed representation of the input data. The compressed representation (also referred to as code, latent variable, latent representation or hidden representation) is denoted as:

$$h_{W,b}(x) = \sigma(W^{(1)}x + b^{(1)}) \quad (\text{A.1})$$

, where $\sigma(\cdot)$ denotes an element-wise activation function, W is a weight matrix, and b is a bias vector. The reconstruction of x is calculated as:

$$\hat{x} = \sigma(W^{(2)}h(x) + b^{(2)}) \quad (\text{A.2})$$

The AE network is trained by minimizing a cost function defined as:

$$J(W, b) = \frac{1}{m} \sum_{i=1}^m \left(\|h_{W,b}(x^{(i)}) - y^{(i)}\|^2 \right) + \frac{\lambda}{2} \sum_l^{L-1} \sum_j^{sl} \sum_i^{sl+1} \left(W_{ji}^{(l)} \right)^2 \quad (\text{A.3})$$

, where m is the number of training data, $h_{W,b}(x)$ as defined in Equation A.1, $x^{(i)}$ and $y^{(i)}$ are the i -th training sample on the input and output, respectively. The second term in Equation A.3 is the regularization term, where λ is the L_2 regularization coefficient, L is the number of layers, sl is the number of neurons in layer l , and $W_{ji}^{(l)}$ is the weights associated with the connection between neuron j in layer l , and neuron i in layer $l+1$. The regularization term helps prevent overfitting to the training data. The cost function $J(W, b)$ (Equation A.3) is minimized through batch gradient descent. The partial

derivatives that are needed for gradient descent are computed using the backpropagation algorithm [122].

The representations for different types of input will be too similar if individual neurons of the AE are activated too frequently. The activation rates of the neurons should be lower so that each neuron is only activated for a small fraction of the training data. The activation rate of the hidden neurons can be lowered by imposing a constraint, called the sparsity constraint [122], from which the name sparse auto encoder (SAE) is derived. When neurons only respond to specific types of input, the SAE can potentially discover a more expressive structure from the input data. The sparsity constraint is added to the cost function as follows:

$$J_{\text{sparse}}(W, b) = J(W, b) + \beta \sum_{j=1}^{s_2} \text{KL}(\rho || \hat{\rho}_j) \quad (\text{A.4})$$

, where $J(W, b)$ is the cost function, β is the coefficient that controls the weight of the sparsity penalty term, s_2 is the number of neurons in the hidden layer, ρ is a sparsity parameter (typically a small value close to zero), and $\hat{\rho}_j$ is the average activation of hidden neuron j calculated by

$$\hat{\rho}_j = \frac{1}{m} \sum_{i=1}^m \left[h_{W,b}(x^{(i)}) \right] \quad (\text{A.5})$$

$\text{KL}(\rho || \hat{\rho}_j)$ is the Kullback-Leibler (KL) divergence between $\hat{\rho}_j$ and ρ . KL-divergence is a standard function for measuring how different two distributions are and grows as $\hat{\rho}_j$ diverges from ρ , effectively causing the weights W to be optimized in a way so that the neurons activate sparsely.

A deep net that learns hierarchical features is formed by stacking two AEs where the output of an AE's hidden layer is used as input for the consecutive AE. The individual layers of the deep net are trained through greedy layer-wise training [17, 56]. The hyper parameters in an SAE that need to be tuned are the number of hidden neurons s_2 , the L_2 regularization parameter, the sparsity parameter ρ , and the sparsity coefficient β .

A.3 CONVOLUTIONAL DEEP BELIEF NETWORK

Convolutional deep belief networks (CDBNs) are generative probabilistic models composed of one visible layer and multiple hidden layers [98]. Each hidden neuron learns a statistical relationship between the neurons in the lower layer; the higher layer representations usually become more complex [99]. A CDBN is a composite of convolutional restricted Boltzmann machines (CRBMs), which in turn is a composite of restricted Boltzmann machines (RBMs) [159]. Therefore, we first discuss the Boltzmann machine (BM) [3], RBM [159], and CRBM [98].

BMs [3] are undirected graphical models with a set of binary hidden neurons $\mathbf{h}$, a set of binary or real-valued visible neurons $\mathbf{v}$, and symmetric connections between these two represented by a weight matrix W . RBMs are BMs with the restriction that connections exist only between the layer of hidden and visible neurons, but not between two neurons in the same layer (bipartite graph). Without this restriction, training a BM would be computationally infeasible for larger networks. The two sets of neurons are divided in two layers. The neurons in the visible layer correspond to the components of

an observation given at the input (number of samples in one window of data). Neurons in the hidden layer model dependencies between the components of observations and can be viewed as non-linear feature detectors [57].

The RBM [159] attempts to learn a probability distribution that fits the training data as accurately as possible. Following the terminology given in [98], the probability distribution of an RBM defined by its energy function is:

$$P(\mathbf{v}, \mathbf{h}) = \frac{1}{Z} e^{-E(\mathbf{v}, \mathbf{h})} \quad (\text{A.6})$$

, where Z is the partition function. When the visible units (inputs) are real-valued, the energy function is defined as:

$$E(\mathbf{v}, \mathbf{h}) = \frac{1}{2} \sum_i v_i^2 - \sum_{i,j} v_i W_{ij} h_j - \sum_j b_j h_j - \sum_i c_i v_i \quad (\text{A.7})$$

, where b_j is the hidden neurons' biases and c_i is the visible neurons' biases. Because a RBM is an undirected network, computing the gradient required to update the weights is in general computationally infeasible. Therefore, instead of using backpropagation as with the SAE, the weights of an RBM are optimized through sampling based methods such as contrastive divergence [58].

The CRBM [98] is an extension of the RBM to a convolutional setting. Instead of fully connecting the visible layer and the hidden layer, the weights between the hidden neurons and the visible neurons are local and shared among all locations in the hidden layer. The intuition behind the CRBM is that if a certain pattern in data is useful at some point in time, then that same pattern can be useful at other points in time [61]. The hidden layer is constructed by K N_W -dimensional filter weights W^k , also referred to as "bases" [99]. The hidden layer consists of K groups with N_H -dimensional arrays where $N_H \triangleq N_V - N_W + 1$ and each unit in group k shares the weights W^k . Each group shares a bias b_k and visible units share a bias c .

Given these preliminaries, the energy function of the CRBM with real-valued visible neurons is defined as:

$$E(\mathbf{v}, \mathbf{h}) = \frac{1}{2} \sum_{i=1}^{N_V} v_i^2 - \sum_{k=1}^K \sum_{j=1}^{N_H} \sum_{r=1}^{N_W} h_j^k W_r^k v_{j+r-1} - \sum_{k=1}^K b_k \sum_{j=1}^{N_H} h_j^k - c \sum_{i=1}^{N_V} v_i \quad (\text{A.8})$$

, where h_j^k denotes the j -th neuron in group k . Using this model, the conditional probability distribution can be computed. Because all neurons in one layer are conditionally independent given the other layer, inference can be performed using block Gibbs sampling [7, 48]. By keeping either $\mathbf{h}$ or $\mathbf{v}$ fixed, sampling from the other layer can be done as follows:

$$P(v_i | \mathbf{h}) = \mathcal{N}(c_i + \sum_k (W^k *_f h^k)_i + c, 1) \quad (\text{A.9})$$

$$P(h_j^k = 1 | \mathbf{v}) = \sigma((\tilde{W}^k *_v v)_j + b_k) \quad (\text{A.10})$$

, where $\mathcal{N}$ denotes the normal distribution, σ is the sigmoid function, $*_v$ is valid convolution, $*_f$ is full convolution, and $\tilde{W}_j^k \triangleq W_{N_W-j+1}^k$ i.e. flipping the original filter W^k .

Max-pooling [147] down samples an (intermediate) representation by applying a max filter over (usually) non overlapping subregions of the representation. The max filter applies the maximum function over the subregions. In order to get max-pooling like behavior in a generative model, Lee et al. [98] introduced probabilistic max-pooling. Probabilistic max-pooling computes the maxima over small neighborhoods of neurons in the hidden layer in a probabilistic sound way, effectively shrinking feature detection output to a pooling neuron; more details can be found in [98]. A schematic diagram of the CRBM is shown in Figure A.2.

Figure A.2: Schematic diagram of an convolutional restricted Boltzmann machine with probabilistic max-pooling

Each window of activity data is given at the input V (visible layer) with size $1 \times N_v$. A $1 \times N_w$ filter is applied to V resulting in K bases H with size N_h . Finally, a pooling layer P^k is added with size $N_p \triangleq N_h/C$, where C is the max-pooling ratio.

Because a typical CRBM is highly over complete, a sparsity penalty term is added to the log-likelihood objective [97]. The training objective is then denoted as:

$$\langle W, b, c \rangle = \underset{W, b, c}{\operatorname{argmin}} \mathcal{L}_{\text{likelihood}}(W, b, c) + \beta \mathcal{L}_{\text{sparsity}}(W, b, c) \quad (\text{A.11})$$

, where $\mathcal{L}_{\text{likelihood}}$ is the negative log likelihood that measures how well the CRBM fits the input data distribution, β is the sparsity regularization parameter, and $\mathcal{L}_{\text{sparsity}}$ is the sparsity constraint.

When the CRBMs are trained layer-wise [17, 56] with contrastive divergence [58], they are stacked to form a CDBN. The hyperparameters that need to be tuned are the number of bases H , the filter length N_w , the max-pooling ratio (local neighborhood size), and the sparsity regularization parameter β .

ACRONYMS

A

AAR animal activity recognition.

AE autoencoder.

AHD activiteit herkenning voor dieren.

ANN artificial neural network.

APS anti-poaching system.

AR activity recognition.

B

BM Boltzmann machine.

C

CDBN convolutional deep belief network.

CNN convolutional neural network.

CRBM convolutional restricted Boltzmann machine.

D

DL deep learning.

DNN deep neural network.

DT decision tree.

E

ECDF empirical cumulative density function.

G

GBT gradient boosted trees.

GPS Global Positioning System.

H

HAR human activity recognition.

HMM hidden Markov model.

I

IMU inertial measurement unit.

IoT internet of things.

K

k-NN k-nearest neighbors.

KL Kullback-Leibler.

L

LDA linear discriminant analysis.

LPWAN low power wide area network.

LR least regression.

M

ML machine learning.

MTL multitask learning.

N

NB naive Bayes.

NN neural network.

P

PCA principal component analysis.

PPV positive predictive value.

R

RBM restricted Boltzmann machine.

RF random forest.

RTC real-time clock.

S

SAE sparse auto encoder.

SFS sequential forward selection.

SVM support vector machine.

U

URL unsupervised representation learning.

V

VE voting ensemble.

BIBLIOGRAPHY

- [1] Z. S. Abdallah, M. M. Gaber, B. Srinivasan, and S. Krishnaswamy. Adaptive mobile activity recognition system with evolving data streams. Neurocomputing, 150(Part A):304–317, 2015. doi:10.1016/j.neucom.2014.09.074.
- [2] K. Abdul Jabbar, M. F. Hansen, M. L. Smith, and L. N. Smith. Early and non-intrusive lameness detection in dairy cows using 3-dimensional video. Biosystems Engineering, 153:63–69, 1 2017. doi:10.1016/J.BIOSYSTEMSENG.2016.09.017.
- [3] D. H. Ackley, G. E. Hinton, and T. J. Sejnowski. A learning algorithm for Boltzmann Machines. Special Issue: Connectionist models and their applications. Cognitive Science, 9(1):147–169, 1985.
- [4] S. Aksoy and R. M. Haralick. Feature normalization and likelihood-based similarity measures for image retrieval. Pattern Recognition Letters, 22(5):563–582, 2001. doi:10.1016/S0167-8655(00)00112-4.
- [5] N. S. Altman. An introduction to kernel and nearest-neighbor non-parametric regression. American Statistician, 46(3):175–185, 1992. doi:10.1080/00031305.1992.10475879.
- [6] S.-i. AMARI. Deep Convolutional Neural Networks for Human Activity Recognition with Smartphone Sensors. Journal of the Society of Mechanical Engineers, 90(823):758–759, 2017. doi:10.1299/jsmemag.90.823_758.
- [7] C. ANDRIEU, N. D. FREITAS, A. DOUCET, and M. I. JORDAN. An Introduction to MCMC for Machine Learning CHRISTOPHE. Journal of Machine Learning Research, 2003-Sept:4144–4151, 2003. doi:10.1109/IROS.2017.8206274.
- [8] L. Andrusiak, E. L. Walters, E. Terry, and K. Simpson. Wildlife Radio-telemetry Standards for Components of British Columbia's Biodiversity No. 5. Number 5. Resources Inventory Committee, 1998.
- [9] L. Atallah, B. Lo, R. King, and G. Z. Yang. Sensor positioning for activity recognition using wearable accelerometers. IEEE Transactions on Biomedical Circuits and Systems, 5(4):320–329, 2011. doi:10.1109/TBCAS.2011.2160540.
- [10] M. A. Ayu, S. A. Ismail, T. Mantoro, and A. F. A. Matin. Real-time activity recognition in mobile phones based on its accelerometer data. In 2016 International Conference on Informatics and Computing, ICIC 2016, number Icic, pages 292–297, Lombok, 2017. IEEE. doi:10.1109/IAC.2016.7905732.

- [11] J. Baek, G. Lee, W. Park, and B.-j. Yun. Accelerometer Signal Processing for User Activity Detection. In M. G. Negoita, R. J. Howlett, and L. C. Jain, editors, Knowledge-Based Intelligent Information and Engineering Systems, pages 610–617. Springer Berlin Heidelberg, Berlin, Heidelberg, 2004. doi:10.1007/978-3-540-30134-9_82.
- [12] M. Banko and E. Brill. Mitigating the Paucity-of-Data Problem: Exploring the Effect of Training Corpus Size on Classifier Performance for Natural Language Processing. In HLT '01 Proceedings of the first international conference on Human language technology research, pages 1–5, San Diego, 2001. Association for Computational Linguistics. doi:http://dx.doi.org/10.3115/1072133.1072204.
- [13] L. Bao and S. S. Intille. Activity Recognition from User-Annotated Acceleration Data. In Pervasive Computing, pages 1 – 17, Berlin, Heidelberg, 2004. Springer Berlin Heidelberg. doi:10.1007/b96922.
- [14] Y. M. Bar-On, R. Phillips, and R. Milo. The biomass distribution on Earth. Proceedings of the National Academy of Sciences, 115(25):6506–6511, 6 2018. doi:10.1073/PNAS.1711842115.
- [15] S. Belongie, K. Branson, P. Dollár, and V. Rabaud. Monitoring Animal Behavior in the Smart Vivarium. International Journal, pages 1–3, 1996.
- [16] Y. Bengio, A. Courville, and P. Vincent. Representation Learning: A Review and New Perspectives. CoRR, 1206.5538(1993):1–30, 2012. doi:10.1145/1756006.1756025.
- [17] Y. Bengio, P. Lamblin, D. Popovici, and H. Larochelle. Greedy Layer-Wise Training of Deep Networks. In Advances in Neural Information Processing Systems 19, pages 153–160, Canada, 2007. The MIT Press. doi:10.7551/mitpress/7503.003.0024.
- [18] J. Bergstra and Y. Bengio. Random search for hyper-parameter optimization. Journal of Machine Learning Research, 13:281–305, 2012.
- [19] P. Bermejo, J. A. Gámez, and J. M. Puerta. Speeding up incremental wrapper feature subset selection with Naive Bayes classifier. Knowledge-Based Systems, 55:140–147, 2014. doi:10.1016/j.knosys.2013.10.016.
- [20] O. R. Bidder, H. A. Campbell, A. Gómez-Laich, P. Urgé, J. Walker, Y. Cai, L. Gao, F. Quintana, and R. P. Wilson. Love thy neighbour: Automatic animal behavioural classification of acceleration data using the k-nearest neighbour algorithm. PLoS ONE, 9(2), 2014. doi:10.1371/journal.pone.0088609.
- [21] G. Bishop-Hurley, D. Henry, D. Smith, R. Dutta, J. Hills, R. Rawnsley, A. Hellicar, G. Timms, A. Morshed, A. Rahman, C. D’Este, and Y. Shu. An investigation of cow feeding behavior using motion sensors. In 2014 IEEE International Instrumentation and Measurement Technology Conference (I2MTC) Proceedings, pages 1285–1290, Montevideo, 2014. IEEE. doi:10.1109/I2MTC.2014.6860952.

- [22] S. Bosch, F. Serra Bragança, M. Marin-Perianu, R. Marin-Perianu, B. J. van der Zwaag, J. Voskamp, W. Back, R. Van Weeren, and P. Havinga. Equimoves: A wireless networked inertial measurement system for objective examination of horse gait. Sensors (Switzerland), 18(3):1–35, 2018. doi:10.3390/s18030850.
- [23] L. R. Brewster, J. J. Dale, T. L. Guttridge, S. H. Gruber, A. C. Hansell, M. Elliott, I. G. Cowx, N. M. Whitney, and A. C. Gleiss. Development and application of a machine learning algorithm for classification of elasmobranch behaviour from accelerometry data. Marine Biology, 165(4):1–19, 2018. doi:10.1007/s00227-018-3318-y.
- [24] C. Brooks, C. Bonyongo, and S. Harris. Effects of global positioning system collar weight on zebra behavior and location error. The Journal of Wildlife Management, 72(2):527–534, 2008. doi:10.2193/2007-061.
- [25] E. Browning, M. Bolton, E. Owen, A. Shoji, T. Guilford, and R. Freeman. Predicting animal behaviour using deep learning: GPS data alone accurately predict diving in seabirds. Methods in Ecology and Evolution, 9(3):681–692, 2018. doi:10.1111/2041-210X.12926.
- [26] A. Bulling, U. Blanke, and B. Schiele. A tutorial on human activity recognition using body-worn inertial sensors. ACM Computing Surveys, 46(3), 2014. doi:10.1145/2499621.
- [27] A. Candel, V. Parmar, E. LeDell, and A. Arora. Deep learning with h2o. H2O. ai Inc., 2016.
- [28] R. Caruana. Multitask Learning. Learning to Learn, 75:95–133, 1997. doi:10.1007/978-1-4615-5529-2_5.
- [29] C.-C. Chang and C.-J. Lin. LIBSVM: A library for support vector machines. ACM Transactions on Intelligent Systems and Technology, 2:27:1–27:27, 2011. Software available at <http://www.csie.ntu.edu.tw/~cjlin/libsvm>.
- [30] M. J. Chase, S. Schlossberg, C. R. Griffin, P. J. Bouché, S. W. Djene, P. W. Elkan, S. Ferreira, F. Grossman, E. M. Kohi, K. Landen, P. Omondi, A. Peltier, S. J. Selier, and R. Sutcliffe. Continent-wide survey reveals massive decline in african savannah elephants. PeerJ, 4:e2354, 8 2016. doi:10.7717/peerj.2354.
- [31] Y. Chen and Y. Xue. A Deep Learning Approach to Human Activity Recognition Based on Single Accelerometer. In Proceedings - 2015 IEEE International Conference on Systems, Man, and Cybernetics, SMC 2015, pages 1488–1492. IEEE, 2016. doi:10.1109/SMC.2015.263.
- [32] T. Choudhury, J. Hightower, A. Lamarca, L. Legrand, A. Rahimi, A. Rea, B. Hemingway, K. Koscher, J. a. Landay, J. Lester, and D. Wyatt. An embedded Activity Recognition system. IEEE Pervasive Computing, 7(2):32–41, 2008. doi:10.1109/MPRV.2008.39.

- [33] D. Cook, K. D. Feuz, and N. C. Krishnan. Transfer learning for activity recognition: A survey. Knowledge and Information Systems, 36(3):537–556, 2013. doi:10.1007/s10115-013-0665-3.
- [34] S. J. Cooke, S. G. Hinch, M. Wikelski, R. D. Andrews, L. J. Kuchel, T. G. Wolcott, and P. J. Butler. Biotelemetry: A mechanistic approach to ecology. Trends in Ecology and Evolution, 19(6):334–343, 2004. doi:10.1016/j.tree.2004.04.003.
- [35] W. E. Cooper. Escaping From Predators: An Integrative View of Escape Decisions. 2015. URL <https://books.google.com/books?hl=en&lr=&id=27ksCQAAQBAJ&pgis=1>.
- [36] A. Czabke, S. Marsch, and T. C. Lueth. Accelerometer based real-time activity analysis on a microcontroller. Pervasive Computing Technologies for Healthcare (PervasiveHealth), 2011 5th International Conference on, pages 40–46, 2011. doi:10.4108/icst.pervasivehealth.2011.245984.
- [37] S. Diaz, J. Settele, E. Brondizio, H. T. Ngo, M. Gueze, J. Agard, A. Arneth, P. Balvanera, K. Brauman, S. Butchart, K. Chan, L. Garibaldi, K. Ichii, J. Liu, S. M. Subramanian, G. Midgley, P. Miloslavich, Z. Molnar, D. Obura, A. Pfaff, S. Polasky, A. Purvis, J. Razzaque, B. Reyers, R. R. Chowdhury, Y.-J. Shin, I. Visseren-Hamakers, K. Willis, and C. Zayas. Summary for policymakers of the global assessment report on biodiversity and ecosystem services. Technical Report May 2019, 2019. URL <https://www.ipbes.net/news/ipbes/ipbes-global-assessment-summary-policymakers-pdf>.
- [38] R. Dutta, D. Smith, R. Rawnsley, G. Bishop-Hurley, J. Hills, G. Timms, and D. Henry. Dynamic cattle behavioural classification using supervised ensemble classifiers. Computers and Electronics in Agriculture, 111:18–28, 2015. doi:10.1016/j.compag.2014.12.002.
- [39] ej-technologies GmbH. Jprofiler. <http://www.ej-technologies.com>, 2001-2017.
- [40] R. H. Emslie. African Rhinoceroses – Latest trends in rhino numbers and poaching. African indaba, e-newsletter, 51:11–12, 2013. URL http://www.rhinoresourcecenter.com/index.php?s=1&act=refs&CODE=ref_detail&id=1368137474.
- [41] S. et al. United states patent. https://static1.squarespace.com/static/5a4d45deaeb62542e82f642e/t/5a8c72e6f9619aaa00307d94/1519153920962/Patent_20180220.pdf. Accessed: 2018-04-25.
- [42] G. Fehlmann, M. J. O’Riain, P. W. Hopkins, J. O’Sullivan, M. D. Holton, E. L. Shepard, and A. J. King. Identification of behaviours from accelerometer data in a wild social primate. Animal Biotelemetry, 5(1):1–11, 2017. doi:10.1186/s40317-017-0121-3.

- [43] D. Figo, P. C. Diniz, D. R. Ferreira, and J. M. P. Cardoso. Preprocessing techniques for context recognition from accelerometer data. Personal and Ubiquitous Computing, 14(7):645–662, 2010. doi:10.1007/s00779-010-0293-9.
- [44] J. Firmat Banzi. A Sensor Based Anti-Poaching System in Tanzania National Parks. International Journal of Scientific and Research Publications, 4(4):1–7, 2014.
- [45] B. Florentino-Liaño, N. O’Mahony, and A. Artés-Rodríguez. Human Activity Recognition Using Inertial Sensors with Invariance to Sensor Orientation. 2012 3rd International Workshop on Cognitive Information Processing (CIP), pages 1–6, 2012. doi:10.1109/CIP.2012.6232914.
- [46] H. Friday, Y. Wah, M. A. Al-garadi, U. Rita, H. F. Nweke, Y. W. Teh, M. A. Al-garadi, U. R. Alo, H. Friday, Y. Wah, M. A. Al-garadi, and U. Rita. Deep learning algorithms for human activity recognition using mobile and wearable sensor networks: State of the art and research challenges. Expert Systems with Applications, 105:233–261, 2018. doi:10.1016/j.eswa.2018.03.056.
- [47] V. P. Gandhi and Z.-y. Zhou. Rising Demand for Livestock Products in India. Australasian Agribusiness Review, 18:103–135, 2010.
- [48] S. Geman and D. Geman. Stochastic Relaxation, Gibbs Distributions, and the Bayesian Restoration of Images. IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, 6(6), 1984. doi:10.1016/b978-0-08-051581-6.50056-8.
- [49] R. Goldman. Understanding quaternions. Graphical Models, 73(2):21–49, 3 2011. doi:10.1016/J.GMOD.2010.10.004.
- [50] L. A. González, G. J. Bishop-hurley, R. N. Handcock, and C. Crossman. Behavioral classification of data from collars containing motion sensors in grazing cattle. Computers and Electronics in Agriculture, 110:91–102, 2015. doi:10.1016/j.compag.2014.10.018.
- [51] S. Grunewalder, F. Broekhuis, D. W. Macdonald, A. M. Wilson, J. W. McNutt, J. Shawe-Taylor, and S. Hailes. Movement Activity Based Classification of Animal Behaviour with an Application to Data from Cheetah (*Acinonyx jubatus*). PLoS ONE, 7(11):1–11, 2012. doi:10.1371/journal.pone.0049120.
- [52] L. Gulf Coast Data Concepts. Human Activity Monitor: HAM. online, 2019. URL <http://www.gcdataconcepts.com/ham.html>.
- [53] D. Gutierrez-Galan, J. P. Dominguez-Morales, E. Cerezuela-Escudero, A. Rios-Navarro, R. Tapiador-Morales, M. Rivas-Perez, M. Dominguez-Morales, A. Jimenez-Fernandez, and A. Linares-Barranco. Embedded neural network for real-time animal behavior classification. Neurocomputing, 272:17–26, 2018. doi:10.1016/j.neucom.2017.03.090.

- [54] I. Guyon and A. Elisseeff. An Introduction to Variable and Feature Selection. Journal of Machine Learning Research (JMLR), 3(3):1157–1182, 2003. doi:10.1016/j.aca.2011.07.027.
- [55] H. He and E. A. Garcia. Learning from imbalanced data. IEEE Transactions on Knowledge and Data Engineering, 21(9):1263–1284, 2009. doi:10.1109/TKDE.2008.239.
- [56] G. Hinton, S. Osindero, and Y.-W. Teh. Communicated by Yann Le Cun A Fast Learning Algorithm for Deep Belief Nets 500 units 500 units. Neural Computation, 18:1527–1554, 2006. doi:10.1162/neco.2006.18.7.1527.
- [57] G. E. Hinton. Boltzmann machine. Scholarpedia, 2(5):1668, 2007. doi:10.4249/scholarpedia.1668. revision #91076.
- [58] G. E. Hinton, S. Osindero, and Y. W. Teh. A Fast Learning Algorithm for Deep Belief Nets. Neural computation, 18(7):1527–54, 2006. doi:10.1162/neco.2006.18.7.1527.
- [59] I. Hinton. A Practical Guide to Training Restricted Boltzmann Machines. Lecture Notes in Computer Science. Neural Networks Tricks of the Trade (2nd ed.) 2012599–619, (Chapter 32):599–619, 2012. doi:10.1007/978-3-642-35289-8_32.
- [60] J. H. Hong, J. Ramos, and A. K. Dey. Toward Personalized Activity Recognition Systems with a Semipopulation Approach. IEEE Transactions on Human-Machine Systems, 46(1):101–112, 2016. doi:10.1109/THMS.2015.2489688.
- [61] G. B. Huang, H. Lee, and E. Learned-Miller. Learning hierarchical representations for face verification with convolutional deep belief networks. Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition, pages 2518–2525, 2012. doi:10.1109/CVPR.2012.6247968.
- [62] T. Huynh and B. Schiele. Analyzing features for activity recognition. In Proceedings of the 2005 joint conference on Smart objects and ambient intelligence innovative context-aware services: usages and technologies - sOc-EUSAI '05, pages 159–163, New York, New York, USA, 2005. ACM Press. doi:10.1145/1107548.1107591.
- [63] I. Inza, P. Larrañaga, R. Etxeberria, and B. Sierra. Feature subset selection by Bayesian networks based optimization. Artificial Intelligence, 123:157–184, 1999. doi:10.1016/S0004-3702(00)00052-7.
- [64] A. J. Izenman. Modern Multivariate Statistical Techniques. Springer Texts in Statistics. Springer New York, New York, NY, 2008. doi:10.1007/978-0-387-78189-1.
- [65] J. M. Johnson and T. M. Khoshgoftaar. Survey on deep learning with class imbalance. Journal of Big Data, 6(1):27, 2019. doi:10.1186/s40537-019-0192-5.
- [66] M. Jones and Z. Anderson. Accelerometer data and video collected while hiking and climbing at ubimount 2016. In Proceedings of the 2017 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2017 ACM International Symposium on Wearable Computers, UbiComp '17, pages 1043–1046, New York, NY, USA, 2017. ACM. doi:10.1145/3123024.3124445.

- [67] M. Jones, C. Walker, Z. Anderson, and L. Thatcher. Automatic detection of alpine ski turns in sensor data. In Proceedings of the 2016 ACM International Joint Conference on Pervasive and Ubiquitous Computing: Adjunct, UbiComp '16, pages 856–860, New York, NY, USA, 2016. ACM. doi:10.1145/2968219.2968535.
- [68] P. Juang, H. Oki, Y. Wang, M. Martonosi, L. S. Peh, and D. Rubenstein. Energy-efficient computing for wildlife tracking. ACM SIGOPS Operating Systems Review, 36(5):96, 2002. doi:10.1145/635508.605408.
- [69] A. Jukan, X. Masip-Bruin, and N. Amla. Smart computing and sensing technologies for animal welfare: A systematic review. ACM Computing Surveys, 50(1), 2017. doi:10.1145/3041960.
- [70] J. Kamminga. Dataset: Generic Online Animal Activity Recognition on Collar Tags., Sep 2017. doi:10.17026/dans-zp6-fmna.
- [71] J. Kamminga. Dataset: Multi Sensor-Orientation Movement Data of Goats, March 2018. doi:10.17026/dans-xhn-bsfb.
- [72] J. Kamminga. jacob-kamminga/Matlab-movement-data-labeling-tool: Generic version release., 8 2019. doi:10.5281/zenodo.3364004.
- [73] J. Kamminga, E. Ayele, N. Meratnia, and P. Havinga. Poaching detection technologies-A survey. Sensors (Switzerland), 18(5):1474, 2018. doi:10.3390/s18051474.
- [74] J. Kamminga, D. Le, and P. Havinga. Ambient sound-based collaborative localization of indeterministic devices. Sensors (Switzerland), 16(9), 2016. doi:10.3390/s16091478.
- [75] J. W. Kamminga. Dataset: Horsing Around – A Dataset Comprising Horse Movement. 4TU.Centre for Research Data., 7 2019. doi:10.4121/uuid:2e08745c-4178-4183-8551-f248c992cb14.
- [76] J. W. Kamminga, H. C. Bisby, D. V. Le, N. Meratnia, and P. J. M. Havinga. Generic Online Animal Activity Recognition on Collar Tags. In Proceedings of the 2017 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2017 ACM International Symposium on Wearable Computers - UbiComp '17, pages 597–606, New York, NY, 2017. ACM Press. doi:10.1145/3123024.3124407.
- [77] J. W. Kamminga, L. M. Janßen, N. Meratnia, and P. J. M. Havinga. Horsing Around—A Dataset Comprising Horse Movement. Data, 4(4):131, 9 2019. doi:10.3390/data4040131.
- [78] J. W. Kamminga, M. Jones, K. Seppi, N. Meratnia, and P. J. Havinga. Synchronization between sensors and cameras in movement data labeling frameworks. In the second Workshop on Data Acquisition To Analysis (DATA'19), November 10, 2019, New York, NY, USA, New York, NY, 2019. Association for Computing Machinery. doi:10.1145/3359427.3361920.

- [79] J. W. Kamminga, D. V. Le, J. P. Meijers, H. Bisby, N. Meratnia, and P. J. Havinga. Robust Sensor-Orientation-Independent Feature Selection for Animal Activity Recognition on Collar Tags. Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies IMWUT, 2(1):1–27, 2018. doi:10.1145/3191747.
- [80] J. W. Kamminga, D. V. Le, N. Meratnia, and P. J. Havinga. A Tutorial on Online Animal Activity Recognition using Motion Sensors. page in preparation, 2020.
- [81] J. W. Kamminga, D. V. Le, N. Meratnia, and P. J. Havinga. Deep Unsupervised Representation Learning for Online Animal Activity Recognition. page in preparation, 2020.
- [82] J. W. Kamminga, D. V. Le, N. Meratnia, and P. J. Havinga. Towards Deep Unsupervised Representation Learning from Accelerometer Time Series for Animal Activity Recognition. In 6th workshop on mining and learning from time series, San Diego, CA, 2020. MiLeTS. URL https://kdd-milets.github.io/milets2020/papers/MiLeTS2020_paper_1.pdf.
- [83] J. W. Kamminga, N. Meratnia, and P. J. Havinga. Dataset: Horse Movement Data and Analysis of its Potential for Activity Recognition. In the second Workshop on Data Acquisition To Analysis (DATA'19), November 10, 2019, New York, NY, USA, New York, NY, 2019. Association for Computing Machinery. doi:10.1145/3359427.3361908.
- [84] D. M. Karantonis, M. R. Narayanan, M. Mathie, N. H. Lovell, and B. G. Celler. Implementation of a real-time human movement classifier using a triaxial accelerometer for ambulatory monitoring. IEEE Transactions on Information Technology in Biomedicine, 10(1):156–167, 2006. doi:10.1109/TITB.2005.856864.
- [85] K. Kira and L. Rendell. The feature selection problem: Traditional methods and a new algorithm. Aaai, pages 129 – 134, 1992. doi:10.1016/S0031-3203(01)00046-2.
- [86] S. B. Kotsiantis. Supervised Machine Learning : A Review of Classification Techniques. Informatica, An International Journal of Computing and Informatics, 3176(31):249–268, 2007.
- [87] C. Ladha, N. Hammerla, E. Hughes, P. Olivier, and T. Ploetz. Dog's life: Wearable Activity Recognition for Dogs. In Proceedings of the 2013 ACM international joint conference on Pervasive and ubiquitous computing - UbiComp '13, pages 415–418, Zurich, 2013. ACM. doi:10.1145/2493432.2493519.
- [88] W. R. Langbauer, K. B. Payne, R. a. Charif, L. Rapaport, and F. Osborn. African Elephants Respond To Distant Playbacks of Low-Frequency Conspecific Calls. Journal of Experimental Biology, 157:35–46, 1991. URL <GotoISI>://WOS: A1991FM39300003.
- [89] D. Le, J. Kamminga, H. Scholten, and P. Havinga. Error bounds for localization with noise diversity. In Proceedings - 12th Annual International

- Conference on Distributed Computing in Sensor Systems, DCOSS 2016, 2016. doi:10.1109/DCOSS.2016.18.
- [90] D. Le, J. Kamminga, H. Scholten, and P. Havinga. Nondeterministic sound source localization with smartphones in crowdsensing. In 2016 IEEE International Conference on Pervasive Computing and Communication Workshops, PerCom Workshops 2016, 2016. doi:10.1109/PERCOMW.2016.7457115.
- [91] D. V. Le, J. Kamminga, H. Scholten, and P. J. Havinga. A Framework to Measure Reliance of Acoustic Latency on Smartphone Status. 2018 IEEE International Conference on Pervasive Computing and Communications Workshops, PerCom Workshops 2018, pages 348–354, 2018. doi:10.1109/PERCOMW.2018.8480354.
- [92] S. P. le Roux, J. Marias, R. Wolhuter, and T. Niesler. Animal-borne behaviour classification for sheep (Dohne Merino) and Rhinoceros (*Ceratotherium simum* and *Diceros bicornis*). Animal Biotelemetry, 5(1):25, 2017. doi:10.1186/s40317-017-0140-0.
- [93] Y. Lecun, Y. Bengio, and G. Hinton. Deep learning. Nature, 521(7553):436–444, 2015. doi:10.1038/nature14539.
- [94] Y. Lecun, S. Chopra, R. Hadsell, M. A. Ranzato, and F. J. Huang. A Tutorial on Energy-Based Learning 1 Introduction : Energy-Based Models. New York, 1:0, 2006.
- [95] Y. Lecun, K. Kavukcuoglu, and C. Farabet. Convolutional networks and applications in vision. ISCAS 2010 - 2010 IEEE International Symposium on Circuits and Systems: Nano-Bio Circuit Fabrics and Systems, pages 253–256, 2010. doi:10.1109/ISCAS.2010.5537907.
- [96] Y. A. LeCun, L. Bottou, G. B. Orr, and K. R. Müller. Efficient BackProp. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), 7700 LECTU:9–48, 2012. doi:10.1007/978-3-642-35289-8-3.
- [97] H. Lee, C. Ekanadham, and A. Y. Ng. Sparse deep belief net model for visual area V2. Adv. Neural Inf. Process. Syst. 20 (NIPS 2007), pages 873–880, 2008. doi:10.1.1.120.9887.
- [98] H. Lee, R. Grosse, R. Ranganath, and A. Y. Ng. Convolutional deep belief networks for scalable unsupervised learning of hierarchical representations. In Proceedings of the 26th Annual International Conference on Machine Learning - ICML '09, pages 1–8, Montreal, 2009. ACM. doi:10.1145/1553374.1553453.
- [99] H. Lee, Y. Largman, P. Pham, and A. Ng. Unsupervised feature learning for audio classification using convolutional deep belief networks. In Proceedings of the 22nd International Conference on Neural Information Processing Systems, pages 1096–1104, Vancouver, British Columbia, Canada, 2009. ACM.

- [100] J. Lester, T. Choudhury, and G. Borriello. A Practical Approach to Recognizing Physical Activities. Pervasive Computing, 3968:1–16, 2006. doi:10.1007/11748625_1.
- [101] F. Li, K. Shirahama, M. A. Nisar, L. Koping, and M. Grzegorzec. Comparison of feature learning methods for human activity recognition using wearable sensors. Sensors (Switzerland), 18(2):1–22, 2018. doi:10.3390/s18020679.
- [102] Y. Li, D. Shi, B. Ding, and D. Liu. Unsupervised Feature Learning for Human Activity Recognition Using Smartphone Sensors. Expert Systems with Applications, 41(14):6067–6074, 2014. doi:10.1016/j.eswa.2014.04.037.
- [103] Y. Liang, X. Zhou, Z. Yu, B. Guo, and Y. Yang. Energy efficient activity recognition based on low resolution accelerometer in smart phones. Advances in Grid and Pervasive {...}, pages 122–136, 2012.
- [104] Q. Liu, J. Williamson, K. Li, W. Mohrman, Q. Lv, R. P. Dick, and L. Shang. Gazelle: Energy-Efficient Wearable Analysis for Running. IEEE Transactions on Mobile Computing, 16(9):2531–2544, 2017. doi:10.1109/TMC.2016.2623304.
- [105] K. Lokhorst. Smart Dairy Farming. Hogeschool van Hall Larenstein, Leeuwarden, 2018.
- [106] K. A. T. Loyd, S. M. Hernandez, J. P. Carroll, K. J. Abernathy, and G. J. Marshall. Quantifying free-roaming domestic cat predation using animal-borne video cameras. Biological Conservation, 160:183–189, 4 2013. doi:10.1016/J.BIOCON.2013.01.008.
- [107] M. Ltd. Moocall. online, 2019. URL <https://moocall.com>.
- [108] J. Marais, S. Petrus, L. Roux, R. Wolhuter, and T. Niesler. Automatic classification of sheep behaviour using 3-axis accelerometer data. Pattern Recognition Association of South Africa, pages 1–6, 2014.
- [109] P. Martiskainen, M. Järvinen, J.-P. Skön, J. Tiirikainen, M. Kolehmainen, and J. Mononen. Cow behaviour pattern recognition using a three-dimensional accelerometer and support vector machines. Applied Animal Behaviour Science, 119(1-2):32–38, 2009. doi:10.1016/j.applanim.2009.03.005.
- [110] V. Masson-Delmotte, P. Zhai, H.-O. Pörtner, D. Roberts, J. Skea, P. R. Shukla, A. Pirani, W. Moufouma-Okia, C. Péan, R. Pidcock, S. Connors, J. B. R. Matthews, Y. Chen, X. Zhou, M. I. Gomis, E. Lonnoy, T. Maycock, M. Tignor, and T. Waterfield. Global warming of 1.5°C An IPCC Special Report, volume 265. 2018. URL https://report.ipcc.ch/sr15/pdf/sr15_spm_final.pdf.
- [111] M. J. Mathie, A. C. Coster, N. H. Lovell, and B. G. Celler. Accelerometry : providing an integrated , practical method for long-term , ambulatory monitoring of human movement. Physiological measurement, 25(2):R1, 2004. doi:10.1088/0967-3334/25/2/R01.

- [112] MATLAB. version 9.5.0.944444 (R2018b). The MathWorks Inc., Natick, Massachusetts, 2018.
- [113] MATLAB. 9.6.0.1072779 (R2019a). The MathWorks Inc., Natick, Massachusetts, 2019.
- [114] A. Matthews, L. Ruykys, B. Ellis, S. Fitzgibbon, D. Lunney, M. S. Crowther, A. S. Glen, B. Purcell, K. Moseby, J. Stott, D. Fletcher, C. Wimpenny, B. L. Allen, L. Van Bommel, M. Roberts, N. Davies, K. Green, T. Newsome, G. Ballard, P. Fleming, C. R. Dickman, A. Eberhart, S. Troy, C. McMahon, and N. Wiggins. The success of GPS collar deployments on mammals in Australia. Australian Mammalogy, 35(1):65–83, 2013. doi:10.1071/AM12021.
- [115] J. Mattisson, H. Sand, P. Wabakken, V. Gervasi, O. Liberg, J. D. C. Linnell, G. R. Rauset, and H. C. Pedersen. Home range size variation in a recovering wolf population: evaluating the effect of environmental, demographic, and social factors. Oecologia, 173(3):813–825, Nov 2013. doi:10.1007/s00442-013-2668-x.
- [116] U. Maurer, A. Rowe, A. Smailagic, and D. Siewiorek. Location and Activity Recognition Using eWatch: A Wearable Sensor Platform. Ambient Intelligence in Everyday Life, 3864:86–102, 2006. doi:10.1007/11825890_4.
- [117] J. Mench. Why it is important to understand animal behavior. ILAR Journal, 39(1):20–26, 1998. doi:10.1093/ilar.39.1.20.
- [118] I. Mierswa, M. Wurst, R. Klinkenberg, M. Scholz, and T. Euler. YALE: Rapid prototyping for complex data mining tasks. Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, 2006:935–940, 2006. doi:10.1145/1150402.1150531.
- [119] R. Nathan. An emerging movement ecology paradigm. Proceedings of the National Academy of Sciences of the United States of America, 105(49):19050–19051, 2008. doi:10.1073/pnas.0808918105.
- [120] R. Nathan, W. M. Getz, E. Revilla, M. Holyoak, R. Kadmon, D. Saltz, and P. E. Smouse. A movement ecology paradigm for unifying organismal movement research. Proceedings of the National Academy of Sciences, 105(49):19052–19059, 12 2008. doi:10.1073/PNAS.0800375105.
- [121] R. Nathan, O. Spiegel, S. Fortmann-Roe, R. Harel, M. Wikelski, and W. M. Getz. Using tri-axial acceleration data to identify behavioral modes of free-ranging animals: general concepts and tools illustrated for griffon vultures. The Journal of experimental biology, 215(Pt 6):986–96, 2012. doi:10.1242/jeb.058602.
- [122] A. Ng. Lecture Notes Sparse Autoencoder. Cs294a, pages 1–19, 2011. doi:10.1371/journal.pone.0006098.
- [123] A. Ng. CS229 Lecture notes - Deep learning. online, 2019. URL http://cs229.stanford.edu/notes-spring2019/cs229-notes-deep_learning.pdf.

- [124] T. T. Ngo, Y. Makihara, H. Nagahara, Y. Mukaigawa, and Y. Yagi. Similar gait action recognition using an inertial sensor. Pattern Recognition, 48(4):1285–1297, 2015. doi:10.1016/j.patcog.2014.10.012.
- [125] F. J. Ordóñez and D. Roggen. Deep convolutional and LSTM recurrent neural networks for multimodal wearable activity recognition. Sensors (Switzerland), 16(1), 2016. doi:10.3390/s16010115.
- [126] M. S. Painter, J. A. Blanco, E. P. Malkemper, C. Anderson, D. C. Sweeney, C. W. Hewgley, J. Červený, V. Hart, V. Topinka, E. Belotti, H. Burda, and J. B. Phillips. Use of bio-loggers to characterize red fox behavior with implications for studies of magnetic alignment responses in free-roaming animals. Animal Biotelemetry, 4(1), 2016. doi:10.1186/s40317-016-0113-8.
- [127] S. J. J. Pan and Q. Yang. A Survey on Transfer Learning. IEEE Transactions on Knowledge and Data Engineering, 1(10):1–15, 2010. doi:10.1109/TKDE.2009.191.
- [128] J. Pärkkä, M. Ermes, P. Korpipää, J. Mäntylä, J. Peltola, and I. Korhonen. Activity classification using realistic data from wearable sensors. IEEE transactions on information technology in biomedicine : a publication of the IEEE Engineering in Medicine and Biology Society, 10(1):119–128, 2006. doi:10.1109/TITB.2005.856863.
- [129] J. K. Petersen. Understanding Technologies Surveillance Spy Devices, Their Origins and Applications. CRC Press, New York, New York, USA, 2001.
- [130] R. Plackett. Karl Pearson and the Chi-squared Test. Quantifying Archaeology, 51:59–72, 1983. doi:10.1016/b978-0-12-639860-1.50009-2.
- [131] T. Plötz, N. Y. Hammerla, and P. Olivier. Feature learning for activity recognition in ubiquitous computing. In IJCAI International Joint Conference on Artificial Intelligence, pages 1729–1734, Barcelona, 2011. ACM. doi:10.5591/978-1-57735-516-8/IJCAI11-290.
- [132] D. M. W. Powers. Evaluation: From Precision, Recall and F-Factor to ROC, Informedness, Markedness & Correlation. Journal of Machine Learning Technologies, Volume 2,(December):37–63, 2011. doi:10.1.1.214.9232.
- [133] S. Preece, J. Goulermas, L. Kenney, and D. Howard. A Comparison of Feature Extraction Methods for the Classification of Dynamic Activities From Accelerometer Data. IEEE Transactions on Biomedical Engineering, 56(3):871–879, 2009. doi:10.1109/TBME.2008.2006190.
- [134] D. Rav, C. Wong, B. Lo, and G.-z. Yang. A Deep Learning Approach to on-Node Sensor Data Analytics for Mobile or Wearable Devices. IEEE Journal of biomedical and health informatics, 21(1):56–64, 2017. doi:10.1109/JBHI.2016.2633287.
- [135] N. Ravi, N. Dandekar, P. Mysore, and M. M. L. Littman. Activity Recognition from Accelerometer Data. Proceedings of the national ..., pages 1541–1546, 2005. doi:10.1007/978-3-642-02481-8_120.

- [136] M. R. Recio, R. Mathieu, P. Denys, P. Sirguey, and P. J. Seddon. Lightweight GPS-Tags, One Giant Leap for Wildlife Tracking? An Assessment Approach. PLoS ONE, 6(12):e28225, 2011. doi:10.1371/journal.pone.0028225.
- [137] S. Reddy, M. Mun, J. Burke, D. Estrin, M. Hansen, and M. Srivastava. Using mobile phones to determine transportation modes. ACM Transactions on Sensor Networks, 6(2):1–27, 2010. doi:10.1145/1689239.1689243.
- [138] A. Rhino, S. Groups, T. Milliken, R. H. Emslie, and B. Talukdar. African and Asian Rhinoceroses – Status, Conservation and Trade. Africa, 230(December 2007):1–18, 2009.
- [139] S. T. Rhino. Poaching: The statistics, October 2015. https://www.savetherhino.org/rhino_info/poaching_statistics Accessed: 14-06-2017.
- [140] I. Rish et al. An empirical study of the naive Bayes classifier. In IJCAI 2001 workshop on empirical methods in artificial intelligence, volume 3, pages 41–46, 2001.
- [141] J. B. Roelofs, F. J. van Eerdenburg, N. M. Soede, and B. Kemp. Pedometer readings for estrous detection and as predictor for time of ovulation in dairy cattle. Theriogenology, 64(8):1690–1703, 11 2005. doi:10.1016/J.THERIOGENOLOGY.2005.04.004.
- [142] S. Romano. A general measure of data-set imbalance. Cross Validated, 10 2016. URL <https://stats.stackexchange.com/q/239982>.
- [143] C. A. Ronao and S.-b. B. Cho. Human activity recognition with smartphone sensors using deep learning neural networks. Expert Systems with Applications, 59:235–244, 2016. doi:10.1016/j.eswa.2016.04.032.
- [144] D. E. Rumelhart, R. Durbin, R. Golden, and Y. Chauvin. Backpropagation: The basic theory. Backpropagation: Theory, architectures and applications, pages 1–34, 1995.
- [145] M. Sadegh, A. Nguyen, M. Kosmala, A. A. Swanson, M. S. Palmer, M. S. Norouzzadeh, A. Nguyen, M. Kosmala, A. A. Swanson, M. S. Palmer, C. Packer, and J. Clune. Automatically identifying, counting, and describing wild animals in camera-trap images with deep learning. Proceedings of the National Academy of Sciences, 115(25):E5716–E5725, 2018. doi:10.1073/pnas.1719367115.
- [146] Y. G. Sahin. Animals as Mobile Biological Sensors for Forest Fire Detection. Sensors, 7:3084–3099, 2007. doi:10.3390/s7123084.
- [147] D. Scherer, A. Müller, and S. Behnke. Evaluation of pooling operations in convolutional architectures for object recognition. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), 6354 LNCS(PART 3):92–101, 2010. doi:10.1007/978-3-642-15825-4_10.

- [148] J. Schneider. Cross validation. online, 1997. URL <https://www.cs.cmu.edu/~schneide/tut5/node42.html>.
- [149] B. Settles. Active learning literature survey. Technical report, University of Wisconsin-Madison Department of Computer Sciences, 2009. URL <papers://5e3e5e59-48a2-47c1-b6b1-a778137d3ec1/Paper/p1867>.
- [150] J. Shamoun-Baranes, R. Bom, E. E. van Loon, B. J. Ens, K. Oosterbeek, and W. Bouten. From sensor data to animal behaviour: An oystercatcher example. *PLoS ONE*, 7(5):28–30, 2012. doi:10.1371/journal.pone.0037997.
- [151] L. Shao, F. Zhu, and X. Li. Transfer Learning for Visual Categorization: A Survey. *Tnnls*, PP(99):1, 2014. doi:10.1109/TNNLS.2014.2330900.
- [152] E. L. C. Shepard, R. P. Wilson, F. Quintana, A. G. Laich, N. Liebsch, D. A. Albareda, L. G. Halsey, A. Gleiss, D. T. Morgan, A. E. Myers, C. Newman, and D. W. Macdonald. Identification of animal movement patterns using tri-axial accelerometry. *Endangered Species Research*, 10(1):47–60, 2010. doi:10.3354/esr00084.
- [153] J. Shlens. A Tutorial on Principal Component Analysis. *CoRR*, 1404.1100:13, 2014. doi:10.1.1.115.3503.
- [154] M. Shoaib, S. Bosch, O. Incel, H. Scholten, and P. Havinga. A Survey of On-line Activity Recognition Using Mobile Phones. *Sensors*, 15(1):2059–2085, 2015. doi:10.3390/s150102059.
- [155] P. Siirtola and J. Rönning. Recognizing Human Activities User-independently on Smartphones Based on Accelerometer Data. *International Journal of Interactive Multimedia and Artificial Intelligence*, 1(5):38, 2012. doi:10.9781/ijimai.2012.155.
- [156] D. Smith, B. Little, P. I. Greenwood, P. Valencia, A. Rahman, A. Ingham, G. Bishop-Hurley, M. S. Shahriar, and A. Hellicar. A study of sensor derived features in cattle behaviour classification models. In *2015 IEEE SENSORS - Proceedings*, Busan, South Korea, 2015. IEEE. doi:10.1109/ICSENS.2015.7370529.
- [157] D. Smith, A. Rahman, G. J. Bishop-Hurley, J. Hills, S. Shahriar, D. Henry, and R. Rawnsley. Behavior classification of cows fitted with motion collars: Decomposing multi-class classification into a set of binary problems. *Computers and Electronics in Agriculture*, 131:40–50, 2016. doi:10.1016/j.compag.2016.10.006.
- [158] L. I. Smith. A tutorial on Principal Components Analysis Introduction. *Department of Computer Science University of Otago*, 51:52, 2002. doi:10.1080/03610928808829796.
- [159] P. Smolensky. Information processing in dynamical systems: Foundations of harmony theory. *Parallel Distributed Processing Explorations in the Microstructure of Cognition*, 1(1):194–281, 1986. URL <http://portal.acm.org/citation.cfm?id=104279.104290>.

- [160] J. Snoek, H. Larochelle, and R. P. Adams. Practical Bayesian Optimization of Machine Learning Algorithms. Advances in neural information processing systems, pages 2951–2959, 6 2012. doi:10.1163/15685292-12341254.
- [161] J. Soltis, R. P. Wilson, I. Douglas-Hamilton, F. Vollrath, L. E. King, and A. Savage. Accelerometers in collars identify behavioral states in captive African elephants *Loxodonta Africana*. Endangered Species Research, 18(3):255–263, 2012. doi:10.3354/esr00452.
- [162] I. F. Spellerberg and P. J. Fedor. A tribute to Claude-Shannon (1916-2001) and a plea for more rigorous use of species richness, species diversity and the 'Shannon-Wiener' Index. Global Ecology and Biogeography, 12(3):177–179, 2003. doi:10.1046/j.1466-822X.2003.00015.x.
- [163] M. Stikic, K. Van Laerhoven, and B. Schiele. Exploring semi-supervised and active learning for activity recognition. Proceedings - International Symposium on Wearable Computers, ISWC, pages 81–88, 2008. doi:10.1109/ISWC.2008.4911590.
- [164] D. Stowell, E. Benetos, and L. F. Gill. On-Bird Sound Recordings: Automatic Acoustic Recognition of Activities and Contexts. IEEE/ACM Transactions on Audio Speech and Language Processing, 25(6):1193–1206, 2017. doi:10.1109/TASLP.2017.2690565.
- [165] C. Sun, A. Shrivastava, S. Singh, and A. Gupta. Revisiting Unreasonable Effectiveness of Data in Deep Learning Era. Proceedings of the IEEE International Conference on Computer Vision, 2017-Octob:843–852, 2017. doi:10.1109/ICCV.2017.97.
- [166] X. Sun, H. Kashima, and N. Ueda. Large-scale personalized human activity recognition using online multitask learning. IEEE Transactions on Knowledge and Data Engineering, 25(11):2551–2563, 2013. doi:10.1109/TKDE.2012.246.
- [167] M. A. Tabak, M. S. Norouzzadeh, D. W. Wolfson, S. J. Sweeney, K. C. Vercauteren, N. P. Snow, J. M. Halseth, P. A. Di Salvo, J. S. Lewis, M. D. White, B. Teton, J. C. Beasley, P. E. Schlichting, R. K. Boughton, B. Wight, E. S. Newkirk, J. S. Ivan, E. A. Odell, R. K. Brook, P. M. Lukacs, A. K. Moeller, E. G. Mandeville, J. Clune, R. S. Miller, S. J. Sweeney, K. C. Vercauteren, N. P. Snow, P. A. Di, S. Jesse, S. L. Michael, D. W. Ben, J. C. Beasley, P. E. Schlichting, R. K. Boughton, B. Wight, E. S. Newkirk, J. S. Ivan, E. A. Odell, R. K. Brook, P. M. Lukacs, A. K. Moeller, E. G. Mandeville, J. Clune, R. S. Miller, and R. S. Miller. Machine learning to classify animal species in camera trap images: Applications in ecology. Methods in Ecology and Evolution, 2019(September 2018):585–590, 2018. doi:10.1111/2041-210X.13120.
- [168] R. Tapiador-Morales, A. Rios-Navarro, A. Jimenez-Fernandez, J. Dominguez-Morales, and A. Linares-Barranco. System based on inertial sensors for behavioral monitoring of wildlife. IEEE CITS 2015 - 2015 International Conference on Computer, Information and Telecommunication Systems, pages 1–4, 2015. doi:10.1109/CITS.2015.7297759.

- [169] I. Technology. ProMove mini. online, 2017. URL <http://inertia-technology.com/>.
- [170] R. Thompson, I. Kyriazakis, A. Holden, P. Olivier, and T. Plötz. Dancing with Horses: Automated quality feedback for dressage riders. UbiComp 2015 - Proceedings of the 2015 ACM International Joint Conference on Pervasive and Ubiquitous Computing, pages 325–336, 2015. doi:10.1145/2750858.2807536.
- [171] C. Thornton, F. Hutter, H. H. Hoos, and K. Leyton-Brown. Auto-WEKA: Combined selection and hyperparameter optimization of classification algorithms. Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, Part F1288:847–855, 2013. doi:10.1145/2487575.2487629.
- [172] UN. UN Climate Change Summit 2018. Technical report, 2018. URL <http://www.un.org/climatechange/>.
- [173] A. Van Nuffel, J. Vangeyte, K. C. Mertens, L. Pluym, S. De Campeneere, W. Saeys, G. Opsomer, and S. Van Weyenberg. Exploration of measurement variation of gait variables for early lameness detection in cattle using the GAITWISE. Livestock Science, 156(1-3):88–95, 9 2013. doi:10.1016/j.livsci.2013.06.013.
- [174] J. A. Vázquez Diosdado, Z. E. Barker, H. R. Hodges, J. R. Amory, D. P. Croft, N. J. Bell, and E. A. Codling. Classification of behaviour in housed dairy cows using an accelerometer-based activity monitoring system. Animal Biotelemetry, 3(1):15, 2015. doi:10.1186/s40317-015-0045-8.
- [175] P. Vincent, H. Larochelle, I. Lajoie, Y. Bengio, and P.-A. Manzagol. Stacked Denoising Autoencoders: Learning Useful Representations in a Deep Network with a Local Denoising Criterion. Journal of Machine Learning Research, 11(3):3371–3408, 2010. doi:10.1111/1467-8535.00290.
- [176] W3C. Motion Sensors Explainer. online, 08 2017. URL <https://www.w3.org/TR/motion-sensors/>.
- [177] E. Walton, C. Casey, J. Mitsch, J. A. Vázquez-Diosdado, J. Yan, T. Dottorini, K. A. Ellis, A. Winterlich, and J. Kaler. Evaluation of sampling frequency, window size and sensor position for classification of sheep behaviour. Royal Society Open Science, 5(2), 2018. doi:10.1098/rsos.171442.
- [178] J. Wang, Y. Chen, S. Hao, X. Peng, and L. Hu. Deep learning for sensor-based activity recognition: A survey. Pattern Recognition Letters, 119:3–11, 2019. doi:10.1016/j.patrec.2018.02.010.
- [179] J. A. Ward, P. Lukowicz, and H. W. Gellersen. Performance metrics for activity recognition. ACM Transactions on Intelligent Systems and Technology, 2(1), 2011. doi:10.1145/1889681.1889687.

- [180] D. Warrick, T. Hedrick, M. J. Fernández, B. Tobalske, and A. Biewener. Hummingbird flight. Current Biology, 22(12):R472–R477, 2012. doi:10.1016/j.cub.2012.04.057.
- [181] S. Watanabe, M. Izawa, A. Kato, Y. Ropert-Coudert, and Y. Naito. A new technique for monitoring the detailed behaviour of terrestrial animals: A case study with the domestic cat. Applied Animal Behaviour Science, 94(1-2):117–131, 2005. doi:10.1016/j.applanim.2005.01.010.
- [182] A. D. Web. Bovidae antelopes, cattle, gazelles, goats, sheep, and relatives. online, 2019. URL <https://animaldiversity.org/accounts/Bovidae/>.
- [183] F. M. Whittington, R. Dunn, G. R. Nute, R. I. Richardson, and J. D. Wood. Effect of pasture type on lamb product quality. (Table 2):27–31, 2003.
- [184] WildAid. Wildaid, June 2017. <http://wildaid.org/> Accessed: 14-6-2017.
- [185] C. C. Wilmers, B. Nickel, C. M. Bryce, J. A. Smith, R. E. Wheat, V. Yovovich, and M. Hebblewhite. The golden age of bio-logging: How animal-borne sensors are advancing the frontiers of ecology. Ecology, 96(7):1741–1753, 2015. doi:10.1890/14-1401.1.
- [186] R. P. Wilson, E. L. C. Shepard, and N. Liebsch. Prying into the intimate details of animal lives: Use of a daily diary on animals. Endangered Species Research, 4(1-2):123–137, 2008. doi:10.3354/esr00064.
- [187] R. P. Wilson, C. R. White, F. Quintana, L. G. Halsey, N. Liebsch, G. R. Martin, and P. J. Butler. Moving towards acceleration for estimates of activity-specific metabolic rate in free-living animals: The case of the cormorant. Journal of Animal Ecology, 75(5):1081–1090, 2006. doi:10.1111/j.1365-2656.2006.01127.x.
- [188] G. Wittemyer, J. M. Northrup, J. Blanc, I. Douglas-Hamilton, P. Omondi, and K. P. Burnham. Illegal killing for ivory drives global decline in African elephants. Proceedings of the National Academy of Sciences of the United States of America, 111(36):13117–21, 9 2014. doi:10.1073/pnas.1403984111.
- [189] WWF/Dalberg. Fighting Illicit Wildlife Trafficking. Technical report, WWF, 2012.
- [190] J. B. Yang, M. N. Nguyen, P. P. San, X. L. Li, and S. Krishnaswamy. Deep convolutional neural networks on multichannel time series for human activity recognition. the 24th International Joint Conference on Artificial Intelligence (IJCAI 2015), 2015-Janua(Ijcai):25–31, 2015.
- [191] X. Yang, A. Dinh, and L. Chen. Implementation of a wearable real-time system for physical activity recognition based on naive Bayes classifier. Bioinformatics and Biomedical Technology (ICBBT), 2010 International Conference on, pages 101–105, 2010. doi:10.1109/ICBBT.2010.5479000.

- [192] M. Zeng, L. T. Nguyen, B. Yu, O. J. Mengshoel, J. Zhu, P. Wu, and J. Zhang. Convolutional neural networks for human activity recognition using mobile sensors. Mobile Computing, Applications and Services (MobiCASE), 2014 6th International Conference on, 6:197–205, 2014.
- [193] M. Zeppelzauer and A. S. Stoeger. Establishing the fundamentals for an elephant early warning and monitoring system. BMC Research Notes, 8(1):409, 2015. doi:10.1186/s13104-015-1370-y.
- [194] M. Zhang and A. a. Sawchuk. A feature selection-based framework for human activity recognition using wearable multimodal sensors. In Proceedings of the 6th International Conference on Body Area Networks, pages 92–98, Beijing, 2011. ACM. doi:10.4108/icst.bodynets.2011.247018.

ABOUT THE AUTHOR

Jacob Wilhelm Kamminga was born on the 22nd September of 1987 in Kantens, Groningen. Jacob received his B.Eng. from the Hanze University, Groningen in 2011. For his Bachelor's thesis he developed a prototype of a novel Human Metabolic Simulator with IngMar Medical, the world leader in breathing simulation. Jacob received his M.Sc in Embedded Systems from the University of Twente in October, 2015. During his studies he worked as an Embedded Developer for Smart Grids within the energy group. His field of expertise is embedded systems combined with machine learning. He is currently researching unsupervised representation learning for animal activity recognition. His primary research interests are embedded signal processing and machine learning in sensor networks.

LIST OF PUBLICATIONS

PUBLISHED

2020

J. W. Kamminga, D. V. Le, N. Meratnia, and P. J. Havinga. Towards Deep Unsupervised Representation Learning from Accelerometer Time Series for Animal Activity Recognition. In 6th workshop on mining and learning from time series, San Diego, CA, 2020. MiLeTS. URL https://kdd-milets.github.io/milets2020/papers/MiLeTS2020_paper_1.pdf

2019

J. W. Kamminga, N. Meratnia, and P. J. Havinga. Dataset: Horse Movement Data and Analysis of its Potential for Activity Recognition. In the second Workshop on Data Acquisition To Analysis (DATA'19), November 10, 2019, New York, NY, USA, New York, NY, 2019. Association for Computing Machinery. doi:10.1145/3359427.3361908

J. W. Kamminga, M. Jones, K. Seppi, N. Meratnia, and P. J. Havinga. Synchronization between sensors and cameras in movement data labeling frameworks. In the second Workshop on Data Acquisition To Analysis (DATA'19), November 10, 2019, New York, NY, USA, New York, NY, 2019. Association for Computing Machinery. doi:10.1145/3359427.3361920

J. W. Kamminga, L. M. Janßen, N. Meratnia, and P. J. M. Havinga. Horsing Around—A Dataset Comprising Horse Movement. Data, 4(4):131, 9 2019. doi:10.3390/data4040131

J. Kamminga. jacob-kamminga/Matlab-movement-data-labeling-tool: Generic version release., 8 2019. doi:10.5281/zenodo.3364004

J. W. Kamminga. Dataset: Horsing Around – A Dataset Comprising Horse Movement. 4TU.Centre for Research Data., 7 2019. doi:10.4121/uuid:2e08745c-4178-4183-8551-f248c992cb14

2018

J. Kamminga, E. Ayele, N. Meratnia, and P. Havinga. Poaching detection technologies-A survey. Sensors (Switzerland), 18(5):1474, 2018. doi:10.3390/s18051474

J. Kamminga. Dataset: Multi Sensor-Orientation Movement Data of Goats, March

2018. doi:10.17026/dans-xhn-bsfb

J. W. Kamminga, D. V. Le, J. P. Meijers, H. Bisby, N. Meratnia, and P. J. Havinga. Robust Sensor-Orientation-Independent Feature Selection for Animal Activity Recognition on Collar Tags. Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies IMWUT, 2(1):1–27, 2018. doi:10.1145/3191747

D. V. Le, J. Kamminga, H. Scholten, and P. J. Havinga. A Framework to Measure Reliance of Acoustic Latency on Smartphone Status. 2018 IEEE International Conference on Pervasive Computing and Communications Workshops, PerCom Workshops 2018, pages 348–354, 2018. doi:10.1109/PERCOMW.2018.8480354

2017

J. Kamminga. Dataset: Generic Online Animal Activity Recognition on Collar Tags., Sep 2017. doi:10.17026/dans-zp6-fmna

J. W. Kamminga, H. C. Bisby, D. V. Le, N. Meratnia, and P. J. M. Havinga. Generic Online Animal Activity Recognition on Collar Tags. In Proceedings of the 2017 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2017 ACM International Symposium on Wearable Computers - UbiComp '17, pages 597–606, New York, NY, 2017. ACM Press. doi:10.1145/3123024.3124407

2016

J. Kamminga, D. Le, and P. Havinga. Ambient sound-based collaborative localization of indeterministic devices. Sensors (Switzerland), 16(9), 2016. doi:10.3390/s16091478

D. Le, J. Kamminga, H. Scholten, and P. Havinga. Error bounds for localization with noise diversity. In Proceedings - 12th Annual International Conference on Distributed Computing in Sensor Systems, DCOSS 2016, 2016. doi:10.1109/DCOSS.2016.18

D. Le, J. Kamminga, H. Scholten, and P. Havinga. Nondeterministic sound source localization with smartphones in crowdsensing. In 2016 IEEE International Conference on Pervasive Computing and Communication Workshops, PerCom Workshops 2016, 2016. doi:10.1109/PERCOMW.2016.7457115

MANUSCRIPTS IN PREPARATION

J. W. Kamminga, D. V. Le, N. Meratnia, and P. J. Havinga. A Tutorial on Online Animal Activity Recognition using Motion Sensors. page in preparation, 2020