A T-DAB field trial using a low-mast infrastructure

Roel Schiphorst

University of Twente
Enschede - The Netherlands

A T-DAB field trial using a low-mast infrastructure

Roel Schiphorst

Signals and Systems Group (SaS)
Department of Electrical Engineering,
Mathematics and Computer Science (EEMCS)
University of Twente

November 2006

Cover: Top section of a C2000 mast with T-DAB band III antennas and microwave dishes. ©W. Toerink

Signals & Systems Group

P.O. Box 217

7500 AE Enschede
the Netherlands

Typesetting: $\text{\LaTeX}2\text{e}$

© Signals & Systems Group, Enschede, 2006

No part of this publication may be reproduced by print, photocopy or any other means without the permission of the copyright owner.

ISBN: 90-365-2424-5

version: 1.0

Samenvatting

De Universiteit Twente heeft van oktober 2004 tot en met juli 2006 een technische T-DAB pilot uitgevoerd in opdracht van het Ministerie van Economische Zaken. Voor dit project is er in Amsterdam een laagvermogen T-DAB netwerk gebouwd op lage opstelpunten voor zowel band III (kanaal 12B) als de L-band (kanaal LH).

In dit project is aangetoond dat een laagvermogen netwerk bestaande uit lage opstelpunten kan functioneren in een naburig kanaal van een hoogvermogen hoge opstelpunten netwerk. Een gap filler kan de stoorcontouren in het servicegebied van het hoogvermogen hoge opstelpunten netwerk effectief neutralizeren. Andere mogelijke oplossingen zoals een smallere verticale openingshoek van het antenne systeem zijn niet onderzocht. Het minimale vermogen van de gap filler moet 24 dB lager zijn dan het uitgangsvermogen van het lage opstelpunten netwerk.

Indien er geen gap filler of andere oplossing wordt gebruikt, is er een stoorcontour met een gemiddelde straal van 1 km waar geen ontvangst mogelijk is van het hoogvermogen hoge opstelpunten netwerk. De stoorcontour rondom een hoogvermogen hoge opstelpunt is niet onderzocht, maar het is aannemelijk dat deze contour vele malen groter is dan de gemeten contour rondom een opstelpunt van het pilot netwerk. Het T-DAB pilot netwerk is gemonteerd op masten van het C2000 TETRA netwerk. De storing van het T-DAB signaal op het TETRA communicatiesysteem is onderzocht door de C2000 organisatie.

Om binnenshuisontvangst te verkrijgen in 95% van de gebouwen,

blijkt uit de binnenshuismetingen dat voor band III het verlies 21.9 dB bedraagt en voor de L-band 25.8 dB. Om deze binnenshuisontvangst te realiseren moet de veldsterkte buitenshuis voor band III minimaal 67.9 dB μ V/m zijn en voor de L-band 81.9 dB μ V/m voor 50% van de locaties en 50% van de tijd bij een antenne op 1.5 m hoogte. Deze waarde kan gebruikt worden in coverage planning software.

Zowel het bestaande T-DAB netwerk van de *Publieke Omroep* alsmede het pilot netwerk (band III en L-band) bieden geen goede binnenshuisdekking. Indien het uitgangsvermogen op ieder opstelpunt wordt verhoogd met 10 dB, dan zullen beide band III netwerken een goede binnenshuisdekking bieden. Natuurlijk is het plaatsen van meer zenderopstelpunten ook een mogelijkheid. Voor de L-band zijn zowel meer opstelpunten als meer uitgangsvermogen nodig om een goede binnenshuisontvangst in Amsterdam te bereiken.

Echter, de huidige internationale afspraken zijn gebaseerd op ontvangst buitenshuis en tijdens de RRC06 conferentie is besloten dat het interferentieniveau aan de buitengrens met 3 dB en in sommige gevallen tot 6 dB mag toenemen om ontvangst binnenshuis te realiseren. Daardoor zullen beide netwerktopologieën, om te voldoen aan de RRC06 normen, meer opstelpunten moeten gebruiken voor een goede binnenshuisdekking.

Daarnaast is ook de prestatie van consumenten T-DAB ontvangers geëvalueerd volgens de EN 50248 norm. Voor een keukenradio met een sprietantenne en uitgaande van een stedelijk kanaalmodel, is de typisch haalbare gevoeligheid 39 dB μ V/m voor band III (wat 4 dB hoger is dan de minimale gevoeligheid die gespecificeerd is in de *Wiesbaden* overeenkomst); voor de L-band is dit 51 dB μ V/m (5 dB hoger). De mediane consumenten T-DAB ontvanger bereikt deze typisch haalbare gevoeligheid. Echter voor de L-band is de gevoeligheid van de mediane consumenten T-DAB ontvanger 6.5 dB minder dan de typisch haalbare L-band gevoeligheid.

Abstract

Between October 2004 and July 2006, the University of Twente carried out a technical T-DAB field trial in Amsterdam which was commissioned by the Dutch Ministry of Economic Affairs. For this trial, a low-power low-mast T-DAB pilot network was constructed both for band III (channel 12B) and the L-band (channel LH).

This field trial provided evidence that a low-power low-mast network topology can coexist with a high-mast high-power network in an adjacent channel. Using gap fillers, the holes in the service area of the high-mast high-power network can be neutralized effectively. Other possible solutions such as a smaller vertical opening angle of the antenna system were not investigated. The minimum power level of the gap fillers should be 24 dB below the output power of the low-mast infrastructure.

If no gap fillers or other solution is used, there exists an interference area with a radius of 1 km on average, where there is no reception of the high-mast high-power network. The interference area around a high-power mast was not investigated, but it is expected that this interference area will be significantly larger. The T-DAB pilot network was mounted on masts of the C2000 TETRA network. The interference of the T-DAB signal on the TETRA system was investigated by the C2000 organization.

For indoor coverage in 95% of the buildings, the indoor penetration loss measurements revealed that the loss for band III is 21.9 dB and for L-band 25.8 dB. For indoor coverage, the outdoor field strength has to be 67.9 dB μ V/m for band III and 81.9 dB μ V/m for L-band for 50% of the

locations and 50% of the time at an antenna height of 1.5 m. This value can be used in coverage planning software.

Both the existing T-DAB network of the *Publieke Omroep* and the pilot network (band III and L-band) do not provide good indoor coverage in Amsterdam. If output power is increased by 10 dB at every transmission site, both band III networks will provide good indoor coverage. Of course, an alternative is to use more transmitter locations. For the L-band more transmitters as well as more output power are required for good indoor reception in Amsterdam.

However, current international regulations are based on outdoor coverage and it was decided at the RRC06 conference that the interference level at the Dutch border may increase by 3 dB and it in particular cases by 6 dB to achieve indoor coverage. So, both the high-mast and low-mast topologies require more transmitter locations to obtain indoor coverage and to be in line with the RRC06 agreement.

In addition, the performance of T-DAB consumer receivers was evaluated according to the EN 50248 norm. For a kitchen radio, assuming an urban channel model and a passive whip antenna, the typically achievable sensitivity will be $39 \text{ dB}\mu\text{V}/\text{m}$ for band III (which is 4 dB higher than the minimum sensitivity specified in the *Wiesbaden* agreement); for the L-band this is $51 \text{ dB}\mu\text{V}/\text{m}$ (5 dB higher). The median T-DAB consumer receiver achieves the typically achievable band III sensitivity. However, for the L-band, the sensitivity of the median T-DAB consumer receiver is 6.5 dB less than the typically achievable L-band sensitivity.

Preface

Many people have contributed in some way to the realization of this report. First of all, I thank *Andries Aarden*. He wrote most of the Matlab code that converts the raw log files of the measurement equipment into the figures shown in this report. Moreover, during the hectic coverage and indoor measurement campaign, he organized and processed the gigabytes of data that were measured every day.

My appreciation also goes to *Jordy Potman*, who set up and performed the consumer T-DAB receiver experiments, *Niels Moseley* for the specification of the measurement vehicle and for writing software both for the coverage and indoor setup, and *Henny Kuipers* and *Geert-Jan Laanstra* for the construction of the indoor unit and measurement vehicle and for performing the antenna roundness measurements on the turntable. My acknowledgements also go to *Harm Cronie* for implementing the COST 207 channel models, *Klaas Hofstra* for testing the L-band receivers, *Marnix Heskamp* for writing the first version of the Matlab scripts, *Anneke van Essen-Rekers* for taking care of most of the administrative work and *Fokke Hoeksema* for the interesting discussions about this project.

I am also grateful to *Arnaud Paagman* and *Klaas Tutelaers* for carrying out the coverage measurements with the measurement vehicle, sometimes at impossible times. My appreciation also goes to *Carlo Splint*, *Leon Broeren*, *Tijmen Hommes*, *Michiel van den Heuvel*, *Mathijs Kreeft*, *Steffen Smit*, *Marcel Danen* and *Arnaud Paagman* for doing the indoor measurement campaign in a 7-day per week scheme.

I thank *Corinne Hamming* of the ANP (Netherlands national news

agency) for the photo reports which we broadcasted in our pilot network. I also appreciate the hospitality of *Herbert Visser* for allowing the university to do the first indoor measurement trial in his house and for the music content of his radio station, 100%NL, which we used in the field trial. I am also grateful to the Dutch manufacturers and importers of T-DAB consumer radios for providing the university with T-DAB receivers; *Sander Tinnemans* of Music Matters, *Henk de Boer* of Blaupunkt, *Taco Potze* of i.Tech, *Henk Graat* of Freesat, *Jan Best* of Trinloc and *Gert-Jan Duijn* of Rebox.

My appreciation also goes to the members of the Technical Advisory Group (TBG), *Toon Strijbosch* of the Ministry of Economic Affairs, *Fernand Pors* of the Radiocommunications Agency Netherlands, *Henk Milius* of Broadcast Partners, *Willem Toerink* of db Europe, *Willem van Ooijen* of Nozema, *Hans Bakhuizen* of the Publieke Omroep, *Ruud Vader* of DigiRadio and *Remko Welling* of the C2000 organization for their fruitful comments during the TBG meetings. I also want to thank *Louis Pierpont* of Radiocommunications Agency for his support during the project.

In this field trial, the C2000 organization played an important role at different aspects. I acknowledge the support of the C2000 Engineering Bureau Amsterdam for enabling the university to carry out the coverage experiments. Moreover, I am grateful to *Theo de Bont* and *Remko Welling* for the interesting discussions and comments about the indoor and coverage measurements.

I am indebted to *Willem Toerink* for his ideas and the effort that he put into this field trial. Finally, I want to thank *Kees Slump* for his ideas and comments but and for solving the non-technical challenges in this project.

Roel Schiphorst
Enschede, the Netherlands
November 2006

Contents

Samenvatting	i
Abstract	iii
Preface	v
Contents	vii
1 Introduction	1
1.1 Research questions	1
1.2 Outline	4
2 Coverage measurements	5
2.1 Introduction	5
2.2 Measurement setup	6
2.2.1 Measurement vehicle	6
2.2.2 Pilot network Amsterdam	9
2.2.3 Distribution of the Ensemble Transport Interface (ETI) signal	12
2.2.4 Pilot ensembles	13
2.3 Calibration	14
2.3.1 Antenna factor	15
2.3.2 Antenna diagram measurement	17
2.3.3 Difference between 2.65 m and 1.5 m antenna height	17

2.4	Band III results	22
2.4.1	Self interference	22
2.4.2	Adjacent channel interference	22
2.4.3	Co-channel interference	24
2.4.4	Service area	29
2.4.5	Redundancy	31
2.4.6	Protection levels	31
2.4.7	SFN network gain	34
2.5	L-band results	38
2.5.1	Self interference	38
2.5.2	Co-channel interference	38
2.5.3	Service area	40
2.5.4	Redundancy	43
2.5.5	Protection levels	45
2.5.6	SFN network gain	51
3	Indoor measurements	55
3.1	Introduction	55
3.2	Measurement setup	56
3.2.1	Method	58
3.2.2	Calibration	61
3.3	Results	61
3.3.1	Example of an indoor measurement	61
3.3.2	Indoor penetration loss	66
4	Consumer receivers	75
4.1	Introduction	75
4.2	Consumer receivers	76
4.2.1	Audio quality	77
4.3	Bodyloss measurements	78
4.3.1	Literature	78
4.3.2	Experimental results	79
4.3.3	Discussion	82
4.4	Measurement setup	82

4.4.1	Setup	82
4.4.2	Calibration	84
4.5	Band III results	84
4.5.1	Performance of RadioScape RS-T1000b DAB monitor	84
4.5.2	Audio quality versus BER	84
4.5.3	Antenna factor measurements	92
4.5.4	Sensitivity experiment	93
4.5.5	Adjacent channel interference experiment	95
4.5.6	Non-adjacent channel interference experiment	98
4.5.7	In-band interference experiment	103
4.6	L-band results	107
4.6.1	Performance of RadioScape RS-T1000b DAB monitor	107
4.6.2	Sensitivity experiment	110
4.6.3	In-band interference experiment	113
4.7	Typical sensitivity of a Terrestrial Digital Audio Broadcasting (T-DAB) consumer receiver	116
4.7.1	Typical sensitivity	119
5	Summary	123
	References	135
	Acronyms	141

Chapter 1

Introduction

In February 2004, the *Publieke Omroep* started T-DAB broadcasts with traditional radio programs in band III. The Dutch Ministry of Economic Affairs intends to hand out also the licenses for commercial multiplex operators (both band III and L-band). This was the start of the technical T-DAB pilot, and the results of this field trial are presented in this report.

In general, there are three topologies for a T-DAB network: the traditional high-power high-mast network, a low-power low-mast network, and a combination of the two. In this report, the first two network topologies are evaluated and the field strength requirements for indoor coverage are deduced. Besides audio services, the T-DAB standard has evolved into a real multimedia standard including audio, video and data services. Of course, the level of these multimedia services depends also on the T-DAB network topology used.

1.1 Research questions

The Dutch Ministry of Economic affairs provided us with the following questions [1]:

- Can a T-DAB network consisting of low-power transmitters with

antennas mounted at relatively low positions (i.e. the pilot network) co-exist with the current T-DAB network consisting of high-power transmitters mounted at relatively high positions (i.e. *Publieke Omroep* network)?

- What is the performance of consumer T-DAB receivers currently on the market compared to the reference *Wiesbaden* receiver?
- What is the indoor penetration loss for band III and the L-band?
- Which network architecture can provide indoor coverage in line with the current *Wiesbaden* agreement [2]?

Besides these questions, also a number of technical research issues were provided [1] that are summarized below. A number of questions regarding the performance of the Digital Audio Broadcasting (DAB) transmitting system are addressed in an internal document of the C2000 organization. For that reason they are not listed here. Each question is followed by a reference to the appropriate section where the question is answered.

1. Which combinations of T-DAB transmitter and network configurations are possible?

Evaluate these networks on the following aspects:

- (a) What is the self-interference of the two networks? (Sections 2.4.1 and 2.5.1)
- (b) What is the co-channel interference of the two networks? (Sections 2.4.3 and 2.5.2)
- (c) What is the adjacent channel interference between the pilot network (channel 12B) and the *Publieke Omroep* network (channel 12C)? (Section 2.4.2)
- (d) What is the ratio of the interference levels at different distances up to 200 km between high and low positions network topologies? (Sections 2.4.3 and 2.5.2)

1.1. Research questions

- (e) What is the effect of downtilt in combination with smaller vertical opening angles of the antenna on the service area and the different interference levels of both networks? (Not answered in this report.)
 - (f) What is the influence of shifting the time synchronization on the service area? (Sections 2.4.1 and 2.5.1)
 - (g) What are the delays of microwave links, line links, internet or satellite connections? And how does this affect the performance of the system? (Section 2.2.3)
 - (h) How redundant and vulnerable are the networks? (Sections 2.4.5 and 2.5.4)
 - (i) What is the Inter-Symbol Interference (ISI) in the following area: water, urban and rural areas, with and without temperature inversion? (Section 2.4.3 and Section 2.5.2)
 - (j) Does flat fading occur, and will it affect the service area? (Sections 2.4.7 and 2.5.6)
 - (k) What are the optimal protection levels? (Sections 2.4.6 and 2.5.5)
 - (l) What is the service area? (Sections 2.4.3, 2.4.4, 2.5.2 and 2.5.3)
 - (m) What is the interference area? (Sections 2.4.3 and 2.5.2)
 - (n) What is the co-channel re-use distance? (Sections 2.4.3 and 2.5.2)
 - (o) What is the indoor penetration loss? (Chapter 3)
 - (p) What is the Single Frequency Network (SFN) gain? (Sections 2.4.7 and 2.5.6)
2. Which combinations of T-DAB transmitter and network configurations are possible to achieve portable indoor coverage in line with the requirements of the *Wiesbaden* agreement [2]? (Chapter 5)

3. What is the performance of a median T-DAB receiver with respect to the sensitivity and adjacent and non-adjacent interferer performance? (Chapter 4)
4. What is the bodyloss of a personal T-DAB receiver? (Section 4.3)
5. How does the performance of the median receiver affect the service and interference area of the T-DAB networks? (Chapter 5)

1.2 Outline

This report contains five chapters which cover the following subjects:

Chapter 1: This introductory chapter.

Chapter 2: This describes experiments carried out with the measurement vehicle in Amsterdam to evaluate the performance of the different network topologies.

Chapter 3 Besides coverage, also the indoor penetration loss of 50 objects has been measured. The results of these measurements are presented in this chapter.

Chapter 4 This chapter describes the DAB receiver characteristics for consumer equipment intended for terrestrial (and cable) reception, operating in band III and L-band.

Chapter 5 The final chapter summarizes the principal findings of this report.

Chapter 2

Coverage measurements

2.1 Introduction

This chapter describes experiments carried out with the measurement vehicle in Amsterdam to evaluate the performance of the pilot network (channel 12B) and the existing network of the *Publieke Omroep* (channel 12C). In addition, an L-band pilot network has been investigated.

In this report, we assume that the reader is familiar with the properties of a wireless channel. A good general introduction about the wireless channel can be found in [3]. In the past, several T-DAB coverage measurements have been conducted both for band III and the L-band. Most measurements were performed in the first half of the 1990s: for band III, in the UK by the *BBC* [4, 5, 6], in Finland [7] by the Finnish Broadcasting Company (*Yleisradio Oy*) and in Bavaria (Germany) [8] by the *Bayerischer Rundfunk*. A field trial in the L-band has been performed in Canada [9] by the *Communications Research Centre*. The main focus of these measurement campaigns was to match the received data with simulation models. In this report the focus is on different network topologies, but the results are also compared with the ITU propagation curves *ITU-R P.1546-1* [10].

The outline of this chapter is as follows. First, the technical details of the measurement vehicle and pilot network are described. Next, the

Figure 2.1: Photograph of the measurement vehicle

calibration of the measurement vehicle is discussed. Finally, the results of the experiments are given.

2.2 Measurement setup

2.2.1 Measurement vehicle

Figure 2.1 shows a photograph of the measurement vehicle, a Peugeot 807, with the band III antenna. Mounting the Radio Frequency (RF) antenna directly on the roof would have resulted in an antenna pattern with a variation of more than ± 1 dB. For that reason, a small mast was constructed on the roof of the vehicle. More information about the antenna diagram can be found in Section 2.3.2.

Figure 2.2 depicts the block diagram for the L-band of the measurement equipment inside the vehicle. For field strength measurements we used the *Rhode & Schwarz* ESPI, and for qualitative analysis of the DAB signal, we installed two *RadioScape* RS-T1000b

2.2. Measurement setup

Figure 2.2: Block diagram of the measurement vehicle (L-band configuration)

DAB monitors. The two monitors allow monitoring two subchannels simultaneously, for example with different protection levels. In addition, a *Rhode & Schwarz* FSH spectrum analyzer was used to monitor a 10-MHz-wide spectrum around the selected multiplex.

Both the ESPI and DAB monitors are connected to the receiving antenna with a 0-dB active splitter. For the band III measurements, an extra ESPI and RS-T1000b monitor was installed to monitor and measure the field strength of the *Publieke Omroep* multiplex. To log the Global Positioning System (GPS) locations and speed, a *Garmin* Street pilot 2650 GPS receiver with dead reckoning was connected to a laptop. The laptop is the control center where all equipment can be monitored.

The analog front-end for band III contains a *Sirio* GPA $\frac{1}{4}\lambda$ ground plane antenna (for the band III measurements) with a 0-dB active splitter which consisted of a *BKV* 165 amplifier with *Merrimac* PDM-40-250 splitters and RG 58 RF cable. In addition, we adjusted the gain of the active splitter to compensate for the cable loss.

For the L-band, the *European Antennas* VOA4-1500/054 antenna was

used with an *ETL* active 4-way 0-dB splitter (DIV 04 L1 A-2322 S). *Aircell* 7 RF cable was selected for the L-band measurements. Also for this band, the cable loss was measured and the field strength values adjusted to correct for this loss (1.6 dB).

Measurement method

The measured field strength depends both on time and place. The European Conference of Postal and Telecommunications Administrations (CEPT) recommendation *Field strength measurements along a route with geographical coordinate registrations* was used [11] to estimate the local average mean of the field strength. This is based on the *Lee* method [12] that prescribes that the field strength measurements should be averaged over 40λ to obtain the local mean. To obtain a 1-dB confidence interval, 50 samples have to be measured which also determines the maximum speed of the vehicle.

As existing software could only sample the field strength every 2 seconds, the university developed its own software to speed up to measurements of ESPIs. This software runs on the laptop and configures the ESPIs to the selected channel and a bandwidth of 1.5 MHz with an integration time of 96 ms (the duration of a DAB frame). The software supports approximately 10 measurements per second. The maximum speed of the vehicle is therefore 40 km/h. For convenience, we chose a maximum speed of 50 km/h, which results in a slightly higher confidence interval.

The software also controls and reads out the FSH and GPS receiver. The DAB monitors are configured by remote desktop. Each monitor logs several parameters, which include time, Bit Error Rate (BER) before and after Forward Error Correction (FEC), Signal-to-Noise Ratio (SNR), null symbol, constellation diagram and Channel Impulse Response (CIR). All log files are combined offline and processed in *Matlab* [13]. The GPS log file is the master log file, and the system time in each log file is used to combine all files. The result is a large matrix containing: time, location, field strength, BER values, etc. For example, if the field strength is plotted,

2.2. Measurement setup

Figure 2.3: Transmitter locations

the values are average per 50 meter.

2.2.2 Pilot network Amsterdam

To test both a low mast and high mast infrastructure, a pilot network was built in Amsterdam, which is in the service area of the *Publieke Omroep*. The *Publieke Omroep* uses a high mast infrastructure, and one of their transmitters (IJ-mast) is located in Amsterdam. The IJ-mast radiates its main power in the south-east direction with 2 kW Effective Radiated Power (ERP).

The pilot network consists of four low-mast band III transmitters (Oostzaan, Vredehof, Diemen and Aambeeldstraat) and five L-band

Figure 2.4: Photograph of the top section of the mast where the DAB transmit antennas are mounted: 1 = band III antenna, 2 = L-band antenna and 3 = microwave dishes. Other installed equipment is property of the C2000 organization. (Photograph taken from <http://www.radio.nl/fmtv>.)

2.2. Measurement setup

Figure 2.5: Antenna diagram of the transmit antennas [14]

transmitters (Oostzaan, Vredehof, Diemen, de Bazel and Aambeeldstraat). Figure 2.3 presents a map of Amsterdam with the locations of the transmitters. Each transmitter has an omnidirectional antenna with 200 W ERP¹ for each channel. The antennas are mounted at a height of 42 meters. Figure 2.4 shows a photograph of the top section of the mast and Figure 2.5 depicts the antenna diagram of the antennas used.

A list of Transmitter Identification Information (TII) codes used can be found in Table 2.1.

A block diagram of each transmitter location is given in Figure 2.6. Basically, each site contains two *Plisch* SDA 730 transmitters (12B and LH) [15]. *Siemens* microwave link equipment is used for distribution of the ETI signals. The two ETI signals are generated by two *RadioScape* broadcast systems. In addition, each location (except Aambeeldstraat and de Bazel) have a gap filler at channel 12C and a band III combiner in order to assess whether a gap filler can suppress the interference area around the 12B pilot

¹This output value (cable losses and antenna gain are included) has been verified by the Radiocommunications Agency Netherlands.

Transmitter site	Main ID	Sub ID
Pilot network		
Aambeeldstraat	1	1
Diemen	2	2
Vredenhof	3	3
de Bazel	8	8
Oostzaan	5	5
PO network (12C)		
IJ-mast	1	9
Haarlem	1	6

Table 2.1: TII codes

transmitters. For a more detailed description of the block diagram, see [14].

2.2.3 Distribution of the ETI signal

The ETI signal has to be distributed from the multiplex system to the transmitters. In principle, different networks can be used including microwave, line, internet or satellite link. The maximal allowable delay of the ETI signal between multiplex system and transmitter is about 1 second. This value also depends on the installed equipment. In the pilot network, a microwave connection has been used which has a delay much smaller than 1 second. Another option is to use a satellite link which has a delay of approximately 320 ms [16] including processing delay time. An internet line connection can also be used, although the delay varies in time and depends on both the load in the network and the location of the multiplex system and transmitters. In [17], the maximum delay between two random locations is 360 ms. An internet line connection may thus be used, but it will not have the reliability which is required for a broadcast system.

2.2. Measurement setup

2.2.4 Pilot ensembles

For our coverage and indoor measurements we used Pseudo Random Bit Sequence (PRBS) data channels at different protection levels. In combination with the *RadioScape* RS-T1000b this allows both the registration of the BER after FEC and an estimate of the BER before FEC. Besides data channels, also video and audio subchannels were broadcasted. The multiplex in band III was transmitted in mode I and the L-band multiplex in mode IV. Both mode II and mode IV are suitable for the L-band, but the latter allows a larger distance between transmitters [18].

(a) band III

Figure 2.6: Block diagram of a transmitter site. The blue blocks are only at the *Aambeeldstraat* location.

(b) L-band

Figure 2.6: Block diagram of a transmitter site. The blue blocks are only at the *Aambeeldstraat* location. (cont)

2.3 Calibration

Before a measurement setup (here the measurement vehicle) can be used for field strength measurements, it has to be calibrated. Two calibrations are needed: antenna factor and antenna diagram measurement.

The antenna factor is the ratio between the electric field strength and the output voltage or power of an antenna. As the *Rhode & Schwarz* ESPI can only measure the received power we need the antenna factor of both the band III and L-band antennas for conversion to the electric field strength.

The antenna diagram, on the other hand, determines among other

factors (e.g. measurement accuracy of the ESPI) how accurately the field strength can be measured.

2.3.1 Antenna factor

To determine the antenna factor we used the Standard Site Method (SSM) [19, 20, 21]. This method requires an open field site of 7 by 14 meters; no obstacles are allowed within 20 meters of this area. The ground plane can be metallic or earth. For purpose of convenience we chose to use the earth as ground plane. An advantage of this method is that it does not require calibrated antennas. Instead it needs three uncalibrated antennas.

The SSM method determines the antenna factors for horizontal polarization. This has a number of advantages including relatively insensitive to site variations. It also yields free-space antenna factors even though the reflecting ground plane will not create a free-space environment during calibration. In this project, only the antenna factor for vertical polarization is important. Antenna factors for vertical polarization are determined in a similar way by rotating the antennas 90 degrees.

Figure 2.7 depicts the measurement setup. The SSM method has an uncertainty of ± 1 dB for frequencies below 800 MHz [20].

Method

The method requires three measurements using the setup of Figure 2.7:

- Measurement 1: Antennas 1 and 2
- Measurement 2: Antennas 1 and 3
- Measurement 3: Antennas 2 and 3

In each measurement, the height of the second antenna is varied until the maximum field strength is achieved. The difference between this value and a direct connection between the cable is defined as A_x .

The antenna factors can be derived using the following equations:

Figure 2.7: Measurement setup of the Standard Site Method [20]

$$AF_1 = 10\log_{10}(f_M) - 24.46 + 1/2[E_D^{max} + A1 + A2 - A3] \quad (2.1)$$

$$AF_2 = 10\log_{10}(f_M) - 24.46 + 1/2[E_D^{max} + A1 - A2 + A3] \quad (2.2)$$

$$AF_3 = 10\log_{10}(f_M) - 24.46 + 1/2[E_D^{max} - A1 + A2 + A3] \quad (2.3)$$

with E_D^{max} equal to 2.0 dB and f_M the selected frequency in MHz i.e. 225.648 Mhz or 1464.944 MHz.

Results

From the measurement results we derived an antenna factor of 15.7 dB for the band III antenna (12B) and an antenna factor of 31.7 dB for the L-band antenna (LH). Experiments with a calibrated antenna (of *Agentschap Telecom*) for band III resulted in a similar antenna factor (± 1 dB).

The theoretical antenna factor for a dipole is defined as:

$$AF = 20\log_{10}(f_M) - 31.8 \quad (2.4)$$

2.3. Calibration

with f_M the selected frequency in MHz. The theoretical antenna factors for band III (12B) and the L-band are 15.3 dB and 31.5 dB, respectively. The measured values are slightly higher, which is probably due to implementation imperfections.

In addition, we measured the cable losses for both bands and included the loss in the field strength conversion.

2.3.2 Antenna diagram measurement

To measure the antenna diagram we used an SSM site where a turntable slowly rotates the measurement vehicle. The setup is depicted in Figure 2.8.

Method

To determine the antenna diagram, a low power DAB transmitter broadcasts a DAB signal. In the far field (>10 m), the measurement vehicle is slowly² rotated on a turntable. In the vehicle, a laptop registers the field strength picked up by the *antenna under test* and the angle of the turntable over ten revolutions. The antenna diagram is determined by averaging these 10 revolutions.

Figure 2.9 shows the antenna diagram for band III, and Figure 2.10 shows it for the L-band. It can be seen that the field strength can be determined for band III with an accuracy of ± 1.2 dB and for the L-band with ± 0.9 dB. In an urban environment, this value will be lower due to the reception of multiple paths. As the ESPI has a smaller accuracy of ± 1.5 dB, the accuracy of the ESPI will determine the accuracy of the field strength measurements.

2.3.3 Difference between 2.65 m and 1.5 m antenna height

The measurement vehicle measures the field strength at 2.65 m, whereas international standards use an antenna height of 1.5 m [2, 22]. For

²Slowly means 1 revolution per minute.

Figure 2.8: Measurement setup for antenna diagram measurements where the measurement vehicle is rotated on a turntable

conversion to a field strength at an antenna height of 10 m which has the same coverage as an antenna at 1.5 m, these standards use a conversion factor of 10 dB. For the measurement vehicle this means that the field strength at 2.65 m is $(2.65 - 1.5) \cdot 10 / (10 - 1.5) = 1.4$ dB higher than at 1.5 m.

To verify these results we measured the field strength at 8 outdoor locations in Amsterdam at antenna heights of 1.5 m and 2.65 m. For these measurements the antennas were mounted on two masts of the appropriate length. The outdoor locations are depicted in Figure 2.11, and the results are listed in Table 2.2. The measured values are within 1 dB of the theoretical value of 1.4 dB. Differences are assumed to be caused by different antenna heights and different transmitter antennas. The coverage field strengths measured were corrected for this difference and show the field strength at an antenna height of 1.5 m.

In addition, the standard deviation of the received signal σ_{time} and the standard deviation of the means of all measurement points σ_{place} was

2.3. Calibration

Figure 2.9: Antenna diagram of the measurement vehicle antenna (band III, 12B)

Channel	difference	
	μ	σ
band III 12B	2.0 dB	0.3 dB
band III 12C	2.5 dB	0.3 dB
L-band LH	0.7 dB	0.3 dB

Table 2.2: Antenna height: difference between antenna heighth at 2.65 and 1.5 m

Figure 2.10: Antenna diagram of the measurement vehicle antenna (L-band, LH)

2.3. Calibration

Figure 2.11: Outdoor locations (legend: red = outdoor locations, blue= transmitters pilot network, green = transmitters Publieke Omroep)
©Google Maps

Channel	σ_{place}	σ_{time}
band III 12B	2.8 dB	0.4 dB
band III 12C	3.2 dB	0.4 dB
L-band LH	2.2 dB	0.7 dB

Table 2.3: Standard deviation of the received signal σ_{time} and the standard deviation of the means of all measurement points σ_{place} for the outdoor measurement points

calculated for these 16 outdoor points. The results are listed in Table 2.3. To calculate these values, the Statistics toolbox of *Matlab* was used. The histogram of σ_{time} tends to be a Gamma distribution [23] (Figure 2.12), and σ_{place} histogram tends to be a (log-) normal distribution.

2.4 Band III results

2.4.1 Self interference

Self-interference in the network will occur if the maximum distance between the transmitters is too large. For mode I, this maximum distance is 74 km [18]. In both our pilot network and in the network of the *Publieke Omroep* this does not occur.

2.4.2 Adjacent channel interference

Adjacent channel interference occurs if the field strength of a neighbouring channel is much larger than the selected channel. According to the EN 50248 norm [24], a maximum difference of 30 dB is allowed for adjacent channels and 40 dB for non-adjacent channels.

In this field trial, we have determined how large the field strength difference between two adjacent channels is when two different network topologies are used. Especially around the pilot transmitters there is an interference area where the strong signal of channel 12B will prevent reception of the multiplex at 12C. With our measurement vehicle, we

2.4. Band III results

Figure 2.12: Histogram of the standard deviation in time of the outdoor measurement points (channel 12C)

measured this difference. One of the solutions to suppress the interference areas is to use a gap filler at channel 12C at the pilot transmitter sites. A gap filler power level of 880 mW and 2 W was evaluated. In addition, we measured the adjacent and non-adjacent performance of consumer receivers (Sections 4.5.5 and 4.5.6).

Figure 2.13 shows the difference in field strength between channel 12B and 12C versus the distance from a transmitter location of the pilot network where the speed of the measurement vehicle is below 50 km/h. As the *Diemen* location is near the highway, several measurement points are invalid due to the excessive speed. All results are averaged (solid lines) per 50-meter, or the 99% limit in this segment is shown (dashed lines). The 99% limit indicates that 99% of all measurements in the segment are below this value.

The red line is the *Wiesbaden* requirement, the black lines apply when no gap filler was used, blue when a gap filler of 880 mW was used and green when the power of the gap fillers is 2 W. The *Aambeeldstraat* transmitter site does not require a gap filler due to the vicinity of the

IJ-mast.

When no gap fillers are used, the holes in the service area of the *Publieke Omroep* are a circle with a radius of ± 800 m for the *Diemen* transmitter site, ± 1000 m for *Vredenhof*, and ± 1650 m for *Oostzaan*. As the field strength of the *Publieke Omroep* is the lowest near *Oostzaan*, the hole in the service is the largest there. A gap filler of 880 mW per pilot site will be enough to neutralize the holes in the service area of the *Publieke Omroep*. The interference area around a high-power mast was not investigated, but it is expected that this interference area will be significantly larger.

2.4.3 Co-channel interference

Figure 2.14 depicts the measured field strength for a route around the *IJsselmeer*³. Figure 2.15 shows the same information in a field strength versus distance plot. As the propagation conditions vary from day to day, these figure give only an indication of the co-channel interference.

Re-use distance

The ITU has derived a relation between distance and (predicted) field strength in [25] and [10]. Figure 2.15 depicts the relation between measured field strength and distance. In addition, four extra lines are plotted in Figure 2.15: a *free space* red line, which gives the field strength for a free space environment; the *itu-p1546-1* green line, which gives the predicted field strength using Recommendation ITU-P1546-1 [10] for land paths; a purple line for sea paths; and a dotted red line which indicates the sensitivity of the measurement equipment.

From Figure 2.15, it can be concluded that the predicted field strength using Recommendation ITU-P1546-1 for land paths is a good estimate of the received field strength.

In the *Wiesbaden* agreement [2], the service area for outdoor coverage is defined as the area where the field strength is greater than 48 dB μ V/m

³A former sea which was separated from the North Sea

2.4. Band III results

(a) Diemen

(b) Vredehof

Figure 2.13: Field strength difference (12B-12C) versus distance from a transmitter location

(c) Oostzaan

(d) Aambeelstraat

Figure 2.13: Field strength difference (12B-12C) versus distance from a transmitter location (cont)

Figure 2.14: Field strength of channel 12B at a large distance of the pilot network

Figure 2.15: Field strength versus distance plot for channel 12B

(50 % place, 50 % time at a 1.5 m antenna height). The area of interference area from other T-DAB networks is defined as the area where the field strength is between 23 dB μ V/m and 48 dB μ V/m. However, the *Wiesbaden* agreement assumes that the transmitters have a 12 dB power reduction at the boundary of the service area. In the pilot network the antennas are omnidirectional so that there is no 12 dB power reduction. If 12 dB power reduction would have been applied, the interference area would be between 35 dB μ V/m and 48 dB μ V/m. Figure 2.15 reveals that the re-use distance in this case is about 50 km.

Figure 2.16: The field strength of channel 12B for multiple measurement routes

2.4.4 Service area

In Figure 2.16, the field strength of channel 12B for multiple measurement routes has been plotted. Figure 2.17 depicts this for channel 12C. In the *Wiesbaden* agreement [2], the service area for outdoor coverage is defined as the area where the field strength is greater than $45 \text{ dB}\mu\text{V}/\text{m}$.

Both networks give good outdoor coverage in Amsterdam. Of course, the pilot network for a commercial service would also include transmitter sites in the south of Amsterdam.

Figure 2.17: The field strength of channel 12C for multiple measurement routes

2.4.5 Redundancy

Figure 2.18 depicts the field strength of the channel 12B network when location *Aambeeldstraat* is switched off. Figure 2.19 shows the accompanying BER after FEC plot. A black color indicates that at this point no BER values have been logged, in other words the receiver could not synchronize to the DAB multiplex.

Due to the strong field strength of channel 12C, the field strength measurement equipment (ESPI) detects for the adjacent 12B channel a relatively strong non-existing field strength around location *Aambeeldstraat*.

It is clear from the figures than when a transmitter of the pilot network fails, only a small part of the coverage in Amsterdam is affected. Using a high power high mast infrastructure would have resulted in a larger hole in the service area.

2.4.6 Protection levels

In this field trial several protection levels were tested. For band III, protection level Unequal Error Protection (UEP)3 and UEP5 were evaluated. Figure 2.20 shows the BER after FEC performance for UEP3 and Figure 2.21 shows this for UEP5. A black color indicates that at this point no BER values were logged, meaning that the receiver could not synchronize to the DAB multiplex. For error-free reception, the BER after FEC should be lower than 10^{-4} [24].

From these figures it is clear that only UEP3 is useable. From our L-band protection level measurements (Section 2.5.5), UEP4 seems to be a good trade off between performance and capacity. If protection level UEP4 is used, the capacity of the multiplex is 1.336 Mbit/s.

The maximum useable protection level obviously depends on the performance of the receiver, in our case the *RadioScape* RS-T1000b DAB monitor. Chapter 4 shows that this receiver has a good performance for band III. However, an interesting question arises, namely what is the theoretical maximum useable capacity? This capacity could be reached

Figure 2.18: Field strength of channel 12B with transmitter site *Aambeeldstraat* switched off.

2.4. Band III results

Figure 2.19: BER after FEC of channel 12B for protection level UEP3 with transmitter site *Aambeeldstraat* switched off.

Figure 2.20: BER after FEC of channel 12B for protection level UEP3.

if the most advanced algorithms are implemented in the receiver. Further research is needed to answer this question.

2.4.7 SFN network gain

In Figure 2.16, the field strength of channel 12B for multiple measurement routes has been plotted. Figure 2.22 depicts the field strength of the network when a *single* transmitter is switched on. The difference between both figures can be considered as SFN gain. This gain can be up to 10 dB. During the coverage measurements, no occurrences of flat fading were measured.

2.4. Band III results

Figure 2.21: BER after FEC of channel 12B for protection level UEP5.

(a) Aambeeldstraat

(b) Vredenhof

Figure 2.22: The field strength of channel 12B when one transmitter is switched on at a time

2.4. *Band III results*

(c) Oostzaan

(d) Diemen

Figure 2.22: The field strength of channel 12B when one transmitter is switched on at a time (cont)

2.5 L-band results

2.5.1 Self interference

Self-interference in the network will occur if the maximum distance between the transmitters is too large. For mode IV, the maximum distance is 37 km and for mode II it is 18 km[18]. In a field trial in Canada [26], a larger distance was found before self-interference occurred. However, the specific geographical area can play a role in this.

In our coverage measurements we did not experience self-interference in the network. The transmitter distance is also much smaller than 37 km.

2.5.2 Co-channel interference

Figure 2.23 depicts the measured field strength for a route around the *IJsselmeer*. Figure 2.24 shows the same information in a field strength versus distance plot. As the propagation conditions vary from day to day, these figure give only an indication of the co-channel interference.

Re-use distance

The ITU derived a relation between distance and (predicted) field strength in [25] and [10]. Figure 2.24 depicts the relation between measured field strength and distance. In addition, three extra lines are plotted in Figure 2.24: a *free space* red line, which gives the field strength for a free space environment; the *itu-p1546-1* green line, which gives the predicted field strength using Recommendation ITU-P1546-1 [10] for land paths; a purple line for sea paths; and a dotted red line which indicates the sensitivity of the measurement equipment.

On the measurement day, the signal of channel LH could be received on the opposite side of the *IJsselmeer*. Compared to our band III measurement (on a different measurement day), it seems that the LH signals propagate further than channel 12B. Moreover, the measured field strength curve is above the free space line, and there appears to be a large difference between this line and the ITU-P1546-1 curves.

2.5. *L-band results*

Figure 2.23: Field strength of channel LH at a large distance of the pilot network

A possible explanation for this is that the opening angle of the L-band antenna is narrower (12 degrees) compared to the band III antennas (32 degrees). The plotted free space line assumes that the field strength propagates in three directions meaning that the power is distributed on the surface of a sphere. When an antenna with a small opening angle is used, this condition does not hold. In addition, the *IJsselmeer* may affect the propagation conditions.

Moreover, in Figure 2.24 the local variations in measured field strength are larger than for the band III (Figure 2.15). This could be explained also by a small opening angle of the antennas. With a small opening angle, high objects will have greater impact on the received field strength. Moreover, there are large variations in the antenna diagram (Figure 2.5) of the L-band antenna, up to 20 dB, which may also explain the large variations.

In the *Maastricht* agreement [22], the service area for outdoor coverage is defined as the area where the field strength exceeds 59 dB μ V/m (50 % place, 50 % time at a 1.5 m antenna height). The area of interference to other T-DAB networks is defined as the area where the field strength is between 31 dB μ V/m and 59 dB μ V/m. However, the *Maastricht* agreement assumes that the transmitters have a 12 dB power reduction at the boundary of the service area. In the pilot network the antennas are omnidirectional so that there is no 12 dB power reduction. If 12 dB power reduction would have been applied, the interference area would be between 43 dB μ V/m and 59 dB μ V/m. Figure 2.24 reveals that the re-use distance in this case is about 100 km.

2.5.3 Service area

In Figure 2.25, the field strength of channel LH for multiple measurement routes has been plotted. In the *Maastricht* agreement [22], the service area for outdoor coverage is defined as the area where the field strength is greater than 59 dB μ V/m.

The L-band pilot network provides good outdoor coverage in Amsterdam. Of course, the pilot network for a commercial service would also include transmitter sites in the south of Amsterdam.

2.5. *L-band results*

Figure 2.24: Field strength versus distance plot for channel LH

Figure 2.25: The field strength of channel LH for multiple measurement routes.

2.5. L-band results

Figure 2.26: Field strength of channel LH with transmitter site *de Bazel* switched off.

2.5.4 Redundancy

Figure 2.26 depicts the field strength of the channel LH network when location *de Bazel* is switched off. Figure 2.27 shows the accompanying BER after FEC plot. The figures, make clear that when a pilot network transmitter fails, only a small part of the coverage in Amsterdam is affected. Using a high power high mast infrastructure would have resulted in a larger hole in the service area.

Figure 2.27: BER after FEC of channel LH for protection level UEP3 with transmitter site *de Bazel* switched off.

2.5.5 Protection levels

In this field trial several protection levels were tested. For the L-band, protection level UEP3, UEP4 and UEP5 were evaluated.

Figure 2.30 shows the BER after FEC performance for UEP3, Figure 2.31 shows this for UEP4 and Figure 2.32 for UEP5. For error-free reception, the BER after FEC should be lower than 10^{-4} [24].

The L-band coverage measurements as well as the consumer receiver experiments revealed that the T-DAB receivers cannot decode the subchannel error-free for mode IV and a rural channel model in the L-band. Figure 2.29 depicts the BER for a UEP3 subchannel, and Figure 2.29 shows the speed of the route. There is a clear relation between speed and BER: if the speed is above 50 km/h (i.e. 15 m/s) the BER is unacceptably high.

In an L-band field trial in Canada [9], the maximum speed for mode IV was found to be 80 km/h and for mode II 180 km/h. As our measurements reveal a maximum speed of 50 km/h for mode IV, it seems that there are implementation errors in the RadioScape T-1000b DAB monitor. Mode II should thus be used for the L-band (which limits the maximum distance of the transmitters to 18 km). This mode can be received up to speeds of 180 km/h.

The areas with a high BER in Figures 2.30, 2.31 and 2.32 are due to the speed of the vehicle. From the figures it seems that protection level UEP4 is a good trade off between performance and capacity.

The maximum useable protection level obviously depends on the performance of the receiver, in our case the *RadioScape* RS-T1000b DAB monitor. In Chapter 4 it is shown that this receiver has very poor performance for the L-band (mode IV) and a rural channel model. For this reason, the results should be used with care.

An interesting question arises, namely what is the theoretical maximum useable capacity? This capacity could be reached if the most advanced algorithms are implemented in the receiver. Further research is needed to answer this question.

Figure 2.28: Speed of the measurement vehicle on the inner ring of Amsterdam

2.5. L-band results

Figure 2.29: BER after FEC of channel LH for protection level UEP3 and mode IV on the inner ring of Amsterdam

Figure 2.30: BER after FEC of channel LH for protection level UEP3

2.5. L-band results

Figure 2.31: BER after FEC of channel LH for protection level UEP4

Figure 2.32: BER after FEC of channel LH for protection level UEP5

2.5.6 SFN network gain

In Figure 2.25, the field strength of channel 12B for multiple measurement routes has been plotted. Figure 2.33 depicts the field strength of the network when a *single* transmitter is switched on. The difference between both figures can be considered as SFN gain. This gain can be up to 10 dB. During the coverage measurements, no occurrences of flat fading were measured.

(a) Aambeeldstraat

(b) Vredenhof

Figure 2.33: Field strength of channel LH when one transmitter is switched on at a time

2.5. *L-band results*

(c) de Bazel

(d) Oostzaan

Figure 2.33: Field strength of channel LH when one transmitter is switched on at a time (cont)

(e) Diemen

Figure 2.33: Field strength of channel LH when one transmitter is switched on at a time (cont)

Chapter 3

Indoor measurements

3.1 Introduction

This chapter describes the results of the indoor measurements. The indoor radio environment is not constant in time and location. This is due to the movement of people and the large number of objects in buildings that can reflect or scatter the radio signal [27]. A general introduction about the indoor and outdoor wireless channel can be found in [3]. For reproducibility reasons, the influence of moving objects (e.g. people) and bodyloss (mobile devices carried on the body) are measured separately. The results of these bodyloss experiments are presented in Section 4.3.

The distribution of field strength at a particular point tends to be log-normal distributed [19]. Variations are caused by time varying changes in the radio environment such as moving objects. In a static environment without moving objects, spatial field strength differences are much larger than in time. Moreover, in buildings, attenuation mainly depends on the distance from the outer wall (but is not linear as it also depends on the interior design) [28].

The received field strength depends on the antenna height of the receiver. At ground level the field strength is the lowest, as this level "sees" the most obstacles between the transmitter and receiver. For that reason,

indoor coverage is most critical at ground level.

In the past, several other indoor measurements have been conducted. In the UK, the *BBC* [4, 5, 6] has measured 39 objects for band III. In this research the median loss was 8 dB with a standard deviation of 4 dB. Good indoor coverage is achieved, if 95% of the locations are covered. For the *BBC* research this means that the indoor loss for 95% of the locations is 14.4 dB. Another research in the UK has been performed by the *NTL* [29]. This researched focussed mainly on large buildings, e.g. offices for band III. The indoor loss in this research was 20.0 dB for 95% of the locations. The L-band indoor penetration loss has been researched both in Germany and Canada. In Canada [9], the penetration loss was between 3 to 30 dB, with a typical value of 15 to 20 dB. In Dresden, Germany, a median indoor loss of about 10 dB has been measured [30]. Recently, the results have been published of a building indoor penetration loss survey in Sydney [31]. In this trial, the losses of both band III and the L-band were measured. This average loss for band III and the L-band for coverage in 95% of the locations were 18.8 dB and 22.4 dB, respectively.

The outline of this chapter is as follows. First the measurement setup is described. Before the indoor measurements can be carried out, calibration of the indoor measuring setup has to take place, so this is discussed next. The last part of this chapter consists of the results of the indoor measurements.

3.2 Measurement setup

Figure 3.1 shows a photograph of the measurement indoor unit. The unit has been built into a custom-made flight case for easy transportation. The setup of the indoor unit is very similar to the measurement vehicle. Figure 3.2 depicts the block diagram. For field strength measurements we used the *Rhode & Schwarz* ESPI, and for qualitative analysis of the DAB signal a *RadioScape* RS-T1000b DAB monitor was installed. A 20 m long RF cable (*Aircell* 7) is connected to the equipment with on the other side the antenna with an RF amplifier to compensate for cable and insertion losses.

3.2. Measurement setup

Figure 3.1: Photograph of the indoor unit

For the L-band the total loss is about 10 dB and for band III a similar value can be found due to the use of a passive splitter. The two RF switches (*DB products* 6SS1R31) allow selection of band III or L-band measurements.

For the band III, a custom-made dipole for channel 12 and *Mini-Circuits* (ZX60-3018G-S) amplifier was used with a passive 2-way splitter (*Mini-Circuits* (ZA2CS-500-15W-S)). For the L-band, the *European Antennas* VOA4-1500/054 antenna and a *Mini-circuits* (ZX60-2534M-S) amplifier was installed with an *ETL* active 2-way 0-dB splitter (DIV 04 L1 A-2322 S).

The indoor measurements are only relative measurements, so the only purpose of the amplifiers is to compensate for cable losses. Both antennas

Figure 3.2: Block diagram of the indoor unit

are installed on a small mast with a height of 73 cm (i.e. table height). Figure 3.3 presents the measurement setup of both antennas.

3.2.1 Method

According to the indoor research conducted in Dresden [30], the spatial variations of the field strength are much larger than the variations in time at one particular location. Moreover, the distribution of the field strength tends to be log-normal. The standard deviation of the spatial variations is 3.5 dB, while for time a value of 0.8 dB [30] was found. Other trials in Spain [32], Germany [8] and the UK [4, 5, 6, 29] found a slightly higher standard deviation. The research in Germany [8] indicated also that an SFN network will lower this value compared to a single transmitter.

The basic indoor measurement setup is to measure N points inside a building and M points outside. There is a tradeoff between the number of points (and therefore also the measurement time of one object) and the accuracy of the measurement.

To validate that the received signal has an log-normal distribution, we

3.2. Measurement setup

Figure 3.3: Indoor antennas

performed an endurance measurement in Amsterdam. This involved the measurement of the received signal of the L-band network every 96 ms for about three days¹. The histogram of the received signal is displayed in Figure 3.4, which indeed resembles a log-normal distribution.

In our research, we chose to measure for channel 12B, 12C and LH, 16 independent² points indoor (5 s each) and 8 independent points outdoor (10 s each). With the values reported in Dresden [30], this results in an accuracy of indoor loss of ± 1.6 dB with a confidence interval of 85%. An improvement of the accuracy to ± 0.8 dB would require 4 times more measurement points. The above scheme allowed us to perform an indoor measurement in 2 hours (typical time).

In the indoor unit, the laptop is the control center. The university has developed a program to configure the ESPI to the selected channel (12B, 12C or LH) and a bandwidth of 1.5 MHz with an integration time of 96 ms

¹The location was situated between the *Aambeeldstraat* and *Vredenhof* transmitter.

²Measurement points can be considered to be independent if the distance to other points is at least $\frac{1}{2}\lambda$.

Figure 3.4: Histogram of received signal (3 days, channel LH)

3.3. Results

(the duration of a DAB frame). Moreover, it selects the correct RF input of the RF switch.

In one measurement of 5 seconds, the ESPI is configured to measure 52 values. Simultaneously with these measurements, the DAB RS-T1000b monitor logs several parameters, which include time, BER before and after FEC, SNR, null symbol, constellation diagram and CIR. All log files are combined offline and processed in Matlab.

3.2.2 Calibration

The indoor measurements only focus on relative field strength (i.e. difference between outside and inside field strength). For that reason we only have to determine the antenna diagram of the antennas used.

Antenna diagram measurement

We determined the antenna diagram using the same procedure as in Section 2.3.2. For the purpose of these measurements, the antennas were mounted in a similar way as for the indoor measurements. The results are depicted in Figures 3.5 and 3.6. For both antennas, the field strength can be determined with an accuracy of ± 1 dB. As the ESPI has a smaller accuracy (± 1.5 dB), the accuracy of the ESPI will determine the accuracy of the indoor penetration loss measurements.

3.3 Results

This section presents the results of the indoor measurements. First, the results of one example indoor measurement are discussed. The second part describes the typical indoor loss for each channel.

3.3.1 Example of an indoor measurement

Figure 3.7 depicts the location of object where an indoor measurement has been conducted. It is located between the *Vredehof, de Bazel* and

Figure 3.5: Antenna diagram of the indoor antenna (band III, 12B)

Figure 3.6: Antenna diagram of the indoor antenna (L-band, LH)

3.3. Results

point no.	mean of loss [dB]	std. dev. loss [dB]	TII codes
1	+5.2	1.5e+00	3:3 (89)
2	+3.1	9.7e-01	3:3 (95)
3	+4.3	2.6e-01	3:3 (82)
4	+6.1	1.4e-01	3:3 (74)
5	+5.4	5.9e-02	1:1 (51) 3:3 (36)
6	+0.2	7.3e-02	3:3 (40)
7	-2.4	7.4e-02	3:3 (100)
8	+0.5	3.7e+00	3:3 (90)
9	+1.5	1.8e-01	3:3 (93)
10	+1.6	1.1e-01	3:3 (78)
11	+4.4	3.7e+00	1:1 (67)
12	+4.4	5.9e-02	1:1 (48) 3:3 (85)
13	+2.2	5.1e-02	1:1 (90) 3:3 (36)
14	+9.7	9.9e-01	1:1 (14) 3:3 (84)
15	+2.3	1.0e-01	1:1 (86)
16	-4.0	4.0e-02	n.a.

Table 3.1: Results of sample indoor measurement for channel 12B

Aambeeldstraat transmitters. It is important to note that the results are unique for each object. So the results of this object cannot be extrapolated to other objects.

Figure 3.8 and Table 3.1 show the results for channel 12B. Both the *Vredehof* and *Aambeeldstraat* transmitter can be received at this location. See Section 2.2.2 for the meaning of the TII codes. The values after the TII code give the relative field strength compared to other transmitters. The indoor loss is 2.8 dB.

Figure 3.9 and Table 3.2 reveal the results for channel 12C. For this network only the *IJ-mast* transmitter can be received. The loss is 4.5 dB which is slightly higher than the loss for the other band III network.

Figure 3.10 and Table 3.3 give the values for the L-band measurements.

Figure 3.7: Location of the sample object (legend: red = indoor location, blue= transmitters of pilot network, green = transmitters of *Publieke Omroep*) ©Google Maps

3.3. Results

Figure 3.8: Results of sample indoor measurement for channel 12B

Figure 3.9: Results of sample indoor measurement for channel 12C

Interestingly, the *de Bazel* transmitter cannot be received at this location. Probably the signal from this transmitter site is blocked by high buildings. The loss for channel LH is 10.4 dB.

3.3.2 Indoor penetration loss

The indoor penetration loss depends both on the construction materials used and on the location and surroundings of the object. For that reason we chose to measure many objects. During a 5-week measurement campaign, 49 objects were measured. The objects are mostly situated in an area where multiple transmitters can be received and where the outdoor field strength is high enough to allow an indoor measurement.

After the measurement campaign, we removed invalid indoor

3.3. Results

point no.	mean of loss [dB]	std. dev. loss [dB]	TII codes
1	+8.4	4.4e-01	1:9 (82)
2	+7.0	1.8e-01	1:9 (83)
3	+8.3	5.4e-01	1:9 (88)
4	+12.2	1.0e+00	1:9 (56)
5	+2.7	7.1e-02	1:9 (69)
6	+4.6	1.1e-01	1:9 (47)
7	+4.9	1.4e+00	1:9 (62)
8	+9.5	9.3e-01	1:9 (58)
9	+1.0	1.8e-01	1:9 (69)
10	+8.2	1.1e+00	1:9 (53)
11	+4.1	1.4e-01	1:9 (70)
12	+7.7	6.2e-01	1:9 (64)
13	-2.1	1.6e-01	1:9 (100)
14	-1.5	9.7e-02	1:9 (71)
15	+0.5	4.8e-01	1:9 (87)
16	-2.4	8.4e-02	1:9 (92)

Table 3.2: Results of sample indoor measurement for channel 12C

Figure 3.10: Results of sample indoor measurement for channel LH

3.3. Results

point no.	mean of loss [dB]	std. dev. loss [dB]	TII codes
1	+5.1	4.3e-01	1:1 (37) 3:3 (40)
2	+7.0	4.6e-01	3:3 (37)
3	+10.8	1.4e-01	1:1 (25) 3:3 (33)
4	+13.7	5.8e-01	1:1 (19) 3:3 (4)
5	+9.7	1.1e-01	3:3 (11)
6	+10.5	6.4e-01	3:3 (23)
7	+16.1	1.1e+00	3:3 (13)
8	+11.1	3.7e-01	3:3 (38)
9	+8.2	3.9e-01	3:3 (35)
10	+13.0	4.0e-01	1:1 (12) 3:3 (27)
11	+13.8	4.3e-01	3:3 (28)
12	+9.9	1.9e-01	3:3 (31)
13	+9.7	4.3e-01	3:3 (37)
14	+14.7	1.1e+00	3:3 (31)
15	+7.5	8.2e-01	3:3 (45)
16	+5.4	3.9e-01	3:3 (38)

Table 3.3: Results of sample indoor measurement for channel LH

Figure 3.11: Valid indoor locations, (legend: red = indoor locations, blue= transmitters of pilot network, green = transmitters of *Publieke Omroep*)
©Google Maps

locations. Examples of invalid locations are situations where indoor and outdoor measurements are at different heights³ or where the outdoor measurements are in the shadow of the building, resulting in a negative average indoor penetration loss. After this purge, 34 valid indoor locations remained. These locations are given in Figure 3.11.

³For practical reasons, it was not always possible to measure at the same height.

3.3. Results

Channel	σ_{place}	σ_{time}
band III 12B	3.8 dB	0.4 dB
band III 12C	3.6 dB	0.4 dB
L-band LH	3.4 dB	0.9 dB

Table 3.4: Standard deviation of the received signal σ_{time} and the standard deviation of the means of all measurement points σ_{place} for the indoor measurement points

Results

Figures 3.12, 3.13 and 3.14 present the histogram of the indoor loss for the individual measurement points⁴. As the indoor loss is defined as the *average* outdoor field strength minus the indoor field strength, a small portion of the distribution has an indoor gain instead of a loss.

The histogram of these points⁵ tends to have an *Extreme value* distribution [33], also known as the *log-Weibull* distribution. Applying the *Jarque-Bera* test⁶ to the indoor loss values also showed that these data cannot be considered as a log-normal distribution. This is an important conclusion as other indoor measurements reported a log-normal distribution.

Moreover, also the standard deviation of the spatial field strength variations and the variation of field strength in time were calculated for these indoor points (see Table 3.4). To calculate these values, the Statistics toolbox of *Matlab* was used. The histogram of the standard deviation in time tends to be a *Gamma* distribution [23] (Figure 2.12), while the standard deviation in place histogram tends to be a (log) normal distribution.

Figure 3.15 depicts the mean of the indoor loss for each object⁷. One can see that there is a relation between the losses of the three channels and

⁴A negative value means a loss.

⁵The Statistics toolbox of *Matlab* was used for fitting the appropriate distribution function.

⁶This test checks if the input data can be considered as a (log-) normal distribution.

⁷Only objects where all bands have valid indoor measurements are shown here.

Figure 3.12: Histogram of the indoor loss for channel 12B

Figure 3.13: Histogram of the indoor loss for channel 12C

3.3. Results

Figure 3.14: Histogram of the indoor loss for channel LH

Channel	μ	σ	95 %	99 %
band III 12B	-4.7 dB	5.8 dB	-22.1 [± 1.5] dB	-31.6 [± 2.1] dB
band III 12C	-5.4 dB	5.5 dB	-21.7 [± 1.5] dB	-30.7 [± 2.0] dB
L-band LH	-6.3 dB	6.6 dB	-25.8 [± 1.6] dB	-36.5 [± 2.3] dB

Table 3.5: Properties of the indoor loss distributions

the object.

In Table 3.5, the properties of distributions found in Figures 3.12, 3.13 and 3.14 are given. The 95% and 99% columns give the indoor loss values for which 95% or 99% of the indoor measurement points have a smaller loss. The value between brackets is the 95% confidence interval for these values.

Figure 3.15: Relation between object and indoor loss for each channel

Chapter 4

Consumer receivers

4.1 Introduction

This chapter describes the DAB receiver characteristics for consumer equipment intended for terrestrial and cable reception, operating in band III and L-band. The most interesting parts of this standard from the perspective of the T-DAB receiver experiments are the descriptions of the minimum RF performance levels and measuring methods.

There is not much previous work on the performance of T-DAB consumer receivers. Only in Canada [34] was the performance of L-band receivers investigated for an audio subchannel of 224 kbps using protection level UEP3.

The outline of this chapter is as follows. First, the consumer receivers that have been tested are presented. This is followed by the measurement setup and an evaluation of the performance of the professional *RadioScape* RS-T1000b DAB monitor, which was used in the coverage measurements (Chapter 2). Finally, the results of each experiment are discussed.

Figure 4.1: Distribution of the chipsets of the tested receivers

4.2 Consumer receivers

In our receiver experiments, we tested 15 consumer receivers (Table 4.1), which include different models (personal, portable and hi-fi) and chipsets (see Figure 4.1). Seven receivers also are able to receive the L-band.

This chapter discusses only the performance of the median receiver (both band III and L-band), which is compared to EN 50248 requirements. The median receiver for each experiment is defined as the receiver where 50% of the tested receivers have a better performance and 50% a worse performance.

The receivers are evaluated in four different experiments:

1. Sensitivity experiment
2. Adjacent interference experiment
3. Non-adjacent interference experiment
4. In-band interference experiment

4.2. Consumer receivers

Manufacturer	Model	Type
Perstel	DR 101	Personal
Pure Digital	TEMPUS-1	Portable
Morphy Richards	Ordio DAB 27015	Portable
FreeSky	FP-2200	Portable
Rebox	R102	Portable
Rebox	R105	Personal
i.Tech	XFM DAB Radio	Portable
i.Tech	BT Aviator 10M	Portable
Pure Digital	EVOKE-1XT	Portable
Pure Digital	Elan	Portable
Pure Digital	DRX-702ES	Hi-Fi
Pure Digital	DRX-701ES	Hi-Fi
Blaupunkt	Nashville DAB35	Car radio
Pure Digital	EVOKE-1XT Tri-Band	Portable
Trinloc	Inspiration	Portable

Table 4.1: Tested consumer receivers

In addition, we performed a bodyloss measurement for the two personal receivers (*Perstel* DR101 and *Rebox* R105).

4.2.1 Audio quality

All RF performance measuring methods in EN 50248 require BER measurements. Unfortunately a lot of consumer receivers do not have BER measurement capabilities. Therefore, we cannot use these measuring methods directly in the T-DAB receiver test. Instead of BER, we use the audio quality of the receiver as a performance measure. In order to determine the audio quality of a receiver, we apply a DAB signal mimicking a particular received RF signal condition to the RF (antenna) input of the receiver and record 25 seconds of the audio signal. We repeat this 15 times for the same received RF signal condition and concatenate the resulting recorded audio signals. The concatenated recorded audio signals

ODG	Description of impairments
0	Imperceptible
-1	Perceptible but not annoying
-2	Slightly annoying
-3	Annoying
-4	Very annoying

Table 4.2: Objective Difference Grade (ODG) scale.

are compared with a concatenated version of the original audio signal using Perceptual Evaluation of Audio Quality (PEAQ) measurement software [35]. This results in an Objective Difference Grade (ODG) indicating the perceptual difference between the recorded receiver audio signal and the original audio signal. The ODG scale ranges from 0 to -4, see Table 4.2.

In the remaining sections, the consumer receiver experiments that have been carried out are described, and further differences with the tests in EN 50248 are indicated. However, the bodyloss measurements will be discussed first.

4.3 Bodyloss measurements

Bodyloss is the loss of the received field strength due to bodyworn devices, i.e. the loss introduced by the human body. In this section, we discuss results from literature and compare these with the values we have measured in a simple experiment. Extensive bodyloss measurements are not within the scope of this research.

4.3.1 Literature

An extensive literature search using multiple source yielded only two useful articles. The first article [36] is about the bodyloss of handheld Global System for Mobile Communications (GSM) telephones. The

4.3. Bodyloss measurements

Figure 4.2: Bodyloss diagram of the Perstel DR101 receiver for band III

measured bodyloss (mean) in this article ranges from 0.9 to 16 dB. Moreover, the bodyloss for 44 persons was determined. It was concluded that the bodyloss varies from person to person as could have been expected.

The second article [37] lists some typical bodyloss values. For a hip-mounted device the bodyloss is 17 dB for a signal of 150 to 170 MHz.

4.3.2 Experimental results

To validate the results of the literature, we performed an experiment with the two available personal DAB receivers: the *Perstel* DR101 and the *Rebox* R105. In this experiment we set up a low power DAB transmitter on an SSM site. In the far field (>10 m), a person is located with the DAB receiver. This receiver was mounted in such a way that it mimics normal use.

The power of the transmitter was then reduced until audible bit-errors occurred in the selected MUSICAM subchannel. This experiment was carried out for 8 different angles (0 degrees is facing to the transmitter) and repeated by conducting the same experiment without any person. As

Figure 4.3: Bodyloss diagram of the Rebox R105 receiver for band III

Receiver	Minimal val.	Median val.	Maximal val.
Perstel DR101 (band III)	-0.6 dB	7.7 dB	26.6 dB
Rebox R105 (band III)	4.4 dB	12.9 dB	25.4 dB
Rebox R105 (L-band)	9.4 dB	17.8 dB	26.4 dB

Table 4.3: Bodyloss results

the headset is the antenna for band III, we mounted the DAB receiver including headset in the way a person would use it. The difference between the field strength in both experiments is an indication of the bodyloss. The accuracy of this experiment is about ± 3 dB (estimated). Figure 4.4 gives an impression of the test setup.

The results of the bodyloss experiments are depicted in Figures 4.2, 4.3 and 4.5.

4.3. Bodyloss measurements

Figure 4.4: Setup of the bodyloss measurements with and without test person

Figure 4.5: Bodyloss diagram of the Rebox R105 receiver for the L-band

4.3.3 Discussion

The experimental results reveal that there is a difference of 5 dB (mean) between the bodyloss of an earphone antenna and a normal band III antenna. In addition, there is a difference of 5 dB (mean) between the loss for band III and L-band. Compared with the few results from literature, it can be concluded that the measured results are in the same range. For band III the typical body loss is 10 dB; for the L-band it is 18 dB.

An interesting question arises whether the results derived from the bodyloss experiment mimic a realistic user scenario. In a normal environment, a person receives the radio signal from multiple directions due to reflection to objects and multiple transmitters. Therefore, actual bodyloss is expected to be lower than the measured loss. Further research is necessary to verify this assumption.

4.4 Measurement setup

To test the consumer receivers, we first captured the I/Q output of a Plisch DAB transmitter. For the band III consumer tests, DAB mode I was captured; for the L-band, mode IV was captured. See also Figure 4.6. After file capture, the appropriate segment was cut out of the file. This segment can be converted to a file with or without channel model, or it can be converted into an interference file. The generated files are used in the setup of Figures 4.7 and 4.8.

4.4.1 Setup

Figure 4.7 depicts the setup for the sensitivity and maximum input level experiment and Figure 4.8 for the (adjacent/non-adjacent) interference experiments and the in-band interference experiment. For Digital to Analog (DA) conversion, we used custom-built DA boards; for up-conversion the *Agilent* E4438C generator and *Rhode & Schwarz* SM300 were utilized. In both setups, PC3 is the master computer which controls

Figure 4.6: Block Scheme for file generation

all other equipment. It also captures the analog audio output of the Device Under Test (DUT) and calculates the ODG metric for each run.

4.4.2 Calibration

A *Rhode & Schwarz* ESPI was connected to the RF output after the analog combiner in order to calibrate the analog output of both RF generators.

4.5 Band III results

4.5.1 Performance of RadioScape RS-T1000b DAB monitor

This section discusses the performance of the *RadioScape* RS-T1000b DAB monitor which was used in the measurement vehicle. The goal of this section is to put the results in Chapter 2 into perspective. For the coverage measurements only the sensitivity and adjacent channel performance are relevant.

Figure 4.9 depicts the results of the sensitivity tests for the *RadioScape* RS-T1000b DAB monitor. More information about the sensitivity experiment can be found in Section 4.5.4. The DAB monitor is much more sensitive than the EN 50248 norm. It also has good sensitivity when a channel model is applied. The experiments with a strong adjacent interferer are shown in Figure 4.9. Also the DAB monitor meets the requirements for this experiment. More information about the adjacent channel experiments can be found in Section 4.5.5.

4.5.2 Audio quality versus BER

In the field trial measurements, the *RadioScape* RS-T1000b DAB monitor was used. To establish the relation between the consumer experiments and the field trial measurements, we tested this professional receiver as well. In addition, we logged both the BER before error correction (FEC) and the ODG to establish the relation between the ODG and the BER before FEC

4.5. Band III results

Figure 4.7: Block Scheme Sensitivity and maximum input level test

Figure 4.8: Block Scheme Interferer and in-band interference experiment

4.5. Band III results

(a) Sensitivity test using no channel model

(b) Sensitivity test using COST 207 urban area channel model

Figure 4.9: Sensitivity tests of the RadioScope RS-T1000b DAB monitor for band III

(c) Sensitivity test using COST 207 rural area channel model

Figure 4.9: Sensitivity tests of the RadioScape RS-T1000b DAB monitor for band III

4.5. Band III results

(a) Strong interferer at channel 12A using no channel model

(b) Strong interferer at channel 12C using no channel model

Figure 4.9: Adjacent channel interference tests of the RadioScape RS-T1000b DAB monitor for band III

(c) Strong interferer at channel 12A using COST 207 urban area channel model

(d) Strong interferer at channel 12C using COST 207 urban area channel model

Figure 4.9: Adjacent channel interference tests of the RadioScape RS-T1000b DAB monitor for band III

4.5. Band III results

(e) Strong interferer at channel 12A using COST 207 rural area channel model

(f) Strong interferer at channel 12C using COST 207 rural area channel model

Figure 4.9: Adjacent channel interference tests of the RadioScape RS-T1000b DAB monitor for band III

Figure 4.9: Audio quality versus sub BER before FEC for protection level UEP3

i.e. pseudo BER [38] for a subchannel with protection level UEP3. This relation is depicted in Figure 4.9.

If the BER before FEC drops below the $1.4 \cdot 10^{-2}$ the audio is not distorted. Therefore a rule of thumb can be established for the coverage measurement results: if the BER before FEC is below 10^{-2} , the audio quality is good for a subchannel with protection level UEP3.

4.5.3 Antenna factor measurements

At Astron, Dwingeloo we measured the Antenna Factor (AF) of consumer whip antennas for band III in an Anechoic chamber. L-band antennas are always internal antennas and could for this reason not be measured. For the measurement we used the antennas of three consumer receivers. In the chamber, a known field strength was applied, and by measuring the

signal power dB(mW)
-72
-75
-78
-81
-84
-87
-90

Table 4.4: Signal powers for determining sensitivity.

received power the Antenna Factor (AF) could be determined. For the consumer-receiver antennas, a typical AF of 25 dB was found. This value is about 9 dB worse compared to the AF of the band III antenna of the measurement vehicle (Section 2.3.1).

More information about the Antenna Factor (AF) experiment can be found in [39].

4.5.4 Sensitivity experiment

The sensitivity test is used to determine the ability of a receiver to receive weak signals. EN 50248 defines a minimum sensitivity requirement of -81 dB(mW) in a Gaussian channel. In the sensitivity measurement procedure of EN 50248, a DAB signal is applied to the antenna input of the receiver. The power of the signal is reduced until the measured BER reaches 10^{-4} for a subchannel with protection level UEP3. The sensitivity of the receiver is then defined as the input power at which the BER reaches 10^{-4} .

In the sensitivity test, we have determined the sensitivity of a receiver as follows: a DAB signal with a center frequency of 225.648 MHz (channel 12B) and a power of -72 dB(mW) is applied to the RF input of the receiver. The audio signal of the receiver, which is tuned to a UEP3 audio subchannel, is then recorded for 25 seconds. This is repeated 15 times and the resulting recorded audio signals are concatenated. The concatenated

recorded audio signals are compared with a concatenated version of the original audio signal to determine the ODG for this signal power level. The whole procedure is repeated for the other signal power levels in Table 4.4. The sensitivity of the receiver is defined as the input power at which the ODG drops below -1 .

EN 50248 also defines a minimum sensitivity requirement of -75 dB(mW) in Rayleigh channels. In the Rayleigh channel sensitivity measurement procedure of EN 50248, a DAB signal is passed through a channel simulator and applied to the antenna input of the receiver. EN 50248 defines two Rayleigh channel profiles for which the Rayleigh channel sensitivity measurements have to be performed. These are a COST 207 Typical Urban channel profile at a velocity of 25 km/h and a COST 207 Rural Area channel profile at a velocity of 120 km/h [40].

To determine the sensitivity in Rayleigh channels, we repeat our normal sensitivity test procedure with DAB input signals, to which either the COST 207 Typically Urban or Rural Area channel profile, defined in EN 50248, is applied. For each of the 15 runs that are performed for a single RF signal condition, a different realization of the channel model is used. Because the audio quality is calculated from the concatenated recorded audio signals, this ensures that the measurement period is long enough to determine an average audio quality. The sensitivity is again the input power at which the ODG drops below -1 .

Results

Figures 4.10a, 4.10b and 4.10c depict the results of the sensitivity experiments with different channel models for the median receiver (solid black line). The audio quality [ODG] is shown along the y-axis and the signal power [dBm] along the x-axis. In addition, three other lines are drawn. The vertical red line is the EN 50248 norm for this experiment, and the two dashed blue lines are the 25% and 75% border lines. For the 25% border this means that the best 25% of the tested receivers have a better performance than this line. The 75% line is defined in a similar manner.

The performance of the median consumer receiver meets the

4.5. Band III results

Adjacent channel signal power dB(mW)	ACS dB
-50	20
-45	25
-40	30
-35	35
-30	40

Table 4.5: Adjacent channel signal powers and ACS

requirements and is more than 10 dB more sensitive than EN 50248 prescribes.

4.5.5 Adjacent channel interference experiment

The Adjacent Channel Selectivity (ACS) test determines the ability of a receiver to receive a signal when a strong unwanted signal occurs in the frequency band next to the frequency band of the wanted signal. EN 50248 defines a minimum ACS requirement of ≥ 30 dB. The ACS measurement procedure of EN 50248 is defined as follows. The power level of the wanted signal at the antenna input of the DAB receiver is adjusted to -70 dB(mW). The signal power of the interfering unwanted signal at a frequency offset of 1.712 MHz is then increased until a BER of 10^{-4} is reached. The ACS is then defined as:

$$ACS = P_{unwanted} - P_{wanted} = P_{unwanted} + 70 [dB],$$

where $P_{unwanted}$ is the signal power of the interfering unwanted signal at which the BER reaches 10^{-4} .

In this experiment, the power level of the wanted signal with a center frequency of 225.648 MHz (channel 12B) at the antenna input of the DAB receiver is also adjusted to -70 dB(mW). The power level of the interfering unwanted signal in the adjacent channel is adjusted according to Table 4.5 corresponding with the ACS values that are indicated in the same table. The ODG of the audio signal of the wanted signal is determined for each

(a) Sensitivity test using no channel model

(b) Sensitivity test using COST 207 urban area channel model

Figure 4.10: Sensitivity tests of the consumer band III receivers

4.5. Band III results

(c) Sensitivity test using COST 207 rural area channel model

Figure 4.10: Sensitivity tests of the consumer band III receivers

of the adjacent channel power levels. The ACS is defined as the ACS value corresponding with the adjacent channel power level for which the ODG drops below -1. The experiment is performed with an interfering unwanted signal in a channel below (offset -1.712 MHz) as well as above (offset +1.712 MHz) the channel of the wanted signal. The ACS test is performed without channel profile as well as for the COST 207 Typically Urban and Rural Area channel profiles, although the last two are not required by EN 50248.

Figure 4.8 shows the setup for the (adjacent/non-adjacent) interference experiments and the in-band interference experiment.

Results

Figure 4.10 depicts the results of the adjacent channel interference experiments with the y-axis showing the audio quality [ODG] and the x-axis showing the power difference between both signals, the Signal-to-Interference Ratio (SIR) [dB]. In total six experiments were performed: an interfering unwanted signal in a channel below (offset -1.712 MHz, channel 12A) as well as in a channel above (offset +1.712 MHz, channel 12C) the channel of the wanted signal. In addition, this was tested for three channel models.

The median consumer receiver meets the EN 50248 norm for this experiment. The performance of a strong interferer higher than the wanted channel is slightly worse than that of a strong interferer lower than the wanted channel. In addition, the 25% worst performing consumer receivers do not meet the requirements for a strong interferer above the wanted channel.

4.5.6 Non-adjacent channel interference experiment

EN 50248 also defines a rejection of unwanted signals or far-off selectivity requirement and measurement. In the receiver tests this was replaced by a Non-Adjacent Channel Selectivity (NACS) test. The NACS test is similar to the ACS test. The only differences are that the interfering

4.5. Band III results

(a) Strong interferer at channel 12A using no channel model

(b) Strong interferer at channel 12C using no channel model

Figure 4.10: Adjacent channel interference tests of consumer band III receivers

(c) Strong interferer at channel 12A using COST 207 urban area channel model

(d) Strong interferer at channel 12C using COST 207 urban area channel model

Figure 4.10: Adjacent channel interference tests of consumer band III receivers (cont)

4.5. Band III results

(e) Strong interferer at channel 12A using COST 207 rural area channel model

(f) Strong interferer at channel 12C using COST 207 rural area channel model

Figure 4.10: Adjacent channel interference tests of consumer band III receivers (cont)

Non-adjacent channel signal power dB(mW)	NACS dB
-40	30
-35	35
-30	40
-25	45
-20	50

Table 4.6: Non-adjacent channel signal powers and NACS

unwanted signal is in the first non-adjacent channel (at a frequency offset of 3.424 MHz) and that the power levels of the interfering signals are higher (see Table 4.6). This means that the corresponding NACS requirements are higher as well. The NACS is defined as the NACS value corresponding with the non-adjacent channel power level for which the ODG drops below -1. The NACS test is performed without channel profile as well as for the COST 207 Typically Urban and Rural Area channel profiles.

Results

Figure 4.10 depicts the results of the non-adjacent channel interference experiments with the y-axis showing the audio quality [ODG] and the x-axis showing the power difference between both signals, the SIR [dB]. In total six experiments were conducted: a strong non-adjacent interfering unwanted signal in a channel below (offset -3.424 MHz, channel 11D) as well as in a channel above (offset +3.424 MHz, channel 12D) that of the wanted signal. In addition, this was tested for three channel models.

For a strong non-adjacent interferer below the wanted channel, the median receiver just meets the requirements. For a strong interferer with a frequency higher than that of the wanted channel, the median receiver has up to 10 dB (for the urban channel model) worse performance than required. Also one can see that the 25% worst performing consumer receivers have difficulties with all non-adjacent interferer experiments. Only the 25% best performing receivers meet the

4.5. Band III results

In-band noise signal power dB(mW)	SNR dB
-100	30
-95	25
-90	20
-85	15
-90	10
-75	5

Table 4.7: In-band noise signal powers and SNR

non-adjacent requirements set by EN 50248.

4.5.7 In-band interference experiment

In addition to the experiments based on EN 50248, we also defined an in-band interference experiment. This experiment determines the ability of a receiver to receive a signal with a low signal-to-noise ratio. It therefore gives an indication of the ability of a receiver to deal with in-band interference.

In the required SNR experiment the power level of the wanted signal, with a center frequency of 225.648 MHz (channel 12B) at the antenna input of the DAB receiver, is adjusted to -70 dB(mW). The power level of an in-band white Gaussian noise signal is adjusted according to Table 4.7 corresponding with the SNR values that are indicated in the same table. The ODG of the audio signal of the wanted signal is determined for each of the in-band noise power levels. The required SNR is defined as the SNR value corresponding with the in-band power level for which the ODG drops below -1. The required SNR experiment is performed without channel profile as well as for the COST 207 Typically Urban and Rural Area channel profiles.

(a) Strong interferer at channel 11D using no channel model

(b) Strong interferer at channel 12D using no channel model

Figure 4.10: Non-adjacent channel interference tests of consumer band III receivers

4.5. Band III results

(c) Strong interferer at channel 11D using COST 207 urban area channel model

(d) Strong interferer at channel 12D using COST 207 urban area channel model

Figure 4.10: Non-adjacent channel interference tests of consumer band III receivers (cont)

(e) Strong interferer at channel 11D using COST 207 rural area channel model

(f) Strong interferer at channel 12D using COST 207 rural area channel model

Figure 4.10: Non-adjacent channel interference tests of consumer band III receivers (cont)

Results

Figure 4.10 depicts the results of the in-band interference experiment, with the y-axis showing the audio quality [ODG] and the x-axis showing the power difference between both signals, the SIR [dB].

The median receiver requires an SNR of about 15 dB. This value is slightly higher than the value found in [41].

4.6 L-band results

Only the *FreeSky* FP-2200, *Rebox* R102, *Rebox* R105¹, *Pure Digital* DRX-702ES, *Blaupunkt* Nashville DAB35, *Pure Digital* EVOKE-1XT Tri-Band and *Trinloc* Inspiration are capable of receiving the L-band. The L-band receiver were tested in a similar manner as the band III receivers. The only differences were the channel used (channel LH) and the mode (mode IV).

Both mode II and mode IV are suitable for the L-band, but the latter allows a larger distance between transmitters [18]. For a commercial service, it is likely that mode II will be used instead of mode IV as the latter is only useable for speeds up to 80 km/h. (The field strength measurements in this report revealed that the maximum speed for mode IV is 50 km/h and not 80 km/h.) According to [34], the performance of a consumer receiver depends on the mode used. For that reason, the results shown in this section should be used with care.

4.6.1 Performance of RadioScape RS-T1000b DAB monitor

This section discusses the performance of the *RadioScape* RS-T1000b DAB monitor which was used in the measurement vehicle. The goal of this section is to put the results in Chapter 2 into perspective. For the coverage measurements in the L-band, only the sensitivity performance is important.

¹Due to synchronization problems, this receiver was tested.

(a) In-band interference using no channel model

(b) In-band interference using COST 207 urban area channel model

Figure 4.10: In-band interference tests of consumer band III receivers

4.6. L-band results

(c) In-band interference using COST 207 rural area channel model

Figure 4.10: In-band interference tests of consumer band III receivers (cont)

Figure 4.10 depicts the results of the sensitivity tests for the *RadioScape* RS-T1000b DAB monitor.

The sensitivity of the DAB monitor meets the requirements of the EN 50248 norm if no channel model or the urban channel model is applied. However, for the rural channel model, the DAB monitor receiver cannot decode the signal at all. Listening to the audio signal of the DAB monitor reveals that the audio signal is good at the start of a run, but that it degrades very quickly. For that reason, the BER results of the coverage measurements should be used with care.

4.6.2 Sensitivity experiment

Figures 4.10a, 4.10b and 4.10c depict the results of the sensitivity experiments with different channel models for the median receiver (solid black line). The y-axis shows the audio quality [ODG], and the x-axis shows the signal power [dBm]. In addition, three other lines are drawn. The vertical red line is the EN 50248 norm for this experiment, and the two dashed blue lines are the 25% and 75% border lines. For the 25% border line this means that the best 25% of the tested receivers have a better performance than this line. The 75% line is defined in a similar manner.

The performance of the median consumer receiver meets the requirements for the no-channel model and the urban area channel. For the rural area channel, the audio quality of the median receiver is too low for good reception.

The coherence time for the COST 207 L-band urban channel is 8.9 ms and for the rural model 4.6 ms. (For band III, the values are 73.7 ms for the urban channel model and 12.5 ms for the rural channel model.) The coherence time is the time that the channel can be considered as constant. For differential detection, such as Differential Quadrature Phase-Shift Keying (DQPSK) that is used in DAB, the channel has to be constant over two symbols for proper demodulation. The duration of an Orthogonal Frequency Division Multiplexing (OFDM) symbol for mode IV is 0.623 ms [42], so a properly designed DAB receiver should be capable of decoding

4.6. L-band results

(a) Sensitivity test using no channel model

(b) Sensitivity test using COST 207 urban area channel model

Figure 4.10: Sensitivity tests of the RadioScope RS-T1000b DAB monitor for L-band

(c) Sensitivity test using COST 207 rural area channel model

Figure 4.10: Sensitivity tests of the RadioScape RS-T1000b DAB monitor for L-band

the signal for a rural channel model. It is expected that the receivers will have a better performance for mode II in the L-band as the OFDM symbol time is smaller (0.312 ms [42]).

In Canada [34] (2004), the performance of L-band receivers was also investigated for mode II. This paper reached similar conclusions. Only one out of six receivers was capable of decoding the signal with the rural area channel model, and three were able to decode the urban area signal. So, compared to this paper, the performance of the receivers has improved.

In addition, the university has carried out a small experiment for a subchannel with protection level UEP3 and mode II. In this experiment, the audio quality of a RF signal level at -70 dBm has been manually evaluated for a short period. In these experiments no audible audio artefacts were noticed for all L-band receivers. Analysis of the COST 207 channel models support these results.

So, to obtain good audio quality in the L-band there are two options:

- Use mode II instead of mode IV, but this also affects the network topology: for mode IV the maximum distance is 37 km and for mode II it is 18 km[18].
- Add more protection to a subchannel (i.e. use protection level 1 or 2). However this also decreases the available capacity up to 30% compared with protection level UEP3. Additional research is required to verify this.

It should be noted that for in-house use, the L-band consumer receivers will work properly as the channel conditions are less severe compared to the rural channel model. Only T-DAB car receivers would be able to decode the signal for the rural channel model.

4.6.3 In-band interference experiment

Figure 4.10 depicts the results of the in-band interference experiment with the y-axis showing the audio quality [ODG] and the x-axis showing the power difference between the two signals, the SIR [dB].

(a) Sensitivity test using no channel model

(b) Sensitivity test using COST 207 urban area channel model

Figure 4.10: Sensitivity tests of consumer L-band receivers

4.6. L-band results

(c) Sensitivity test using COST 207 rural area channel model

Figure 4.10: Sensitivity tests of consumer L-band receivers (cont)

The median receiver requires an SNR of about 15 dB for the urban channel model. This value is less than the SNR value of 18 dB found in [41].

4.7 Typical sensitivity of a T-DAB consumer receiver

Another interesting question is whether the minimum sensitivity set by the *Wiesbaden* agreement can be achieved by a consumer receiver. In this section, the typical achievable sensitivity of a T-DAB receiver will be derived.

The sensitivity of a receiver is mainly determined by the combination of three factors:

1. Thermal noise (in semiconductor devices)
2. Noise figure of the analog RF front-end
3. The required Signal-to-Noise (SNR) ratio

Thermal noise

Every semiconductor device has a noise floor caused by thermal noise [43, 44]:

$$P = k_B T \Delta f \quad (4.1)$$

with

k_B The Boltzmann's constant: $1.38 \cdot 10^{-23}$ Joules per Kelvin

T The temperature in Kelvin (room temperature is 295 K)

Δf The signal bandwidth in Hertz

In dBm-scale this equation becomes for room temperature:

$$P = -174 + 10 \log(\Delta f) \quad (4.2)$$

4.7. Typical sensitivity of a T-DAB consumer receiver

(a) In-band interference using no channel model

(b) In-band interference using COST 207 urban area channel model

Figure 4.10: In-band interference tests of consumer L-band receivers

(c) In-band interference using COST 207 rural area channel model

Figure 4.10: In-band interference tests of consumer L-band receivers (cont)

4.7. Typical sensitivity of a T-DAB consumer receiver

In case of DAB, the signal bandwidth is 1.5 MHz and the noise floor becomes $P = -174 + 10 \log(1.5 \cdot 10^6) = -112$ dBm.

Noise figure

Each DAB receiver contains an analog RF front-end. This front-end introduces extra noise in the wanted DAB channel; this is called the Noise Figure (NF). A typical noise figure for a DAB front-end in band III and L-band is 6 dB [45]. This means that the noise floor in a receiver is increased by 6 dB.

Required Signal-to-Noise ratio

After the analog RF front-end, the SNR should be high enough to have a BER² below 10^{-4} . A BER below 10^{-4} means good reception [24]. In [45], a relation between SNR and BER is given, see Figure 4.10 for band III (mode I) and Figure 4.11 for L-band (mode 2). From this figure, one can conclude that the minimal SNR for band III is 15 dB for code rate $\frac{1}{2}$ (i.e. protection level UEP3)³; for the L-band it is 17 dB.

4.7.1 Typical sensitivity

The minimal sensitivity that a T-DAB receiver can have in band III is the sum of thermal noise, noise figure and required SNR: $-112 + 6 + 15 = -91$ dBm. For L-band the minimal sensitivity is: $-112 + 6 + 17 = -89$ dBm. (This is a worst case scenario of a rural area channel model with a speed of 130 km/h.)

Converted to field strength, these values are:

- band III: 41 dB μ V/m (-91 dBm (sensitivity for a rural channel model) + 122 (conversion to dB μ V/m)+ 10 (Antenna Factor with regards to a dipole antenna))
- L-band: 56 dB μ V/m (-89 dBm (sensitivity for a rural channel model) + 138.5 (conversion to dB μ V/m) + 6 [45] (Antenna Factor with regards to a dipole antenna))

²After error correction, i.e. the MPEG audio stream.

³We used protection level UEP3 in our receiver tests. See also [24].

Figure 4.10: The performance of DAB in a simulated Raleigh Channel, Mode 1, Rural environment, 130 km/h speed, Band III, taken from [45]

Figure 4.11: The performance of DAB in a simulated Raleigh Channel, Mode 2, Rural environment, 130 km/h speed, L-Band, taken from [45]

4.7. Typical sensitivity of a T-DAB consumer receiver

Thus, for band III, the minimal sensitivity is 6 dB less than the value set by the *Wiesbaden* agreement; for L-band the difference is 10 dB. The sensitivity of consumer receivers will be better for another channel model (urban: band III 2 dB and for L-band: 5 dB). Also a better (e.g. active) antenna will close the gap. The consumer receiver experiments showed that, for band III, the median receiver has a similar performance as the sensitivity derived in this section. For the L-band, however, the performance of the median receiver is, even for the urban channel model, 6.5 dB less than the performance of the rural channel model that is used in this section.

Summary

For a kitchen radio and assuming an urban channel model and a passive (whipe) antenna, the typically achievable sensitivity will be 39 dB μ V/m for band III and 51 dB μ V/m for the L-band.

Chapter 5

Summary

With the results presented in the previous chapters, the research questions in the introduction can now be answered. For purpose of convenience, each question and related answer are located in a separate section below.

Can a T-DAB network consisting of low-power transmitters with antennas mounted at relatively low positions (i.e. the pilot network) coexist with the existing T-DAB network consisting of high-power transmitters mounted at relatively high positions (i.e. Publieke Omroep network)?

In this report, a worst case scenario was investigated involving a high-mast and high-power T-DAB network of the *Publieke Omroep* at channel 12C and the low-mast and low-power pilot network at channel 12B. In Amsterdam, the IJ-mast of the *Publieke Omroep* radiates its main power in a south easterly direction with 2 kW ERP. The transmitters of the pilot network use an omnidirectional antenna with 200 W ERP.

In this setup, there is an interference area around the pilot transmitters where the strong signal of channel 12B will prevent reception of the multiplex at 12C. Due to the near vicinity of the *Aambeeldstraat* pilot location, there is no interference area for the pilot network around the IJ-mast. One of the solutions to suppress the interference areas is to use

a gap filler at channel 12C at the pilot transmitter sites. Other possible solutions such as a smaller vertical opening angle of the antenna system were not investigated.

If no gap fillers are used, the holes in the service area of the *Publieke Omroep* are a circle with a radius of ± 800 m for transmitter site *Diemen*, ± 1000 m for *Vredehof* and ± 1650 for *Oostzaan*. As the field strength of the *Publieke Omroep* is the lowest near *Oostzaan*, the hole in this service area is the largest. A gap filler of 880 mW which is 24 dB lower than the radiated power of the pilot transmitter, will be enough to neutralize the holes in the service area of the *Publieke Omroep*. The interference area around a high-power mast was not investigated, but it is expected that this interference area will be significantly larger. The T-DAB pilot network was mounted on masts of the C2000 TETRA network. The interference of the T-DAB signal on the TETRA communication system was investigated by the C2000 organization.

What is the performance of consumer T-DAB receivers currently on the market compared to the reference *Wiesbaden* receiver?

For band III, the median T-DAB consumer receiver has a better or equal performance than the reference receiver (using mode I) specified by the EN 50248 norm. Only for strong adjacent interferers does the median receiver have a performance up to 10 dB worse than required. Only the 25% best performing receivers meet the non-adjacent requirements set by EN 50248.

As the L-band is expected to be issued to one multiplex operator, the adjacent and non-adjacent interference will be caused by the same operator. For that reason, the adjacent and non-adjacent performance have no relevance for the L-band licenses. The median T-DAB L-band receiver has a better or equal performance compared to the EN 50248 norm (using mode IV), except for the rural channel model. The rural channel model mimics a rural environment at a velocity of 120 km/h. Using mode II instead of mode IV is likely to increase the performance of the receivers for this situation. This is supported by the results of a short experiment using

Band	μ	σ	95%
band III	-5.1 dB	5.7 dB	-21.9 [± 1.5] dB
L-band LH	-6.3 dB	6.6 dB	-25.8 [± 1.6] dB

Table 5.1: Properties of the indoor loss distributions

mode II. For in-house use, the L-band consumer receivers are expected to work properly as the channel conditions are less severe than for the rural channel model. The rural channel model is important for T-DAB car receivers. Another option is to use a lower protection level, but this also decreases the available capacity up to 30% compared with protection level UEP3.

For a kitchen radio and assuming an urban channel model and a passive (whipe) antenna, the typical achievable sensitivity will be 39 dB μ V/m for band III (which is 4 dB higher than the minimum sensitivity specified in the *Wiesbaden* agreement); for the L-band it is 51 dB μ V/m (5 dB higher). The median T-DAB consumer receiver achieves the typically achievable band III sensitivity. However, for the L-band, the sensitivity of the median T-DAB consumer receiver is 6.5 dB less the typically achievable L-band sensitivity.

What is the indoor penetration loss for both band III and the L-band?

The indoor penetration loss depends on the percentage of the buildings that have to be covered. For good indoor coverage, it is assumed that 95% of the buildings have to be covered. Using this value, the loss for band III is 21.9 dB and for L-band 25.8 dB. See also Table 5.1. (A negative value means a loss.) In this table, the values between brackets are the 95% confidence intervals. The indoor penetration loss values are slightly higher than the values found in literature (see Chapter 3).

In the Final Acts of the RRC06 conference [46], an indoor penetration loss of 16 dB was used for band III, which is 6 dB less than the value derived in this report.

	band III outdoor	band III indoor
Sensitivity	39 dB μ V/m	39 dB μ V/m
Indoor loss (95%)	-	21.9 dB
99% to 50% place	7.0 dB (13 dB)	7.0 dB (13 dB)
Req. outdoor field strength	46.0 dB μ V/m (52.0)	67.9 dB μ V/m (73.9)

Table 5.2: Link budget for band III

Which network architecture can provide indoor coverage that meets the current *Wiesbaden* agreement [2]?

A link budget has to be constructed to answer this question. For each band, two link budgets will be calculated: outdoor and indoor coverage with a portable radio (without the influence of the human body).

For band III, a consumer receiver with a whip antenna can have a minimum field strength of 39 dB μ V/m. For the L-band this value is 51 dB μ V/m. For outdoor coverage the value is converted to 50% of the locations. The same settings were also used in the coverage measurements. Indoor coverage is calculated in a similar way, but now indoor penetration loss is added. The results are shown in Tables 5.2 and 5.3.

For conversion from 99% to 50% of the locations (i.e. $2.33 \cdot \sigma_{place}$), we used values from the indoor and coverage measurements. The values between brackets are those according to the *Wiesbaden* agreement. Apparently, an SFN network reduces the spatial standard deviation. The field trial yielded a spatial standard deviation of 2.2 to 2.8 dB (outdoor) instead of 5.5 dB according to *Wiesbaden* [2].

In the UK [29] a minimum outdoor field strength for indoor coverage of 71 dB μ V/m was found. This value is 3 dB higher than the required field strength found in this report. In the Final Acts of the RRC06 conference [46] a value of 66 dB μ V/m was derived for indoor coverage in 95% of the indoor locations.

	L-band outdoor	L-band indoor
Sensitivity	51 dB μ V/m	51 dB μ V/m
Indoor loss (95%)	-	25.8 dB
99% to 50% place	5.1 dB (13 dB)	5.1 dB (13 dB)
Req. outdoor field strength	56.1 dB μ V/m (64.0)	81.9 dB μ V/m (89.8)

Table 5.3: Link budget for the L-band

For indoor coverage the outdoor field strength for band III has to be 67.9 dB μ V/m and for L-band 81.9 dB μ V/m, for 50% of the locations and 50% of the time at an antenna height of 1.5 m. This value can be used in coverage planning software. For bodyworn devices (mobile telephones, personal radios) these values should be increased by 10 dB for band III and 18 dB for the L-band. In received power values [dBm] the difference between these values is 14.0 dB whereas the difference in Antenna Factor (AF) is 16.5 dB. So, the field strength requirements of the L-band network are 2.5 dB less than for band III.

On the other hand, this value can only be achieved if the sensitivity performance of the L-band consumer is improved. Current L-band T-DAB consumer receivers are 6.5 dB less sensitive than the typically achievable L-band sensitivity. Band III receivers on the other hand have a sensitivity equal to the typically achievable band III sensitivity.

Figure 5.1, 5.2 and 5.3 present the current indoor reception for the three networks using the values derived in this section. In Figure 5.2 there is indoor coverage around every pilot site, because the gap fillers were switched on. With the current network configuration, there is no good indoor coverage for both band III and L-band in Amsterdam.

Good indoor coverage can be obtained by increasing the power level or using more transmitter locations. In Figures 5.4, 5.5 and 5.6, the expected indoor reception is shown when the output power of each transmitter location is increased by 10 dB. For both band III networks this results in

good indoor coverage. Another option is of course to use more transmitter locations. For the L-band, more transmitters as well as more output power are required for good indoor reception in Amsterdam.

However, current international regulations are based on outdoor coverage and it was decided at the RRC06 conference [46] that the interference level at the Dutch border may increase by 3 dB and it in particular cases by 6 dB to achieve indoor coverage. So, both the high-mast and low-mast topologies require more transmitter locations to obtain indoor coverage and to be in line with the RRC06 agreement.

Figure 5.1: Indoor reception of channel 12B with the current pilot network configuration (green is indoor reception, red no indoor reception)

Figure 5.2: Indoor reception of channel 12C with the current *Publieke Omroep* network configuration (green is indoor reception, red no indoor reception)

Figure 5.3: Indoor reception of channel LH with the current pilot network configuration (green is indoor reception, red no indoor reception)

Figure 5.4: Expected indoor reception of channel 12B with the current pilot network configuration with 10 dB extra transmit power at each location (green is indoor reception, red no indoor reception)

Figure 5.5: Expected indoor reception of channel 12C with the current *Publieke Omroep* network configuration with 10 dB extra transmit power at each location (green is indoor reception, red no indoor reception)

Figure 5.6: Expected indoor reception of channel LH with the current pilot network configuration with 10 dB extra transmit power at each location (green is indoor reception, red no indoor reception)

References

- [1] EZ. *TP/OT 4051169: offerte aanvraag voor wetenschappelijk onderzoek betreffende TDAB*, 2004.
- [2] CEPT. *FINAL ACTS of the CEPT T-DAB Planning meeting (3)*. Maastricht, 2002.
- [3] J. Bach Andersen, T.S. Rappaport, and S. Yoshida. *Propagation Measurements and Models for Wireless Communications Channels*. IEEE Communications Magazine, January 1995.
- [4] M.C.D. Maddocks, I.R. Pullen, and J.A. Green. *Digital Audio Broadcasting: Measuring techniques and coverage performance for a medium power VHF single frequency network*. BBC research, (2), 1995.
- [5] J.A. Green. *Building penetration loss measurements for DAB signals at 211MHz*. BBC research, (14), 1992.
- [6] M.C.D. Maddocks, I.R. Pullen, and J.A. Green. *Field trials with a high-power VHF single frequency network for DAB: Measurement techniques and network performance*. EBU Technical Review, (Autumn), 1994.
- [7] V. Erikilä and M. Jokisalo. *DAB field trials in Finland*. EBU Technical Review, (Autumn), 1994.

- [8] A. Lau, M. Pausch, and W. Wütschner. *First results of field tests with the DAB single frequency network in Bavaria*. EBU Technical Review, (Autumn), 1994.
- [9] G. Chouinard, F. Conway, W.A. Stacey, and J.R. Trenholm. *Digital Radio Broadcasting in Canada: A strategic approach to DRB implementation*. EBU Technical Review, (Winter), 1994.
- [10] ITU-R. *Recommendation ITU-R P.1546-1: Method for point-to-area predictions for terrestrial services in the frequency range 30 MHz to 3000 MHz*. 2003.
- [11] European Radiocommunications Committee (ERC). *Field strength measurements along a route with geographical coordinate registrations, ERC/REC/(00)08*. Technical report, 2003.
- [12] W.C.Y. Lee. *Estimate of local average power of a mobile radio signal*. IEEE Transactions on Vehicular Technology, 34(1):22 – 27, February 1985.
- [13] <http://www.mathworks.com>.
- [14] db Europe BV. *Bill of Materials DAB pilot*. Technical report, 2005.
- [15] http://www.plisch.de/?id=162&id_lc=25&mode=id&id_go=162.
- [16] <http://www.anik.ca/satellites/transmissions/delay-response-times.htm>.
- [17] C.J. Bovy, H.T. Mertodimedjo, G. Hooghiemstra, H. Uijterwaal, and P. van Mieghem. *Analysis of end-to-end delay measurements in Internet*. PAM, 2002.
- [18] W. Hoeg and T. Lauterbach, editors. *Digital Audio Broadcasting: Principles and applications of Digital Radio*. Wiley, second edition, 2003.
- [19] A.A. Smith. *Radio Frequency Principles and Applications. The Generation, Propagation, and Reception of Signals and Noise*. IEEE Press, 1998.

References

- [20] ANSI. C63.5: *American National Standard for Electromagnetic Compatibility - Radiated Emission Measurements in Electromagnetic Interference (EMI) Control - Calibration of Antennas (9 kHz to 40 GHz)*. 1998.
- [21] A.A. Smith. *Standard-Site Method for Determining Antenna Factors*. IEEE Transactions on Electromagnetic Compatibility, 24(3):316–322, 1982.
- [22] CEPT. *FINAL ACTS of the CEPT T-DAB Planning meeting (4)*. Maastricht, 2002.
- [23] <http://mathworld.wolfram.com/GammaDistribution.html>.
- [24] CENELEC. *Characteristics of DAB Receivers*. EN 50248, 1999.
- [25] ITU-R. *Recommendation ITU-R P.370-7: VHF and UHF propagation curves for the frequency range from 30 MHz to 1000 MHz*. 1995.
- [26] B. Breton, R. Voyer, and D. Jacques. *Coverage design aspects of L-band DAB with transmission modes II and IV*. International Broadcasting Conference (IBC), September 1997.
- [27] N. Yarkoni and N. Blaunstein. *Prediction of Propagation Characteristics in Indoor Radio Communication Environments*. Progress in Electromagnetic Research, PIER-59, 2006.
- [28] A.A. Smith. *Attenuation of Electric and Magnetic Fields by Buildings*. IEEE Transactions on Electromagnetic Compatibility, 20(3), 1978.
- [29] S. Mason. *Indoor reception of DAB - consequences for planning and implementation*. EBU Technical Review, July 2004.
- [30] O. Michler and M. Strey. *DAB-Indoor-Versorgung im L-band*. SLM, 1998.
- [31] W. Dickson. *T-DAB Sydney Trial: Building penetration loss Survey for band III and L-band TDAB*. October 2005.

- [32] M.M. Velez, P. Angueira, D. de la Vega, and A. Arrinda J.L Ordiales. *L-band DAB Eureka 147 Field Trials and Coverage Measurements in Urban Areas*. IEEE Transactions on Broadcasting, 48(2), June 2002.
- [33] <http://mathworld.wolfram.com/ExtremeValueDistribution.html>.
- [34] A. Carr and B. McLarnon. *DAB-T receiver performance characterisation*. International Broadcasting Conference (IBC), September 2004.
- [35] M. Kahrs and K. Brandenburg, editors. *Applications of Digital Signal Processing to Audio and Acoustics*, chapter 1. Audio quality determination based on perceptual measurement techniques. Kluwer Academic Publishers, 1998.
- [36] G.F. Pedersen, K. Olesen, and S.L. Larsen. *Bodyloss for Handheld Phones*. In *Proceedings of the 49th Vehicular Technology Conference*, volume 2, pages 1580–1584, Houston, Texas, USA, May 1999.
- [37] General Electric Company. *Two-way Personal Radio System Design*. <http://www.softwright.com/faq/engineering/Building%20and%20Body%20Loss%20Values.html>.
- [38] R. Schramm. *Pseudo channel BER - an objective quantity for assessing DAB coverage*. EBU Technical Review, Winter 1997.
- [39] M.J. Norden (Astron). *T-DAB field strength measurements*. January 2006.
- [40] M. Pätzold. *Mobile Fading Channels*. John Wiley & Sons, 2002.
- [41] Y.H Jeong, S.R. Park, and S.I. Lee. *Evaluation of Protection Ratios on COFDM for In-band adjacent-channel Digital Audio Broadcasting*. Proceedings of IEEE Region 10 International Conference on Electrical and Electronic Technology, 2001.
- [42] ETSI. *Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers*. ETSI EN 300 401, 2001.

References

- [43] Wikipedia. *Johnson-Nyquist noise*. http://en.wikipedia.org/wiki/Thermal_noise.
- [44] P.Z. Peebles. *Probability, random variables and random signal principles*. McGraw-Hill, third edition, 1993.
- [45] ETSI. *Digital Audio Broadcasting (DAB); Signal strengths and receiver parameters; Targets for typical operation*. ETSI EN 101 758, 2001.
- [46] *Final Acts of the Regional Radiocommunication Conference 2006 (RRC-06)*. <http://www.itu.int/ITU-R/conferences/rrc/rrc-06/index.asp>.

Acronyms

ACS Adjacent Channel Selectivity

AF Antenna Factor

BER Bit Error Rate

CDF Cumulative probability Density Function

CEPT European Conference of Postal and Telecommunications
Adminstrations

CIR Channel Impulse Response

DA Digital to Analog

DAB Digital Audio Broadcasting

DIQ Digital baseband In-phase and Quadrature

DQPSK Differential Quadrature Phase-Shift Keying

DUT Device Under Test

ERP Effective Radiated Power

ETI Ensemble Transport Interface

FEC Forward Error Correction

GPS Global Positioning System

GSM Global System for Mobile Communications

I/Q Inphase/Quadrature

MUSICAM Masking pattern adapted Universal Subband Integrated Coding And Multiplexing

NACS Non-Adjacent Channel Selectivity

NF Noise Figure

ODG Objective Difference Grade

OFDM Orthogonal Frequency Division Multiplexing

PC Personal Computer

PEAQ Perceptual Evaluation of Audio Quality

PRBS Pseudo Random Bit Sequence

RF Radio Frequency

SFN Single Frequency Network

SIR Signal-to-Interference Ratio

SNR Signal-to-Noise Ratio

T-DAB Terrestrial Digital Audio Broadcasting

TII Transmitter Identification Information

UEP Unequal Error Protection

SSM Standard Site Method