Chapter 4

Vertical System Functions

4.1. Summary

This chapter discusses the roles and effects of *vertical system functions (VFs)*, which provide the required system functionality to address the needs of the CO applications.

4.2. Introduction

In the scope of this book, a CO is defined as a collection of sensors, actuators, controllers or other COs that communicate with each other to achieve, more or less autonomously, a common goal. This recursive definition accounts for the cases where groups of COs can be regarded as a single CO. Such arrangements enable them to combine hardware and software components to support advanced sensor applications. Thus, organizing such components into a framework that can cope with the inherent complexity of the overall CO system will be an important exercise for developers.

The list below of key points in the design space of a CO is based on the requirements set for the wireless sensor platforms developed independently at UCLA and UC Berkeley [37, 48]:

- *Small physical size*: reducing physical size has always been one of the key design issues. For instance, some applications will need more powerful CO units than others.

Chapter written by Marcelo PIAS, George COULOURIS, Pedro José MARRÓN, Daniel MINDER, Nirvana MERATNIA, Maria LIJDING, Paul HAVINGA, Şebnem BAYDERE, Erdal ÇAYIRCI and Chiara PETRIOLI.

Hence, COs are likely to be heterogenous devices in terms of processing, communication and sensing capabilities. Such diversity poses the challenge to find the right balance between the physical device size and the minimal set of required hardware subsystems to be implemented in a CO.

- *Low power consumption:* energy limits processing, lifetime and interconnect capabilities of the basic CO device. The system should make efficient use of the resources striving to minimize the overall power consumption. As a result, this will increase the CO active time without battery recharging, which is an issue for a set of applications such as large-scale forest fire monitoring.

- *Concurrency-intensive operation:* data will be frequently gathered from local sensors or received from other COs. They are then processed through filtering/aggregation, and sent to other COs through the network. These tasks should be carried out simultaneously in order to achieve the target sensing and actuation goals at the highest performance. Therefore, strict resource sharing and task scheduling are key design issues.

- *Diversity in design and usage:* networked sensor devices will tend to be application-domain specific providing only the necessary hardware support. For instance, sensors and actuators built for medical healthcare applications exhibit more complexity when compared to simpler sensors used in environmental monitoring. Therefore, the hardware and software framework of a CO should facilitate trade-offs among component reuse, cost and efficiency.

- *Robust operation:* CO devices will be numerous and deployed over a large environment. The individual devices should be carefully designed to have reliability as one of the key properties. Although device failures can be overcome with distributed fail-over techniques, this approach should be avoided whenever possible because of the communication costs incurred. COs need autonomous management abilities to self-test, self-calibrate and self-repair as recently advocated in [56, 62].

- *Security, privacy and trust:* each CO should have sufficient security mechanisms in place to prevent and counter unauthorized access, denial-of-service attacks and unintentional damage of the locally stored information. These mechanisms need to be considered in the design phase in order to make them pervasive throughout the system.

- *Compatibility:* the cost to develop software components dominates the cost of the overall system. It is important to be able to reuse code developed for other systems.

- *Flexibility:* the CO system will evolve over time both in terms of hardware and software. Support for this growth can be introduced in the system through hardware programmability and reconfiguration by using programmable processors and FPGA-based platforms. Also, software modularity introduces flexibility and should be prioritized during the system design.

The question that arises is whether any available real-time operating system (RTOS) suits this list of requirements. Some researchers believed that traditional

RTOS was unsuitable and therefore designed alternatives such as the micro-threaded operating system TinyOS [48]. Whether this new OS is entirely appropriate for a CO system remains to be investigated. As advanced sensor applications emerge, it is likely that the emphasis will be put on the design of more complex micro-electro-mechanical (MEMS) sensors as already suggested in [129]. To support this sensor development, a CO system will be built from powerful resources that need more implemented functionality and efficient interactions than those currently offered by TinyOS. Readers are referred to Chapter 5 for a comprehensive discussion on CO systems and architectures.

The rest of the chapter is organized as follows: section 4.3 defines a VF in the context of COs. Section 4.4 briefly discusses the characteristics and requirements of the CO applications studied in Chapter 2. Different types of VFs to address these application needs are then discussed including context and location management, data consistency, and communication and security, to name just a few. Section 4.5 gives a summary of the VFs discussed in the chapter and concludes with some final remarks.

4.3. Vertical System Function (VF)

The current operating systems proposed for WSNs and COs cannot offer all the required functionality to the applications. Thus, a VF is defined in this chapter as the *functionality that addresses the needs of applications in specific domains and in some cases a VF also offers minimal essential functionality that is missing from available RTOS*.

Figure 4.1 introduces a simplified architectural view of an application example originally discussed in [48]. The goal is to monitor the temperature and light conditions of an area and periodically transmit their measurements to a central base station. In this example, there are three VFs that applications may “invoke”: the communication subsystem (core system function), the light sensors and temperature sensors (application specific functions). Each VF is represented in the diagram by a vertical stack of components. We envisage that *standardized APIs* will create mechanisms for linking applications to vertical functions.

A component, represented by the labeled box in the diagram, is defined as a self-contained unit of code that encapsulates its implementation and interacts with its environment by means of well-defined interfaces. Such an interaction can be achieved through a *software wiring* process that connects the output ports of a component to the input ports of another one. The composition of components can be represented as a system configuration graph, where components are vertices and their interconnects form the graph edges [24, 48, 61].

The essence of component interactions is twofold. The *control* interaction handles the requests for data to lower-level components (top-down). In contrast, the *data* interaction deals with the requested data by creating a bottom-up data flow path between components. This is shown in the figure as vertical lines with arrows.

Figure 4.1. Example of VFs: temperature and light sensing application

The component wiring process will facilitate the synthesis of individual components into a larger-scale system. Components may be grouped together to form more concise modules [24, 81]. The CO system may be arranged into several *levels of abstraction*, from the most abstract (closest to the application) down to the most concrete (closest to the hardware devices). Abstraction allows better software structuring for clarity and reuse. Although layers are natural consequences of arranging components in the system, they are not a design requirement.

The implementation of a VF will follow a layered approach when the system architecture is designed in such a way. Although layered architectures facilitate key design properties such as flexibility and abstraction levels, they require attention to conformance and can severely impact performance in systems that lack hardware resources, for instance, low-power wireless sensor platforms.

The question to address in this case is how we map a general layered CO system architecture to a resource-constrained hardware platform without sacrificing overall performance. Ideally, we seek to minimize the overhead imposed on the system by the various components and levels of abstraction. It is important to note that critical

real-time applications such as control of industrial plants may not tolerate high system response times.

To achieve an energy-efficient design, the traditional strict modularization or layering is not appropriate. In WSNs, for instance, monolithic design of communication software is used to reach the required energy-efficiency needs. However, such a design choice makes system development and management very difficult.

An approach that can be used to improve performance in systems low in resources is to implement the VF using *cross-layer* interactions, where the software components do not necessarily interact with components immediately above or below in the abstraction level [75]. For instance, most abstract components (closest to the application) may bypass other components and interact directly with the most concrete components (closest to the hardware). The cross-layer design explored in [28, 40] have shown promising results in reducing power consumption.

The architectural framework introduced in Figure 4.1 refers to a stand-alone CO. We believe that in practice there will be collections of COs in constant interaction to accomplish a pre-assigned goal. In some application scenarios, VFs will be implemented through a chain of software components that may or may not be within the operational boundaries of a single CO, but rather distributed in the network. For example, a VF that is responsible for collecting temperature readings of rooms in an office building needs distributed coordination among COs located in each room in order to implement the intended functionality.

4.4. Types of vertical system functions

The set of characteristics exhibited in CO applications are more diverse than those found in applications of traditional wireless and wired networks. Critical factors impact the architectural and protocol design of such applications. These factors also introduce some strict constraints.

Chapter 2 examined this set of characteristics and requirements. Below, we briefly review the relevant ones and discuss the most suitable VFs to address them. The reader should refer to Chapter 2 for a comprehensive study on selected COs applications.

Network topology: in a CO application, nodes may communicate directly provided they are geographically close to each other. Such a communication can be established in a *single-hop* network topology. When nodes are located far from each other, they need to rely on third nodes to forward their data packets, therefore requiring a *multi-hop* sensor network. VFs which may offer direct support to this characteristic are *communication* (section 4.4.3) and *distributed storage and data search* (section 4.4.5).

Scalability: the number of COs that may support an application can vary depending on the environment where it is deployed and on its task. This property is important in outdoor applications and it is often a design issue for techniques for *distributed storage and search*. As the system scales up, consistency of the data gathered from multiple sources should be addressed in an efficient manner. The *data consistency* functionality is extensively discussed in section 4.4.2.

Fault tolerance: it is very possible that some COs may fail during the operation of the network for various reasons including battery discharge and harsh environmental operation conditions. The *data consistency* VF tackles some of the issues associated with node failures. In addition, the *communication* VF should provide the data communication resilience required by the applications. Fault tolerance is also closely related to the *security* VF (section 4.4.4) since node failures may be caused by attackers.

Localization: there exist several CO applications for target tracking and physical event detection, including intrusion and forest fire, that require node and/or target localization. GPS may be the natural choice for calculating a node's location. These devices, however, do not work in indoor areas and still carry a high cost for low-power sensor nodes. The *context and location management* VF (section 4.4.1) reviews the most recent research advances in this area.

Time synchronization: applications need to establish a common sense of time among the COs participating in their sensing and actuation goals. Such a functionality can be offered through a *time synchronization* VF (section 4.4.8).

Security: the CO system may be threatened by unauthorized users trying to access the network. Also, there are security risks on the physical layer of the network. For example, a jamming signal may corrupt the radio communication between the entities in the mission-critical networks. In a CO, security is pervasive and must be integrated into every system component to achieve a secure system. Thus, the security functionality is likely to be offered at different levels and not exclusively by the *security, privacy and trust* VF.

Data traffic characteristics: the amount of data traveling inside the network determines the traffic characteristics of an application. In a particular application, the data transferred among nodes may be limited to a few bytes for simple measurements whereas heavy video-audio traffic may be conveyed in another application scenario. At least three VFs can provide the adequate support for different types of traffic. The *communication* and *distributed storage and data search* for high-level dissemination of sensor data offer mechanisms for transferring the data of interest in the network. In addition, the *data aggregation* (section 4.4.6) provides an energy-efficient optimization tool for various types of data traffic.

Networking infrastructure: CO networks can be *infrastructured* or *infrastructureless* (*ad hoc*). In some applications, the data can be collected by some mobile

nodes when passing by the source nodes. This is an important characteristic that determines the type of system approach used (with or without supporting infrastructure) in the majority of VFs surveyed in this chapter including the techniques for *context and location management* VF and MAC layer/routing protocols in the *communication* VF.

Mobility: in some applications, all physical components of the system may be static whereas in others, the architecture may contain mobile nodes. Applications which can benefit from autonomous robots for actuation may require special assistance for mobility. Adequate support for medium and high mobility in multi-hop networks is still an open issue that should be addressed in the implementation of future VFs such as *context and location management*, *communication* and many others.

Node heterogeneity: the majority of CO applications include nodes that have distinct hardware and software technical specifications. In a precision agriculture application, for instance, there may exist various types of sensors such as biological and chemical. Energy may be limited in some of the nodes. Thus, the *data search VF mechanism* needs to be energy-efficient. Also, data will originate from different sensor nodes so that adequate schemes for ensuring consistency of heterogeneous sensor data must be used. This can be offered to the CO application through the *data consistency* and *aggregation* VFs.

Power awareness: power consumption is one of the performance metrics and limiting factors in almost any CO application. Systems require prolonged network lifetimes. Thus, efficient power consumption strategies must be developed. Power-aware communication protocols are supported in the *communication* VF. Also, as more complex sensors are designed – for instance in healthcare applications – there is a growing need for tighter control on nodes' resources to save energy. The *resource management* VF (section 4.4.7) deals with the power consumption issue.

Real-time: the system delay requirements are very stringent in real-time applications. The broad meaning of delay in this context is comprised of the system data processing and network delay. For instance, in an industrial automation scenario, actuation signals are required in real-time. VFs are capable of offering the required functionality to applications through cross-layer system approaches which can significantly reduce the overall system delay. Thus, resource monitoring and system adaptation achieved with cross-layer component-based interactions are important schemes that should be made available to the applications. The *resource management* VF can offer the necessary functionality to real-time applications.

Reliability: end-to-end reliability guarantees that the transmitted data is properly received by the receiving-end. In some applications, end-to-end reliability may

be a dominating performance metric, whereas it may not be important for others. In security and surveillance applications in particular, guaranteed end-to-end delivery is of high importance. The non-functional requirement can be fulfilled through the coordination and interaction of various VFs including *data consistency, communication and security, privacy and trust*.

We will follow the order below to discuss the relevant VFs in the sections that follow:

4.4.1. Context and location management

Distributed CO systems are designed to measure properties of the physical world. They are therefore suitable for gathering the context of an entity, which is the information that can be used to characterize its situation. Individuals, locations or any relevant object can be such entities [13].

Most researchers argue that context information has three major attributes through which it can be accessed: the identity of the entities, their location and the time at which the information has been gathered. Since a reasonable amount of data is collected in large systems, context management systems are needed to handle them. Such systems can separate applications from the process of data processing and context fusion. Additionally, this allows a number of COs to share the gathered context.

Changes in context may also trigger actions to influence the monitored entity. Specialized actuators, for instance, may be programmed to control pipe valves when a fluid pressure reaches a certain threshold. To achieve precise actuation and detailed analysis of collected measurement data, however, the spatial distribution of sensors needs to be known. Thus, determining the *location* of COs is a requirement of a large number of applications, including monitoring of habitat, urban and indoor areas.

This section explores the design space of vertical functions for context and location management.

4.4.1.1. *Context management*

Classical context management systems use infrastructure-based directories to store the information, for example, Aura [39] and Nexus [49]. This has the advantage of the device knowing where the information can be queried from. On the other hand, to avoid bottlenecks, the data has to be structured in some way and distributed among several devices. With usually small COs, the distribution of the context is system-driven. Also, the context often has only limited spatial relevance which is reflected by the typical wireless communication which is also spatially restricted. It is reasonable to store the context at or near the location where it is generated.

To start with the gathering of the sensor data, MiLAN [44] allows for the decoupling of application and data gathering. The user has to provide a specification of which sensors, or a set of sensors, can provide what QoS for which data. Additionally, the user specifies which data with what QoS are needed when the application is in various states. Then, MiLAN makes sure that the needed data is available. The actual source of the data is transparent to the application.

The management of data in a single device is the focus of the MobileMan project [27]. It creates a cross-layer architecture for the network protocol stack in mobile ad hoc networks. MobileMan primarily aims at developing a network protocol stack that is optimized with cross-layer interactions. A more general approach is followed in TinyCubus [75]. Cross-layer data such as context information is stored in a state repository. The cross-layer framework ensures that data needed by an application component is provided by another.

With TinyDB [71], a whole network can be regarded as a database. It mainly focuses on external queries since they are parsed and optimized externally, but a fixed set of pre-parsed and pre-optimized queries could also be used inside the network. Such database approaches thus provide an easy way to get context data when the storage location is unknown.

In geographic hash tables [97], the storage location can be calculated from the index key. Each node has to have a geographic location, and the data is stored in the node geographically nearest to the hash of its key. Thus, context data can be queried directly from the storage node.

The COs themselves belong to the context as well. [135] presents a self-monitoring system for sensor networks. It continuously computes aggregates (sum, average, count) of network properties like loss rates, energy levels, etc., and disseminates them in the network in an energy-efficient manner. All objects can access the system context of the network.

We have shown the different parts of context management, starting with the gathering of sensor data. This data is made available to all components of an application and

to other nodes in the network in different ways. Several approaches exist for these purposes, but to the best of our knowledge none covers the complete context management area. Therefore, more research is needed here.

4.4.1.2. *Context-aware applications*

Applications are called context-aware if they adapt their behavior based on the context. Several forms of this adaptation exist including the selection of information, the change of the presentation or the triggering of some action based on gathered context.

The GUIDE project [25] developed a tourist guide for the city of Lancaster in the UK. Personal and environmental context are used including, for example, the visitor's interests, his or her current location, the time of the day and the opening hours of attractions. The information is presented with respect to the age and the technical background of the visitor.

Sharing of context of a mobile phone user was the focus of the TEA project [110]. The user can set his current context using his mobile phone, for example, to "Free" or "Meeting". This information is presented to the caller who can then decide to call anyway, to leave a message, or to cancel the call.

Gaia OS [100] provides support for Active Spaces which combines physical and virtual contextual information related to the physical space and allows interaction with the physical space. Applications can be developed without strict knowledge of the infrastructure – Gaia is responsible for mapping these applications to a physical space. A framework that separates model, view, and controllers allows for runtime adaptation due to changes in the environment.

In ad hoc environments, context-based adaptation may have different goals, e.g. lower energy consumption or lower delay. Impala [68] contains an application adaptor that adapts the application protocols to different runtime conditions, which include system and application parameters. Adaptation decisions are made using a finite state machine where states represent different protocols/applications. Each directed edge carries a parameter expression for the condition under which the switch occurs. The adaptation goal is, therefore, implicitly given by these conditions.

TinyCubus [75] uses several variables in three dimensions: "system parameters", "application requirements", and "optimization parameters" of the object context to perform the adaptation. For each combination of parameter values, an algorithm which performs best is known to the system. Based on policies and different adaptation strategies, a set of algorithms is selected that provides the functionality required by the application and that fulfills the best desired optimization.

4.4.1.3. *Location management*

Location services for mobile ad hoc networks only offer limited context information, i.e. the position of mobile objects. Prior to storing the location in such a service, the location has to be determined. Small COs usually do not have a GPS device, so different approaches are needed.

We refer the reader to [47, 84] for an extensive discussion on infrastructured and infrastructure-less location mechanisms. This section covers some of the most recent research advances in location management and determination.

A scalable, distributed location service is GLS [67]. Each node has a small set of other nodes as its location servers and updates them periodically with its location. Therefore, it does not have to know their actual identities but only their identifiers. All routing, including routing of location queries, uses a predefined ordering of node identifiers and a predefined geographic hierarchy.

Two basic approaches are commonly used to determine the position of objects. Having the distances to three objects of which the location is known, its own location can be calculated. The other possibility is to measure the angle to two known objects. Since most COs are equipped with omnidirectional antennae, a very accurate measurement of the angles is not feasible. However, [74] shows that the location estimation is significantly more accurate and feasible on Mica2 motes using two directional antennae.

Several methods exist to determine the distances to other nodes, for example time of flight or attenuation. Besides the normal radio, ultrasound can be used [109], which is a more accurate system for distance measurement and does not suffer from problems like relying on radio received signal strength. In order to calculate the node locations, in [109] a global non-linear optimization problem is set up and solved. A fully distributed approximation for the solving algorithm is presented. Some special nodes capable of long distance ranging (e.g. using long range ultrasound) are used as initial location beacons.

The location discovery algorithm in [36] works with distance measurements based on the received signal strength indication (RSSI) values delivered by the RF chip. Especially in indoor environments, RSSI can have an error as large as 50% of the measured distance. Since the error conforms to a Gaussian random variable, it can be calculated with the location. The standard deviation is used as the degree of precision of the location. The precision estimates of all values are considered in all subsequent calculations of location for undetermined nodes, thus accumulating the errors in the results of the new calculation.

While the last approach assumes static nodes, an algorithm for semi-static sensor networks is presented in [33]. It uses the properties of a randomly deployed sensor

network, more precisely, the average density of nodes that are uniformly distributed. Assuming a fixed transmission range for all nodes, the distance between any two nodes can be calculated using only the hop count between them. In a further step, the hop count is combined with a distance estimate obtained in the traditional way. By limiting the number of hops a distance message can travel, the precision can be increased again.

Although considerable research has been done in the area of location estimation, positioning is still too inaccurate. Also, for mobile COs no satisfactory approaches exist. Therefore, more research is needed in this direction.

4.4.2. Data consistency

The benefits of having several CO nodes mostly come from the fact that many nodes simultaneously monitor the same physical area. Nodes can be put into sleep mode without any loss of precision in the network. This results in the conservation of energy and an increased network lifetime.

The reliability of the system is also improved with several sensor nodes. This scenario, however, raises issues regarding data inconsistencies which may occur due to various reasons, for instance inherent imprecision associated with sensors, inconsistent readings and unreliable data transfer, to name just a few.

This VF provides the functionality to ensure consistency of the sensor data at various system abstraction levels:

- Data consistency may mean that data retrieved from a location in the sensor network should be consistent with data sent to the same location.
- Data consistency may also mean that all sensors sensing the same physical phenomenon should more or less agree on the measured value.
- In a rule-based system, data consistency may mean that all actuators agree on the action that needs to be taken.

Different mechanisms have been used to solve data inconsistency problems in various levels. As will be shown in the next section, while the focus of the first definition of “data consistency” is on a low level, the second concerns the “data consistency” on a higher level and is more commonly known as “consensus” and “data aggregation”. The third definition, also on a higher level, relates to the future direction of handling data inconsistency for complex WSN applications.

4.4.2.1. Consistency handling mechanisms (operation of WSN)

The following requirements are needed to ensure accurate and consistent operation of the WSN and COs:

Localization

In order to interpret sensor data and collaborate with other nodes, it is crucial for sensor nodes to know approximately the position of the nodes with whom they collaborate. Usually, the manual configuration of nodes' positions is not feasible, and in situations where nodes are mobile this approach is even impossible. The availability of calculating and communication capabilities on nodes makes it possible to use automated location techniques.

Synchronization

WSNs and distributed CO systems must have a mechanism to ensure all nodes have an equal understanding of time and the moment at which events take place. Consequently, the nodes must keep their local clocks approximately synchronized with respect to a reference time, which may be one of the sensor nodes or an external source of time (e.g. GPS). The time synchronization VF is discussed in section 4.4.8.

Reliable data transfer

Applications require guaranteed delivery of information and/or customizable degrees of reliability for data transfer. As sensor nodes are ubiquitously deployed, they can overcome lack of reliability through cooperation. Nevertheless, achieving dependability through collaboration among error-prone entities is a challenging task. On the one hand, collaboration mechanisms should be ingenious enough to provide best-effort robust communication of important data, even in harsh conditions. On the other hand, the overhead introduced by cooperation along with the additional energy consumption should be kept to a reasonable level. Due to the fact that standard approaches cannot be applied to WSNs, reliability remains an open research issue.

Routing

Routing is an essential mechanism in networking, WSNs included. Unlike traditional networks, there are no dedicated routers in ad hoc sensor networks. Instead, data forwarding from source(s) to destination(s) is accomplished through local collaboration among neighbors. The various techniques proposed in other works strive to achieve energy-efficiency while maintaining a best-effort level of reliability.

Coverage

The coverage problem in WSNs generally refers to how well an area is monitored. Monitoring an area by several sensors has the advantages of (i) being able to turn off some of the sensors, thus saving valuable energy, and (ii) enhancing the accuracy of the sensed data by averaging multiple readings, for instance.

4.4.2.2. Consistency handling mechanisms (data processing)

Data consistency at the data processing phase can be achieved through the following mechanisms.

State monitoring

Sensor nodes can detect any change in the state of the environment in which they are placed directly from the sensed and measured data. In many situations, the whole network will not have a single global state that needs to be monitored, but the network will monitor the states of local processes, restricted to a confined area. The state might also be unique to each sensor node, or to the object the node is operating on behalf of.

An attempt to formalize state monitoring is presented in [102]. Instead of composing a state machine that is triggered by the occurrences of events, the authors propose to describe the creations between states and the events that trigger state-changes through a set of rules and predicates over events and their parameters. In this way, arbitrarily complex state-change conditions can be defined. In this system, states have a binary nature as they are either occurring or not occurring. A change of state can be used to trigger additional events or to perform actions. Strohbach *et al.* [119] used a similar approach, using simple predicate logic to monitor hazardous situations such as chemical drums.

Crucial to the design of a collaborative distributed state monitoring is the use of a high-level description of the state transitions, and other relevant aspects.

Data fusion

If redundancy is used to cover each point or region with multiple sensors, then the accuracy and the consistency of sensed data can be improved by merging or fusing correlated sensor data. Various schemes for data fusion have been proposed which deal with the reduction in transmission rates of the radio module (an expensive sensor node resource).

In this case, however, we are faced with the problem of fusing or combining the data reported by each of the sensors monitoring a specified point or region.

This is a challenge as measurements recorded by the sensors can differ (because of inherent imprecision in the sensors and/or the relative location of a sensor with respect to the monitored region) and the fact that sensors might be faulty. The objective of sensor data fusion is to take the multiple measurements and determine either the correct measurement value or a range in which the correct measurement lies.

The sensor fusion problem is closely related to the Byzantine agreement problem that has been extensively studied in other works. In [107], a hybrid distributed sensor-fusion algorithm is presented. Each sensor needs to compute a range, in which the true value lies as well as the expected value. For this calculation each sensor sends its measurement and its estimated accuracy to every other sensor. This algorithm is executed by every sensor using the measurement ranges received from the remaining sensors monitoring the same region combined with the sensor's own measurement. A

typical drawback of this approach is the considerable communication overhead introduced by exchanging so many messages. This is an important issue in the context of energy constrained WSN nodes.

Event detection

Event detection is similar to state monitoring in the sense that the sensor network itself is in charge of monitoring the environment in which its nodes are placed, and it is used to detect the occurrence of certain events.

With the event detection mechanism, exceptional situations can be detected and consequently reported. Each sensor node has the task of detecting a possible event based on the data it obtains through its sensors, and through communication with other nodes. Additionally, the occurrence of an event, along with its position, magnitude or other properties need to be reported. In many situations, the value of these additional properties can only be determined, or more accurately be determined, when the sensor data of multiple sensor nodes are considered. The detection and reporting of these tasks will need to be performed in an efficient way, using only limited communication between the nodes, whenever data of interest is gathered, instead of reporting every sensed data sample. Additionally, a description of the event and its properties will be needed to perform the task.

Event detection has been tried in several WSN applications already. In [128], a description is given on a networked sensor array for monitoring volcanic eruptions. Seismic and infrasonic data is gathered continuously, and when higher levels of activity are measured, the recently measured data from different sensors is correlated and analyzed to find data on the recent event. The implementation described does not make use of in-network processing of the sensor data, but a feasibility analysis is performed. Other uses of event detection are shown in systems that are concerned with the detection, identification, localization or tracking of objects in sensor fields [101, 123, 42, 31]. In these applications, sensor nodes around the object or event of interest collaborate to find the location of the object or event.

Fault tolerance and consensus

Clouqueur *et al.* in [26] presents two distinct approaches, value-fusion and decision-fusion, for achieving fault tolerance in collaborative target detection algorithms. When performing a target detection task, multiple sensors in a region detect the presence of an object using sound, motion, or heat associated with the object of interest. Therefore, combining their views and obtaining a consistent conclusion through the fusion process is highly desirable. The value-fusion method consists of two phases: (i) exchanging the measured values and (ii) arriving to a consensus by computing the average of values and comparing it to a threshold. In the presence of faulty sensors, in order to preserve precision and accuracy, the extreme values are dropped from the set that is going to be averaged. In contrast, in the decision-fusion method, each device

first makes an independent decision as to whether or not a target is present and then the devices exchange their decisions to arrive at a fault tolerant consensus decision. As in value-fusion, the fused data is obtained by averaging data received from all the sensors. For the situation of faulty nodes, exact agreement is used to preserve precision. The comparative results show that value-fusion is clearly preferable if the sensor network is highly reliable and fault-free. However, when faulty nodes are present, the performance of value-fusion degrades faster than the performance of decision-fusion and decision-fusion becomes superior to value-fusion. Achieving fault tolerance through consensus is a broad problem. Generally, each node has the task of trying to obtain a confident statement of the state or situation the environment is in. This information constitutes the state information present at the node. The state information needs to be refreshed periodically to account for changes in the topology due to movement of wireless sensors or due to nodes encountering crash failures.

The major challenge within the WSN context is to devise protocols that minimize the effort for refreshing and exchanging state information over the network. The protocol described in [64] generates consensus under the assumption that the number of faulty nodes is less than the number of correct nodes. The protocol is designed to enable self-correction in the network by isolating the faulty nodes and putting them in sleep mode, thereby increasing the concentration of nodes having correct information and improving their ability to generate consensus. The consensus process relies on forming a quorum, i.e. subgroups of sensor nodes with a certain minimum size. For instance, if there are k nodes having the same area of interest, the size of the quorum should be at least $(k + 1)/2$. A quorum is created after exchanging information among nodes as follows: (i) the node that needs to generate consensus starts the process by sending its information, (ii) other nodes answer with positive or negative acknowledgements, according to their information and (iii) the consensus is generated if the initial node receives more than $(k + 1)/2$ positive acknowledgements. As we have mentioned before, under WSN constraints, protocols should reduce as much as possible the number of messages exchanged.

One way to achieve this is using aggregation [3] within the consensus process, either by concatenating values, summarizing them, or by the counting of a set. Other operations as well as aggregation of data other than scalar numbers could also be possible. Key factors in using aggregation is that the operation reduces the amount of data from a whole series of numbers (or different type of data) to a single number, or a single value, or small set of values, and that the aggregation can be performed hierarchically, creating an aggregate of a larger data set from the aggregates of smaller sets. Aggregate operations do need the support of some sensor network management structure or service to ensure proper operation. Aggregation can also make the protocol more susceptible to channel errors: for low to medium bit error rates concatenation has good performance, whereas for a high bit error rate aggregation is not recommended.

In conclusion, the consensus problem in WSN has additional constraints compared to traditional distributed systems. However, it is a very important process for increasing the confidence of the overall system, both by fusing sensed data and by providing fault tolerance.

4.4.2.3. *Consistency handling mechanisms (application programming)*

The more intelligent collaborative WSN applications become, the greater the need for algorithms capable of supporting collective reasoning and actions in an efficient way. The execution space for these collaborative algorithms is represented by groups of COs that combine their efforts to be able to agree on an action to be taken.

Such collaborative algorithms need to benefit from a novel high-level description mechanism (language) oriented towards the collective model of solving tasks. A promising mechanism, extensively explored in the database research community, is to have a rule-based language [119] to implement collaborative WSN applications. In this case, a set of rules that are stated as machine-understandable statements describes legal or allowable states or situations as well as the alerts that must be given when otherwise.

Although such a scenario has the advantage of providing a high adaptive framework for collaborative WSN applications, which in turn can enhance system performance, it may cause severe problems if the rules and policies have not been carefully specified. A contributing factor to data inconsistency in rule-based collaborative applications is *versioning*. To prevent this kind of inconsistency from happening, the fact that the COs use the same (latest) version of the rules should be enforced. On the other hand, since rules and policies should be executed collaboratively, the best performance of the system highly depends on consistency between such rules for all COs involved. Otherwise, rules may cause conflict and prevent the system from functioning.

Therefore, strategies are needed to check for rule consistencies of COs.

4.4.3. *Communication functionality*

The communication vertical function refers to the capability of any pair (or group) of devices to exchange information. Different kinds of communications can be performed: one-to-all, one-to-many, many-to-one, many-to-many. If we consider the case of WSNs with a single sink, one-to-all or one-to-many communications are needed for the sake of interest and query dissemination, while many-to-one communication is exploited to gather sensed data at the sink.

The first problem that needs to be addressed is CO addressing. Communication in a COs environment is expected to be *data-centric* and attribute-based. This means that along with addressing a specific CO the communication infrastructure should be able

to deliver data to and from groups of COs which share a set of attributes specifying the destination/source address of the information. For example, a user could issue a query about the average temperature of an area in an office building. This query should be delivered to the objects with temperature sensors. Similarly, once measures on the temperature have been taken, the COs in the specific area will send packets to the sink(s) reporting the measured values.

Other important VF parameters which should be included in a query are the time constraints and accuracy with which a given query needs to be answered. These are application-dependent and even query-dependent parameters: (a) for a query to be successfully resolved, the sensors must deliver new data, (b) the query must be answered fast enough, and (c) the precision with which the query is answered must meet the query requirements. This translates into a new concept of "quality of service" requirements.

Once a communication request between two or more COs is initiated, protocols have to be adopted to deliver the transmitted information from the sender to the final destination. Such protocols will typically involve physical layer protocols, data link protocols (FEC, ARQ protocols), MAC protocols, "topology control" schemes (e.g. addressing the self-organization of nodes into a hierarchical network topology or into dynamically changing communications infrastructures according to given awake-asleep schedules) and routing protocols.

The second issue to address is the fact that a one-fits-all protocol stack may not be suitable for this scenario. It is possible to identify the "vertical functions" that should be provided and possible implementations of such functions for specific sets of possible applications. The communication protocols will benefit from and sometimes require the information provided by different vertical functions such as time synchronization and location awareness. Not only time and location information is included in the delivered data, but some protocols such as geographic-based routing can exploit location-awareness to reduce routing overhead and the nodes' storage demand.

Mobility of the objects is the third issue to be tackled. Although in many CO scenarios the devices themselves are unlikely to be mobile, they can be located on mobile users or mobile stations so that their location changes in time in a predictable or unpredictable way. On one hand this may have a beneficial effect (e.g. load balancing the energy consumption among the different nodes), but on the other hand it requires mobility management or mobility-aware protocols to be added to the protocol stack. The mobility of some of the devices have been explored by some architectures such as the data mules [112], in which a group of mobile nodes move in the deployment area collecting data from the sensor nodes and delivering the collected data to the sinks.

Although TinyOS [48] has been serving as the basis for experimentation of existing and new communication protocols, a common and consolidated framework for comparisons needs to be developed further.

4.4.4. *Security, privacy and trust*

COs are usually placed in locations that are accessible to everyone, including attackers. For example, sensor networks are expected to consist of a few hundred nodes that may cover a large area. It is impossible to protect each of them from physical or logical attacks. Thus, every single node is a possible point of attack.

In a CO, security is pervasive. [87] states that security must be integrated into every component to achieve a secure system. Components designed without security can become a point of attack, as [54] shows. However, specific vertical functions to enforce security are available for applications.

We start by describing how the hardware can be secured. Then, several encryption approaches for COs are presented. We conclude with a look at routing protocols.

4.4.4.1. *Resource protection*

Having physical access to the devices without countermeasures, an attacker could read the node's memory including cryptographic keys and reprogram the node with malicious code. Therefore, security starts with the hardware of sensor networks.

Tamper-resistant devices would make the integration of security in sensor networks much easier – we could rely on the strength of security protocols or cryptographic functions which have been around for many years. Unfortunately, total tamper-resistance is very hard to achieve [9]. There are a lot of known techniques to read data from devices which actually are meant to be tamper-resistant. For instance, [60] describes methods for extracting protected software and data from smartcard processors. They show invasive techniques such as microprobing and non-invasive techniques such as software attacks, eavesdropping and fault generation. They even go further and also show that additional countermeasures such as additional metallization layers, which form a sensor grid above the actual circuit, do not protect the circuit fully. Of course, some of these methods require a well-funded adversary, but reviewing for instance military applications, the existence of such an adversary is highly probable. Additionally, achieving such a tamper-resistance level is very costly, which in most cases is not in line with the requirement that a single device should be low cost.

Thus, the conclusion is that in sensor networks tamper-resistant devices can be used only in very limited and specialized areas. In the majority of cases, the design of the security protocols has to take into account that some devices get compromised

by the adversary. Thus, security protocols for sensor networks have to be designed in a way that they tolerate malfunctioning/attacking nodes while the whole sensor network remains functional. Karlof and Wagner [54] discuss a *graceful degradation* of the network in contrast to a totally compromised network.

Besides the above security issues, another danger for sensor networks, which is hard to prevent is the denial of service attack (DoS) on the physical layer. In such an attack, the attacker broadcasts a high-energy signal to prevent any node from communicating. The attacker can also use the features of the MAC protocol by continuously requesting channel access to eliminate all normal communication. Cryptographically secure spread-spectrum communication would be a defence against such jamming, but unfortunately, such RF-devices are not commercially available yet [87]. In the case of the jammed region not covering the whole network, the border nodes could create a map of this region and reroute traffic around the jammed region [130]. Also, battery exhaustion is a DoS attack. This can be counteracted, for instance, with rate limiting [130], which causes the network to ignore requests beyond a threshold value. Thus, although there are some approaches to cope with some kinds of DoS attacks, there is still further research needed in this area.

4.4.4.2. Encryption

Encryption is the basic technique for securing and authenticating transmitted data. Using asymmetric cryptography on highly resource constrained devices is often not possible due to delay, energy and memory constraints [20, 18]. It is also not expected that the devices of such sensor networks are going to have more resources in the future. There is an interesting observation by Karlof and Wagner that sensor network devices will more likely ride Moore's law *downward* [54]. They make the point that instead of doubling computational power every 18 months, it may be more likely that the devices become even smaller and cheaper solutions are sought.

Using symmetric cryptographical methods, the easiest solution is a shared key for the whole network as in secure pebblenets [11]. The disadvantages are obvious: if a single node is compromised, all the network traffic can be decrypted. Additionally, no device-to-device authenticity can be achieved.

If a unique key is only shared between any two nodes of the network, a single compromised node only has a limited impact. The attacker can only read and modify data that was sent to it, i.e. the compromised node directly. All other network traffic remains secure. As a drawback of this approach, a node needs to store keys for all other nodes, which may not be in line with scalability and memory constraints. Moreover, these unique keys have to be established in some way.

SPINS [88] uses a central base station to establish new session keys. This introduces a single point of failure that has to be protected exceptionally. Additionally,

COs exhibit a strong ad hoc character. Therefore, neither an infrastructure nor a base station can be assumed. A decentralized key management system is, therefore, more practical.

Several approaches are based upon random pairwise key pre-distribution [35, 23]. That is, before deployment – for instance, by the sensor manufacturer – every device is supplied with a random set of keys from a key pool. After deployment, the devices try to establish connections by finding a commonly shared key or by creating a new key through a secure path including other devices. Due to random pre-distribution, real authenticated communication between arbitrary devices is not always possible. It can only be assured with some probability that two arbitrary devices are able to communicate in a secure way. Moreover, an attacker could also reconstruct the complete key pool by compromising enough nodes.

If the key pre-distribution does not rely on a random set but on some algorithmic chosen set, the secure communication between arbitrary devices can be guaranteed. In [125], such an approach is presented. The authors suggest physical contact¹ for establishing the initial key set: the manufacturer could pre-distribute this initial set of keys according to their algorithm. In their approach, when two devices do not share a key yet, they can establish a new key by sending key-shares along node-disjoint paths via secured point-to-point communication to each other. When all key-shares are available at both nodes (which want to establish a new key) they just have to perform, for instance, a bitwise XOR operation on all key-shares: the result of this operation is the newly unique key, shared only by those two devices. It should be clear that the attacker would also need access to all key-shares in order to gain knowledge of the new key.

Since in-network processing is used to save power, end-to-end encryption can only be used sparingly. Along an aggregation tree, only point-to-point encryption is feasible, but an attacker in the tree has full access to the data. If the aggregation is locally bounded, the results of the aggregation can be sent directly and encrypted to the target node since no intermediate node is expected to change the data.

4.4.4.3. *Secrecy*

Encryption is not sufficient for ensuring secrecy of data. Traffic analysis on the ciphertext can reveal sensitive information about the data. When, for example, a motion detector sends a message, we do not need to know the data, but can assume that it detected a motion. On higher layers, additional dummy messages have to be generated to hide the important messages. This seems to be diametrical in resource

1. (Physical contact for establishing an initial security association, i.e. a shared secret/key is also suggested by Stajano and Anderson [118]).

constrained COs, but secrecy may be a more important goal than energy saving in some cases.

A dynamic virtual infrastructure for WSNs is presented in [126]. The system contains a coordinate system, a cluster structure and a routing structure. An energy-efficient protocol is proposed to maintain the anonymity of the network virtual infrastructure by randomizing communications so that it cannot be observed by an external attacker.

4.4.4.4. *Privacy*

The primary goal of sensor networks is to observe real-life phenomena. As long as nature is the target, there is no privacy issue, but if humans are observed, privacy is threatened. However, COs used in medical applications, for example, have to monitor the status of a patient. Encryption has to ensure that data cannot be overheard and is only available to legitimate applications. If nodes are compromised, other mechanisms like intrusion detection have to exclude these nodes from receiving data.

Data of other sensor networks might be available to everyone. Such networks should only deliver data in a coarse-grained detail level that is not dangerous to privacy. For example, the system should only return average values of larger areas but not of single locations. The result has to be calculated in a distributed manner so that no single node has access to the complete result.

Sensor networks are small enough and will become even smaller in the future. Therefore, they are very suitable for spying on people. However, besides jamming transmitters and bug detectors, pure technological solutions are not able to solve the problem. [87] suggests a mix of societal norms, new laws and technological responses. However, they will require more research in the future.

4.4.4.5. *Data integrity*

An attacker in the network can generate a false sensor or, more severe, aggregation data. The more aggregated the data is, the more valuable it is. Therefore, there is a need to especially protect the aggregated data. [93] proposed SIA, a framework for secure information aggregation in large sensor networks: efficient protocols for the computation of the median, the average, the minimum and maximum of a value, and the estimation of the network size. Using random sampling mechanisms and interactive proofs, the user is able to verify that the answer of an aggregator is a good approximation of the true value.

4.4.4.6. *Trust*

With several COs contributing to a common goal, it is necessary to assess the reliability of the information provided by an individual CO. With respect to services

and transactions, trust has been researched for several years. Research on data-centric and fully distributed architectures has just started.

A distributed voting system is proposed in [23]. When a node detects a misbehavior of another node, it can cast a vote against this node. Above a certain number of votes, all other nodes refuse to communicate with this node. To avoid a malicious node casting votes against many legitimate nodes, each node is limited to a number of votes.

In [38], a more general reputation-based framework for sensor networks is presented. Each node monitors the behavior of other nodes and builds up their reputation thereupon. This reputation is used to evaluate the trustworthiness of other nodes. Thus, nodes with a bad reputation can be excluded from the community.

COs exhibit strong cooperation when performing an action. Thus, a single node becomes less important to the overall result. Therefore, strong cooperation will be one of the feasible approaches to secure the entire system through extensive data validation.

4.4.4.7. *Protocols*

Encryption mechanisms are not enough to defend against attackers. Careful protocol design is needed as well. [54] describes several attacks against known routing protocols for sensor networks: spoofed, altered or replayed routing information, selective forwarding, sinkhole attacks, sybil attacks, wormholes, HELLO flood attacks and acknowledgement spoofing. For several routing protocols, the relevant attacks are highlighted. Countermeasures could not be given for all protocols since security was not a design issue.

In [30], a routing protocol is presented that is resilient to attempts to obstruct data delivery as it sends every packet along multiple, independent paths.

Ariadne [50] uses efficient symmetric key primitives to prevent compromised nodes from tampering with uncompromised routes consisting of uncompromised nodes. It also deals with a large number of types of DoS attacks. Since it is designed for ad hoc networks, it may be suitable only for some COs.

4.4.5. *Distributed storage and data search*

In COs and WSNs, efficient storage and querying of data are both critical and challenging issues. Especially in WSNs, large amount of sensed data are collected by a high number of tiny nodes. Scalability, power and fault tolerance constraints make distributed storage, search and aggregation of the sensed data essential. It is possible to perceive a WSN as a distributed database and run queries which can be given in

SQL format. These queries can also imply rules about how to aggregate the sensed data while being conveyed from sensor nodes to the query owner.

Since the lifetime of a WSN is generally dependent on irreplaceable power sources in tiny sensor nodes, power efficiency is one of the critical design factors for WSNs [6]. Data aggregation techniques [17, 135] that reduce the number of data packets conveyed through the network are therefore important and are also required for effective fusion of data collected by a vast number of sensor nodes [6, 43]. Data aggregation in sensor networks combines the sensed data coming from the nodes based on the parameters passed in queries. It can be classified according to one of the following approaches:

- **Temporal or spatial aggregation:** data can be aggregated based on time or location. For example, temperature readings taken every hour or temperature readings from various regions in a sensor field can be averaged. Also, a hybrid approach, which combines time and location based aggregation, can be used.
- **Snapshot or periodical aggregation:** data aggregation can be done on the receipt of a query (snapshot mode). Alternatively, temporarily aggregated data can be reported periodically.
- **Centralized or distributed aggregation:** a central node can gather and then aggregate data, or data can be aggregated while being conveyed through a sensor network. A hybrid approach is also possible where clusters are formed, and a node in each cluster aggregates the data from the cluster.
- **Early or late aggregation:** data can be aggregated at the earliest opportunity, or the aggregation of data may not be allowed before a certain number of hops hinder the collaboration between neighboring nodes.

Data queries can be made not only for aggregated data but also for non-aggregated data. A query in a sensor network may be perceived as the task or interest dissemination process. Sensor nodes can be queried by using continuous or snapshot queries. Continuous queries can be periodical where the sensed data are reported at certain time intervals or event driven where certain events stimulate nodes to report the sensed data.

The following characteristics of WSNs should be considered while designing a data storage, querying and aggregation scheme for WSNs:

- Sensor nodes are limited in both memory and computational resources. They cannot buffer a large number of data packets.
- Sensor nodes generally disseminate short data packets to report an ambient condition, e.g. temperature, pressure, humidity, proximity report, etc.
- The observation areas of sensor nodes often overlap. Therefore, many sensor nodes may report correlated data of the same event. However, in many cases, the replicated data are needed because the sensor network concept is based on the cooperative effort of low fidelity sensor nodes [6]. For example, nodes may only report proximity,

and the size and the speed of the detected object can be derived from the locations of the nodes reporting them, and from the timing of the reports. The collaboration among the nodes should not be hampered by the data aggregation scheme.

- Since there may be thousands of nodes in a sensor field, associating data packets from numerous sensors to the corresponding event and correlating the data about the same event reported at different times may be a very complicated task for a single sink node or a central system to handle.

- Due to large number of nodes and other constraints such as power limitations, sensor nodes are generally not globally addressed [6]. Therefore, address-centric protocols (end-to-end routing) are mostly inefficient. Instead of address-centric protocols, data-centric or location-aware addressing protocols, where intermediate nodes can route data according to its content [63] or the location of the nodes [21], should be used.

- Querying the whole network node by node is impractical. Thus, attribute-based naming and data-centric routing [114] are essential for WSNs.

Queries made to search data available in a WSN should be resolved in the most power-efficient way. This can be achieved by reducing either the number of nodes involved in resolving a query or the number of messages generated to convey the results. There is a considerable research interest to develop efficient data querying schemes for WSNs.

In the section that follows, we examine data dissemination techniques which are closely related to data querying, and then query processing and resolution techniques.

4.4.5.1. Data dissemination

Data dissemination protocols are designed to efficiently transmit and receive queries and sensed data in WSNs. We briefly discuss five of the best known data dissemination protocols for WSNs. There are many others that can be categorized as data-centric, hierarchical and location-based. Since the focus is on distributed storage and search we do not list the other protocols.

The routing protocols for WSNs are generally designed for networks that have fixed homogenous sensor nodes and are based on the assumption that all nodes try to convey data to a central node, often called the sink. However, in CO networks, there will be heterogenous nodes that can be mobile, and the sensed data will be needed by many nodes, i.e. multiple sinks. Therefore, we can say that new routing protocols will be needed for COs.

Classic flooding

In classic flooding, a node that has data to disseminate broadcasts the data to all of its neighbors.

Figure 4.2. *Classic flooding*

Whenever a node receives new data, it makes a copy of the data and sends the data to all of its neighbors, except the node from which it just received the data. In Figure 4.2, an example is depicted. A sends the message to its neighbors B and C. Then, B and C copy the message and send the message to their neighbors D and E respectively. The algorithm finishes when all the nodes in the network have received a copy of the message.

Gossiping

Gossiping [6] uses randomization to conserve energy as an alternative to the classic flooding approach. Instead of forwarding data to all its neighbors, a gossiping node only forwards data to one randomly selected neighbor.

SPIN

SPIN [43] is based on the *advertisement* of data available in sensor nodes. When a node has data to send, it broadcasts an advertisement (ADV) packet. The nodes interested in this data reply back with a request (REQ) packet, then the node disseminates the data to the interested nodes by using data (DATA) packets. When a node receives data, it also broadcasts an ADV, and relay DATA packets to the nodes that sent REQ packets. Hence, the data is delivered to every node that may have an interest. This process is shown in Figure 4.3.

Directed diffusion

In SPIN, the routing process is stimulated by sensor nodes. Another approach, namely directed diffusion [53], is sink oriented. A sink is the name given to the central node responsible for gathering data from all the other nodes in directed diffusion,

Figure 4.3. *SPIN data exchange*

where the sink floods a task to stimulate data dissemination throughout the sensor network. While the task is being flooded, sensor nodes record the nodes which send the task to them as their gradient, and hence the alternative paths from sensor nodes to the sink are established. When there is data to send to the sink, this is forwarded to the gradients. One of the paths established is reinforced by the sink. After that point, the packets are not forwarded to all of the gradients but to the gradient in the reinforced path. A sample interest description is shown in Figure 4.4, and data dissemination in directed diffusion is illustrated in Figure 4.5.

LEACH

LEACH [45] is a clustering-based protocol that uses randomized rotation of local cluster heads to evenly distribute the load among the sensors in the network. In **LEACH**, the nodes organize themselves into local clusters, with one node acting as a local cluster head. **LEACH** includes randomized rotations of the high-energy cluster head position such that it rotates among the various sensors in order not to drain the battery of a single sensor. In addition, **LEACH** performs local data fusion to compress the amount of data being sent from the clusters to the base station. Sensors

```

Type
Interval
Duration
Rect
: four-legged animal
: 20ms
: 10 seconds
: [-100,100,200,400]
// Detect animal location
// Send back events every 20ms
// For the next 10 seconds
// From sensors within range

```

Figure 4.4. A sample interest description

Figure 4.5. Directed diffusion

elect themselves to be local cluster heads at any given time with a certain probability. These cluster head nodes broadcast their status to the other sensors in the network. Each sensor node determines to which cluster it wants to attach itself by choosing the cluster head that requires the minimum communication energy. Once all the nodes are organized into clusters, each cluster head creates a schedule for the nodes in its cluster. This allows the radio components of each non-cluster head node to be turned off at all times except during each node's transmit time, thus the energy dissipated is minimized. Once the cluster head has all the data from the nodes in its cluster, the cluster head node aggregates the data and then transmits the compressed data to the base station. However, being a cluster head drains the battery of that node. In order to spread this energy usage over multiple nodes, the cluster head nodes are not fixed. The decision to become a cluster head depends on the amount of energy left

at the node. In this way, nodes with more energy will perform the energy-intensive functions of the network. Each node makes its decision about whether to be a cluster head independent from the other nodes in the network and thus no extra negotiation is required to determine the cluster heads. The cluster formation algorithm is depicted in Figure 4.6.

Figure 4.6. LEACH cluster formation

4.4.5.2. Query processing and resolution

After a query arrives to a sensor node, it is first processed by the sensor node. If the node can resolve the query, the result of the query is disseminated. This approach is one of the simplest ways of resolving and processing a query. Sensor nodes usually take advantage of collaborative processing to resolve queries so that a smaller number of messages are transmitted in the network. Queries can be flooding-based, where a query is flooded to every node in the network. Alternatively, they can be expanded ring search (ERS) based, where a node does not relay a query that it can resolve. In this subsection, we briefly explain data storage and querying techniques.

TinyDB

TinyDB [69] is a query processing system for extracting information from a network of TinyOS sensors. TinyDB provides a simple, SQL-like interface to specify the data, along with additional parameters, such as the rate at which data should be refreshed, similar to traditional databases. Given a query specifying data interests, TinyDB collects the data from nodes in the environment, filters and aggregates them. TinyDB does this via power-efficient in-network processing algorithms. Some key features of TinyDB areas are as follows:

- **Metadata management:** TinyDB provides a metadata catalog to describe the kinds of sensor readings that are available in the sensor network.

- **High-level queries:** TinyDB uses a declarative query language that lets the data be described without having to state how to get it. This makes it easier to write applications.

- **Network topology:** TinyDB manages the underlying radio network by tracking neighbors, maintaining routing tables, and ensuring that every node in the network can efficiently and (relatively) reliably deliver its data to the user.

- **Multiple queries:** TinyDB allows multiple queries to be run on the same set of nodes at the same time. Queries can have different sample rates and access different sensor types, and TinyDB efficiently shares work between queries when possible.

- **Incremental deployment via query sharing:** TinyDB nodes share queries with each other: when a node hears a network message for a query that it is not yet running, it automatically asks the sender of that data for a copy of the query, and begins running it. The TinyDB system contains two applications: one application runs on the sensor platforms and another application runs on the PC side. A user requests his query using the Java application on the PC. This query is disseminated to sensor nodes and the application on the sensor platforms retrieves and returns the requested information.

```
SELECT Temp
FROM Sensors
WHERE temp>threshold
TRIGGER ACTION SetSnd(512)
EPOCH DURATION
```

Figure 4.7. *Triggering SQL query*

TinyDB includes a facility for simple triggers or queries that execute some command when a result is produced. A sample query is given in Figure 4.7 which calls the SetSnd function to give an alarm when the temperature is over some threshold value, and this value is checked every 512 seconds. TinyDB includes the ability to run queries that log into the flash memory in the sensor nodes. TinyDB provides commands for creating tables that reside in flash, running queries that insert into these tables, running queries that retrieve from these tables and deleting these tables. Only one query can log to a buffer at a time and new queries will overwrite data that was previously logged to a table. Currently, a query that selects from a flash table and a query that writes to the same table cannot be run. The logging of the query should be stopped using the TinyDB client utility prior to collecting data from flash tables.

When running queries longer than four seconds by default, TinyDB enables power management and time synchronization. This means that each sensor is on for exactly the same four seconds of every sample period. Results from every sensor node for a particular query should arrive at the base station within four seconds of each other. This time synchronization and power management enables long running deployments

of the sensors. TinyDB aggregates results on the way to the sink node. TAG [72] is an aggregation service offered by TinyDB. It operates as follows: users pose aggregation queries from a powered, storage-rich base station. Operators that implement the query are distributed into the network by piggy-backing on the existing ad hoc networking protocol. Sensors route data back towards the user through a routing tree rooted at the base station. As data flows up this tree, it is aggregated according to an aggregation function and value-based partitioning specified in the query. In order for users to pose declarative queries, an SQL-like programming language was designed.

Aggregates are classified in four categories according to their state requirements, tolerance of loss, duplicate sensitivity and monotonicity:

- Duplicate insensitive/sensitive aggregates are unaffected by duplicate readings.
- Duplicate sensitive aggregates will change when a duplicate reading is reported.
- Exemplary/summary aggregates return one or more representative values from the set of all values.
- Summary aggregates compute some property over all values.
- Monotonic aggregates aggregate the property so that when a function f is applied to two partial state records for all resulting values, it will be greater or lower than each of the evaluation of pairs of values. This provides increasing or decreasing values for aggregate results.
- Distributive/algebraic/holistic/unique/context-sensitive aggregates: depending on the function a pair of values has to be carried. For example, AVERAGE function requires the number of elements used to compute the result and the result to further continue in processing. Distributive aggregates do not require other data to calculate a result; therefore, the size of the partial records is the same as the size of the final record. COUNT, MAX and MIN are examples of distributive aggregates. Algebraic aggregates require intermediary state information to continue the operation. The AVERAGE function is an example of an algebraic aggregate. Holistic aggregates require whole values to be kept together prior to computing the result. MEAN is one of these operators. Unique aggregates are similar to holistic aggregates except that the amount of state that must be propagated is proportional to the number of distinct values in the partition.
- In context-sensitive aggregates, the partial state records are proportional in size to some property of the data values in the partition. Many approximate aggregates are content-sensitive. Fixed-width histograms and wavelets are examples of these operators.

Queries in TAG contain named attributes. When a TAG sensor receives a query, it converts named fields into local catalog identifiers. Nodes lacking attributes specified in the query simply tag the missing entry as NULL. This increases the scalability as not all the nodes are required to have a global knowledge of all attributes. Attributes can be sensor values, remaining energy or network neighborhood information. TAG

computes aggregates in the network whenever possible to decrease the number of message transmissions, delay and power consumption. Given the goal of decreasing the number of transmitted messages, during the collection phase each parent waits for some time period prior to transmitting its own message in order to aggregate the child nodes' responses. How long each node waits for other nodes' responses is $(\text{EPOCH DURATION})/d$, where d is the maximum depth of the tree. In order to group received data, group id is tagged to each sensor's partial state record, so that response data is aggregated for the nodes with the same group id. When a node receives an aggregate from a child, it checks the group id. If the child is in the same epoch as the node, it combines the two values. If it is in another epoch, it stores the value of the child's group along with its own value for forwarding in the next epoch.

Figure 4.8. Partitioning of time into EPOCHS

By explicitly dividing time into epochs as in Figure 4.8, while waiting for other nodes' responses to arrive, the CPU can be set to idle during this time. However, the depth of the tree has to be known for this principle to be made successful. However, waking up the processor will require synchronization to be employed. Finally, real users of sensor networks are most likely not sophisticated software developers. Therefore, TinyDB has been supported by toolkits for the easy access of data including TASK and others. The complexity of sensor network application development must be reduced and deployment must be made easy to ensure the success of sensor network technology in the real world.

Cougar

Cougar [132] is a query layer for sensor networks. The query layer accepts queries in a declarative language that are then optimized to generate efficient query execution plans with in-network processing, which can significantly reduce resource requirements. Cougar is motivated by three design goals. First, declarative queries are especially suitable for sensor networks. Clients issue queries without knowing how

the results are generated, processed and returned to the client. Second, it is very important to preserve limited resources such as energy and bandwidth. Since sensor nodes have the ability to perform local computation, part of the computation can be moved from the client and pushed into the sensor network, aggregating records or eliminating irrelevant records. Third, different applications usually have different requirements, from accuracy, energy consumption to delay. For example, a sensor network deployed in a battlefield or rescue region may only have a short lifetime but a higher degree of dynamics. On the other hand, for a long term scientific research project that monitors an environment, power-efficient execution of long-running queries might be the main concern. More expensive query processing techniques may shorten processing time and improve result accuracy, but might use a lot of power. The query layer can generate query plans with different trade-offs for different users. The component of the system that is located at each node is called a query proxy. Architecturally, the query proxy lies between the network layer and the application layer, and the query proxy provides higher level services through queries. Gateway nodes are connected to components outside of the sensor network using long-range communication and all communication with users of the sensor network goes through the gateway node.

```
SELECT FROM WHERE GROUP BY HAVING DURATION EVERY attributes,
aggregates SensorData S Predicate
attributes
predicate
time interval
time span e
```

Figure 4.9. *Query template*

Declarative queries are the preferred way of interacting with a sensor network. The queries having the form in Figure 4.9 are considered. It is very similar to the SQL language but it has limitations when compared to SQL. One difference between the query template and SQL is that the query template has additional support for long-running, periodic queries. The DURATION clause specifies the lifetime of a query and the EVERY clause determines the rate of query answers. A simple aggregate query is an aggregate query without GROUP BY and HAVING clauses. In order to compute these aggregates, further processing such as in-network aggregation has to be done. In order to process data in-network, several sensor nodes transmit the packet to a central node named the leader-node, which calculates the aggregates of incoming messages. There are three approaches that can be taken to collect sensor data at a leader-node: messages can be directly delivered to the leader-node using an ad hoc routing protocol, messages can be merged into the same packet to limit the amount of packets transmitted, and partial aggregation on the way to the central node can

be done by intermediary nodes. Synchronization is needed if the messages are to be merged and duplicate sensitive operators such as SUM and AVERAGE require data to be transmitted once. Synchronization is used to determine for each node in each round of the query, how many sensor readings to wait for and when to perform packet merging or partial aggregation. Since the query processing facility has been designed as a layer, Cougar assumes that several ad hoc routing protocols with modifications can be used for the delivery of the messages. An AODV protocol has been used with extensions for simulations. According to Cougar, routes are set up in an initialization phase and each message carries the hop count of the message. Each node records the ID of the received message as a parent node and a reverse path to the leader is set up. Two methods are used to maintain the tree. Local repair is used when a broken link is detected. The depth of the tree with a sequence number is used between nodes that are spatially close to find a new parent in the case of a communication failure. Another method is to reconstruct the tree whenever the number of messages expected reach below some user defined threshold.

Figure 4.10. A Cougar query plan

In order to resolve queries like “What is the minimum average temperature during the next seven days?” two levels of aggregation have to be done. First, the average temperature has to be computed and then the minimum operator has to be applied. In order to resolve these kinds of queries, query plans are used. A query plan is needed to compute complex aggregate queries that a user poses. It also decides how much computation is pushed into the network and it specifies the role and responsibility of each sensor node, how to execute the query and how to coordinate the relevant sensors. It is constructed by flow blocks, where each flow block consists of a coordinated collection

of data from a set of sensor nodes at the leader of the flow block, as depicted in Figure 4.10. The task of a flow block is to collect data from relevant sensor nodes and to perform some computation at the destination or sensor internal nodes. A flow block is specified by different parameters such as the set of source sensor nodes, a leader selection policy, the routing structure and the computation that the block should perform. Each flow block is called a cluster and maintained by heartbeat messages transmitted by the leader of the flow. Several optimizations can be applied to query plan construction such as creating flow blocks that are sharable between different queries and the use of the join operator which enforces two conditions coming from different data flows to be true before returning a value. The join operator represents a wide range of possible data reductions. Depending on the selectivity of the join, it is possible to reduce the resulting data size.

ACQUIRE: active query forwarding

The active query forwarding in sensor networks (ACQUIRE) [104] aims to reduce the number of nodes involved in queries. In ACQUIRE, each node that forwards a query tries to resolve it. If the node resolves the query, it does not forward it further but sends the result back. Nodes collaborate with their n hop neighbors, where n is referred to as the look ahead parameter. If a node cannot resolve a query after collaborating with n hop neighbors, it forwards it to another neighbor. When n is equal to 1, ACQUIRE performs as flooding in the worst case. Query resolution in ACQUIRE is depicted in Figure 4.11.

Figure 4.11. Query resolution in ACQUIRE

MARQ: Mobility Assisted Resolution of Queries

MARQ [46] makes use of the mobile nodes to collect data from the sensor network. In MARQ, every node has contact with some of the other nodes. When contacts move around, they interact with other nodes and collect data. Nodes collaborate with their contacts to resolve the queries.

SQTL: Sensor Query and Tasking Language

Sensor query and tasking language (SQTL) [114] is proposed as an application layer protocol that provides a scripting language. SQTL supports three types of events, which are defined by the keywords *receive*, *every* and *expire*. The *receive* keyword defines events generated by a node when the node receives a message; the *every* keyword defines events occurred periodically; and the *expire* keyword defines the events occurred when a timer expires. If a node receives a message that is intended for it and contains a script, the node executes the script.

SQS: SeMA Querying Protocol for Micro-Sensors

Figure 4.12. *SeMA architecture*

SeMA is an enhanced client-server architecture in which clients are supported to adapt themselves to the new network resources they discover on-the-fly. The nodes get service information either by catching the periodically advertised services or by generating a service request. Applications establish light-weight sessions with the resources using the address returned to them. Binding is done when the service is needed. SeMA is a cross-layer protocol, capable of operating on generic wireless data link layer protocols, such as IEEE 802.11. SeMA addresses issues such as service announcement,

binding, session management and data routing. The monitoring of sensor networks is an application of the SeMA architecture. The terrain of the sensor deployment area is assumed to be suitable for navigating by means of mobile units, which form the information retrieval backbone of the overall monitoring application [12]. These mobile units are either wireless equipment-carrying living, or autonomous, robots as seen in multi-robot exploration studies. The architectural view of the system is shown in Figure 4.12.

All available resources on the SeMA network are considered as services. They play a major role on a SeMA network, since mechanisms of the protocol are built with the aim of providing means to access those services. Specification of a service should include necessary information for SeMA clients to determine whether the service fulfills the client's need. Thus, services are modeled with a generic name, and follow attribute-value pairs. This definition is sufficient for a host to discover a required service without any bindings beforehand. Details of XML processing of services and ad hoc routing in the backbone can be found in reference [12]. In a sensor network application, clients of the ad hoc network backbone become the middleman, which is defined in XML in Figure 4.13. They participate in forming query driven sensor trees adaptively and backbone features are used to announce queries and return collected results.

```
<service name = monitoring application>
<keyword attribute = validUntil>20031128193044EEST</keyword>
<keyword attribute = queryPredicate>sensor:read[value>100 and
  order(value)<5]</keyword>
<keyword attribute = resultFunction>fn:concat</keyword>
</service>
```

Figure 4.13. XML definition of a monitoring service

Queries for data of interest are transmitted through the backbone in service announcement packets. Service definitions contain an XQuery predicate, a result function and query timeout period (QTP), as well as geographic region boundaries of the area of interest. An XQuery predicate is used to extract the readings that interest the monitoring application. Then, if specified in the service, these readings may be processed via the given result function. The actual query result to be submitted is the returned data from this XQuery function. XQuery specifies more than 200 functions (including functions in SQL) that include numerical processing, data aggregation (sum, avg, min, max), string operations (string-join, starts-with, ends-with), pattern matching (matches, replace, tokenize) and more. By using XQuery in value fetching and processing, the sensor querying process conforms to XML standard, from the

monitoring application down to the sensor nodes. Temporarily posed sensor drivers convert service parameters and the XQuery predicate to a bitwise coded format. The coded query is sent to sensors in the payload field of the set-up packet. In this model, sensor nodes are assumed to be very simple equipment with limited processing and battery power. The set-up packet initiates a tree topology network in the area of interest among the sensors that have accepted the query.

DADMA: Data Aggregation and Dilution by Modulus Addressing

In DADMA, a sensor network is considered as a distributed relational database composed of a single view that joins virtual local tables named Virtual Local Sensor Node Tables (VLSNT) located at sensor nodes. Figure 4.14 shows the distributed database perception of DADMA. Records in VLSNT are measurements taken upon a query arrival and consist of two fields: task and amplitude. Since a sensor node may have more than one sensor attached to it, the task field indicates the sensor, e.g. temperature sensor, humidity sensor, etc. that takes the measurement. Since sensor nodes have limited memory capacities, they do not store the results of measurements. Therefore, there can be a single reading for each sensor attached to a node, and the task field is the key field in the VLSNT created upon a query arrival. Our perception of WSNs makes relational algebra practical to retrieve the sensed data without much memory requirement, which is different from the scheme explained in [70], where the sensed data for each task are maintained at a different column in a table.

Sensor Network Database View (SNDV) can be created temporarily either at the sink, i.e. the node that collects the data from the sensor network, or at an external proxy server. An SNDV record has three fields: task, location and amplitude. While data is being retrieved from a sensor node, the location of the sensor node is also added to the sensed data. Since multiple sensor nodes may have the same type of sensors, i.e. multiple sensors can carry out the same sensing task, task and location become the key fields in an SNDV. In applications where nodes are not location-aware, it is also possible to replace the location field with the local identifications of the reporting nodes. The location field can also be used to identify a group of nodes according to the aggregate and dilute functions explained below. It should be noted that SNDV is a temporary view where the results of a query are collected.

For many WSN applications, the sensed data need to be associated with the location data. For example, in target tracking and intrusion detection WSNs, sensed data are almost meaningless without relating them to a location. Therefore, location-awareness of sensor nodes is a requirement imposed by many WSN applications. There are a number of practical location finding techniques for WSNs as reported in [8].

Since each query results in a new SNDV, to keep the aggregated/diluted history of a WSN it may be needed to maintain a permanent External Sensor Network Database Table (ESNDT) in a remote proxy server. In ESNDT, the records obtained from

Figure 4.14. A sensor network perceived as a distributed database

queries, i.e. the records in SNDVs, are stored after being joined with a time label. For example, a demon can generate queries at specific time intervals or at the occurrence of a specific event, and insert the records of SNDVs resulting from these queries into the ESNDT. To distinguish the equal amplitudes sensed by the same node about a specific task during different periods, the task, location and time fields make up the key fields in an ESNDT.

In DADMA, a statement that has the structure given in Figure 4.15 starts a query. This structure is largely a part of the SQL standard [10] except for the last field starting with “based on” which will be explained later in this section. Using an SQL style statements for a generic query interface has some advantages as described in [70]. Programmers and system administrators can use this practical and standard interface for all kinds of WSN applications. Hardware design for WSNs can also be optimized to run this language.

In the select keyword of the SQL statement, common aggregation functions such as avg, min, max can be used to indicate how to aggregate the amplitude field. The fields to be projected from an ESNDT are also listed after this keyword. The “from” keyword indicates the nodes to be involved in the query. Any means that even a single node may be enough to resolve the query, and any node in the sensor network can do it. When the “every” keyword is used, all of the nodes in the sensor network are supposed to be involved in the query. When a task or a set of tasks is given in the query, only the sensors in the specified types carry out the measurement. Aggregate

```

Select    [task, time, location, [distinct | all], amplitude,
          [[avg | min | max | count | sum ] (amplitude)]
From      [any, every, task, aggregate-m, dilute-m]
Where     [power available [<|>] PA]
          Location [in | not in] RECT |
          tmin<time<tmax|
          amplitude [<|==|>] a]
Group by task
Based on [time limit = lt | packet limiy = lp |
          resolution =r |   region = xy]

```

Figure 4.15. *The structure of an SQL statement for DADMA*

and dilute keywords are also introduced to spatially group the nodes. The “where” keyword is for defining selection conditions according to available power and/or time and/or amplitude and/or location. The “group by” field is used to specify the set of tasks for which the aggregation of the sensed data will be carried out. The “based on” keyword is followed by the parameters required for the aggregation and dilution algorithm run by the sensor nodes. In [22], the distributed algorithm that process the queries in this format is explained.

4.4.6. Data aggregation

Since WSNs are comprised of large numbers of energy-constrained, inexpensive devices deployed in possibly inaccessible areas, battery re-charge or replacement is not a viable option. For this reason, energy-efficient protocols have to be developed to minimize device energy consumption, hence maximizing the amount of time during which the network can be fully operational (denoted as network lifetime in the following). In such resource constrained devices, the dominant component in terms of energy consumption is the wireless transceiver. This imposes the development of an energy-efficient protocol stack.

In general terms, an energy-efficient communication protocol is a protocol designed to minimize the energy-consumption associated with its operations without significantly degrading other relevant metrics performance (such as delay, throughput, etc.). Energy-conservation often involves trade-offs (energy vs. accuracy, energy vs. delay, etc.) that have to be considered when in the protocol design.

The basic building blocks to energy-efficient solutions for WSNs are the following. The wireless interface consumes a fixed amount of energy for receiving (due to the transceiver circuitry), while the cost for transmitting is comprised of two components: the first is fixed and is due to the transceiver circuitry, and the second component

depends on the emission power. Depending on the transmission range of the considered technology, the cost due to the fixed component may be either negligible or higher than the cost due to the emission power. Short transmission ranges (between 20-30 m) have comparable costs when in an idle state, or when receiving and transmitting. In these scenarios (which reflect the typical operational scenarios of a CO network), the network lifetime is prolonged by keeping the nodes in the "asleep" state in which the interface is not operational, nodes cannot transmit or receive packets, but the energy consumption is much lower (around two orders of magnitude smaller than the cost in the idle state). Other possible states include the idle state, in which the transceiver is operational but no communication exchange is taking place, and the transmit (receive) state in which the transceiver is operational and is currently transmitting (receiving) a packet. The exploitation of the scheduling between awake states (idle, transmit, receive) and the asleep state is one of the basic tools used by energy-efficient protocols for decreasing energy consumption. Other techniques include minimizing the amount of transmitted information, avoiding the waste of resources, transmitting only when it is likely that the data will be received correctly, minimizing protocol overhead, and designing awake/asleep schedules that do not significantly increase data latency. In many sensor network applications, the low transmission range translates in the need of keeping the transceiver asleep for as long as possible. Thus, decreasing the amount of information transmitted and the corresponding overhead are still important issues for managing energy-efficiency. By reducing the load, it is possible to decrease the amount of time devices have to be in the awake state.

Some solutions have been developed for minimizing the load of the WSNs, which are based on the elimination of the redundancy in the transmitted data. In a WSN, many nearby nodes detect the same or similar events, so that the information they transmit is highly correlated. Some of the relay nodes can thus buffer a few packets and process them, eliminating redundancy. This process is often referred to as data aggregation or data fusion. Data fusion reduces the amount of transmitted data (thus possibly the energy consumption) at the price of increased delay. Other trade-offs which have to be considered in the design of a good data aggregation strategy are energy vs. robustness and energy vs. accuracy. Depending on how data fusion is performed at the aggregation points, the precision with which an event is reported may be compromised. It is possible to simply concatenate in the same packet the data of several packets (saving in terms of header bytes). However, the majority of the advantages that can be obtained in decreasing the load come with techniques which combine the data. The drawback here is that this approach results in a partial decrease in precision/accuracy. A second problem is that the inherent redundancy of the transmitted information makes the data delivery process more robust in the presence of transmission errors. If redundancy is avoided, then aggregated packets should be strongly protected to avoid their corruption or wrongful delivery. An effective solution for data fusion has to consider all these different trade-offs, so that data fusion is maximized while maintaining data latency, accuracy and robustness degradation within limits tolerable for the specific application.

Data fusion has two aspects: a scheme to select the roles of the different devices that act as aggregators (how many aggregation points there are, and where), and the data fusion strategy used at these points (how to determine which data to aggregate, how long is it worth waiting for or how many packets before aggregating and forwarding, etc.). Data fusion should also be combined with other protocols (data link, routing, etc.) for further optimization.

In the following, we review the most recent works in the area of data aggregation.

4.4.6.1. *Types of aggregation*

Packet-level aggregation

This scheme works by dropping duplicate packets and by merging several packets to reduce the overhead due to header transmission. This technique can always be applied to only affect data latency. No loss occurs in terms of data precision. No compression of highly correlated data is performed.

Total aggregation

In this case, all data received within a given time interval can be fully aggregated. This kind of aggregation can be realistic for given types of queries. For instance, when the average temperature in the area monitored by the networks is needed at the network collection point (the sink), an aggregation tree could be built rooted at the sink in which each internal node can be an aggregation point. Each point has simply to collect from each of its children the average value of the temperature, and the number of samples it was obtained from. All these values are then combined to form a single packet that conveys the average temperature in the area monitored by the point subtree. The size of the packet which will be sent out, containing the new average and number of samples, is the same as that of the packets received at the point.

Geographic aggregation

This scheme of aggregation, proposed in [2], assumes that data related to certain events can be aggregated if their sources are geographically close and the events happen within a certain time interval. This implies that data precision is maintained. (The precision here refers to both the geographical place of the events and the times of their occurrence.) Such aggregation tries to model scenarios in which the sources can classify events and send a code classifying an event, together with the time of occurrence and the location to the sink(s). With this time of aggregation, aggregation points away from the sources of the events may not be able to aggregate data. To obviate these problems, [2] proposes enhancing the method by co-locating aggregation points with cluster heads, i.e. specific network nodes chosen in such a way that aggregation points are well-spread throughout the network.

In [115], the authors point out the major advantages of data fusion. Many of the queries asked by users require aggregating and combining the data generated by the

sources (so why not perform such processing aggregation in the network instead of at the final destination, saving energy and network resources?). In-network aggregation also allows for the comparison of different measurements of a given event before transmitting the information to the sink(s). A comparison among different samples at the aggregation points allows for the identification and filtering of false or inaccurate measurements performed by faulty or malicious sensor nodes.

There is a huge difference in terms of network load when answering an average or a median query: the first can be answered by delivering aggregated information and the second needs to bring to the sink(s) information on the distribution of the sensed values. The solution proposed in [115] addresses this problem, proposing a representation of value distributions which allows us to answer the listed types of queries with a bounded accuracy while significantly compressing the amount of information which have to be disseminated in the network. This is achieved by defining and transmitting compressed information on the measured value distribution, denoted as a quantile digest. Quantile digests can be combined by aggregation points without compromising the resulting accuracy, and can be used at the final destination to answer quantile, range and consensus queries. The amount of transmitted information is significantly reduced in the case in which all the sensed data have to be reported.

[32] describes a security problem associated with data fusion. The current data fusion process puts a great deal of trust in aggregation points. Not only is a consensus-based mechanism needed to filter out information transmitted by malicious nodes, but also a scheme has to be designed for the sink(s) to have proof of the validity of the reported aggregated information, since aggregation points themselves may be faulty or malicious. The way this problem is solved in the paper is by adopting a witness-based data fusion node assurance scheme. It is assumed that there are more nodes which gather the same data and result in the same aggregated packets, even if only one aggregation point reports such results to the sink(s). Such nodes know of each other. Each node computes a summary of the results and encrypts it, sending it to the selected aggregation point which will have to transmit all such summaries together with the aggregated data to the sink(s). The final destinations will then be able to compare the summaries of the witnesses and of the aggregated data and use a voting scheme to decide if the reported data is reliable.

4.4.6.2. *Selection of the best aggregation points*

In [99], a way to select aggregation points is presented. The goal is to maximize the aggregation gain (the reduction in terms of network load achieved via data fusion) while maintaining the end-to-end delay below an application-dependent threshold T . A static sensor network with a single sink is considered. The authors provide a mathematical formulation to select one single aggregation point per path in order to maximize performance. Heuristics are then derived from this formulation and integrated with WSN routing (tree-based or directed diffusion based routing). A performance

evaluation shows the advantage that can be achieved by means of such a way of selecting aggregation points with regard to more empirical approaches. The paper also points out how delay of data fusion should be rewarded by a significant amount of aggregated data, so lower or higher delay spent at aggregation points should depend on the amount of data that can be fused at that aggregation point.

In [117], the authors assume a set of aggregation points and address the problem of setting the timeouts at the different aggregation points encountered along the source-destination paths. The assumptions made are the periodic transmission of data from the source to the sink and the adoption of a tree-based converge-casting. Three different approaches are compared: 1) periodic simple, in which all the packets received within time T are aggregated, 2) periodic per hop, in which an aggregation point waits to receive data from all its children in the dissemination tree before it sends the aggregated packet out (recall the traffic is periodic), and 3) the proposed approach in periodic per hop adjusted. In this latter approach, the authors envisage the use of cascading timeouts. Not only do timeouts depend on the aggregation point position in the dissemination tree but a node timeout will happen just before its parent. In this way, a cascading effect (i.e. data originating at the leaves will be clocked out first, reaching nodes in the next tree level in time to be aggregated at that level together with the data originated at that level and so on) reduces the overall delay to reach the sink. Comparative simulations among the different schemes show that, as expected, a cascading timeout-based scheme reduces delay without impacting the resulting received data accuracy. Similar ideas have been reported in [133] for the case in which the WSN traffic is event-based. The authors discuss the potential inefficiencies associated with data fusion in the case where timers are not synchronized: though the packets sent by sources are generated at similar times as they detect the occurrence of an event, unsynchronized settings of the aggregation point timers may result in an aggregation point at level i not being able to gather information from the nodes at level $i + 1$ before performing aggregation. To avoid this problem, each aggregation point starting its timer informs its neighbors, also triggering their timer start, and the timer's duration depends on the aggregation point level in the tree. The solution proposed exploits synchronization and different timer settings at the different levels to allow a node at level i to gather information from the previous levels before its timer clocks out.

In [19], it is proposed that clustering to select cluster heads as aggregation points is exploited. In addition, the paper proposes assigning an interval of possible values to each metric of interest and to select critical values for each measured metric. A pattern code is then computed based on the measured values and sent to the cluster head. The cluster head uses this aggregated implicit information of the data gathered by the sensor node to deduce whether some of the data to transmit are redundant and to avoid redundant transmissions before they occur. Redundancy is thus eliminated by a pattern code exchange between the sensor nodes and their cluster head and by the cluster head deciding based on such codes, which sensor should send the data. This

also avoids security problems associated with cluster heads receiving data and having to decrypt them to perform the data fusion operation. In the proposed scheme, denoted EPSDA (energy-efficient and secure pattern-based data aggregation), data encryption is performed end-to-end by means of symmetric cryptography. A way to select aggregation points in a hierarchical WSN organization is also proposed in [7], based on an ILP formulation which jointly addresses aggregation points selection and routing. In [89], the authors define a metric to evaluate the level of compression achieved via data fusion. Variants of protocols for data dissemination proposed in other works (LEACH and PEGASIS) are then proposed in order to maximize the possibility to perform aggregation. It is shown how the extended solutions decrease network load and energy consumption without significantly affecting accuracy over the basic LEACH and PEGASIS schemes.

In [113], the authors claim that instead of grouping devices into clusters based on a distance-based criterion, the hierarchical tree-based communication infrastructure used to deliver the data back to the sink should be designed to group the same subtree nodes which belong to the same group. Group affiliation is attribute-based and reflects the possibility to answer similar queries and to lead to possibly redundant, merged data (in addition to the affiliation to the same group, devices are organized into a tree also based on a distance criterion so that highly correlated data are likely to have such redundancy eliminated close to the sources). This groupware-based tree results in a significant increase in terms of capability to effectively aggregate data. In addition, the TiNA (Temporal coherency aware in Network Aggregation) scheme is adopted. New data are reported only when they differ significantly from the last reported data (how significantly is an application-dependent factor which is communicated via interest dissemination). Overall the two schemes combined lead to significant energy saving.

In [41], an adaptive scheme to determine how many packets to wait for (and how much time to wait for) before performing aggregation is proposed. First, the authors propose a solution in which, instead of waiting for a fixed amount of time or a fixed amount of packets, an aggregation point simply tries to exploit the availability of the wireless channel. If the channel is available, the aggregation point transmits a packet aggregating the queued packets. This reflects, for example, the following way of reasoning. If data aggregation and awake/asleep schedules are decoupled, there will be times in which the aggregation point has its radio interface and in which the channel is free. Transmitting or delaying transmission does not significantly change the energy consumption (as the costs associated with transmitting or being idle when the transceiver is operational are similar in these networks), but can severely affect the end-to-end delay so it may be convenient to transmit anyway. This scheme is named the on-demand scheme. What is not considered in this scheme is that a single device decision to transmit may impact the possibility of another device to do the same in a CSMA/CA-based network. What would be interesting to have is a dynamic scheme which adapts its decision to make the MAC layer operate at a desirable operational

point, limiting on one side the amount of transmitted data (aggregating several packets in the queue in each packet sent out) but also maintaining a low delay period. This is the idea behind the proposed dynamic feedback scheme which adopts a dynamic controller to achieve this goal. Simulation results show that in schemes which rely on fixed thresholds, the proposed solutions achieve the best compromise between the decrease of network load and delay. The dynamic feedback scheme is particularly valuable as it is able to operate efficiently under varying network load conditions.

4.4.7. Resource management

Generally speaking, COs are battery powered devices that usually lack resources, such as a CPU, memory and power, to name a few.

COs may form a self-organizing network, in which COs arbitrarily join and leave the network or even move during an operation. Since system components are distributed, any action often involves multiple COs at a time. Due to the distributed, dynamic and uncertain nature of system components (since both COs and communication are associated with uncertainty), the design of such embedded wireless collaborative systems proves to be difficult and requires a scheme to facilitate the system design and application development.

Resource management aims at providing a way to manage the resources of a system by enabling high-level system primitives to hide unnecessary low-level details. It enables the application to be independent of the actual underlying distributed system. It should also address the dynamic nature of available resources, such as variable network bandwidth. Because the system is built of fault-prone components, failures should be handled as normal and not as exceptions.

4.4.7.1. Design challenges

Traditionally, *system software* aims at providing a unified way of using underlying resources. System software operates the system and manages available resources in a way that provides higher-level services that are usually required. System software consists of three major components:

- *Operating system (OS)*: the OS aims at providing a set of services that are generally needed by application developers, such as starting and stopping processes or allocating memory and other resources. These services make the system much easier to manage, since the actual low-level details are kept hidden from the application developer. The operating system provides a unified interface to use resources and also manages its allocation among incoming requests.
- *Protocol stack*: communication software is decomposed into a set of standardized layers, referred to as a *protocol stack*. Different layers provide different abstraction levels of generally needed networking services. Layers use some of the underlying

services to provide some higher-level services. It aims at hiding the heterogeneous low-level details of the network. The standardization of these layers played a significant role in the success of Internet deployment.

- *Middleware*: this is a reusable system software that bridges the gap between the end-to-end functional requirements and the lower-level OSs and protocol stacks. Thus, it is a piece of software running in each member of the network, and its goal is to provide high-level services that are independent of the heterogeneous underlying systems.

The layered design has proved to be a very successful approach to designing complex systems. Defining high-level interfaces to easily use underlying complex functionality makes application development easier, but unfortunately makes the tuning of *non-functional properties* extremely difficult. These properties usually remain spread across several system layers, thus it is impossible to make modifications to them in a single place. Energy-efficiency or fault tolerance are such non-functional properties. Optimization issues, such as energy-efficiency, usually require special details that may be hidden by the interfaces. Higher layers can make better decisions by working together with the OS, and sometimes it is beneficial to influence the behavior of the OS to meet some higher level needs. Optimizations in separated layers may not achieve a global and synchronized goal. A well known example is the unfortunate action of the OS putting the system into stand-by while the user is giving a presentation.

In networking, the layers of the protocol stack are defined in a way to let them be developed independently. However, a number of dependencies and redundancies among different protocol layers make the communication *energy-inefficient*. In [28, 40], in which the cross-layer nature of low-power ad hoc wireless network design is characterized, it is shown that cross-layer design is more energy-efficient.

Therefore, for energy-efficient designs, the traditional strict modularization or layering is not appropriate. For example, in sensor networks, the monolithic design of communication software is common to reach the required energy-efficiency needs. However, such a design makes system development and management very difficult. In the next sections, we will present solutions that allow both development and management easy, and at the same time allow for optimization of non-functional properties.

4.4.7.2. *Adaptation in resource management*

In embedded wireless collaborative systems, the availability of the underlying resources is highly dynamic. For example, the networking conditions may change frequently, thus the available bandwidth and the certainty of communication varies. Such a change may influence the chosen networking layers or possibly change the whole behavior of the application. The traditionally applied approach of a resource request and its allocation does not provide the needed flexibility anymore [94]. The system must adapt to changes in the surrounding physical and virtual environment.

Instead of allocation, a *resource negotiation* should take place and the allocation of available resources should be adaptive. *Adaptation* is the ability of a system to change its behavior in response to environmental changes.

Early experiments highlighted that in the case of dynamic underlying resources, the ultimate goal of resource management is to combine adaptation with allocation. It is not beneficial to handle the system as a transparent entity with fixed services; instead, the system should allow the negotiation of resource demands and supplies. To manage such dynamic resources, the system software should meet new requirements. It should drive the negotiation of resource supply and demand together with the applied mechanisms based on the environment.

4.4.7.3. *Adaptation and enabling technologies*

Over the years, various technologies have contributed to the evolution of adaptation and reconfigurable software design [5, 76]. Since the main aim is to enable the software to reconfigure itself dynamically based on some conditions, the core of the majority of approaches is the interception and redirection of interactions among software entities.

Middleware

Middleware is defined as a piece of higher-layer software present in each member of a possibly heterogeneous network [29]. Its purpose is to provide high-level services to make the development of networked applications easier by hiding details of the underlying infrastructure, such as the OS and network protocol details. Since it represents another level of indirection and transparency, it is a straightforward way to provide adaptive behavior.

Middleware is commonly divided into four layers [111]. *Host infrastructure middleware* is directly on top of the OS and provides a high-level API to hide lower-level heterogeneity. *Distribution middleware* provides high-level programming models, such as remote objects, enabling the developers to use local and remote objects in a similar way. *Common middleware services* define higher-level domain independent components to help manage resources. Finally, *domain-specific middleware* is usually designed specifically for a particular class of applications. Any of these middleware layers may be a suitable place to provide adaptive behavior.

Many of the adaptive middleware platforms work by intercepting and modifying messages to provide a level of indirection to influence behavior of the application. Most of the adaptive middleware approaches are based on some popular object-oriented middleware platform such as CORBA or JavaRMI. A large number of adaptive middleware approaches exist, and their taxonomy can be found in [77].

However middleware-based adaptive frameworks may not be sufficiently flexible; their application is straightforward from the software development point of view.

These solutions may provide a way to extend heterogeneous, layered systems with the ability to adapt.

Component-based design

Software decomposition to separate modules has become a fundamental approach to make the development of reusable components independent of each other. Software components are reusable software entities that third parties can develop independently and can easily be composed and deployed as general components in the future [122]. Popular platforms include COM/DCOM [79], Microsoft.NET [78] and Enterprise Java Beans [120].

Well-defined interface specifications enable service clients and providers to be developed independently; however, it turns out that the specification of the functional interface usually does not provide enough flexibility to reuse the component. The details of how the component would behave in certain conditions are usually crucial to design choices. To trust a component, specific guarantees should be available regarding its non-functional properties. These guarantees are called *contracts* [15].

Contracts may be categorized into four levels. Level 1 is the basic or syntactic level that defines the functional interface needed to use the module. Level 2 provides behavioral level contracts, which gives more information about how the functionality reacts in different conditions. Level 3 is the synchronization level, which describes synchronization properties required in parallel environments. Finally, level 4 describes QoS properties, such as response delay.

The composition of modules can be categorized into two large groups. In *static composition*, the developer chooses the appropriate composition at compile-time and it cannot be changed later in run-time. In contrast, *dynamic composition* makes it possible to add, remove or reconfigure components during run-time. *Late binding* is the technology that enables coupling of compatible components at run-time.

The system may also support multiple different versions of a given component with different contracts. In such cases, this may be an enabling technology to adaptively select the versions that are the most appropriate for the given environmental conditions.

Computational reflection

Computational reflection is the ability of a software system to reason about and possibly alter its own behavior [73]. Reflection exposes a system's implementation at a level of abstraction that contains enough details and enables necessary changes. The ability of a system to observe and change itself is a key enabling technology towards self-modifying code.

Computational reflection involves two activities. *Introspection* allows the system to observe its own structure or behavior. This may involve revealing its structure or evaluation of software-sensors to collect statistics. The other main act is *intercession*, which enables the system to act on the observations and make necessary modifications. This may be the replacement of a module, or installation of new monitoring components.

In reflective systems, the actual *base-level* software includes its abstract self-representation as a special object. This is called a *meta-level* representation, which represents the actual objects of the base-level. The two levels should remain causally connected.

Direct exploration of the meta-level would provide many details about the base-level objects, but it also makes the process difficult and error-prone. A *meta-object protocol* (MOP) [57] is a higher-level interface that enables easier introspection and intercession by enabling systematic access to meta-level objects. MOP can be categorized as enabling either structural or behavioral reflection. *Structural reflection* reveals inner structural details, such as class hierarchy, object interconnection and data types. In contrast, *behavioral reflection* focuses on higher-level computational semantics of the application, such as the application of a new mechanism.

Reflection may be provided by a programming language in a native way, such as in Lisp [116], Python [95] or in some Java derivatives such as Reflective Java [131]. Even if the programming language does not directly support reflection, similar functionality can be implemented in a higher level using a middleware platform [16] such as KAVA [127] or OpenCorba [66]. Instead of programming construct representation, reflective middleware deals with the self-representation of middleware services.

Reflective abilities of a software system obviously play a key role to provide adaptation.

Separation of concerns

Over the past few years, some major difficulties in software decomposition have been revealed [86]. Consequently, it was realized that the same functional behavior can be implemented with several different decompositions.

Separation of concerns [1] is a software development technology that aims at separating the development of the application's functional behavior (business logic) from other non-functional requirements. The non-functional concerns are usually cross-cutting concerns spread across several modules, such as QoS, energy consumption or fault tolerance. This approach allows for the separate development and maintenance of concerns, while providing a straightforward opportunity for adaptation.

The most widely used approach is *Aspect Oriented Programming* (AOP) [59]. It includes abstraction techniques and language constructs to manage different concerns of the system separately. The codes implementing different concerns, called aspects, can be developed separately. *Pointcuts* are placed into the functional code to signal the locations where different aspects may be woven. Finally, a specialized compiler called the *aspect weaver* is used to combine aspects with the business logic of the application (Figure 4.16). Examples of such AOP frameworks are the AspectJ compiler [58] and KAVA [127].

Figure 4.16. *Aspect weaving in AOP*

Composition filters [14] is an approach that dynamically intercepts messages that are sent and received by components. Filters can be applied to all input and output messages, or can select particular messages. Such filters are developed independently and can be compiled into the source code or can be preserved as run-time manipulation objects.

Similarly, aspect weaving at compile-time results in a tangled executable, which is not reconfigurable later. However, some recent approaches delay the weaving process until link- or run-time [124], thus providing a way to tune different aspects of the system during execution.

4.4.7.4. *Adaptation frameworks*

This section introduces some of the most important cross-layer adaptation frameworks and projects. These frameworks assume that mobile devices are more resource rich than wireless sensor nodes. However, these frameworks present interesting adaptivity concepts that could be at least partially implemented in smaller devices to achieve a desirable degree of resource management.

Odyssey

Odyssey [85] was one of the early attempts to demonstrate *application-aware adaptation*. It demonstrated how application-awareness would result in enhancements in system performance.

Odyssey supports the change of application quality based on low-level system conditions. When the system cannot guarantee the required supply, the application should regulate its demand. The project demonstrated the effectiveness of the approach by scaling down video quality in case the bandwidth decreased.

The key point in Odyssey was to extend the OS resource allocation API with resource call-backs. Applications register a tolerance window in Odyssey and receive a call-back when the required resource levels cannot be kept within the tolerance window. At that point, the application can adapt and the resources can be registered again. Only minor changes are needed to port applications to Odyssey, and it is demonstrated that in some cases it is also possible to avoid any changes.

In [82], Narayanan extends Odyssey to achieve a cross-layer adaptation solution in order to support mobile interactive applications. These kind of applications require low response times and a long battery life, while the available resources are varying. Their work introduces the term *fidelity* as a metric of accuracy. *Data fidelity* is the extent to which the degraded version of a data object matches its reference version. On the other hand, *computational fidelity* is a run-time parameter of an algorithm that can change the quality of its output. The framework uses *multi-fidelity computation* to achieve adaptive behavior.

A major difficulty addressed in their framework is to bridge the gap between the three independent parameter dimensions:

- user satisfaction metrics (utility);
- application parameters (fidelity choice);
- resource supply and demand of the system (resources).

The presented solution uses *resource supply predictors* to predict the available amount of system resources, such as CPU availability. *Performance predictors* give performance metrics, such as delay or battery lifetime, as a function of resource supply and demand, and *resource demand predictors* compute application resource needs as a function of fidelity and non-tuneable properties.

Some of these predictions are application-dependent. This is solved by providing an application-dependent binary module called a *hint module*. Moreover, the system has to be aware what fidelity values are possible for the given application and what are the actually used non-tunable parameters. These are declared in the *application configuration file*.

The architecture of the run-time system can be seen in Figure 4.17. Note that only the hint module is application-dependent. The central component that drives the adaptation is the *solver*. Its task is to search the state space of tunable parameters and find a set of values that maximizes the utility. When the application starts, it submits the

Figure 4.17. System architecture for multi-fidelity API

values of non-tunable parameters. A set of generic supply predictors predict the applications' resource supply for the near future. The solver searches the space of tuneable parameters for the best possible combination.

The evaluation of candidates is done by computing their utility, which is application-dependent. The solver sends the tuneable and non-tunable parameters as well as the resource supply prediction to the utility function. The utility function invokes performance predictors to compute delay and battery drain for the particular choice. Performance predictors call application-specific resource demand predictors to compute performance.

Resource demand monitors compute the resource demand of the operations performed. The logger records these values together with the applied parameters to update demand-predictors based on online learning techniques.

The effectiveness of the framework is demonstrated by several experiments ranging from augmented reality to speech recognition.

RAPIDware

The aim of the RAPIDware project [96] is to design an adaptive, component-based middleware for dynamic mission critical systems. These systems must continue to operate correctly even during exceptional situations. Such systems require run-time adaptation, including the ability to modify and replace components, in order to survive hardware component failures, network outages and security attacks. RAPIDware is a significant research effort, which applies the combination of computational reflection and aspect-oriented programming to support software recomposition at run-time.

Sadjadi *et al.* [105] present an adaptable communication component called *MetaSocket*. It is an extension of a regular Java socket to provide adaptable communication services. A *MetaSocket* is created using Adaptive Java [55], a reflective extension to Java.

To convert an existing Java class into an adaptable component, two main steps are required. Figure 4.18 illustrates the two steps on a multicast socket component, which enables it to adapt to meet different QoS needs. The first step is called *absorption*, which transforms the class to a base-level Adaptive Java component. This base-level class has a set of mutable method invocations, which expose the functionality of the absorbed class. In the example, the absorption steps create a send-only multicast socket, which implements only the *send()* and *close()* adaptable invocations. Links between invocations and the methods are highlighted by lines in the figure. The following step is called *metafication*, which enables the systematic investigation and changing of base-level invocations. In the example, this means inserting or removing filters to the multicast stream, such as different error-correction filters. By this, the socket component is adaptable to meet different quality requirements.

Figure 4.18. *MetaSocket* absorption and metafication

These steps use TRAP/J [106], a Java implementation of TRAP, to weave in the required adaptive behavior. The framework takes an existing Java class together with the list of required adaptable invocations as its input, and makes the required adaptable class as its output. It uses the AspectJ compiler [58] to generate the adapt-ready version of the application.

A *MetaSocket* enables the middleware or an application to monitor the communication status and to insert, remove and configure adaptation filters at run time. With the help of *MetaSockets*, a kernel-middleware interaction framework is provided in [108] to support both horizontal and vertical cooperating of components. The Kernel Middleware Exchange (KMX) project addresses the interaction between the middleware and OS layers to support universal adaptation. This approach is especially well-suited to mobile ad hoc networks and overlay networks, where a set of nodes collaborate to accomplish collaborative services.

This framework thus provides an interesting mixture of aspect-oriented programming and reflection to easily turn software components into adaptable ones. Their

work also points out how a universal adaptation framework can be feasible by using such components.

GRACE

The Illinois GRACE project [4, 103] aims at providing an adaptation framework for saving energy in mobile multimedia systems. In the considered system, all the system layers and applications are allowed to be adaptive. These adaptive entities cooperate with each other to achieve a system-wide optimal configuration in the presence of variations in the available resources and application demands.

One of the main questions addressed in this research is how to achieve global adaptation with an acceptable overhead, since adaptation with global scope potentially results in a larger overhead. GRACE supports three levels to provide a balance between the scope and the temporal granularity of adaptation:

Global adaptation is invoked only infrequently, in response to large changes in resource supply or demand. It considers all applications and all the system levels. A global coordinator performs the resource allocation by searching through the space of all possible configurations and evaluating the overall utility and resource usage for the particular choice.

Per-application adaptation considers only one application but all system layers at a time. At this time, the accuracy about the resource demands of the actual application is more accurate, thus making finer granularity decisions possible.

Internal adaptation adapts only a single system layer or application at a time. Since it does not need to consider the cross-product of configurations, it can be very efficient. Unfortunately, the system may only remain in a local minimum of optimality.

Another main question this framework addresses is how to make the prediction of future demands and supplies. All the adaptation levels require predicting the resource demands for each application. Global adaptation requires long-term prediction, while per-application adaptation requires prediction only for the next job. For the moment, history-based prediction techniques are commonly used.

The prediction is not straightforward, since the resource usage depends on the actual system and application configuration in use. The approach in GRACE to address this problem is to divide the prediction problem into two parts. The *system-independent* part can be predicted entirely by the application. The other is the *system-dependent* part, which is handled by the specific system layer. For example, the CPU time demand of a job can be divided into the number of instructions and the time per instruction parts. The former is independent of the system, while the latter depends on the actual configuration.

GRACE provides an architecture for the optimization process as well. This framework controls when different levels of adaptation are triggered and also finds the optimal configuration. In the proposed solution, local and global adaptations together allow the system to find a better configuration. The simulation-based evaluation shows the benefits of the solution.

DEOS

The DEOS project addresses the problem of how to best meet the dynamic QoS requirements of end-users in face of dynamic changes in the underlying hardware/software platform's resources. However, the project mostly focuses on QoS issues. The proposed solution involves both the system and the application.

In the project, *Q-fabric* [90, 91] is presented. Q-fabric is a kernel-level abstraction for cooperative, distributed resource management and adaptation. The solution is based on a kernel-level event notification service, which follows the publish/subscribe paradigm to exchange specific events. Such events may be related to monitoring activity, or can also be the trigger event of an adaptation process. Since the event service is fully anonymous, it is a flexible way to let separate local resource managers cooperate.

A resource manager can be seen in Figure 4.19. Its task is to distribute system resources among a number of competing applications based on a policy. The monitor entity keeps track of changes in resource allocations and keeps statistics, and it also submits monitoring events. The adaptor receives such events and makes decisions about triggering changes either in local or remote resource allocations.

Figure 4.19. A resource manager

The approach can be combined with middleware-level mechanisms [92]. Combining a middleware with such a kernel event service allows the flexibility of a global resource management. Such a resource management framework may also be important to coordinate adaptation.

ECOSystem

Zeng *et al.* [134] presents ECOSystem (Energy-Centric Operating System), which is an approach to let the operating system manage energy as a first-class system

resource. It manages energy consumption at the OS level and also influences applications in their energy consumption.

Their energy-centric resource management is based on *currentcy* (current currency). Currentcy reflects the ratio of supply and demand and provides a way of efficient resource management in the case of resource shortages.

The project has demonstrated the effectiveness of the approach in a Linux environment. Its basis is the accounting of the energy consumption of processes. The system specifies each task's relative importance and provides an energy-conserving allocation strategy as well.

Neugebauer *et al.* [83] introduces a similar approach; it also applies energy pricing to efficiently manage resources. In the presented model, a price is calculated for resources that are congested. These prices capture the ratio of demand and supply. These resources are charged afterwards, thus price represents a meaningful feedback to applications.

The project uses the Nemesis OS [51]. The Nemesis OS shifts many functionalities (e.g. protocol stack) to the user level, thus avoiding anonymous resource allocations. This makes more accurate resource accounting possible.

Both of the approaches use the OS to account for resource prices and to figure out the relative usage costs. They enable a distributed solution to resource management and adaptation.

4.4.7.5. Adaptation categorization and its parameters

One criterion for the classification of adaptation is whether the system is capable of free recomposition of its components or just uses some built-in settings. *Parameter adaptation* is the modification of variables that influence the behavior of the component. This requires built-in support for the given parameter and also the interface to modify it. In contrast, *compositional adaptation* involves the adaptation of new algorithms and the run-time recomposition of the software. The latter enables a very general ability to adapt; however, the former is much easier to implement. In the former, the time of composition may entirely influence the flexibility of the solution. Development time adaptation results in a hardwired ability to change behavior. Composition may occur at compile, link, or even load-time; however, they all result in a *static* composition. In contrast, run-time adaptation results in a completely *dynamic* system.

In order to choose the most suitable adaptation approach, the following parameters should be taken into account:

- *The best configuration*: when the adaptation of the system occurs, the goal is to find the most appropriate configuration for the new environmental conditions. In the majority of cases, selecting the most optimal configuration leads to further complications. When investigating the possible candidates, the outcome of the choices should be predicted by the system. This is not easy, even in a simple case; moreover, a number of adaptable components and all their available cross-compositions may result in a huge configuration space. The system should search through this space and figure out the new configuration. This may result in a significant overhead.

- *Scope of adaptation*: to limit the number of available configurations, it is crucial to investigate the scope of adaptation. A global adaptation involves all the adaptable components of several networked entities. The scope may be limited to (i) a node, (ii) one of its applications, or (iii) even a single module. Unfortunately, limiting the scope may result in an oversight of the best configuration.

- *Time of adaptation*: an important decision to make is when the adaptation should occur. Adaptation may happen continuously; however, in more complex cases, it may result in a large overhead. A way to avoid this is to allow adaptation on a periodic basis; however, this may still result in a large amount of unnecessary overhead. The most sophisticated approach is to do adaptation on a reactive basis. This means that the occurrence of some conditions would trigger the system to find a more optimal configuration.

- *Resource supply and demand*: there may be critical reasons for the need to change the behavior of the system. To gather these conditions, some monitoring functionality is required. Continuously monitoring a large number of quantities may result in a significant overhead, so it is better to monitor only those parameters that are actually necessary. Conditions that may trigger adaptation may result in a change of either resources or demands.

The triggering event may be related to some *hardware* level resource changes. For example, the change from AC to battery supply would result in changes that the application would do. On the other hand, a significant change in the *application* resource needs may also trigger an adaptation, since it would influence the applied allocation strategies. In many cases, changes in *network* conditions should result in an adaptation as well. Network bandwidth is the classic example of a highly dynamic resource that highly influences services that higher layers may use. Another and more general category of operating conditions is the *context*, for example, the detection of the user or location in which the system may operate in.

- *Agility*: an important property of adaptation is the speed at which it can occur. A straightforward approach would be to let the system react as quickly as possible, but other problems may arise. It is possible that the new configuration is valid only for a very short period of time, thus the system would never settle down in a stable state. For example, when resources change very quickly, it is better to select a safe parameter set and not to follow the bandwidth changes. The adaptation should result in a stable configuration.

- *Place of redirection*: the basis of most adaptations is the redirection of module interactions. The question arises where the redirection should occur. The entity that drives the adaptation may be built entirely in the OS, but may also lay outside and handle the entire OS as an adaptable layer. A large number of higher-level solutions are available that push the interception and redirection of modules up to the middleware.

4.4.7.6. Future direction of adaptivity in WSN

DCOS (Data Centric Operating System) [34] is an operating system for WSNs. In these networks, the resources on the nodes are extremely constrained. DCOS was designed to fit inside the limited memory of a sensor node while being able to provide real-time guarantees and energy-efficient operation.

Sensor networks are usually driven by events, which can range from environmental phenomena to software events. DCOS applies the *Data-Centric Architecture (DCA)*, where data is the main abstraction of events. The system is built of software components called *Data-Centric Entities (DCEs)*. These entities produce data and they can be triggered by other data. Therefore, the operation of the resulting system depends on what kind of data types are produced and what entities are triggered.

The central element of this architecture is the *Data-Centric Scheduler*. It is the component that keeps track of all the entities inside a node and decides which ones to activate. Moreover, this element is responsible for managing how components should be connected and enables the data flow between them.

DCOS is a dynamic system, which is able to adapt its functionality. Several DCEs may exist with the same behavior, and possibly several sequences of DCEs result in the same functionality. DCOS supports run-time reconfiguration to adapt its functionality to create the most efficient configuration.

Thus, the architecture provides a simple and straightforward path towards indirect software interactions. This ability is the main enabler of adaptive behavior. A next step to have adaptive behavior on a WSN-wide scale is to extend the concept of DCA to the whole network.

4.4.8. Time synchronization

Time synchronization is an important vertical function. Applications need to establish a common sense of time among the COs participating in their sensing and actuation goals.

Forest fire monitoring is a scenario that requires not only the information of whether there has been an indication of fire, but also where and when this is happening. The collected sensor data provides the basis for the decision making

process, which may trigger actions to be taken in the monitored environment in order to address abnormal circumstances. Thus, the true time of the observed events is crucial to the prompt action of fire fighting.

It is sufficient to associate local clock timestamps with the sensor data when decisions can be made locally. For instance, the decision of regulating the fluid flux of an industrial pipe may be taken locally and actions would follow through local CO actuators, for example, a regulating valve.

However, there are cases where the collected sensor data will be aggregated from various COs at various points inside the network. To perform such a function, the data need to be timestamped at the source.

In this case, the data originates from multiple sources which may or may not agree on a similar time. Thus, a common view of time among the COs is an essential aspect to correlate multiple sources of sensor data in order to produce a consistent and reliable result.

We list two time frameworks that could suit the CO applications:

- *Relative time*: the sense of time is established with respect to an agreed time reference which could be an elected CO among a specific group. This is applicable to scenarios where preserving the order of events is the only required function from a time synchronization service.
- *Absolute time*: in other cases, preserving the order of events is crucial but it is not the only functionality needed. Applications might require event data to be timestamped when they occurred with an absolute time value with respect to a true time standard, such as the universal coordinated time (UTC).

Messages containing the event data could take different routing paths in the network to be transmitted from the CO sources to the sinks. When the application requires strict order preserving, relative time could be used. It is important to note that absolute time is applicable to scenarios where the applications need both order preserving and a sense of true time.

The measurement of structural vibration in a building requires that the data collected from the instrumented cooperating objects be associated with an absolute timestamp. As it is important to correlate the time of day of the events in this case, the clocks of the COs must be synchronized with each other with respect to a true time. This would allow engineers to analyze data regarding the entire building structure and from the neighboring buildings.

Some of the challenges that impact the design of ad hoc time synchronization protocols are discussed in [98, 121]. We present a summary of these issues here:

- **Energy-efficiency:** sensor network applications often require nodes to be small and cheap. The device size poses physical limitations to the amount of energy that can be stored in a battery using the current technology. In some scenarios, the charging of a depleted battery or the replacement of discharged ones could be extremely difficult and expensive. In some oceanography monitoring applications where the physical access to the deep water is through a boat expedition, the COs deployed should strive to be energy-efficient. Thus, it is important that the time synchronization service strives to achieve energy-efficiency. This raises the question of whether GPS devices often used for time synchronization on the Internet could be adopted in inexpensive sensor networks. The issues to be addressed are cost, size and power consumption of GPS receivers.
- **End-to-end delay:** in some scenarios, the network may be partitioned because of changes to the network topology (e.g. mobility of nodes or addition/removal of COs). In this case, the delay between any two points in the network may be difficult to estimate because of the large variations in delay. This can introduce problems to the design of protocols that rely on stable delay characteristics of network paths to achieve high and predictable accuracy.
- **Infrastructure:** in some applications, the network will be created in an ad hoc set-up. Although such foreseen applications would represent a niche market today, self-organizing protocols that can create an overlay for time synchronization should be considered in the design space of protocols. The Network Time Protocol (NTP) [80] hierarchical structure may not be easily adapted to this type of ad hoc network topology.
- **Configuration:** a few human operators will be responsible for a large number of COs possibly in the order of thousands. The configuration, usually carried out by system administrators who manually specify the time servers for each node, could be a serious problem. The dynamics of this scenario demands a more automated system configuration than the one found in time protocols such as NTP.

An important question to ask is whether the NTP [80], currently in use on the Internet, could be adopted without further modification in low-cost WSNs. This protocol has been used for more than ten years and proved to work reasonably well on the Internet with thousand of nodes synchronized worldwide. The protocol is well-known in the research community (see [29]).

In summary, the NTP relies on an external time reference to synchronize the top layer of time servers called *stratum 1* servers. Servers in the second highest layers are called *stratum 2* and so on. The primary source of time in NTP is often the time pulse received with a 1 Hz frequency by a GPS device locally attached to a server.

As the NTP protocol has been originally developed considering other design issues, some of the challenges discussed above cannot be addressed if the protocol

is adopted unmodified in sensor network applications. One of the issues is energy-efficiency, as the external source of time (e.g. GPS) tends to consume more power than other components of a sensor node and does not work in indoor areas which have no line-of-sight to the satellites. This is certainly not an issue in the case with the Internet where the NTP server is a standard PC plugged into a power socket.

However, the issue raised in [98], where the NTP protocol maintains a synchronized system clock by regularly adding small increments to a system counter, is an important one. This behavior precludes the sensor node processor of being switched to a power-saving idle mode. In addition, NTP servers must be prepared to handle synchronization requests at any point in time. This could potentially introduce a problem as the communication module of a CO (e.g. radio) shows the highest cost among the other components when it is transmitting or listening to any signal from the network. Thus, this module could not be put in sleep mode in order to save energy.

GPS devices of small size and low power consumption have been developed and are now commercially available. The Leadtek 9546 low-power GPS receiver [65] was recently integrated into a sensor board of the Crossbow Mote [52]. These devices consume a current of 60 mA at 3.3 V in full operation. Despite the fact that such a consumption profile is higher compared to the micro-controller current draw of 8 mA, it is comparable to the energy consumption profile of the radio module.

However, such sensor nodes are optimized to operate in sleep mode most of the time. If the GPS is configured to occasionally operate to acquire the time signal, its energy consumption may not be an issue. Although adding this particular GPS module to a sensor board increases its cost by 50% today, we believe that the cost will drop significantly because of economy of scale. In contrast, this is also the case for the current cost of sensor nodes, which are similar to the cost of a sensor board equipped with GPS.

We list below some open issues with time synchronization in large-scale distributed COs and WSNs:

- The characteristics of the network topology in ad hoc WSNs may introduce severe delays because of disconnected parts of the network. To compensate for such uncertainties, the time synchronization protocol needs to be *tolerant* to the message delay irrespective of its dominant source (e.g. processing, transmission).
- The clock drift in cheap oscillators could have values ranging from 10 ppm to 100 ppm which represent a drift between 0.036 seconds (10 ppm) and 0.36 seconds (100 ppm) every hour. Therefore, the update frequency used in time synchronization protocols needs to be carefully considered with respect to the characteristics of different types of hardware.
- The scope of time synchronization is quite important. Some applications require the ordering of events occurring within a specific area, which means that only a subset

of nodes deployed in that area may be synchronized. However, other applications will need to correlate events collected from different areas in a global scale.

- When some sensor nodes become responsible for providing the time reference to other nodes in the network, the issue of trusting the source of time arises. Also, if a GPS time signal is used in some reference nodes, a related question is how we can guarantee the authenticity of the GPS time.

- Romer *et al.* [98] suggest that calibration of sensors is a much more general and complex problem than time synchronization. The interesting question is whether the current proposed time synchronization techniques can be used for general sensor calibration problems. Also, it may be the case that time synchronization (at least for outdoor sensor deployment) can be achieved by instrumenting low-cost, low-power GPS devices to sensor nodes as previously discussed.

4.5. Summary and conclusions

This section presents summaries of the VFs reviewed in this chapter. The summary of each VF follows a similar format. An overview of the VF is given, which is then followed by a discussion of identified trends and relevant open issues.

Chapter 2 discussed a list of characteristics and requirements of selected COs applications. Table 4.1 relates each of these requirements to the VFs. See Chapter 2 for a comprehensive discussion on selected COs applications and their requirements.

4.5.1. Context and location management

Distributed COs systems are designed to measure properties of the physical world. They are therefore suitable for gathering the context of an entity, which is the information that can be used to characterize its situation. Individuals, locations or any relevant objects can be such entities [13]. Since a reasonable amount of data is collected in large systems, context management systems are needed to handle them. Such systems can separate applications from the process of sensor processing and context fusion. To achieve precise actuation and detailed analysis of collected measurement data, however, the location of sensors and actuators need to be known.

Changes in context may trigger actions to influence the monitored entity. Specialized actuators, for instance, may be programmed to control pipe valves when a fluid pressure reaches a certain threshold.

Trends

Traditional context management systems use infrastructure-based directories to store the information, for example Aura [39] and Nexus [49]. In the last few years, there has been a clear trend towards ad hoc (infrastructure-less) systems. Such systems

Characteristic/requirement (Chapter 2)	Vertical System Function	Section
Network topology – topologies to support either single or multi-hop communication.	Communication; distributed storage and search	4.4.3; 4.4.5
Scalability – necessary system support to growing number of COs.	Distributed storage and search; data consistency	4.4.5; 4.4.2
Fault tolerance – provides the mechanisms for supporting the resilience of the system in failures.	Data consistency; communication; security	4.4.2; 4.4.3; 4.4.4
Localization – determining a node's location is the basic required functionality for various applications.	Context and location management	4.4.1
Time synchronization – COs need to establish a common sense of time.	Time synchronization	4.4.8
Security – this is pervasive and must be integrated into every system component to achieve a secure system.	Security, privacy and trust	4.4.4
Data traffic characteristics – the system should provide support for various types of application traffic.	Communication; distributed storage and data search; data aggregation	4.4.3; 4.4.5; 4.4.6
Networking infrastructure – CO networks can be infrastructured or infrastructureless (ad hoc).	Context and location management; communication	4.4.1; 4.4.3
Mobility – the physical components of the system in some applications may be static whereas in others, the architecture may contain mobile nodes.	Context and location management; communication	4.4.1; 4.4.3
Node heterogeneity – most CO applications include nodes that have distinct hardware and software factors.	Data lookup mechanisms; data consistency; data aggregation	4.4.5; 4.4.2; 4.4.6
Power awareness – power consumption is one of the performance metrics and limiting factors in almost every CO application.	Communication; resource management	4.4.3; 4.4.7
Real-time – the system delay requirements are very stringent in real-time applications. The broad meaning of delay in this context comprises the system data processing and network delay.	Resource management	4.4.7
Reliability – guarantees that the data is properly received by the applications.	Data consistency; communication; security, privacy and trust	4.4.2; 4.4.3; 4.4.4

Table 4.1. Application requirements and VFs

better reflect the limited spatial relevance of context since this is stored at or near the location where it is generated. Current systems focus on the gathering of sensor data using QoS specifications (MiLan [44]), the management of context for cross-layer data in the network stack (MobileMan [27]) or more generally for the whole node (TinyCubus [75]), the storage of information in the network of COs at calculated geographic locations (Geographic Hash Table [97]), the querying of information using a SQL-like language based on the “network as a database” abstraction (TinyDB [71]), and the self-monitoring of COs ([135]) since they belong to the context themselves. Most of the systems consider hybrid COs as well. MiLan also presents a further direction to the research: the simplification of the use of COs. The user specifies what it wants and not how.

Applications that use context to adapt their behavior are called context-aware. Such applications include visitor information systems (e.g. GUIDE), support in workspaces such as context dependent configurations of mobile phones (TEA) or smart environments (e.g. Gaia), where facilities in the environment interact with user devices, also, applications based on ad hoc networks in development. Due to this fact, adaptation of applications to the context is crucial. This can either be done application-driven, that is, the application decides which actions should be taken, or system-driven, where the system manages the adaptation transparently. The latter class has drawn attention over the last few years. A few adaptive middlewares or frameworks have been proposed including Impala [68], which is based on a finite state machine, or TinyCubus [75], which tries to select the best set of algorithms based on several parameters, policies and different adaptation strategies.

Location services for mobile ad hoc networks only offer limited context information, in this case, the position of mobile objects. A scalable, distributed location service is, for example, GLS [67]. Prior to storing the location in such a service, the location has to be determined. Small COs usually do not have a GPS device, so different methods have been developed in the last few years. Two basic approaches are commonly used: having the distance of three objects of which the location is known, its own location can be calculated. The other possibility is to measure the angle to two known objects. Since most COs are equipped with omnidirectional antennae, a very accurate measurement of the angles is not feasible. However, [74] shows that it is feasible and more accurate to use two directional antennae on small Mica2 nodes. Several methods exist to determine the distances to other nodes: [36] uses RSSI values delivered by the RF chip in combination with an error model, [33] presents an algorithm for semi-static sensor networks that works with hop counts, and [109] uses more accurate ultrasound and maps the location estimation to a global non-linear optimization problem which is approximated fully distributed.

Some open issues

Current context management solutions for ad hoc networks focus only on one part of context management. None cover the complete context management area of

the gathering of data, in-node data management, in-network data distribution, and in-network data querying.

Positioning is still too inaccurate; better algorithms are required here. Also, for mobile COs, no good approaches exist.

4.5.2. *Data consistency and adaptivity in WSNs*

The benefits of having several nodes in a WSN mostly come from the fact that many nodes simultaneously monitor the same physical area. Nodes can be put into sleep mode without any loss of precision in the network. This results in an increase in energy conservation and, therefore, the network lifetime.

The reliability of the system is also improved with several sensor nodes. This scenario, however, raises issues of data inconsistency which may occur due to various reasons: for instance, inherent imprecision associated with sensors, inconsistent readings and unreliable data transfer, to name just a few.

This VF provides the functionality to ensure consistency of the sensor data at various system abstraction levels:

- Data consistency may mean that data retrieved from a location in the sensor network should be consistent with data sent to the same location.
- Data consistency may also mean that all sensors sensing the same physical phenomenon should more or less agree on the measured value.
- In a rule-based system, data consistency may mean that all actuators agree on the action that needs to be taken.

The following parameters are needed to ensure accurate and consistent *operation* of WSNs and distributed COs:

- **localization:** to interpret sensor data and collaborate with other nodes;
- **synchronization:** to ensure that all nodes have an equal understanding of time and the moment at which events take place;
- **reliable data transfer:** to guarantee delivery of information and/or customizable degrees of reliability for data transmission;
- **routing:** to accomplish forwarding data from source(s) to destination(s) through collaboration among neighbors in an energy efficient manner while maintaining a best effort level of reliability;
- **coverage:** to cover a large area while being able to turn off some of the sensors, thus, saving valuable energy, as well as enhancing the accuracy of the sensed data.

Data consistency at the *data processing level* can be achieved through the following mechanisms:

- **state monitoring:** to detect any change in the state of the environment in which sensors are placed, directly from the sensed data;
- **data fusion:** to take the multiple measurements, some of which may be faulty, and determine either the correct measurement value or a range in which the correct measurement lies;
- **event detection:** for the WSN to be in charge of monitoring the environment in which its nodes are placed;
- **fault tolerance and consensus:** to preserve precision and to agree on measured data and required actions in the presence of faulty collaborative sensors.

Trends

For state monitoring, describing the conditions between states and the events that trigger state-change through a set of rules and predicates over events and their parameters has proved to be popular. The authors in [102] proposed this approach for the first time, which was later also used and modified by Strohschach *et al.* [119]. Research in this direction is on the rise. Also, hybrid distributed algorithms similar to the one proposed by Sahni *et al.* [107], which is executed by every sensor using the measurement ranges received from the remaining sensors monitoring the same region as data, accompanied with the sensor's own measurement, have received considerable attention.

Environmental monitoring, detection, identification, localization or tracking of objects in sensor fields have created a new domain for event detection. Research reported in [101, 123, 42, 31, 128] are a few examples.

Introducing, defining and implementing the concept of collaboration in various levels of abstraction is the newest trend in the area of data consistency, which seems to have great potential to solve various issues of the operation of WSN, data processing and application programming.

Some open issues

There are still open issues in the area of data consistency for WSNs and COs. Here we elaborate on some of the most important ones.

A reasonable number of location techniques have been proposed in other works. An integration framework (e.g. standardized APIs) of such mechanisms would be useful for the applications. This stems from the fact that the application requirements are dynamic and often change. The ability to adapt to these frequent changes is thus essential. Since various localization techniques have been defined, the integration framework may choose a proper localization technique to be utilized based on the requested accuracy at the time and the environmental status.

Reliable and energy-efficient data transfer which is application-dependent for improved performance is required. No doubt collaboration between sensor nodes will increase the reliability of the transferred data in the WSN. However, the overhead introduced by cooperation along with the additional energy consumption should be at a reasonable level. Indeed, in order to avoid being suboptimal, protocols should be developed according to particular application requirements.

Data fusion issues that require further investigation are the associated overhead of the fusion process and the heterogeneity of data due to different sensor sources.

Also, a high-level descriptive language oriented towards the collective model of solving tasks is necessary in order to implement distributed collaborative WSN applications. This language should support DCAs and provide real-time guarantees for energy-efficient operations.

4.5.3. Communication functionality

The communication vertical function refers to the capability of any pair (or group) of devices to exchange information. Different types of communication can be performed: one-to-all, one-to-many, many-to-one, many-to-many. If we consider the case of WSNs with a single sink, one-to-all or one-to-many communications are needed for query dissemination, while many-to-one communication is explored to gather sensed data at the sink.

Trends

Communication in COs environment is expected to be data-centric and attribute-based. This means that as well as addressing a specific CO, the communication infrastructure should be able to deliver data to and from groups of COs which share a set of attributes specifying the destination/source address of the information. For example, a user could issue a query on the average temperature of an area in an office building. This query should then be delivered to the objects with temperature sensors. Similarly, once measures on the temperature have been taken, the COs in the specific area will send packets to the sink(s) reporting the measured values.

The trend of data-centric and attribute-based data dissemination may lead to the selection of different communication overlays depending on the values to be reported. A given overlay interconnects COs of the same "group" sharing a common set of attributes (attribute-based routing). Attribute-based routing could leverage the burden of delivering queries to objects which cannot answer the query. Also, attribute-aware communication infrastructures may optimize sensor data fusion by selecting routes which maximize the chances of aggregating a given type of data, overall decreasing the network load and energy-consumption [113].

Some open issues

Important VF parameters which should be included in a query are the time constraints and accuracy with which a given query needs to be answered. These are application-dependent and even query-dependent parameters: (a) for a query to be successfully resolved, the sensors must deliver fresh data, (b) the query must be answered fast enough, and (c) the precision with which the query is answered must meet the query requirements. This can be regarded as a new concept of QoS requirements that remains to be explored.

The second issue to address is the fact that a one-fits-all protocol stack may not be suitable to this scenario. It is possible to identify the “vertical functions” that should be provided and possible implementations of such functions for specific sets of possible applications. The communications protocols will benefit from and sometimes require the information provided by different vertical functions such as time synchronization and location awareness. Not only are time and location information included in the delivered data, but some protocols such as geographic-based routing can exploit location-awareness to reduce routing overhead and the nodes storage demand. The interactions between complementary vertical functions from the application viewpoint should be further investigated.

Mobility of objects is the third issue to be tackled. Although in many CO scenarios, the devices themselves are unlikely to be mobile, they can be, however, located on mobile users or mobile stations so that their location changes in time in a predictable or unpredictable way. On the one hand, this may have a beneficial effect (e.g. load balancing the energy consumption among the different nodes), but on the other hand, it requires mobility management or mobility-aware protocols to be added to the protocol stack. The mobility of some of the devices have been explored by some architectures such as the data mules [112], in which a group of mobile nodes move in the deployment area collecting data from the sensor nodes and delivering the collected data to the sinks.

4.5.4. Security, privacy and trust

COs and WSNs are usually placed in locations that are accessible to everyone – including attackers. For example, sensor networks are expected to consist of a couple of hundred nodes that may cover a large area. It is impossible to protect each of them from physical or logical attacks. Thus, every single node is a possible point of attack.

In a CO, security is pervasive. [87] states that security must be integrated into every component to achieve a secure system. Components designed without security can become a point of attack as [54] shows. However, specific vertical functions which enforce security are available for applications.

Since fully tamper-resistant devices are hard to build [9] and would cost too much money, protocols for sensor networks have to be designed in a way that tolerates malfunctioning/attacking nodes while the whole sensor network remains functional.

Trends

Karlof and Wagner [54] describe several attacks against known routing protocols for sensor networks and present countermeasures for some attacks. This shows that secure routing protocols are a trend themselves since security was only a minor issue before. New routing protocols were developed that are resilient to black-hole attacks ([30]) or that use efficient symmetric key primitives to prevent compromised nodes from tampering with uncompromised routes consisting of uncompromised nodes (Ariadne [50]). [130] also deals with a large number of DoS attacks with an approach that maps jammed regions and reroutes data around them. [93] proposed SIA, a framework for secure information aggregation in large sensor networks, which uses random sampling mechanisms and interactive proofs to verify that the answer of an aggregator is a good approximation of the true value.

Encryption is the basic technique for securing and authenticating transmitted data. Using asymmetric cryptography on highly resource constrained devices is often not possible due to delay, energy and memory constraints [20, 18]. With symmetric cryptographical methods, two communicating COs need a common key. Secure pebblenets [11] use a shared key for the whole network but since the compromise of one single node leads to a security failure of the whole network, pairwise approaches have been developed in the last years. SPINS [88] uses a central base station to establish new pairwise session keys, and [35, 23] is based on random pairwise key pre-distribution. [125] does not rely on infrastructure or pre-distribution: physical contact between nodes is used for establishing the initial key, and new keys are then established by sending key-shares along node-disjoint paths via secured point-to-point communication to each other.

Traffic analysis on the ciphertext can reveal sensitive information about the data, even if it is encrypted. To provide better secrecy, dummy messages can be generated. This seems to be diametrical in resource constrained COs, but secrecy may be a more important goal than energy-saving in some cases. [126] presents an energy-efficient framework that maintains the anonymity of a virtual infrastructure including routing by randomizing communications.

Using COs, especially sensor networks, humans can be observed which leads to privacy problems. Encryption tackles overhearing and data coarsening ensures that no conclusions can be drawn from the data to a single person. The usage of sensor networks to spy on individuals cannot be met with technology alone, but with a mix of societal norms, new laws and technological responses [87].

With several COs contributing to a common goal, it is necessary to assess the reliability of the information provided by an individual CO. With respect to services and transactions, trust has been researched for several years. For data-centric and fully distributed architectures, research has just started. A distributed voting system is proposed in [23], where votes can be cast against misbehaving nodes until all other nodes refuse to communicate with this node. [38] is a more general reputation-based framework with each node monitoring the behavior of other nodes and building up their reputation thereupon. Nodes with a bad reputation can be excluded from the community.

Some open issues

Existing protocols have to be made resilient to attacks, and more new protocols have to be designed as well. Intelligent intrusion detection systems for COs are also needed.

Encryption concepts for aggregation are needed since along an aggregation tree, only point-to-point encryption is feasible, but an attacker in the tree has full access to the data. No general solutions to this problem exist so far.

Some of the key distribution protocols consume a lot of power, therefore energy-efficient algorithms without assumptions about the available infrastructures are required.

Energy-efficient solutions are needed for secrecy. Systems are needed where the user can specify the amount of energy it should spend for dummy messages and the maximum delay it wants to accept to enable mix cascades in COs.

Another important question is how the illegitimate use of sensor networks, for example, to spy on individuals, can be prevented.

Concerning trust, energy is the main problem, since the exchange of votes and reputation data consumes a reasonable amount of power.

4.5.5. Distributed storage and data search

In COs and WSNs efficient storage and querying of data are both critical and challenging issues. Especially in WSNs, large amounts of sensed data are collected by a high number of tiny nodes. Scalability, power and fault tolerance constraints make distributed storage, search and aggregation of these sensed data essential.

It is possible to envisage a WSN as a distributed database and run queries which can be given in SQL format. These queries can also imply some rules about how to aggregate the sensed data while being conveyed from the sensor nodes to the query

owner. Data aggregation [17, 135] techniques that reduce the number of data packets conveyed through the network are therefore important and also required for effective fusion of data collected by a vast number of sensor nodes [6, 43]. A query in a sensor network may be perceived as the task or interest dissemination process. Sensor nodes process the task or interest and return data to the interested owner.

The following characteristics of WSNs should be considered while designing a data storage, querying and aggregation scheme for WSNs:

- Sensor nodes are limited in both memory and computational resources. They cannot buffer a large number of data packets.
- Sensor nodes generally disseminate short data packets to report an ambient condition, e.g. temperature, pressure, humidity, proximity report, etc.
- The observation areas of sensor nodes often overlap. Therefore, many sensor nodes may report correlated data of the same event. However, in many cases, the replicated data are needed because the sensor network concept is based on the cooperative effort of low fidelity sensor nodes [6]. For example, nodes may report only proximity, then the size and the speed of the detected object can be derived from the locations of the nodes reporting them and timings of the reports. The collaboration among the nodes should not be hampered by the data aggregation scheme.
- Since there may be thousands of nodes in a sensor field, associating data packets from numerous sensors with the corresponding events and correlating the data of the same reported event at different times may be a very complicated task for a single sink node or a central system.
- Due to a large number of nodes and other constraints such as power limitations, sensor nodes are generally not globally addressed [6]. Therefore, the use of address-centric protocols are mostly inefficient. Instead, data-centric or location-aware addressing protocols, where intermediate nodes can route data according to its content [63] or the location of the nodes [21], should be used.
- Querying the whole network node by node is impractical. Thus, attribute-based naming and data-centric routing [114] are essential for WSNs.

Trends

Queries made to search data available in a WSN should be resolved in the most power-efficient way. This can be achieved by reducing either the number of nodes involved in resolving a query or the number of messages generated to convey the results.

There is considerable research interest in developing efficient data querying schemes for WSNs. Data querying systems in general have two major components: interest and data dissemination, and query processing and resolution. Query resolution usually involves data aggregation for energy-efficient processing. We first examine

interest and data dissemination techniques, which are closely related to data querying, and then query processing and resolution techniques.

Interest and data dissemination

Protocols for data dissemination protocols are designed to efficiently transmit and receive queries and sensed data in WSNs. In this subsection, we briefly explain five of the best known protocols:

- *Classic flooding*: in classic flooding, a node that has data to disseminate broadcasts the data to all of its neighbors.
- *Gossiping* [6]: this technique uses randomization to conserve energy as an alternative to the classic flooding approach. Instead of forwarding data to all its neighbors, a gossiping node only forwards data to one randomly selected neighbor.
- *SPIN* [43]: this protocol is based on the advertisement of data available in sensor nodes. When a node has data to send, it broadcasts an ADV packet. The nodes interested in this data reply back with a REQ packet. Then, the node disseminates the data to the interested nodes by using DATA packets. When a node receives data, it also broadcasts an ADV and relays DATA packets to the nodes that send REQ packets. Hence, the data is delivered to every node that may have an interest.
- *Directed diffusion* [53]: in SPIN, the routing process is stimulated by sensor nodes. Another approach, namely directed diffusion, is sink-oriented. A sink is the name given to the central node responsible for gathering data from all the other nodes in directed diffusion, where the sink floods a task to stimulate data dissemination throughout the sensor network. While the task is being flooded, sensor nodes record the nodes which send the task to them as their gradient, and hence the alternative paths from sensor nodes to the sink are established. When there is data to send to the sink, this is forwarded to the gradients. One of the paths established is reinforced by the sink. After that point, the packets are not forwarded to all of the gradients but to the gradient on the reinforced path.
- *LEACH* [45]: this is a clustering-based protocol that employs randomized rotation of local cluster heads to evenly distribute the load among the sensors in the network. In LEACH, the nodes organize themselves into local clusters, with one node acting as a local cluster head. LEACH includes randomized rotations of the high-energy cluster head position such that it rotates among the various sensors in order not to drain the battery of a single sensor. In addition, LEACH performs local data fusion to compress the amount of data being sent from the clusters to the base station.

Query processing and resolution

When a query arrives at a sensor node, it is first processed by the node. If the node can resolve the query, the result of the query is disseminated. This approach is one of the simplest ways of resolving and processing a query. Sensor nodes usually take advantage of collaborative processing to resolve queries so that smaller number of

messages are transmitted in the network. Queries can be flooding-based where a query is flooded to every node in the network. Alternatively, they can be ERS based where a node does not relay a query that it can resolve. Currently available query processing systems are summarized below:

- *TinyDB* [69]: a query processing system for extracting information from a network of TinyOS sensors. TinyDB provides a simple SQL-like interface to specify the data, along with additional parameters such as the rate at which data should be refreshed much as in traditional databases. Given a query specifying data interests, TinyDB collects data from nodes in the environment, filters and aggregates them. TinyDB does this via power-efficient in-network processing algorithms. Some key features of TinyDB are as follows: TinyDB provides metadata management, provides a declarative query language, supports multiple query resolution on the same set of nodes and supports different levels of in-network aggregation. It also includes a facility for simple triggers or queries that execute some command when a result is produced.
- *Cougar* [132]: a query layer for sensor networks which accepts queries in a declarative language that are then optimized to generate efficient query execution plans with in-network processing which can significantly reduce resource requirements.
- *Active query forwarding scheme (ACQUIRE)* [104]: this aims at reducing the number of nodes involved in queries. In this scheme, each node that forwards a query tries to resolve it. If the node resolves the query, it does not forward it further but sends the result back. Nodes collaborate with their n hop neighbors, where n is referred to as the look ahead parameter. If a node cannot resolve a query after collaborating with n hop neighbors, it forwards it to another neighbor. When n equals 1, ACQUIRE carries out flooding in the worst case.

Some open issues

The routing protocols for WSNs are generally designed for networks that have fixed homogenous sensor nodes and are based on the assumption that all nodes try to convey data to a central node, often named the sink. However, in COs networks there will be heterogenous nodes that can be mobile, and the sensed data will be needed by many nodes, i.e. multiple sinks. Distributed data storage and search (DSS) solutions should have support for heterogeneity. Additionally, open research issues on DSS can be summarized as follows: replication, concurrency and consistency control of distributed data, mobility support, general purpose solutions for declarative query languages, interoperability with open standards and query driven architectures with QoS support.

4.5.6. Resource management

COs may form a self-organizing network, in which COs arbitrarily join and leave or even move during this operation. Since system components are distributed, any

action often involves multiple COs at a time. Due to the distributed, dynamic and uncertain (since both COs and communication are associated with uncertainty) nature of system components, the design of such embedded wireless collaborative systems proves to be difficult and requires a scheme to facilitate the system design and application development.

Resource management aims at providing a way to manage the resources of a system by enabling high-level system primitives to hide unnecessary low-level details. It enables the application to be independent of the actual underlying distributed system. It should also address the dynamic nature of available resources, such as variable network bandwidth. Because the system is built of error-prone components, failures should be handled as normal and not as exceptions.

Trends

Over the years, various enabling technologies have contributed to the evolution of adaptation and reconfigurable software, each having its own advantages and disadvantages. The most important ones are middleware, component-based design, computational reflection and separation of concerns. Recent efforts have been directed towards replacing the traditional strict modularization or layering design with a more energy-efficient one, i.e. cross-layered design. However, most of the important cross-layer adaptation frameworks and projects that have been proposed assume mobile devices that are richer than wireless sensor nodes in terms of resources. Therefore, adaptation frameworks designed specifically for WSNs are emerging.

OSs for WSNs with DCA and specifically designed with limited memory are considered to form one of the main trends in the area of adaptation in WSNs. Due to the increasing interest in having adaptive behavior on a WSN-wide scale, recently attention has been paid to extending the concept of DCA to the whole network.

Some open issues

One of the most important open issues regarding resource management is designing an architecture tailored to support different adaptation models. Since application requirements, environmental conditions and available resources and services may frequently change, depending on goals of the application at the time, sensor nodes must be able to adapt accordingly. However, since these goals may change as well, different adaptation models are required from which the most appropriate one can be automatically selected. As an example, the application may, at one time, aim for frequent and high accuracy sensor readings and at another time, aim for less data accuracy and more energy-efficient readings.

A direct result of the above-mentioned issue is the need for multi-dimensional optimization techniques for resource management.

4.5.7. Time synchronization

Applications need to establish a common sense of time among the COs participating in their sensing and actuation goals. Such a functionality can be offered through a time synchronization vertical function.

Forest fire monitoring is a scenario that requires not only the information of whether there has been an indication of fire, but also where and when this is happening. The collected sensor data provides the basis for the decision making process, which may trigger actions to be taken in the monitored environment in order to address abnormal circumstances. Thus, the true time of the observed events is crucial to the prompt action of fire fighting.

It is sufficient to associate local clock timestamps with the sensor data when decisions can be made locally. For instance, the decision of regulating the fluid flux of an industrial pipe may be taken locally and actions would follow through local CO actuators, for example, a regulating valve.

However, there are cases where the collected sensor data will be aggregated from various COs at various points inside the network. To perform such a function, the data need to be timestamped at the source. In this case, the data originates from multiple sources which may or may not agree on a similar time. Thus, a common view on time among the COs is an essential aspect to correlate multiple sources sensor data in order to produce a consistent and reliable result.

Trends

An important question to ask is whether the NTP [80], currently in use on the Internet, could be adopted without further modification in low-cost WSNs. This protocol relies on an external time reference to synchronize the top layer of time servers called *stratum 1* servers.

As the NTP protocol was originally developed considering other design issues, some of the challenges that arise in CO and WSN scenarios cannot be addressed if the protocol is adopted unmodified in sensor network applications. One of the issues is energy-efficiency, as the external source of time (e.g. GPS) tends to consume more power than other components of a sensor node, and does not work in indoor areas which have no line-of-sight to the satellites.

However, the issue raised in [98], where the NTP protocol maintains a synchronized system clock by regularly adding small increments to a system counter, is an important one. This behavior precludes the sensor node processor of being switched to a power-saving idle mode. In addition, NTP servers must be prepared to handle synchronization requests at any point in time. This could potentially introduce a problem as the communication module of a CO (e.g. radio) shows the highest cost among the

other components when it is transmitting or listening to any signal from the network. Thus, this module could not be put in sleep mode in order to save energy.

GPS devices of small size and low power consumption have been developed and are now commercially available. The Leadtek 9546 low-power GPS receiver [65] was recently integrated into a sensor board of the Crossbow Mote [52]. These devices consume a current of 60 mA at 3.3 V in full operation. Despite the fact that such a consumption profile is higher compared to the micro-controller current draw of 8 mA, it is comparable to the energy consumption profile of the radio module.

However, such sensor nodes are optimized to operate in sleep mode most of the time. If the GPS is configured to occasionally operate to acquire the time signal, its energy consumption may not be an issue. Although adding this particular GPS module to a sensor board increases its cost by 50%, we believe that the cost will drop significantly because of the economy of scale. This is also the case for the current cost of sensor nodes, which is similar to the cost of a sensor board equipped with GPS.

The current trend is towards the design of self-configuring protocols on the assumption that NTP cannot be directly used in COs and WSNs applications. The latest research results address the time synchronization problem with approaches that do not rely on GPS time signals. As researchers realize that low-power and low-cost GPS devices are becoming commercially available, the research trend may shift to hybrid protocol designs where GPS is used as the primary source of time. Such information is then disseminated throughout the network to non-GPS nodes. How such time servers ought to be organized in the network (e.g. hierarchical such as NTP) would be an important research question.

Some open issues

The characteristics of the network topology in ad hoc WSNs may introduce severe delays because of disconnected parts of the network. To compensate for such uncertainties, the time synchronization protocol needs to be *tolerant* to the message delay irrespective of its dominant source (e.g. processing, transmission).

The second issue is related to trust. When some sensor nodes become responsible to provide the time reference to other nodes in the network, the issue of trusting the source of time arises. Also, if a GPS time signal is used in some reference nodes, a related question is how we can guarantee the authenticity of the GPS time.

Finally, Romer *et al.* [98] suggest that calibration of sensors is a much more general and complex problem than time synchronization. The interesting question is whether the current proposed time synchronization techniques can be used for general sensor calibration problems. Also, it may be the case that time synchronization (at least for outdoor sensor deployment) can be achieved by instrumenting low-cost, low-power GPS devices to sensor nodes as previously discussed.

4.6. Bibliography

- [1] Software fundamentals: collected papers by David L. Parnas, *SIGSOFT Softw. Eng. Notes*, 26(4), 2001.
- [2] A. Marcucci, M. Nati, C. Petrioli and A. Vitaletti, The Impact of Data Aggregation and Hierarchical Organization on Wireless Sensor Networks, Technical report, Rome University, 2004.
- [3] A. Köpke, H. Karl and A. Wolisz, Consensus using aggregation – a wireless sensor network specific solution, Technical Report TKN-04-004, Technical University of Berlin, April 2004.
- [4] Sarita V. Adve, Albert F. Harris, Christopher J. Hughes, Douglas L. Jones, Robin H. Kravets, Klara Nahrstedt, Daniel Grobe Sachs, Ruchira Sasanka, Jayanth Srinivasan and Wanghong Yuan, The Illinois grace project: Global resource adaptation through cooperation, in *Proceedings of the Workshop on Self-Healing, Adaptive, and self-MANaged Systems (SHAMAN)*, June 2002.
- [5] Mehmet Aksit and Zied Choukair, Dynamic, adaptive and reconfigurable systems overview and prospective vision, in *Proceedings of the 23rd International Conference on Distributed Computing Systems Workshops (ICDCSW'03)*, May 2003.
- [6] I.F. Akyildiz, W. Su, Y. Sankarasubramaniam and E. Cayirci, A Survey on Sensor Networks, *IEEE Communications Magazine*, pp. 102–114, August 2002.
- [7] J.N. Al-Karaki and A.E. Kamal, On the correlated data gathering problem in wireless sensor networks, in *Proceedings of the Ninth International Symposium on Computers and Communications (ISCC 2004)*, vol. 1, pp. 226–231, June 2004.
- [8] A. Nasipuri and K. Li, A directionality based location discovery scheme for wireless sensor networks, in *1st ACM International Workshop on Wireless Sensor Networks and Applications*, 2002.
- [9] Ross Anderson and Markus Kuhn, Tamper resistance – a cautionary note, in *Proceedings of the Second Usenix Workshop on Electronic Commerce*, pp. 1–11, November 1996.
- [10] ANSI, SQL Standard, Technical Report X3, 135-1992.
- [11] Stefano Basagni, Kris Herrin, Danilo Bruschi and Emilia Rosti, Secure pebblenets, in *MobiHoc '01: Proceedings of the 2nd ACM International Symposium on Mobile Ad Hoc Networking & Computing*, pp. 156–163, New York, NY, USA, 2001. ACM Press.
- [12] S. Baydere and M.A. Ergin, An architecture for service access in mobile ad hoc networks, in *Proceedings of IASTED WOC*, Banff, Canada, July 2002.
- [13] Christian Becker, *System Support for Context-Aware Computing*, Fakultät Informatik, Elektrotechnik und Informationstechnik, Stuttgart University, 2004.
- [14] Lodewijk Bergmans and Mehmet Aksit, Composing crosscutting concerns using composition filters, *Commun. ACM*, vol. 44, no. 10, pp. 51–57, 2001.
- [15] Antoine Beugnard, Jean-Marc Jézéquel, Noël Plouzeau and Damien Watkins, Making components contract aware, *Computer*, vol. 32, no. 7, pp. 38–45, 1999.

- [16] Gordon S. Blair, G. Coulson, P. Robin and M. Papathomas, An architecture for next generation middleware, in *Proceedings of the IFIP International Conference on Distributed Systems Platforms and Open Distributed Processing*, London, 1998. Springer-Verlag.
- [17] A. Boulis, S. Ganerival and M.B. Srivastava, Aggregation in Sensor Networks: An Energy Accuracy Trade-off, in *Proceedings of IEEE SNPA '03*, pp. 128–138, May 2003.
- [18] Michael Brown and Donny Cheung, PGP in constrained wireless devices, in *Proceedings of the 9th USENIX Security Symposium*, 2000.
- [19] H. Cam, S. Ozdemir, P. Nair and D. Muthuavinashiappan, ESPDA: Energy-efficient and Secure Pattern-based Data Aggregation for wireless sensor networks, in *Proceedings of IEEE Sensors 2003*, vol. 2, pp. 732–736, October 2003.
- [20] D. Carman, P. Kruus and B. Matt, Constraints and approaches for distributed sensor network security, Technical Report #00-010, NAI Labs, September 2000.
- [21] E. Cayirci, Addressing in wireless sensor networks, in *COST-NSF Workshop on Exchanges and Trends in Networking (Nextworking '03)*, Crete, 2003.
- [22] E. Cayirci and T. Coplu, Data Aggregation and Dilution by Using Modulus Addressing in Wireless Sensor Networks, in *Proceedings of the 2004 Intelligent Sensors, Sensor Networks and Information Processing Conference*, pp. 373–379, December 2004.
- [23] Haowen Chan, Adrian Perrig and Dawn Song, Random key predistribution schemes for sensor networks, in *SP '03: Proceedings of the 2003 IEEE Symposium on Security and Privacy*, p. 197, Washington, DC, USA, 2003. IEEE Computer Society.
- [24] E. Cheong, J. Liebman, J. Liu and F. Zhao, TinyGALS: A Programming Model for Event-Driven Embedded Systems, in *18th Annual ACM Symposium on Applied Computing (SAC '03)*, Melbourne (FL), USA, March 2003.
- [25] Keith Cheverst, Nigel Davies, Keith Mitchell, Adrian Friday and Christos Efstratiou, Developing a context-aware electronic tourist guide: some issues and experiences, in *CHI '00: Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pp. 17–24, New York, NY, USA, 2000. ACM Press.
- [26] T. Clouqueur, P. Ramanathan, K.K. Saluja and K.-C. Wang, Value-fusion versus decision-fusion for fault tolerance in collaborative target detection in sensor networks, in *Proceedings of the 4th Annual Conference on Information Fusion*, 2001.
- [27] Marco Conti, Gaia Maselli, Giovanni Turi and Silvia Giodano, Cross-layering in mobile ad hoc network design, *IEEE Computer*, vol. 37, no. 2, pp. 48–51, 2004.
- [28] Marco Conti, Gaia Maselli, Giovanni Turi and Silvia Giordano, Cross-layering in mobile ad hoc network design, *IEEE Computer*, pp. 48–51, February 2004.
- [29] George Coulouris, Jean Dollimore and Tim Kindberg, *Distributed Systems, Concepts and Design*, Addison-Wesley, 3rd edition, 2001.
- [30] Jing Deng, Richard Han and Shivakant Mishra, A Performance Evaluation of Intrusion-Tolerant Routing in Wireless Sensor Networks, in *Proceedings of the 2nd IEEE International Workshop on Information Processing in Sensor Networks (IPSN 2003)*, pp. 349–364, April 2003.

- [31] D.M. Doolin, S.D. Glaser and N. Sitar, Software architecture for GPS-enabled wildfire sensorboard, in *TinyOS Technology Exchange*, February 2004.
- [32] W. Du, J. Deng, Y.S. Han and P.K. Varshney, A witness-based approach for data fusion assurance in wireless sensor networks, in *Proceedings of the IEEE Global Telecommunications Conference*, vol. 3, pp. 1435–1439, December 2003.
- [33] Stefan Dulman and Paul Havinga, Statistically enhanced localization schemes for randomly deployed wireless sensor networks, in *Proceedings of the DEST International Workshop on Signal Processing for Sensor Networks*, Melbourne, Australia, 2004.
- [34] Stefan Dulman, Tjerk Hofmeijer and Paul Havinga, Wireless sensor networks dynamic runtime configuration, in *Proceedings of ProRISC 2004*, 2004.
- [35] Laurent Eschenauer and Virgil D. Gligor, A key-management scheme for distributed sensor networks, in *CCS '02: Proceedings of the 9th ACM conference on Computer and communications security*, pp. 41–47, New York, NY, USA, 2002. ACM Press.
- [36] Leon Evers, Stefan Dulman and Paul Havinga, A Distributed Precision Based Localization Algorithm for Ad hoc Networks, in *Proceedings of the Second International Conference on Pervasive Computing 2004*, pp. 269–286, Linz/Vienna, Austria, April 2004.
- [37] J. Feng, F. Koushanfar and M. Potkonjak, *Sensor Network Architecture*, Chapter 12. CRC Press, July 2004.
- [38] Saurabh Ganeriwal and Mani B. Srivastava, Reputation-based framework for high integrity sensor networks, in *SASN '04: Proceedings of the 2nd ACM workshop on Security of ad hoc and sensor networks*, pp. 66–77, New York, NY, USA, 2004. ACM Press.
- [39] D. Garlan, D. Siewiorek, A. Smailagic and P. Steenkiste, Project Aura: Towards Distraction-Free Pervasive Computing, *IEEE Pervasive Computing*, special issue on “Integrated Pervasive Computing Environments”, vol. 1, no. 2, pp. 22–31, 2002.
- [40] Andrea J. Goldsmith and Stephen B. Wicker, Design challenges for energy-constrained ad hoc wireless networks, *IEEE Wireless Communications*, vol. 9, pp. 8–27, August 2002.
- [41] Tian He, Brian M. Blum, John A. Stankovic and Tarek Abdelzaher, AIDA: Adaptive application-independent data aggregation in wireless sensor networks, *ACM Transactions on Embedded Computing Systems (TECS)*, vol. 3, no. 2, May 2004.
- [42] Tian He, Sudha Krishnamurthy, John A. Stankovic, Tarek Abdelzaher, Liqian Luo, Radu Stoleru, Ting Yan, Lin Gu, Jonathan Hui and Bruce Krogh, Energy-efficient surveillance system using wireless sensor networks, in *MobiSYS '04: Proceedings of the 2nd International Conference on Mobile Systems, Applications, and Services*, pp. 270–283. ACM Press, 2004.
- [43] W.R. Heinzelan, J. Kulik and H. Balakrishnan, Adaptive Protocols for Information Dissemination in Wireless Sensor Networks, in *ACM MobiCom '99*, pp. 174–185, Seattle, Washington (USA), August 1999.
- [44] Wendi B. Heinzelman, Amy L. Murphy, Hervaldo S. Carvalho and Mark A. Perillo, Middleware to support sensor network applications, *IEEE Network*, vol. 18, no. 1, pp. 6–14, January/February 2004.

- [45] W.R. Heinzelman, A. Chandrakasan and H. Balakrishnan, "Energy-efficient communication protocol for wireless microsensor networks", in *International Conference on System Sciences*, January 2000.
- [46] A. Helmy, Mobility-assisted resolution of queries in large-scale mobile sensor networks, *Computer Networks (Elsevier)*, vol. 43, no. 4, pp. 437–458, November 2003.
- [47] J. Hightower and G. Borriello, Location Systems for Ubiquitous Computing, *Computer*, vol. 34, no. 8, pp. 57–66, August 2001. This article is also featured in "IT Roadmap to a Geospatial Future", a 2003 report from the Computer Science and Telecommunications Board of the National Research Council.
- [48] J. Hill, R. Szewczyk, A. Woo, S. Hollar, D. Culler and K. Pister, System Architecture Directions for Networked Sensors, in *Ninth International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS '00)*, Cambridge (MA), USA, November 2000.
- [49] Fritz Hohl, Uwe Kubach, Alexander Leonhardi, Kart Rothermel and Markus Schwehm, Next century challenges: Nexus – an open global infrastructure for spatial-aware applications, in *MobiCom '99: Proceedings of the 5th annual ACM/IEEE international conference on Mobile computing and networking*, pp. 249–255, New York, NY, USA, 1999. ACM Press.
- [50] Yih-Chun Hu, A. Perrig and D.B. Johnson, Ariadne: A Secure On-demand Routing Protocol for Ad Hoc Networks, in *Proceedings of the 8th annual international conference on Mobile computing and networking (Mobicom)*, Atlanta, Georgia, USA, September 2002.
- [51] Eoin Hyden, *Operating System Support for Quality of Service*, PhD thesis, Wolfson College, University of Cambridge, February 1994.
- [52] Crossbow Tech Inc., *MTS 420 Datasheet*, <http://www.xbow.com>.
- [53] C. Intanagonwiwat, R. Govindan and D. Estrin, Directed Diffusion: A Scalable and Robust Communication Paradigm for Sensor Networks, in *ACM MobiCom '00*, pp. 56–67, Boston, Massachusetts (USA), August 2000.
- [54] C. Karlof and D. Wagner, Secure routing in wireless sensor networks: Attacks and countermeasures, in *Proceedings of the 1st IEEE International Workshop on Sensor Network Protocols and Applications*, Anchorage, AK, May 2003.
- [55] Eric P. Kasten, Philip K. McKinley, S.M. Sadjadi and Kurt Stirewalt, Separating introspection and intercession to support metamorphic distributed systems, in *ICDCSW '02: Proceedings of the 22nd International Conference on Distributed Computing Systems*, pp. 465–472, Washington, DC, USA, 2002. IEEE Computer Society.
- [56] J.O. Kephart and D.M. Chess, The Vision of Autonomic Computing, *IEEE Computer Magazine*, vol. 36, no. 1, pp. 41–50, January 2003.
- [57] Gregor Kiczales, Jim des Rivières and Daniel G. Bobrow, *The art of metaobject protocol*, MIT Press, Cambridge, MA, USA, 1991.
- [58] Gregor Kiczales, Erik Hilsdale, Jim Hugunin, Mik Kersten, Jeffrey Palm and William G. Griswold, An overview of AspectJ, *Lecture Notes in Computer Science*, vol. 2072, pp. 327–355, 2001.

- [59] Gregor Kiczales, John Lamping, Anurag Menhdhekar, Chris Maeda, Cristina Lopes, Jean-Marc Loingtier and John Irwin, Aspect-oriented programming, in Mehmet Akşit and Satoshi Matsuoka, editors, *Proceedings European Conference on Object-Oriented Programming*, vol. 1241, pp. 220–242. Springer-Verlag, Berlin, Heidelberg, and New York, 1997.
- [60] O.Kömmerling and M. Kuhn, Design Principles for Tamper-Resistant Smartcard Processors, in *Proceedings of the USENIX Workshop on Smartcard Technology (Smartcard '99)*, pp. 9–20, Chicago, Illinois, USA, May 1999.
- [61] E. Kohler, R. Morris, B. Chen, J. Jannotti and M.F. Kaashoek, The Click Modular Router, *ACM Transactions on Computer Systems*, vol. 18, no. 3, pp. 263–297, August 2000.
- [62] F. Koushanfar, M. Potkonjak and A. Sangiovanni-Vincentelli, Fault Tolerance in Wireless Ad hoc Sensor Networks, *IEEE Sensors*, vol. 2, pp. 1491–1496, June 2002.
- [63] B. Krishnamachari, D. Estrin and S. Wicker, Modeling Data-Centric Routing in Wireless Sensor Networks, in *IEEE INFOCOM'02*, New York, USA, June 2002.
- [64] M. Kumar, A consensus protocol for wireless sensor networks, Master's thesis, Wayne State University, 2003.
- [65] Leadtek, *GPS 9546 Module Technical Specification*, www.leadtek.com, August 2003.
- [66] Thomas Ledoux, Opencorba: A reflective open broker, in *Reflection '99: Proceedings of the Second International Conference on Meta-Level Architectures and Reflection*, pp. 197–214, London, UK, 1999. Springer-Verlag.
- [67] Jinyang Li, John Jannotti, Douglas S.J. De Couto, David R. Karger and Robert Morris, A scalable location service for geographic ad hoc routing, in *Proceedings of the 6th ACM International Conference on Mobile Computing and Networking (MobiCom '00)*, pp. 120–130, Boston, Massachusetts, August 2000.
- [68] Ting Liu and Margaret Martonosi, Impala: A middleware system for managing autonomic, parallel sensor systems, in *Proc. of the 9th ACM SIGPLAN Symp. on Principles and Practice of Parallel Programming*, pp. 107–118, 2003.
- [69] S. Madden, J. Hellerstein and W. Hong, TinyDB: In-Network Query Processing in TinyOS, Technical Report TinyOS Document, version 4, September 2003.
- [70] S. Madden, R.S. Szewczyk, M.J. Franklin and D. Culler, Supporting Aggregate Queries over Ad hoc Wireless Sensor Networks, in *4th IEEE Workshop on Mobile Computing Systems and Applications*, New York (USA), June 2002.
- [71] Samuel Madden, Michael J. Franklin, Joseph M. Hellerstein and Wei Hong, The design of an acquisitional query processor for sensor networks, in *Proceedings of the 2003 ACM SIGMOD International Conference on Management of Data*, pp. 491–502. ACM Press, 2003.
- [72] S.R. Madden, M.J. Franklin, J.M. Hellerstein and W. Hong, TAG: A Tiny Aggregation Service for Ad hoc Sensor Networks, in *OSDI Conference*, Boston, MA, USA, December 2002.

- [73] Pattie Maes, Concepts and experiments in computational reflection, in *OOPSLA '87: Conference Proceedings on Object-oriented Programming Systems, Languages and Applications*, pp. 147–155. ACM Press, 1987.
- [74] N. Malhotra, M. Krasniewski, C. Yang, S. Bagchi and W. Chappell, Location Estimation in Ad hoc Networks with Directional Antenna, in *Proceedings of the 25th International Conference on Distributed Computing Systems (ICDCS)*, Columbus, Ohio, June 2005.
- [75] Pedro José Marrón, Andreas Lachenmann, Daniel Minder, Jörg Hähner, Robert Sauter and Kurt Rothermel, Tinycubus: A flexible and adaptive framework for sensor networks, in Erdal Çayırıcı Şebnem Baydere and Paul Havinga, editors, *Proc. of the 2nd European Workshop on Wireless Sensor Networks*, pp. 278–289, Istanbul, Turkey, January 2005.
- [76] Philip K. McKinley, S. Masoud Sadjadi, Eric P. Kasten and Betty H.C. Cheng, Composing adaptive software, *IEEE Computer*, pp. 56–64, July 2004.
- [77] Philip K. McKinley, S. Masoud Sadjadi, Eric P. Kasten and Betty H.C. Cheng, A taxonomy of compositional adaptation, Technical Report MSU-CSE-04-17, Department of Computer Science, Michigan State University, East Lansing, Michigan, May 2004.
- [78] Microsoft.net.
- [79] Com: Delivering on the promises of component technology, 2000.
- [80] D.L. Mills, Internet Time Synchronization: the Network Time Protocol, *IEEE Trans. Communications*, vol. 39, no. 10, pp. 1482–1493, October 1991.
- [81] H. Naguib and G. Coulouris, Towards Automatically Configurable Multimedia Applications, in *ACM Multimedia Middleware workshop at MM '01*, Ottawa, Canada, October 2001.
- [82] Dushyanth Narayanan, *Operating System Support for Mobile Interactive Applications*, PhD thesis, School of Computer Science, Computer Science Department, Carnegie Mellon University, August 2002.
- [83] Rolf Neugebauer and Derek McAuley, Energy is just another resource: Energy accounting and energy pricing in the Nemesis OS, in *Proceedings of the 8th Workshop on Hot Topics in Operating Systems*, Schloss Elmau, Germany, May 2001.
- [84] D. Niculescu and B. Nath, Position and Orientation in Ad hoc Networks, *Journal of Ad Hoc Networks*, vol. 2, no. 2, pp. 133–151, April 2004.
- [85] Brian Noble, M. Satyanarayanan, Dushyanth Narayanan, James Tilton, Jason Flinn and Kevin Walker, Agile application-aware adaptation for mobility, in *Proceedings of the 16th ACM Symposium on Operating System Principles*, St. Malo, October 1997.
- [86] D.L. Parnas, On the criteria to be used in decomposing systems into modules, *Commun. ACM*, vol. 15, no. 12, pp. 1053–1058, 1972.
- [87] Adrian Perrig, John Stankovic and David Wagner, Security in wireless sensor networks, *Commun. ACM*, vol. 47, no. 6, pp. 53–57, 2004.
- [88] Adrian Perrig, Robert Szewczyk, J.D. Tygar, Victor Wen and David E. Culler, Spins: security protocols for sensor networks, *Wirel. Netw.*, vol. 8, no. 5, pp. 521–534, 2002.

- [89] T. Pham, Eun Jik Kim and M. Moh, On data aggregation quality and energy efficiency of wireless sensor network protocols – extended summary, in *Proceedings of the First International Conference on Broadband Networks (BroadNets 2004)*, pp. 730–732, October 2004.
- [90] Christian Poellabauer, Hasan Abbasi and Karsten Schwan, Cooperative run-time management of adaptive applications and distributed resources, in *MULTIMEDIA '02: Proceedings of the Tenth ACM International Conference on Multimedia*, pp. 402–411. ACM Press, 2002.
- [91] Christian Poellabauer and Karsten Schwan, Kernel support for the event-based cooperation of distributed resource managers, in *RTAS '02: Proceedings of the Eighth IEEE Real-Time and Embedded Technology and Applications Symposium (RTAS'02)*, p. 3. IEEE Computer Society, 2002.
- [92] Christian Poellabauer, Karsten Schwan, Sandip Agarwala, Ada Gavrilovska, Greg Eisenhauer, Santosh Pande, Calton Pu and Matthew Wolf, Service morphing: Integrated system- and application-level service adaptation in autonomic systems, in *Proceedings of the 5th Annual International Workshop on Active Middleware Services (AMS 2003)*, June 2003.
- [93] B. Przydatek, D. Song and A. Perrig, SIA: Secure Information Aggregation in Sensor Networks, in *Proceedings of the 1st ACM International Conference on Embedded Networked Sensor Systems*, pp. 255–265, May 2003.
- [94] Anu Purhonen and Esa Tuulari, *Ambient intelligence and the development of embedded system software*, pp. 51–67. Kluwer Academic Publishers, Norwell, MA, USA, 2003.
- [95] Python website, URL: <http://www.python.org/>.
- [96] RAPIDware Project website, URL: <http://www.cse.msu.edu/rapidware/>.
- [97] Sylvia Ratnasamy, Brad Karp, Li Yin, Fang Yu, Deborah Estrin, Ramesh Govindan and Scott Shenker, Ght: a geographic hash table for data-centric storage, in *Proceedings of the 1st ACM International Workshop on Wireless Sensor Networks and Applications*, pp. 78–87. ACM Press, 2002.
- [98] K. Rmer, P. Blum and L. Meier, *Time Synchronization and Calibration in Wireless Sensor Networks*, Chapter 7. Wiley and Sons, September 2005.
- [99] Uts Roedig, Andre Barroso and Cormac Sreenan, Determination of aggregation points in wireless sensor networks, in *Proceedings of the 30th EUROMICRO Conference (EUROMICRO '04)*, 2004.
- [100] Manuel Roman and Roy H. Campbell, Gaia: enabling active spaces, in *EW 9: Proceedings of the 9th Workshop on ACM SIGOPS European Workshop*, pp. 229–234, New York, NY, USA, 2000. ACM Press.
- [101] K. Römer, Tracking real-world phenomena with smart dust, 2004.
- [102] Kay Römer and Friedemann Mattern, Event-based systems for detecting real-world states with sensor networks: A critical analysis, in *DEST Workshop on Signal Processing in Sensor Networks at ISSNIP*, pp. 389–395, Melbourne, Australia, December 2004.
- [103] Daniel Grobe Sachs, Wanghong Yuan, Christopher J. Hughes, Albert Harris, Sarita V. Adve, Douglas L. Jones, Robin H. Kravets and Klara Nahrstedt, Grace: A hierarchical adaptation framework for saving energy, Technical report UIUCDCS-R-2004-2409, Computer Science, University of Illinois, February 2004.

- [104] N. Sadagopan, B. Krishnamachari and A. Helmy, Active Query Forwarding in Sensor Networks (ACQUIRE), *Elsevier Journal of Ad Hoc Networks*, January 2005.
- [105] S.M. Sadjadi, P.K. McKinley and E.P. Kasten, Architecture and operation of an adaptable communication substrate, in *Proceedings of the The Ninth IEEE Workshop on Future Trends of Distributed Computing Systems (FTDCS '03)*, pp. 46–56, May 2003.
- [106] S.M. Sadjadi, P.K. McKinley, R.E.K. Stirewalt and B.H.C. Cheng, Trap: Transparent reflective aspect programming, Technical Report MSU-CSE-03-31, Department of Computer Science, Michigan State University, East Lansing, Michigan, November 2003.
- [107] S. Sahni and X. Xu, Algorithms for wireless sensor networks, *International Journal on Distributed Sensor Networks*, pp. 35–56, 2004.
- [108] F.A. Samimi, P.K. McKinley, S.M. Sadjadi and P. Ge, Kernel-middleware interaction to support adaptation in pervasive computing environments, In *Proceedings of the 2nd Workshop on Middleware for Pervasive and Ad Hoc Computing*, pp. 140–145. ACM Press, 2004.
- [109] Andreas Savvides, Heemin Park and Mani B. Srivastava, The bits and flops of the n-hop multilateration primitive for node localization problems, in *WSNA '02: Proceedings of the 1st ACM International Workshop on Wireless Sensor Networks and Applications*, pp. 112–121, New York, NY, USA, 2002. ACM Press.
- [110] Albrecht Schmidt, Antti Takaluoma and Jani Mäntyjärvi, Context-Aware Telephony Over WAP, *Personal Ubiquitous Comput.*, vol. 4, no. 4, pp. 225–229, 2000.
- [111] Douglas C. Schmidt, Middleware for real-time and embedded systems, *Commun. ACM*, vol. 45, no. 6, pp. 43–48, 2002.
- [112] R.C. Shah, S. Roy, S. Jain and W. Brunette, Data MULEs: Modeling a Three-tier Architecture for Sparse Sensor Networks, in *IEEE Workshop on Sensor Network Protocols and Applications (SNPA)*, May 2003.
- [113] A. Sharaf, Jonathan Beaver, Alexandros Labrinidis and K. Chrysanthis, Balancing energy efficiency and quality of aggregate data in sensor networks, *The International Journal on Very Large Data Bases (VLDB)*, vol. 13, December 2004.
- [114] C. Shen, C. Srisathapornphat and C. Jaikaeo, Sensor Information Networking Architecture and Applications, *IEEE Personal Communications Magazine*, pp. 52–59, August 2001.
- [115] Nisheeth Shrivastava, Chiranjeeb Buragohain, Divyakant Agrawal and Subhash Suri, Aggregation: Medians and beyond: new aggregation techniques for sensor networks, in *Proceedings of the 2nd International Conference on Embedded Networked Sensor Systems*, November 2004.
- [116] Brian Cantwell Smith, Reflection and semantics in LISP, in *POPL '84: Proceedings of the 11th ACM SIGACT-SIGPLAN Symposium on Principles of Programming Languages*, pp. 23–35, New York, NY, USA, 1984. ACM Press.
- [117] I. Solis and K. Obraczka, The impact of timing in data aggregation for sensor networks, in *IEEE International Conference on Communications 2004*, vol. 6, pp. 3640–3645, June 2004.

- [118] Frank Stajano and Ross Anderson, The resurrecting duckling: Security issues for ad hoc wireless networks, in *7th International Workshop on Security Protocols*, LNCS, pp. 172–194, 1999.
- [119] Martin Strohbach, Hans-Werner Gellersen, Gerd Kortuem and Christian Kray, Cooperative artefacts: Assessing real world situations with embedded technology, in *Adjunct Proceedings of UbiComp 2003*, September 2003.
- [120] Enterprise javabeans technology, 2000.
- [121] B. Sundararaman, U. Buy and A.D. Kshemkalyani, Clock Synchronization in Wireless Sensor Networks: A Survey, *Ad hoc Networks*, vol. 3, no. 3, pp. 281–323, May 2005.
- [122] Clement Szyperski, *Component Software: Beyond Object-Oriented Programming*, Addison-Wesley, January 1998.
- [123] The Ohio State University NEST Team, A line in the sand, August 2003.
- [124] E. Truyen, B. Jrgensen, W. Joosen and P. Verbaeten, Aspects for run-time component integration, 2000.
- [125] Arno Wacker, Timo Heiber, Holger Cermann and Pedro Marron, A fault tolerant Key-Distribution Scheme for Securing Wireless Ad hoc Networks, in *Proceedings of the Second International Conference on Pervasive Computing 2004*, pp. 194–212, Linz/Vienna, Austria, April 2004.
- [126] A. Wadaa, S. Olariu, L. Wilson, M. Eltoweissy and K. Jones, On Providing Anonymity in Wireless Sensor Networks, in *Proceedings of the Tenth International Conference on Parallel and Distributed Systems (ICPADS '04)*, pp. 411–418, Newport Beach, CA, USA, July 2004.
- [127] Ian Welch and Robert J. Stroud, Kava – a reflective java based on bytecode rewriting, in *Proceedings of the 1st OOPSLA Workshop on Reflection and Software Engineering*, pp. 155–167. Springer-Verlag, 2000.
- [128] Geoffrey Werner-Allen, Jeff Johnson, Mario Ruiz, Jonathan Lees and Matt Welsh, Monitoring volcanic eruptions with a wireless sensor network, in *Proceedings of 2nd European Workshop on Wireless Sensor Networks*, Istanbul, Turkey, February 2005.
- [129] J. Wong, S. Megerian and M. Potkonjak, Design Techniques for Sensor Appliances: Foundations and Light Compass Case Study, in *40th IEEE/ACM Design Automation Conference*, pp. 66–71, June 2003.
- [130] Anthony D. Wood and John A. Stankovic, Denial of service in sensor networks, *Computer*, vol. 35, no. 10, pp. 54–62, 2002.
- [131] Zhixue Wu, Reflective Java and a reflective component-based transaction architecture, in *Proceedings of Workshop on Reflective Programming in C++ and Java*, 1998.
- [132] Y. Yao and J.E. Gehrke, Query Processing in Sensor Networks, in *First Biannual Conference on Innovative Data Systems Research (CIDR 2003)*, Asilomar, California, USA, January 2003.
- [133] Wei Yuan, S.V. Krishnamurthy and S.K. Tripathi, Synchronization of multiple levels of data fusion in wireless sensor networks, in *IEEE Global Telecommunications Conference (GLOBECOM '03)*, vol. 1, pp. 221–225, December 2003.

- [134] Heng Zeng, Carla S. Ellis and Alvin R. Lebeck, Experiences in managing energy with ecosystem, *IEEE Pervasive Computing*, January-March 2005.
- [135] Jerry Zhao, Ramesh Govindan and Deborah Estrin, Computing aggregates for monitoring wireless sensor networks, in *Proceedings of First IEEE International Workshop on Sensor Network Protocols and Applications*, pp. 139–149, May 2003.