## Mimicking the nature: Hook-and-loop adhesion systems for elastomers

R. Anyszka<sup>12\*</sup>, W. Dierkes<sup>1</sup>, A. Blume<sup>1</sup>, D. M. Bieliński<sup>2</sup> and E. Sarlin<sup>3</sup>

- <sup>1</sup> University of Twente, Faculty of Engineering Technology, Department of Mechanics of Solids, Surfaces & Systems (MS³), Chair of Elastomer Technology & Engineering, Enschede, The Netherlands
- <sup>2</sup> Lodz University of Technology, Faculty of Chemistry, Institute of Polymer and Dye Technology, Lodz, Poland
- <sup>3</sup> Tampere University of Technology, Department of Materials Science, Tampere, Finland
- \* r.p.anyszka@utwente.nl; rafal.anyszka@p.lodz.pl

Nowadays, silica has become one of the most important fillers in the rubber industry. However, the polar character of its surface requires a chemical treatment before its incorporation to the less-polar or non-polar rubber matrix. Currently the most prevalent approach toward silica surface modification is the use of silane coupling agents which form strong covalent bonds between a silica and an elastomer. These bonds are relatively stiff and in most cases cannot be reconstructed after rupture. To overcome these disadvantages, a completely new approach was made. This new approach was inspired by the hook-and-loop velcro system widely spread in nature, which facilitates reconnectable mechanical links between two surfaces. The challenging task is to apply the hook-and-loop system in a macromolecular level by implementing physical entanglements for an alternative silica/elastomer interaction.

In this study a monohydroxy-telechelic butadiene oligomer was utilized as a backbone for the molecular "hook" synthesis. The hydroxyl group reacted with isocyanate group from triethoxyisocyanate silane in order to form reactive sites toward the silica surface. Whereas, double carbon-carbon bonds in vinyl position were utilized to attach side mercapto-terminated groups of significant stearic hindrance providing sufficient entanglements with an elastomer matrix, acting as molecular "loops" (Fig. 1). This approach is a first step to implement the hook-and-loop system in a macromolecular level for the rubber industry and technology.




Figure 1: Scheme of the molecular "hook" synthesis and its attachments to a silica surface.

This document is only for the exclusive use by attendees of the DKT 2018 scientific conference. Passing on to third parties or publishing the contents or parts of the contents requires the express consent of the author(s).