

---

# Comparative study of Deep Learning methods for One-shot Image Classification (abstract)

---

Joep van den Bogaert<sup>\*@</sup> Haleh Mohseni<sup>\*</sup> Mahmoud Khodier<sup>\*</sup> <sup>@J.V.D.BOGAERT@TUE.NL</sup>  
Yuliyana Stoyanov<sup>\*</sup> Decebal Constantin Mocanu<sup>\*</sup> Vlado Menkovski

<sup>\*</sup>Dep. of Mathematics and Computer Science, Eindhoven University of Technology, The Netherlands

## Abstract

Training deep learning models for images classification requires large amount of labeled data to overcome the challenges of overfitting and underfitting. Usually, in many practical applications, these labeled data are not available. In an attempt to solve this problem, the one-shot learning paradigm tries to create machine learning models capable to learn well from one or (maximum) few labeled examples per class. To understand better the behavior of various deep learning models and approaches for one-shot learning, in this abstract, we perform a comparative study of the most used ones, on a challenging real-world dataset, i.e Fashion-MNIST.

## 1. Methods and Results

To perform the study, we proceed in a step-wise fashion approach. First, we split the training set of the Fashion-MNIST data (Xiao et al., 2017) in three subsets: a labeled training subset ( $S_1$ ) consisting of all data (30000 images) from five classes (i.e. 1, 2, 3, 8, and 9); a labeled training subset ( $S_2$ ) consisting in just one randomly chosen labeled example per class (5 images) from the remaining classes (i.e. 0, 4, 5, 6 and 7); and an unlabeled training set ( $S_3$ ) consisting in all the remaining examples from the classes 0, 4, 5, 6 and 7 (29995 images). For testing we used the unaltered testing set of Fashion-MNIST.

To analyze the performance of the different approaches, secondly, we optimized a standard Convolutional Neural Networks model on  $S_1$  ( $\text{CNN}_{S_1}$ ) by performing a thorough hyperparameter optimization. Further on, we present the top five approaches that we followed: (1) we fine tune  $\text{CNN}_{S_1}$  on  $S_2$  using trans-

Table 1. Accuracy of the various models studied.

Model	Accuracy [%]
$\text{CNN}_{S_1}^1$	59.3
$\text{CNN}_{S_1}^2$	72.4
$\text{CNN}_{AE}^3$	64.0
$\text{SN}^4$	63.1
$\text{DC}^5$	66.5

fer learning without data augmentation ( $\text{CNN}_{S_1}^1$ ), (2) we fine tune  $\text{CNN}_{S_1}$  one  $S_2$  using transfer learning and optimized data augmentation ( $\text{CNN}_{S_1}^2$ ), (3) we trained a convolutional autoencoder on  $S_3$  and we transferred its weights to a CNN which was fine tuned on  $S_2$  ( $\text{CNN}_{AE}^3$ ), (4) we trained Siamese Networks (Koch et al., 2015) ( $\text{SN}^4$ ) on  $S_1$  and then fine tuned them on an augmented version of  $S_2$ , (5) we have start performing a Divide and Conquer ( $\text{DC}^5$ ) approach, where we divided the classification task in subtasks for which specialized autoencoders and CNNs were used. The results are reported in Table 1.

## 2. Conclusion

The obtained results are to a degree unexpected. More exactly, in this specific scenario, they show that data augmentation and hyperparameter optimization can lead a simple CNN model to reach better accuracy than more complex neural networks models. As further work, we intend to develop further the Divide and Conquer approach, which seems to have a very good potential in the one-shot learning context.

## Acknowledgments

This research has been done as part of the PDEng Data Mining module at JADS, Netherlands.

## References

- Koch, G., Zemel, R., & Salakhutdinov, R. (2015). Siamese neural networks for one-shot image recognition. .
- Xiao, H., Rasul, K., & Vollgraf, R. (2017). Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms.